

# ARKANSAS STATE HIGHWAY COMMISSION

## PROPOSAL DOCUMENTS

### *FOR THE CONSTRUCTION OF*

STATE JOB NO. A60063

FEDERAL AID PROJECT STPSC-9210(62)

HWY. 7 IMPVTS. (HOT SPRINGS) (S)

STATE HIGHWAY 7 SECTION 9

IN GARLAND COUNTY

Bound herein are the Supplemental Specifications, Special Provisions, Proposal Documents and Schedule of Items applicable to this proposed construction contract.

Applicable to this proposed construction contract, but not bound herein, are the Arkansas State Highway Commission Standard Specifications for Highway Construction, Edition of 2014, and the Construction Plans.

**ADDENDUM NO. 1**

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

PROGRAM MANAGEMENT DIVISION

LITTLE ROCK, ARKANSAS

June 15, 2026

**TO:** Eligible Bidders – Jobs:      A60063      A90046      CB0401      BR2814

**SUBJECT:** Proposal Documents Change

FHWA 1273 Supplement – Wage Rate Determination has been revised for the subject projects. You should substitute the revised sheets into your proposal documents for each project you are an eligible bidder on and consider these revisions when submitting your bid.

**ACKNOWLEDGEMENT OF THIS ADDENDUM SHALL BE MADE BY SIGNING BELOW AND SUBMITTING THIS SIGNED FORM TO THE PROGRAM MANAGEMENT DIVISION BY EMAIL AT [pmd@ardot.gov](mailto:pmd@ardot.gov) OR BY FAX AT (501)569-2623.**

Sincerely,



For

Daniel Siskowski  
Division Engineer  
Program Management

\_\_\_\_\_  
Name

\_\_\_\_\_  
Company

EMAILED ADDENDA



## CAUTION TO BIDDERS

Please review Section 102 of the Standard Specifications, 2014 Edition for Bidding Requirements and Conditions. Mistakes or omissions can be costly. Important items for you to check are included in, but not limited to, those listed below. This checklist is furnished only to assist you in submitting a proper bid. Check as you read.

- ☐ Have you contacted ARDOT ([pmd@ardot.gov](mailto:pmd@ardot.gov) or 501-569-2261) to become an eligible bidder? This is required to submit a bid in the letting and must occur by 4:30pm the day prior to the letting.
- ☐ Have you acknowledged all Addenda by email or fax?
- ☐ Is the unit price entered appropriate for the item?
- ☐ Have you entered a unit price for each bid item except in the case of authorized alternate pay items? (A zero bid (\$0.00) is a valid price and will be considered.)
- ☐ Have you checked the Schedule of Items for various pay items that may have a minimum or maximum unit bid price? (Refer to the Standard Specifications for further information concerning these items)
  - ✓ Asphalt Binder
  - ✓ Relocating Precast Concrete Barrier
  - ✓ Water
  - ✓ Mobilization
- ☐ Have you limited your bid for Mobilization to five percent (5%) of the subtotal?
- ☐ For Federal-aid projects, did you complete the Certification for Federal aid Contracts?
- ☐ Prior to submitting your bid, did you check for error messages, and are all the folders "green"?
- ☐ If submitting a paper copy of the Proposal Guaranty (Bid Bond) is it signed by an officer of your company **AND** the Surety Agent?
- ☐ Did you ensure your Proposal Guaranty (if you are submitting a paper bond) will arrive prior to the time and date stated on Page 2 of the Proposal Documents?

1-17-08  
Revised: 6-1-09  
Revised: 2-15-12  
Revised: 1-15-15  
Revised: 5-26-16  
Revised: 11-17-17  
Revised: 7-5-23  
Revised: 8-4-25  
Revised: 12-18-25

## **ARKANSAS DEPARTMENT OF TRANSPORTATION**

### **NOTICE OF NONDISCRIMINATION**

The Arkansas Department of Transportation (ARDOT) complies with all civil rights provisions of federal statutes and related authorities that prohibit discrimination in programs and activities receiving federal financial assistance. Therefore, ARDOT does not discriminate on the basis of race, sex, color, age, national origin, religion (not applicable as a protected group under the FMCSA Title VI Program), or disability in the admission, access to and treatment in ARDOT's programs and activities, as well as ARDOT's hiring or employment practices. Complaints of alleged discrimination and inquiries regarding ARDOT's nondiscrimination policies may be directed to the Civil Rights Division, P. O. Box 2261, Little Rock, AR 72203, (501) 569-2298, (Voice/TTY 711), or the following email address: [Civil.Rights@ardot.gov](mailto:Civil.Rights@ardot.gov)

Free language assistance may be available upon request.

This notice is available from the ADA/504/Title VI Coordinator in large print, on audiotape, and in Braille.

## TITLE VI CONTRACT PROVISIONS

### APPENDIX A

During the performance of this contract, the contractor, for itself, its assignees and successors in interest (hereinafter referred to as the “contractor”) agrees as follows:

(1) Compliance with Regulations: The contractor (hereinafter includes consultants) will comply with the Acts and the Regulations relative to Non-discrimination in Federally-assisted programs of the U.S. Department of Transportation, Federal Highway Administration, as they may be amended from time to time, which are herein incorporated by reference and made a part of this contract.

(2) Nondiscrimination: The contractor, with regard to the work performed by it during the contract, will not discriminate on the grounds of race, color, or national origin in the selection and retention of subcontractors, including procurements of materials and leases of equipment. The contractor will not participate directly or indirectly in the discrimination prohibited by the Acts and the Regulations, including employment practices when the contract covers any activity, project, or program set forth in Appendix B of 49 CFR Part 21.

(3) Solicitations for Subcontracts, Including Procurements of Materials and Equipment: In all solicitations, either by competitive bidding, or negotiation made by the contractor for work to be performed under a subcontract, including procurements of materials, or leases of equipment, each potential subcontractor or supplier will be notified by the contractor of the contractor's obligations under this contract and the Acts and the Regulations relative to Nondiscrimination on the grounds of race, color, or national origin.

(4) Information and Reports: The contractor will provide all information and reports required by the Acts, the Regulations, and directives issued pursuant thereto and will permit access to its books, records, accounts, other sources of information, and its facilities as may be determined by the Recipient or the Federal Highway Administration to be pertinent to ascertain compliance with such Acts, Regulations, and instructions. Where any information required of a contractor is in the exclusive possession of another who fails or refuses to furnish the information, the contractor will so certify to the Recipient or the Federal Highway Administration, as appropriate, and will set forth what efforts it has made to obtain the information.

(5) Sanctions for Noncompliance: In the event of a contractor's noncompliance with the Nondiscrimination provisions of this contract, the Recipient will impose such contract sanctions as it or the Federal Highway Administration may determine to be appropriate, including, but not limited to:

- (a) Withholding of payments to the contractor under the contract until the contractor complies, and/or
- (b) Cancelling, terminating or suspending a contract, in whole or in part.

(6) Incorporation of Provisions: The contractor will include the provisions of paragraphs one through six in every subcontract, including procurements of materials and leases of equipment, unless exempt by the Acts, the Regulations and directives issued pursuant thereto. The contractor will take action with respect to any subcontract or procurement as the Recipient or the Federal Highway Administration may direct as a means of enforcing such provisions including sanctions for noncompliance. Provided, that if the contractor becomes involved in, or is threatened with litigation by a subcontractor, or supplier because of such direction, the contractor may request the Recipient to enter into any litigation to protect the interests of the Recipient. In addition, the contractor may request the United States to enter into the litigation to protect the interests of the United States.

## TITLE VI CONTRACT PROVISIONS

### APPENDIX E

During the performance of this contract, the contractor, for itself, its assignees, and successors in interest (hereinafter referred to as the "contractor") agrees to comply with the following non-discrimination statutes and authorities; including but not limited to:

**Pertinent Non-Discrimination Authorities:**

- Title VI of the Civil Rights Act of 1964 (42 U.S.C. § 2000d et seq., 78 stat. 252), (prohibits discrimination on the basis of race, color, national origin); and 49 CFR Part 21.
- The Uniform Relocation Assistance and Real Property Acquisition Policies Act of 1970, (42 U.S.C. § 4601), (prohibits unfair treatment of persons displaced or whose property has been acquired because of Federal or Federal-aid programs and projects);
- Federal-Aid Highway Act of 1973, (23 U.S.C. § 324 et seq.), (prohibits discrimination on the basis of sex);
- Section 504 of the Rehabilitation Act of 1973, (29 U.S.C. § 794 et seq.), as amended, (prohibits discrimination on the basis of disability); and 49 CFR Part 27;
- The Age Discrimination Act of 1975, as amended, (42 U.S.C. § 6101 et seq.), (prohibits discrimination on the basis of age);
- Airport and Airway Improvement Act of 1982, (49 USC§ 471, Section 47123), as amended, (prohibits discrimination based on race, creed, color, national origin, or sex);
- The Civil Rights Restoration Act of 1987, (PL 100-209), (Broadened the scope, coverage and applicability of Title VI of the Civil Rights Act of 1964, The Age Discrimination Act of 1975 and Section 504 of the Rehabilitation Act of 1973, by expanding the definition of the terms "programs or activities" to include all of the programs or activities of the Federal-aid recipients, sub-recipients and contractors, whether such programs or activities are Federally funded or not);
- Titles II and III of the Americans with Disabilities Act, which prohibit discrimination on the basis of disability in the operation of public entities, public and private transportation systems, places of public accommodation, and certain testing entities (42 U.S.C. §§ 12131-12189) as implemented by Department of Transportation regulations at 49 C.F.R. parts 37 and 38;
- The Federal Aviation Administration's Non-discrimination statute (49 U.S.C. § 47123) (prohibits discrimination on the basis of race, color, national origin, and sex);
- Executive Order 12898, Federal Actions to Address Environmental Justice in Minority Populations and Low-Income Populations, which ensures Non-discrimination against minority populations by discouraging programs, policies, and activities with disproportionately high and adverse human health or environmental effects on minority and low-income populations;
- Executive Order 13166, Improving Access to Services for Persons with Limited English Proficiency, and resulting agency guidance, national origin discrimination includes discrimination because of Limited English proficiency (LEP). To ensure compliance with Title VI, you must take reasonable steps to ensure that LEP persons have meaningful access to your programs (70 Fed. Reg. at 74087 to 74100);
- Title IX of the Education Amendments of 1972, as amended, which prohibits you from discriminating because of sex in education programs or activities (20 U.S.C. 1681et seq).

Arkansas Department of Transportation  
Supplemental Specifications and Special Provisions Listing  
State Job Number A60063

The following supplemental specifications and special provisions for this project supplement the standard specifications, edition of 2014. In case of conflict, the supplemental specifications and special provisions shall govern.

|           |                                                                                        |
|-----------|----------------------------------------------------------------------------------------|
| ERRATA    | ERRATA FOR THE BOOK OF STANDARD SPECIFICATIONS                                         |
| FHWA-1273 | REQUIRED CONTRACT PROVISIONS FEDERAL-AID CONSTRUCTION CONTRACTS                        |
| FHWA-1273 | SUPPLEMENT - EQUAL EMPLOYMENT OPPORTUNITY - NOTICE TO CONTRACTORS                      |
| FHWA-1273 | SUPPLEMENT - SPECIFIC EQUAL EMPLOYMENT OPPORTUNITY RESPONSIBILITIES (23 U.S.C. 140)    |
| FHWA-1273 | SUPPLEMENT - EQUAL EMPLOYMENT OPPORTUNITY - GOALS AND TIMETABLES                       |
| FHWA-1273 | SUPPLEMENT - EQUAL EMPLOYMENT OPPORTUNITY - FEDERAL STANDARDS                          |
| FHWA-1273 | SUPPLEMENT - POSTERS AND NOTICES REQUIRED FOR FEDERAL-AID PROJECTS                     |
| FHWA-1273 | SUPPLEMENT - WAGE RATE DETERMINATION                                                   |
| JOB SP    | CARGO PREFERENCE ACT REQUIREMENTS                                                      |
| JOB SP    | PROHIBITION OF CERTAIN TELECOMMUNICATIONS AND VIDEO SURVEILLANCE SERVICES OR EQUIPMENT |
| JOB SP    | BUY AMERICA - CONSTRUCTION MATERIALS                                                   |
| JOB SP    | VENDOR REGISTRATION REQUIREMENT                                                        |
| JOB SP    | DOCUMENTATION OF PAYMENTS MADE – PROMPT PAYMENT (SIGNET)                               |
| JOB SP    | DOCUMENTATION OF PAYMENTS MADE TO DISADVANTAGED BUSINESS ENTERPRISES                   |
| JOB SP    | BIDDING REQUIREMENTS AND CONDITIONS                                                    |
| JOB SP    | MANDATORY ELECTRONIC CONTRACT                                                          |
| JOB SP    | MANDATORY ELECTRONIC DOCUMENT SUBMITTAL                                                |
| JOB SP    | ASSESSMENT OF WORKING DAYS - MAINTENANCE OF TRAFFIC                                    |
| JOB SP    | LIQUIDATED DAMAGES PROCEDURE FOR BID LETTINGS                                          |
| JOB SP    | ELECTRONIC TICKETING SYSTEMS (E-TICKETING)                                             |
| JOB SP    | DESIGN AND QUALITY CONTROL OF ASPHALT MIXTURES                                         |
| JOB SP    | LONGITUDINAL JOINT DENSITIES FOR ACHM SURFACE COURSES                                  |
| JOB SP    | SUBMISSION OF ASPHALT CONCRETE HOT MIX ACCEPTANCE TEST RESULTS                         |
| JOB SP    | PRICE ADJUSTMENT FOR ASPHALT BINDER                                                    |
| JOB SP    | PRICE ADJUSTMENT FOR FUEL                                                              |
| JOB SP    | ASPHALT MIXTURES WITH PG 76-22 BINDER                                                  |
| JOB SP    | WARM MIX ASPHALT                                                                       |
| JOB SP    | COLD MILLING - MILL & INLAY                                                            |
| JOB SP    | MAINTENANCE OF TRAFFIC                                                                 |
| JOB SP    | ROADWAY CONSTRUCTION CONTROL – PAVEMENT PRESERVATION                                   |
| JOB SP    | SURFACE-APPLIED DETECTABLE WARNING PANELS                                              |
| JOB SP    | LOOP WIRING REVISION 1.4                                                               |
| JOB SP    | CONCRETE PULL BOX                                                                      |
| JOB SP    | WATER POLLUTION CONTROL                                                                |
| JOB SP    | PRIME CONTRACTOR PERFORMANCE EVALUATION                                                |

Arkansas Department of Transportation  
Supplemental Specifications and Special Provisions Listing  
State Job Number A60063

The following supplemental specifications and special provisions for this project supplement the standard specifications, edition of 2014. In case of conflict, the supplemental specifications and special provisions shall govern.

|          |                                                                                |
|----------|--------------------------------------------------------------------------------|
| JOB SP   | INSURANCE, CONSTRUCTION, AND FLAGGING REQUIREMENTS ON RAILROAD PROPERTY (G&W)  |
| SP 108-1 | LIQUIDATED DAMAGES                                                             |
| SS 100-3 | CONTRACTOR'S LICENSE                                                           |
| SS 100-4 | DEPARTMENT NAME CHANGE                                                         |
| SS 102-2 | ISSUANCE OF PROPOSALS                                                          |
| SS 102-3 | PREQUALIFICATION OF BIDDERS                                                    |
| SS 103-2 | CONTACT INFORMATION FOR MOTORIST DAMAGE CLAIMS                                 |
| SS 105-4 | MAINTENANCE DURING CONSTRUCTION                                                |
| SS 107-2 | RESTRAINING CONDITIONS                                                         |
| SS 108-2 | WORK ALLOWED PRIOR TO ISSUANCE OF WORK ORDER                                   |
| SS 108-3 | WORK ORDER FOR FIXED COMPLETION DATE CONTRACTS                                 |
| SS 306-1 | QUALITY CONTROL AND ACCEPTANCE                                                 |
| SS 400-1 | TACK COATS                                                                     |
| SS 400-4 | DESIGN AND QUALITY CONTROL OF ASPHALT MIXTURES                                 |
| SS 400-5 | PERCENT AIR VOIDS FOR ACHM MIX DESIGNS                                         |
| SS 400-6 | LIQUID ANTI-STRIP ADDITIVE                                                     |
| SS 400-7 | TRACKLESS TACK                                                                 |
| SS 404-3 | DESIGN OF ASPHALT MIXTURES                                                     |
| SS 409-2 | ASPHALT LABORATORY FACILITY                                                    |
| SS 410-1 | CONSTRUCTION REQUIREMENTS AND ACCEPTANCE OF ASPHALT CONCRETE PLANT MIX COURSES |
| SS 410-2 | DEVICES FOR MEASURING DENSITY FOR ROLLING PATTERNS                             |
| SS 410-4 | EVALUATION OF ACHM SUBLOT REPLACEMENT MATERIAL                                 |
| SS 416-1 | RECYCLED ASPHALT PAVEMENT                                                      |
| SS 603-1 | LANE CLOSURE NOTIFICATION                                                      |
| SS 604-1 | RETROREFLECTIVE SHEETING FOR TRAFFIC CONTROL DEVICES IN CONSTRUCTION ZONES     |
| SS 604-3 | TRAFFIC CONTROL DEVICES IN CONSTRUCTION ZONES (MASH)                           |
| SS 604-4 | CLASSIFICATION AND APPLICATION OF MARKINGS                                     |
| SS 802-5 | CONCRETE FOR STRUCTURES                                                        |

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**ERRATA FOR THE BOOK OF STANDARD SPECIFICATIONS**

Errors noted in the printed book of Standard Specifications for Highway Construction, Edition of 2014, are listed below and this publication is hereby revised as follows:

- Page 124: The third sentence of the first paragraph of Subsection 110.03(c) should read: The Engineer will make a decision within 10 business days concerning the necessity or practicability of the request.
- Page 195: The sixth paragraph of subsection 303.02 should read: For Classes 1 through 8 materials, the fraction passing the #200 (0.075 mm) sieve shall not be greater than three-fourths of the fraction passing the #40 (0.0425 mm) sieve. For Classes 3 through 8, the fraction passing the #40 (0.425 mm) sieve shall have a liquid limit not greater than 25.
- Page 363: In the second paragraph of Subsection 502.02, the reference to ASTM 775 should be replaced by “ASTM A 775”.
- Page 636: In the second paragraph of Subsection 730.02, the references to AASHTO M 183 should be replaced with ASTM A36.
- Page 637: The last sentence of the second paragraph of Subsection 730.03 should read: All bolts, nuts, and washers shall be galvanized according to AASHTO M 232 or ASTM B 695, Class 40 or 50.
- Page 767: In the fourth paragraph of Subsection 807.06(a), the reference to ASTM B595 should be replaced by “ASTM B695”.
- Page 841: Subsection 817.04(a) should read: The treatment of lumber and timber shall meet the applicable requirements of the current edition of the AWP, Standards U1, Commodity Specification E, Use Category UC4C.

## REQUIRED CONTRACT PROVISIONS FEDERAL-AID CONSTRUCTION CONTRACTS

- I. General
- II. Nondiscrimination
- III. Non-segregated Facilities
- IV. Davis-Bacon and Related Act Provisions
- V. Contract Work Hours and Safety Standards Act Provisions
- VI. Subletting or Assigning the Contract
- VII. Safety: Accident Prevention
- VIII. False Statements Concerning Highway Projects
- IX. Implementation of Clean Air Act and Federal Water Pollution Control Act
- X. Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion
- XI. Certification Regarding Use of Contract Funds for Lobbying
- XII. Use of United States-Flag Vessels:

### ATTACHMENTS

A. Employment and Materials Preference for Appalachian Development Highway System or Appalachian Local Access Road Contracts (included in Appalachian contracts only)

### I. GENERAL

1. Form FHWA-1273 must be physically incorporated in each construction contract funded under title 23, United States Code, as required in 23 CFR 633.102(b) (excluding emergency contracts solely intended for debris removal). The contractor (or subcontractor) must insert this form in each subcontract and further require its inclusion in all lower tier subcontracts (excluding purchase orders, rental agreements and other agreements for supplies or services). 23 CFR 633.102(e).

The applicable requirements of Form FHWA-1273 are incorporated by reference for work done under any purchase order, rental agreement or agreement for other services. The prime contractor shall be responsible for compliance by any subcontractor, lower-tier subcontractor or service provider. 23 CFR 633.102(e).

Form FHWA-1273 must be included in all Federal-aid design-build contracts, in all subcontracts and in lower tier subcontracts (excluding subcontracts for design services, purchase orders, rental agreements and other agreements for supplies or services) in accordance with 23 CFR 633.102. The design-builder shall be responsible for compliance by any subcontractor, lower-tier subcontractor or service provider.

Contracting agencies may reference Form FHWA-1273 in solicitation-for-bids or request-for-proposals documents, however, the Form FHWA-1273 must be physically incorporated (not referenced) in all contracts, subcontracts and lower-tier subcontracts (excluding purchase orders, rental agreements and other agreements for supplies or services related to a construction contract). 23 CFR 633.102(b).

2. Subject to the applicability criteria noted in the following sections, these contract provisions shall apply to all work

performed on the contract by the contractor's own organization and with the assistance of workers under the contractor's immediate superintendence and to all work performed on the contract by piecework, station work, or by subcontract. 23 CFR 633.102(d).

3. A breach of any of the stipulations contained in these Required Contract Provisions may be sufficient grounds for withholding of progress payments, withholding of final payment, termination of the contract, suspension / debarment or any other action determined to be appropriate by the contracting agency and FHWA.

4. Selection of Labor: During the performance of this contract, the contractor shall not use convict labor for any purpose within the limits of a construction project on a Federal-aid highway unless it is labor performed by convicts who are on parole, supervised release, or probation. 23 U.S.C. 114(b). The term Federal-aid highway does not include roadways functionally classified as local roads or rural minor collectors. 23 U.S.C. 101(a).

### II. NONDISCRIMINATION (23 CFR 230.107(a); 23 CFR Part 230, Subpart A, Appendix A; EO 11246)

The provisions of this section related to 23 CFR Part 230, Subpart A, Appendix A are applicable to all Federal-aid construction contracts and to all related construction subcontracts of \$10,000 or more. The provisions of 23 CFR Part 230 are not applicable to material supply, engineering, or architectural service contracts.

In addition, the contractor and all subcontractors must comply with the following policies: Executive Order 11246, 41 CFR Part 60, 29 CFR Parts 1625-1627, 23 U.S.C. 140, Section 504 of the Rehabilitation Act of 1973, as amended (29 U.S.C. 794), Title VI of the Civil Rights Act of 1964, as amended (42 U.S.C. 2000d et seq.), and related regulations including 49 CFR Parts 21, 26, and 27; and 23 CFR Parts 200, 230, and 633.

The contractor and all subcontractors must comply with: the requirements of the Equal Opportunity Clause in 41 CFR 60-1.4(b) and, for all construction contracts exceeding \$10,000, the Standard Federal Equal Employment Opportunity Construction Contract Specifications in 41 CFR 60-4.3.

Note: The U.S. Department of Labor has exclusive authority to determine compliance with Executive Order 11246 and the policies of the Secretary of Labor including 41 CFR Part 60, and 29 CFR Parts 1625-1627. The contracting agency and the FHWA have the authority and the responsibility to ensure compliance with 23 U.S.C. 140, Section 504 of the Rehabilitation Act of 1973, as amended (29 U.S.C. 794), and Title VI of the Civil Rights Act of 1964, as amended (42 U.S.C. 2000d et seq.), and related regulations including 49 CFR Parts 21, 26, and 27; and 23 CFR Parts 200, 230, and 633.

The following provision is adopted from 23 CFR Part 230, Subpart A, Appendix A, with appropriate revisions to conform to the U.S. Department of Labor (US DOL) and FHWA requirements.

**1. Equal Employment Opportunity:** Equal Employment Opportunity (EEO) requirements not to discriminate and to take affirmative action to assure equal opportunity as set forth under laws, executive orders, rules, regulations (see 28 CFR Part 35, 29 CFR Part 1630, 29 CFR Parts 1625-1627, 41 CFR Part 60 and 49 CFR Part 27) and orders of the Secretary of Labor as modified by the provisions prescribed herein, and imposed pursuant to 23 U.S.C. 140, shall constitute the EEO and specific affirmative action standards for the contractor's project activities under this contract. The provisions of the Americans with Disabilities Act of 1990 (42 U.S.C. 12101 et seq.) set forth under 28 CFR Part 35 and 29 CFR Part 1630 are incorporated by reference in this contract. In the execution of this contract, the contractor agrees to comply with the following minimum specific requirement activities of EEO:

a. The contractor will work with the contracting agency and the Federal Government to ensure that it has made every good faith effort to provide equal opportunity with respect to all of its terms and conditions of employment and in their review of activities under the contract. 23 CFR 230.409 (g)(4) & (5).

b. The contractor will accept as its operating policy the following statement:

"It is the policy of this Company to assure that applicants are employed, and that employees are treated during employment, without regard to their race, religion, sex, sexual orientation, gender identity, color, national origin, age or disability. Such action shall include: employment, upgrading, demotion, or transfer; recruitment or recruitment advertising; layoff or termination; rates of pay or other forms of compensation; and selection for training, including apprenticeship, pre-apprenticeship, and/or on-the-job training."

**2. EEO Officer:** The contractor will designate and make known to the contracting officers an EEO Officer who will have the responsibility for and must be capable of effectively administering and promoting an active EEO program and who must be assigned adequate authority and responsibility to do so.

**3. Dissemination of Policy:** All members of the contractor's staff who are authorized to hire, supervise, promote, and discharge employees, or who recommend such action or are substantially involved in such action, will be made fully cognizant of and will implement the contractor's EEO policy and contractual responsibilities to provide EEO in each grade and classification of employment. To ensure that the above agreement will be met, the following actions will be taken as a minimum:

a. Periodic meetings of supervisory and personnel office employees will be conducted before the start of work and then not less often than once every six months, at which time the contractor's EEO policy and its implementation will be reviewed and explained. The meetings will be conducted by the EEO Officer or other knowledgeable company official.

b. All new supervisory or personnel office employees will be given a thorough indoctrination by the EEO Officer, covering all major aspects of the contractor's EEO obligations within thirty days following their reporting for duty with the contractor.

c. All personnel who are engaged in direct recruitment for the project will be instructed by the EEO Officer in the contractor's procedures for locating and hiring minorities and women.

d. Notices and posters setting forth the contractor's EEO policy will be placed in areas readily accessible to employees, applicants for employment and potential employees.

e. The contractor's EEO policy and the procedures to implement such policy will be brought to the attention of employees by means of meetings, employee handbooks, or other appropriate means.

**4. Recruitment:** When advertising for employees, the contractor will include in all advertisements for employees the notation: "An Equal Opportunity Employer." All such advertisements will be placed in publications having a large circulation among minorities and women in the area from which the project work force would normally be derived.

a. The contractor will, unless precluded by a valid bargaining agreement, conduct systematic and direct recruitment through public and private employee referral sources likely to yield qualified minorities and women. To meet this requirement, the contractor will identify sources of potential minority group employees and establish with such identified sources procedures whereby minority and women applicants may be referred to the contractor for employment consideration.

b. In the event the contractor has a valid bargaining agreement providing for exclusive hiring hall referrals, the contractor is expected to observe the provisions of that agreement to the extent that the system meets the contractor's compliance with EEO contract provisions. Where implementation of such an agreement has the effect of discriminating against minorities or women, or obligates the contractor to do the same, such implementation violates Federal nondiscrimination provisions.

c. The contractor will encourage its present employees to refer minorities and women as applicants for employment. Information and procedures with regard to referring such applicants will be discussed with employees.

**5. Personnel Actions:** Wages, working conditions, and employee benefits shall be established and administered, and personnel actions of every type, including hiring, upgrading, promotion, transfer, demotion, layoff, and termination, shall be taken without regard to race, color, religion, sex, sexual orientation, gender identity, national origin, age or disability. The following procedures shall be followed:

a. The contractor will conduct periodic inspections of project sites to ensure that working conditions and employee facilities do not indicate discriminatory treatment of project site personnel.

b. The contractor will periodically evaluate the spread of wages paid within each classification to determine any evidence of discriminatory wage practices.

c. The contractor will periodically review selected personnel actions in depth to determine whether there is evidence of discrimination. Where evidence is found, the contractor will promptly take corrective action. If the review indicates that the discrimination may extend beyond the actions reviewed, such corrective action shall include all affected persons.

d. The contractor will promptly investigate all complaints of alleged discrimination made to the contractor in connection with its obligations under this contract, will attempt to resolve such complaints, and will take appropriate corrective action

within a reasonable time. If the investigation indicates that the discrimination may affect persons other than the complainant, such corrective action shall include such other persons. Upon completion of each investigation, the contractor will inform every complainant of all of their avenues of appeal.

#### **6. Training and Promotion:**

a. The contractor will assist in locating, qualifying, and increasing the skills of minorities and women who are applicants for employment or current employees. Such efforts should be aimed at developing full journey level status employees in the type of trade or job classification involved.

b. Consistent with the contractor's work force requirements and as permissible under Federal and State regulations, the contractor shall make full use of training programs (i.e., apprenticeship and on-the-job training programs for the geographical area of contract performance). In the event a special provision for training is provided under this contract, this subparagraph will be superseded as indicated in the special provision. The contracting agency may reserve training positions for persons who receive welfare assistance in accordance with 23 U.S.C. 140(a).

c. The contractor will advise employees and applicants for employment of available training programs and entrance requirements for each.

d. The contractor will periodically review the training and promotion potential of employees who are minorities and women and will encourage eligible employees to apply for such training and promotion.

**7. Unions:** If the contractor relies in whole or in part upon unions as a source of employees, the contractor will use good faith efforts to obtain the cooperation of such unions to increase opportunities for minorities and women. 23 CFR 230.409. Actions by the contractor, either directly or through a contractor's association acting as agent, will include the procedures set forth below:

a. The contractor will use good faith efforts to develop, in cooperation with the unions, joint training programs aimed toward qualifying more minorities and women for membership in the unions and increasing the skills of minorities and women so that they may qualify for higher paying employment.

b. The contractor will use good faith efforts to incorporate an EEO clause into each union agreement to the end that such union will be contractually bound to refer applicants without regard to their race, color, religion, sex, sexual orientation, gender identity, national origin, age, or disability.

c. The contractor is to obtain information as to the referral practices and policies of the labor union except that to the extent such information is within the exclusive possession of the labor union and such labor union refuses to furnish such information to the contractor, the contractor shall so certify to the contracting agency and shall set forth what efforts have been made to obtain such information.

d. In the event the union is unable to provide the contractor with a reasonable flow of referrals within the time limit set forth in the collective bargaining agreement, the contractor will, through independent recruitment efforts, fill the employment vacancies without regard to race, color, religion, sex, sexual orientation, gender identity, national origin, age, or disability; making full efforts to obtain qualified and/or qualifiable minorities and women. The failure of a union to provide

sufficient referrals (even though it is obligated to provide exclusive referrals under the terms of a collective bargaining agreement) does not relieve the contractor from the requirements of this paragraph. In the event the union referral practice prevents the contractor from meeting the obligations pursuant to Executive Order 11246, as amended, and these special provisions, such contractor shall immediately notify the contracting agency.

#### **8. Reasonable Accommodation for Applicants /**

**Employees with Disabilities:** The contractor must be familiar with the requirements for and comply with the Americans with Disabilities Act and all rules and regulations established thereunder. Employers must provide reasonable accommodation in all employment activities unless to do so would cause an undue hardship.

#### **9. Selection of Subcontractors, Procurement of Materials**

**and Leasing of Equipment:** The contractor shall not discriminate on the grounds of race, color, religion, sex, sexual orientation, gender identity, national origin, age, or disability in the selection and retention of subcontractors, including procurement of materials and leases of equipment. The contractor shall take all necessary and reasonable steps to ensure nondiscrimination in the administration of this contract.

a. The contractor shall notify all potential subcontractors, suppliers, and lessors of their EEO obligations under this contract.

b. The contractor will use good faith efforts to ensure subcontractor compliance with their EEO obligations.

#### **10. Assurances Required:**

a. The requirements of 49 CFR Part 26 and the State DOT's FHWA-approved Disadvantaged Business Enterprise (DBE) program are incorporated by reference.

b. The contractor, subrecipient or subcontractor shall not discriminate on the basis of race, color, national origin, or sex in the performance of this contract. The contractor shall carry out applicable requirements of 49 CFR part 26 in the award and administration of DOT-assisted contracts. Failure by the contractor to carry out these requirements is a material breach of this contract, which may result in the termination of this contract or such other remedy as the recipient deems appropriate, which may include, but is not limited to:

- (1) Withholding monthly progress payments;
- (2) Assessing sanctions;
- (3) Liquidated damages; and/or
- (4) Disqualifying the contractor from future bidding as non-responsible.

c. The Title VI and nondiscrimination provisions of U.S. DOT Order 1050.2A at Appendixes A and E are incorporated by reference. 49 CFR Part 21.

**11. Records and Reports:** The contractor shall keep such records as necessary to document compliance with the EEO requirements. Such records shall be retained for a period of three years following the date of the final payment to the contractor for all contract work and shall be available at reasonable times and places for inspection by authorized representatives of the contracting agency and the FHWA.

a. The records kept by the contractor shall document the following:

(1) The number and work hours of minority and non-minority group members and women employed in each work classification on the project;

(2) The progress and efforts being made in cooperation with unions, when applicable, to increase employment opportunities for minorities and women; and

(3) The progress and efforts being made in locating, hiring, training, qualifying, and upgrading minorities and women.

b. The contractors and subcontractors will submit an annual report to the contracting agency each July for the duration of the project indicating the number of minority, women, and non-minority group employees currently engaged in each work classification required by the contract work. This information is to be reported on [Form FHWA-1391](#). The staffing data should represent the project work force on board in all or any part of the last payroll period preceding the end of July. If on-the-job training is being required by special provision, the contractor will be required to collect and report training data. The employment data should reflect the work force on board during all or any part of the last payroll period preceding the end of July.

### III. NONSEGREGATED FACILITIES

This provision is applicable to all Federal-aid construction contracts and to all related construction subcontracts of more than \$10,000. 41 CFR 60-1.5.

As prescribed by 41 CFR 60-1.8, the contractor must ensure that facilities provided for employees are provided in such a manner that segregation on the basis of race, color, religion, sex, sexual orientation, gender identity, or national origin cannot result. The contractor may neither require such segregated use by written or oral policies nor tolerate such use by employee custom. The contractor's obligation extends further to ensure that its employees are not assigned to perform their services at any location under the contractor's control where the facilities are segregated. The term "facilities" includes waiting rooms, work areas, restaurants and other eating areas, time clocks, restrooms, washrooms, locker rooms and other storage or dressing areas, parking lots, drinking fountains, recreation or entertainment areas, transportation, and housing provided for employees. The contractor shall provide separate or single-user restrooms and necessary dressing or sleeping areas to assure privacy between sexes.

### IV. DAVIS-BACON AND RELATED ACT PROVISIONS

This section is applicable to all Federal-aid construction projects exceeding \$2,000 and to all related subcontracts and lower-tier subcontracts (regardless of subcontract size), in accordance with 29 CFR 5.5. The requirements apply to all projects located within the right-of-way of a roadway that is functionally classified as Federal-aid highway. 23 U.S.C. 113. This excludes roadways functionally classified as local roads or rural minor collectors, which are exempt. 23 U.S.C. 101. Where applicable law requires that projects be treated as a project on a Federal-aid highway, the provisions of this subpart will apply regardless of the location of the project. Examples include: Surface Transportation Block Grant Program projects funded under 23 U.S.C. 133 [excluding recreational trails projects], the Nationally Significant Freight and Highway

Projects funded under 23 U.S.C. 117, and National Highway Freight Program projects funded under 23 U.S.C. 167.

The following provisions are from the U.S. Department of Labor regulations in 29 CFR 5.5 "Contract provisions and related matters" with minor revisions to conform to the FHWA-1273 format and FHWA program requirements.

#### 1. Minimum wages (29 CFR 5.5)

a. *Wage rates and fringe benefits.* All laborers and mechanics employed or working upon the site of the work (or otherwise working in construction or development of the project under a development statute), will be paid unconditionally and not less often than once a week, and without subsequent deduction or rebate on any account (except such payroll deductions as are permitted by regulations issued by the Secretary of Labor under the Copeland Act ([29 CFR part 3](#))), the full amount of basic hourly wages and bona fide fringe benefits (or cash equivalents thereof) due at time of payment computed at rates not less than those contained in the wage determination of the Secretary of Labor which is attached hereto and made a part hereof, regardless of any contractual relationship which may be alleged to exist between the contractor and such laborers and mechanics. As provided in paragraphs (d) and (e) of 29 CFR 5.5, the appropriate wage determinations are effective by operation of law even if they have not been attached to the contract. Contributions made or costs reasonably anticipated for bona fide fringe benefits under the Davis-Bacon Act ([40 U.S.C. 3141\(2\)\(B\)](#)) on behalf of laborers or mechanics are considered wages paid to such laborers or mechanics, subject to the provisions of paragraph 1.e. of this section; also, regular contributions made or costs incurred for more than a weekly period (but not less often than quarterly) under plans, funds, or programs which cover the particular weekly period, are deemed to be constructively made or incurred during such weekly period. Such laborers and mechanics must be paid the appropriate wage rate and fringe benefits on the wage determination for the classification(s) of work actually performed, without regard to skill, except as provided in paragraph 4. of this section. Laborers or mechanics performing work in more than one classification may be compensated at the rate specified for each classification for the time actually worked therein: *Provided*, That the employer's payroll records accurately set forth the time spent in each classification in which work is performed. The wage determination (including any additional classifications and wage rates conformed under paragraph 1.c. of this section) and the Davis-Bacon poster (WH-1321) must be posted at all times by the contractor and its subcontractors at the site of the work in a prominent and accessible place where it can be easily seen by the workers.

b. *Frequently recurring classifications.* (1) In addition to wage and fringe benefit rates that have been determined to be prevailing under the procedures set forth in [29 CFR part 1](#), a wage determination may contain, pursuant to § 1.3(f), wage and fringe benefit rates for classifications of laborers and mechanics for which conformance requests are regularly submitted pursuant to paragraph 1.c. of this section, provided that:

(i) The work performed by the classification is not performed by a classification in the wage determination for which a prevailing wage rate has been determined;

(ii) The classification is used in the area by the construction industry; and

(iii) The wage rate for the classification bears a reasonable relationship to the prevailing wage rates contained in the wage determination.

(2) The Administrator will establish wage rates for such classifications in accordance with paragraph 1.c.(1)(iii) of this section. Work performed in such a classification must be paid at no less than the wage and fringe benefit rate listed on the wage determination for such classification.

c. *Conformance.* (1) The contracting officer must require that any class of laborers or mechanics, including helpers, which is not listed in the wage determination and which is to be employed under the contract be classified in conformance with the wage determination. Conformance of an additional classification and wage rate and fringe benefits is appropriate only when the following criteria have been met:

(i) The work to be performed by the classification requested is not performed by a classification in the wage determination; and

(ii) The classification is used in the area by the construction industry; and

(iii) The proposed wage rate, including any bona fide fringe benefits, bears a reasonable relationship to the wage rates contained in the wage determination.

(2) The conformance process may not be used to split, subdivide, or otherwise avoid application of classifications listed in the wage determination.

(3) If the contractor and the laborers and mechanics to be employed in the classification (if known), or their representatives, and the contracting officer agree on the classification and wage rate (including the amount designated for fringe benefits where appropriate), a report of the action taken will be sent by the contracting officer by email to [DBAconformance@dol.gov](mailto:DBAconformance@dol.gov). The Administrator, or an authorized representative, will approve, modify, or disapprove every additional classification action within 30 days of receipt and so advise the contracting officer or will notify the contracting officer within the 30-day period that additional time is necessary.

(4) In the event the contractor, the laborers or mechanics to be employed in the classification or their representatives, and the contracting officer do not agree on the proposed classification and wage rate (including the amount designated for fringe benefits, where appropriate), the contracting officer will, by email to [DBAconformance@dol.gov](mailto:DBAconformance@dol.gov), refer the questions, including the views of all interested parties and the recommendation of the contracting officer, to the Administrator for determination. The Administrator, or an authorized representative, will issue a determination within 30 days of receipt and so advise the contracting officer or will notify the contracting officer within the 30-day period that additional time is necessary.

(5) The contracting officer must promptly notify the contractor of the action taken by the Wage and Hour Division

under paragraphs 1.c.(3) and (4) of this section. The contractor must furnish a written copy of such determination to each affected worker or it must be posted as a part of the wage determination. The wage rate (including fringe benefits where appropriate) determined pursuant to paragraph 1.c.(3) or (4) of this section must be paid to all workers performing work in the classification under this contract from the first day on which work is performed in the classification.

d. *Fringe benefits not expressed as an hourly rate.* Whenever the minimum wage rate prescribed in the contract for a class of laborers or mechanics includes a fringe benefit which is not expressed as an hourly rate, the contractor may either pay the benefit as stated in the wage determination or may pay another bona fide fringe benefit or an hourly cash equivalent thereof.

e. *Unfunded plans.* If the contractor does not make payments to a trustee or other third person, the contractor may consider as part of the wages of any laborer or mechanic the amount of any costs reasonably anticipated in providing bona fide fringe benefits under a plan or program, *Provided*, That the Secretary of Labor has found, upon the written request of the contractor, in accordance with the criteria set forth in § 5.28, that the applicable standards of the Davis-Bacon Act have been met. The Secretary of Labor may require the contractor to set aside in a separate account assets for the meeting of obligations under the plan or program.

f. *Interest.* In the event of a failure to pay all or part of the wages required by the contract, the contractor will be required to pay interest on any underpayment of wages.

## 2. Withholding (29 CFR 5.5)

a. *Withholding requirements.* The contracting agency may, upon its own action, or must, upon written request of an authorized representative of the Department of Labor, withhold or cause to be withheld from the contractor so much of the accrued payments or advances as may be considered necessary to satisfy the liabilities of the prime contractor or any subcontractor for the full amount of wages and monetary relief, including interest, required by the clauses set forth in this section for violations of this contract, or to satisfy any such liabilities required by any other Federal contract, or federally assisted contract subject to Davis-Bacon labor standards, that is held by the same prime contractor (as defined in § 5.2). The necessary funds may be withheld from the contractor under this contract, any other Federal contract with the same prime contractor, or any other federally assisted contract that is subject to Davis-Bacon labor standards requirements and is held by the same prime contractor, regardless of whether the other contract was awarded or assisted by the same agency, and such funds may be used to satisfy the contractor liability for which the funds were withheld. In the event of a contractor's failure to pay any laborer or mechanic, including any apprentice or helper working on the site of the work all or part of the wages required by the contract, or upon the contractor's failure to submit the required records as discussed in paragraph 3.d. of this section, the contracting agency may on its own initiative and after written notice to the contractor, take such action as may be necessary to cause the suspension of any further payment, advance, or guarantee of funds until such violations have ceased.

b. *Priority to withheld funds.* The Department has priority to funds withheld or to be withheld in accordance with paragraph

2.a. of this section or Section V, paragraph 3.a., or both, over claims to those funds by:

- (1) A contractor's surety(ies), including without limitation performance bond sureties and payment bond sureties;
- (2) A contracting agency for its procurement costs;
- (3) A trustee(s) (either a court-appointed trustee or a U.S. trustee, or both) in bankruptcy of a contractor, or a contractor's bankruptcy estate;
- (4) A contractor's assignee(s);
- (5) A contractor's successor(s); or
- (6) A claim asserted under the Prompt Payment Act, [31 U.S.C. 3901–3907](#).

### 3. Records and certified payrolls (29 CFR 5.5)

a. *Basic record requirements* (1) *Length of record retention.* All regular payrolls and other basic records must be maintained by the contractor and any subcontractor during the course of the work and preserved for all laborers and mechanics working at the site of the work (or otherwise working in construction or development of the project under a development statute) for a period of at least 3 years after all the work on the prime contract is completed.

(2) *Information required.* Such records must contain the name; Social Security number; last known address, telephone number, and email address of each such worker; each worker's correct classification(s) of work actually performed; hourly rates of wages paid (including rates of contributions or costs anticipated for bona fide fringe benefits or cash equivalents thereof of the types described in [40 U.S.C. 3141\(2\)\(B\)](#) of the Davis-Bacon Act); daily and weekly number of hours actually worked in total and on each covered contract; deductions made; and actual wages paid.

(3) *Additional records relating to fringe benefits.* Whenever the Secretary of Labor has found under paragraph 1.e. of this section that the wages of any laborer or mechanic include the amount of any costs reasonably anticipated in providing benefits under a plan or program described in [40 U.S.C. 3141\(2\)\(B\)](#) of the Davis-Bacon Act, the contractor must maintain records which show that the commitment to provide such benefits is enforceable, that the plan or program is financially responsible, and that the plan or program has been communicated in writing to the laborers or mechanics affected, and records which show the costs anticipated or the actual cost incurred in providing such benefits.

(4) *Additional records relating to apprenticeship.* Contractors with apprentices working under approved programs must maintain written evidence of the registration of apprenticeship programs, the registration of the apprentices, and the ratios and wage rates prescribed in the applicable programs.

b. *Certified payroll requirements* (1) *Frequency and method of submission.* The contractor or subcontractor must submit weekly, for each week in which any DBA- or Related Acts-covered work is performed, certified payrolls to the contracting

agency. The prime contractor is responsible for the submission of all certified payrolls by all subcontractors. A contracting agency or prime contractor may permit or require contractors to submit certified payrolls through an electronic system, as long as the electronic system requires a legally valid electronic signature; the system allows the contractor, the contracting agency, and the Department of Labor to access the certified payrolls upon request for at least 3 years after the work on the prime contract has been completed; and the contracting agency or prime contractor permits other methods of submission in situations where the contractor is unable or limited in its ability to use or access the electronic system.

(2) *Information required.* The certified payrolls submitted must set out accurately and completely all of the information required to be maintained under paragraph 3.a.(2) of this section, except that full Social Security numbers and last known addresses, telephone numbers, and email addresses must not be included on weekly transmittals. Instead, the certified payrolls need only include an individually identifying number for each worker (e.g., the last four digits of the worker's Social Security number). The required weekly certified payroll information may be submitted using Optional Form WH-347 or in any other format desired. Optional Form WH-347 is available for this purpose from the Wage and Hour Division website at <https://www.dol.gov/sites/dolgov/files/WHDL/legacy/files/wh347.pdf> or its successor website. It is not a violation of this section for a prime contractor to require a subcontractor to provide full Social Security numbers and last known addresses, telephone numbers, and email addresses to the prime contractor for its own records, without weekly submission by the subcontractor to the contracting agency.

(3) *Statement of Compliance.* Each certified payroll submitted must be accompanied by a "Statement of Compliance," signed by the contractor or subcontractor, or the contractor's or subcontractor's agent who pays or supervises the payment of the persons working on the contract, and must certify the following:

(i) That the certified payroll for the payroll period contains the information required to be provided under paragraph 3.b. of this section, the appropriate information and basic records are being maintained under paragraph 3.a. of this section, and such information and records are correct and complete;

(ii) That each laborer or mechanic (including each helper and apprentice) working on the contract during the payroll period has been paid the full weekly wages earned, without rebate, either directly or indirectly, and that no deductions have been made either directly or indirectly from the full wages earned, other than permissible deductions as set forth in [29 CFR part 3](#); and

(iii) That each laborer or mechanic has been paid not less than the applicable wage rates and fringe benefits or cash equivalents for the classification(s) of work actually performed, as specified in the applicable wage determination incorporated into the contract.

(4) *Use of Optional Form WH-347.* The weekly submission of a properly executed certification set forth on the reverse side of Optional Form WH-347 will satisfy the requirement for submission of the "Statement of Compliance" required by paragraph 3.b.(3) of this section.

(5) *Signature.* The signature by the contractor, subcontractor, or the contractor's or subcontractor's agent must be an original handwritten signature or a legally valid electronic signature.

(6) *Falsification.* The falsification of any of the above certifications may subject the contractor or subcontractor to civil or criminal prosecution under [18 U.S.C. 1001](#) and [31 U.S.C. 3729](#).

(7) *Length of certified payroll retention.* The contractor or subcontractor must preserve all certified payrolls during the course of the work and for a period of 3 years after all the work on the prime contract is completed.

c. *Contracts, subcontracts, and related documents.* The contractor or subcontractor must maintain this contract or subcontract and related documents including, without limitation, bids, proposals, amendments, modifications, and extensions. The contractor or subcontractor must preserve these contracts, subcontracts, and related documents during the course of the work and for a period of 3 years after all the work on the prime contract is completed.

d. *Required disclosures and access* (1) *Required record disclosures and access to workers.* The contractor or subcontractor must make the records required under paragraphs 3.a. through 3.c. of this section, and any other documents that the contracting agency, the State DOT, the FHWA, or the Department of Labor deems necessary to determine compliance with the labor standards provisions of any of the applicable statutes referenced by § 5.1, available for inspection, copying, or transcription by authorized representatives of the contracting agency, the State DOT, the FHWA, or the Department of Labor, and must permit such representatives to interview workers during working hours on the job.

(2) *Sanctions for non-compliance with records and worker access requirements.* If the contractor or subcontractor fails to submit the required records or to make them available, or refuses to permit worker interviews during working hours on the job, the Federal agency may, after written notice to the contractor, sponsor, applicant, owner, or other entity, as the case may be, that maintains such records or that employs such workers, take such action as may be necessary to cause the suspension of any further payment, advance, or guarantee of funds. Furthermore, failure to submit the required records upon request or to make such records available, or to permit worker interviews during working hours on the job, may be grounds for debarment action pursuant to § 5.12. In addition, any contractor or other person that fails to submit the required records or make those records available to WHD within the time WHD requests that the records be produced will be precluded from introducing as evidence in an administrative proceeding under [29 CFR part 6](#) any of the required records that were not provided or made available to WHD. WHD will take into consideration a reasonable request from the contractor or person for an extension of the time for submission of records. WHD will determine the reasonableness of the request and may consider, among other things, the location of the records and the volume of production.

(3) *Required information disclosures.* Contractors and subcontractors must maintain the full Social Security number and last known address, telephone number, and email address

of each covered worker, and must provide them upon request to the contracting agency, the State DOT, the FHWA, the contractor, or the Wage and Hour Division of the Department of Labor for purposes of an investigation or other compliance action.

#### **4. Apprentices and equal employment opportunity (29 CFR 5.5)**

a. *Apprentices (1) Rate of pay.* Apprentices will be permitted to work at less than the predetermined rate for the work they perform when they are employed pursuant to and individually registered in a bona fide apprenticeship program registered with the U.S. Department of Labor, Employment and Training Administration, Office of Apprenticeship (OA), or with a State Apprenticeship Agency recognized by the OA. A person who is not individually registered in the program, but who has been certified by the OA or a State Apprenticeship Agency (where appropriate) to be eligible for probationary employment as an apprentice, will be permitted to work at less than the predetermined rate for the work they perform in the first 90 days of probationary employment as an apprentice in such a program. In the event the OA or a State Apprenticeship Agency recognized by the OA withdraws approval of an apprenticeship program, the contractor will no longer be permitted to use apprentices at less than the applicable predetermined rate for the work performed until an acceptable program is approved.

(2) *Fringe benefits.* Apprentices must be paid fringe benefits in accordance with the provisions of the apprenticeship program. If the apprenticeship program does not specify fringe benefits, apprentices must be paid the full amount of fringe benefits listed on the wage determination for the applicable classification. If the Administrator determines that a different practice prevails for the applicable apprentice classification, fringe benefits must be paid in accordance with that determination.

(3) *Apprenticeship ratio.* The allowable ratio of apprentices to journeyworkers on the job site in any craft classification must not be greater than the ratio permitted to the contractor as to the entire work force under the registered program or the ratio applicable to the locality of the project pursuant to paragraph 4.a.(4) of this section. Any worker listed on a payroll at an apprentice wage rate, who is not registered or otherwise employed as stated in paragraph 4.a.(1) of this section, must be paid not less than the applicable wage rate on the wage determination for the classification of work actually performed. In addition, any apprentice performing work on the job site in excess of the ratio permitted under this section must be paid not less than the applicable wage rate on the wage determination for the work actually performed.

(4) *Reciprocity of ratios and wage rates.* Where a contractor is performing construction on a project in a locality other than the locality in which its program is registered, the ratios and wage rates (expressed in percentages of the journeyworker's hourly rate) applicable within the locality in which the construction is being performed must be observed. If there is no applicable ratio or wage rate for the locality of the project, the ratio and wage rate specified in the contractor's registered program must be observed.

b. *Equal employment opportunity.* The use of apprentices and journeyworkers under this part must be in conformity with

the equal employment opportunity requirements of Executive Order 11246, as amended, and [29 CFR part 30](#).

c. Apprentices and Trainees (programs of the U.S. DOT).

Apprentices and trainees working under apprenticeship and skill training programs which have been certified by the Secretary of Transportation as promoting EEO in connection with Federal-aid highway construction programs are not subject to the requirements of paragraph 4 of this Section IV. 23 CFR 230.111(e)(2). The straight time hourly wage rates for apprentices and trainees under such programs will be established by the particular programs. The ratio of apprentices and trainees to journeyworkers shall not be greater than permitted by the terms of the particular program.

**5. Compliance with Copeland Act requirements.** The contractor shall comply with the requirements of 29 CFR part 3, which are incorporated by reference in this contract as provided in 29 CFR 5.5.

**6. Subcontracts.** The contractor or subcontractor must insert FHWA-1273 in any subcontracts, along with the applicable wage determination(s) and such other clauses or contract modifications as the contracting agency may by appropriate instructions require, and a clause requiring the subcontractors to include these clauses and wage determination(s) in any lower tier subcontracts. The prime contractor is responsible for the compliance by any subcontractor or lower tier subcontractor with all the contract clauses in this section. In the event of any violations of these clauses, the prime contractor and any subcontractor(s) responsible will be liable for any unpaid wages and monetary relief, including interest from the date of the underpayment or loss, due to any workers of lower-tier subcontractors, and may be subject to debarment, as appropriate. 29 CFR 5.5.

**7. Contract termination: debarment.** A breach of the contract clauses in 29 CFR 5.5 may be grounds for termination of the contract, and for debarment as a contractor and a subcontractor as provided in 29 CFR 5.12.

**8. Compliance with Davis-Bacon and Related Act requirements.** All rulings and interpretations of the Davis-Bacon and Related Acts contained in 29 CFR parts 1, 3, and 5 are herein incorporated by reference in this contract as provided in 29 CFR 5.5.

**9. Disputes concerning labor standards.** As provided in 29 CFR 5.5, disputes arising out of the labor standards provisions of this contract shall not be subject to the general disputes clause of this contract. Such disputes shall be resolved in accordance with the procedures of the Department of Labor set forth in 29 CFR parts 5, 6, and 7. Disputes within the meaning of this clause include disputes between the contractor (or any of its subcontractors) and the contracting agency, the U.S. Department of Labor, or the employees or their representatives.

**10. Certification of eligibility.** a. By entering into this contract, the contractor certifies that neither it nor any person or firm who has an interest in the contractor's firm is a person or firm ineligible to be awarded Government contracts by virtue of [40 U.S.C. 3144\(b\)](#) or § 5.12(a).

b. No part of this contract shall be subcontracted to any person or firm ineligible for award of a Government contract by virtue of [40 U.S.C. 3144\(b\)](#) or § 5.12(a).

c. The penalty for making false statements is prescribed in the U.S. Code, Title 18 Crimes and Criminal Procedure, [18 U.S.C. 1001](#).

**11. Anti-retaliation.** It is unlawful for any person to discharge, demote, intimidate, threaten, restrain, coerce, blacklist, harass, or in any other manner discriminate against, or to cause any person to discharge, demote, intimidate, threaten, restrain, coerce, blacklist, harass, or in any other manner discriminate against, any worker or job applicant for:

a. Notifying any contractor of any conduct which the worker reasonably believes constitutes a violation of the DBA, Related Acts, this part, or [29 CFR part 1](#) or [3](#);

b. Filing any complaint, initiating or causing to be initiated any proceeding, or otherwise asserting or seeking to assert on behalf of themselves or others any right or protection under the DBA, Related Acts, this part, or [29 CFR part 1](#) or [3](#);

c. Cooperating in any investigation or other compliance action, or testifying in any proceeding under the DBA, Related Acts, this part, or [29 CFR part 1](#) or [3](#); or

d. Informing any other person about their rights under the DBA, Related Acts, this part, or [29 CFR part 1](#) or [3](#).

## **V. CONTRACT WORK HOURS AND SAFETY STANDARDS ACT**

Pursuant to 29 CFR 5.5(b), the following clauses apply to any Federal-aid construction contract in an amount in excess of \$100,000 and subject to the overtime provisions of the Contract Work Hours and Safety Standards Act. These clauses shall be inserted in addition to the clauses required by 29 CFR 5.5(a) or 29 CFR 4.6. As used in this paragraph, the terms laborers and mechanics include watchpersons and guards.

**1. Overtime requirements.** No contractor or subcontractor contracting for any part of the contract work which may require or involve the employment of laborers or mechanics shall require or permit any such laborer or mechanic in any workweek in which he or she is employed on such work to work in excess of forty hours in such workweek unless such laborer or mechanic receives compensation at a rate not less than one and one-half times the basic rate of pay for all hours worked in excess of forty hours in such workweek. 29 CFR 5.5.

**2. Violation; liability for unpaid wages; liquidated damages.** In the event of any violation of the clause set forth in paragraph 1. of this section the contractor and any subcontractor responsible therefor shall be liable for the unpaid wages and interest from the date of the underpayment. In addition, such contractor and subcontractor shall be liable to the United States (in the case of work done under contract for the District of Columbia or a territory, to such District or to such territory), for liquidated damages. Such liquidated damages shall be computed with respect to each individual laborer or

mechanic, including watchpersons and guards, employed in violation of the clause set forth in paragraph 1. of this section, in the sum currently provided in 29 CFR 5.5(b)(2)\* for each calendar day on which such individual was required or permitted to work in excess of the standard workweek of forty hours without payment of the overtime wages required by the clause set forth in paragraph 1. of this section.

\* \$31 as of January 15, 2023 (See 88 FR 88 FR 2210) as may be adjusted annually by the Department of Labor, pursuant to the Federal Civil Penalties Inflation Adjustment Act of 1990.

### 3. Withholding for unpaid wages and liquidated damages

a. *Withholding process.* The FHWA or the contracting agency may, upon its own action, or must, upon written request of an authorized representative of the Department of Labor, withhold or cause to be withheld from the contractor so much of the accrued payments or advances as may be considered necessary to satisfy the liabilities of the prime contractor or any subcontractor for any unpaid wages; monetary relief, including interest; and liquidated damages required by the clauses set forth in this section on this contract, any other Federal contract with the same prime contractor, or any other federally assisted contract subject to the Contract Work Hours and Safety Standards Act that is held by the same prime contractor (as defined in § 5.2). The necessary funds may be withheld from the contractor under this contract, any other Federal contract with the same prime contractor, or any other federally assisted contract that is subject to the Contract Work Hours and Safety Standards Act and is held by the same prime contractor, regardless of whether the other contract was awarded or assisted by the same agency, and such funds may be used to satisfy the contractor liability for which the funds were withheld.

b. *Priority to withheld funds.* The Department has priority to funds withheld or to be withheld in accordance with Section IV paragraph 2.a. or paragraph 3.a. of this section, or both, over claims to those funds by:

- (1) A contractor's surety(ies), including without limitation performance bond sureties and payment bond sureties;
- (2) A contracting agency for its procurement costs;
- (3) A trustee(s) (either a court-appointed trustee or a U.S. trustee, or both) in bankruptcy of a contractor, or a contractor's bankruptcy estate;
- (4) A contractor's assignee(s);
- (5) A contractor's successor(s); or
- (6) A claim asserted under the Prompt Payment Act, [31 U.S.C. 3901](#)–3907.

**4. Subcontracts.** The contractor or subcontractor must insert in any subcontracts the clauses set forth in paragraphs 1. through 5. of this section and a clause requiring the subcontractors to include these clauses in any lower tier subcontracts. The prime contractor is responsible for compliance by any subcontractor or lower tier subcontractor with the clauses set forth in paragraphs 1. through 5. In the

event of any violations of these clauses, the prime contractor and any subcontractor(s) responsible will be liable for any unpaid wages and monetary relief, including interest from the date of the underpayment or loss, due to any workers of lower-tier subcontractors, and associated liquidated damages and may be subject to debarment, as appropriate.

**5. Anti-retaliation.** It is unlawful for any person to discharge, demote, intimidate, threaten, restrain, coerce, blacklist, harass, or in any other manner discriminate against, or to cause any person to discharge, demote, intimidate, threaten, restrain, coerce, blacklist, harass, or in any other manner discriminate against, any worker or job applicant for:

- a. Notifying any contractor of any conduct which the worker reasonably believes constitutes a violation of the Contract Work Hours and Safety Standards Act (CWHSSA) or its implementing regulations in this part;
- b. Filing any complaint, initiating or causing to be initiated any proceeding, or otherwise asserting or seeking to assert on behalf of themselves or others any right or protection under CWHSSA or this part;
- c. Cooperating in any investigation or other compliance action, or testifying in any proceeding under CWHSSA or this part; or
- d. Informing any other person about their rights under CWHSSA or this part.

## VI. SUBLETTING OR ASSIGNING THE CONTRACT

This provision is applicable to all Federal-aid construction contracts on the National Highway System pursuant to 23 CFR 635.116.

1. The contractor shall perform with its own organization contract work amounting to not less than 30 percent (or a greater percentage if specified elsewhere in the contract) of the total original contract price, excluding any specialty items designated by the contracting agency. Specialty items may be performed by subcontract and the amount of any such specialty items performed may be deducted from the total original contract price before computing the amount of work required to be performed by the contractor's own organization (23 CFR 635.116).

a. The term "perform work with its own organization" in paragraph 1 of Section VI refers to workers employed or leased by the prime contractor, and equipment owned or rented by the prime contractor, with or without operators. Such term does not include employees or equipment of a subcontractor or lower tier subcontractor, agents of the prime contractor, or any other assignees. The term may include payments for the costs of hiring leased employees from an employee leasing firm meeting all relevant Federal and State regulatory requirements. Leased employees may only be included in this term if the prime contractor meets all of the following conditions: (based on longstanding interpretation)

- (1) the prime contractor maintains control over the supervision of the day-to-day activities of the leased employees;
- (2) the prime contractor remains responsible for the quality of the work of the leased employees;

(3) the prime contractor retains all power to accept or exclude individual employees from work on the project; and

(4) the prime contractor remains ultimately responsible for the payment of predetermined minimum wages, the submission of payrolls, statements of compliance and all other Federal regulatory requirements.

b. "Specialty Items" shall be construed to be limited to work that requires highly specialized knowledge, abilities, or equipment not ordinarily available in the type of contracting organizations qualified and expected to bid or propose on the contract as a whole and in general are to be limited to minor components of the overall contract. 23 CFR 635.102.

2. Pursuant to 23 CFR 635.116(a), the contract amount upon which the requirements set forth in paragraph (1) of Section VI is computed includes the cost of material and manufactured products which are to be purchased or produced by the contractor under the contract provisions.

3. Pursuant to 23 CFR 635.116(c), the contractor shall furnish (a) a competent superintendent or supervisor who is employed by the firm, has full authority to direct performance of the work in accordance with the contract requirements, and is in charge of all construction operations (regardless of who performs the work) and (b) such other of its own organizational resources (supervision, management, and engineering services) as the contracting officer determines is necessary to assure the performance of the contract.

4. No portion of the contract shall be sublet, assigned or otherwise disposed of except with the written consent of the contracting officer, or authorized representative, and such consent when given shall not be construed to relieve the contractor of any responsibility for the fulfillment of the contract. Written consent will be given only after the contracting agency has assured that each subcontract is evidenced in writing and that it contains all pertinent provisions and requirements of the prime contract. (based on long-standing interpretation of 23 CFR 635.116).

5. The 30-percent self-performance requirement of paragraph (1) is not applicable to design-build contracts; however, contracting agencies may establish their own self-performance requirements. 23 CFR 635.116(d).

## **VII. SAFETY: ACCIDENT PREVENTION**

This provision is applicable to all Federal-aid construction contracts and to all related subcontracts.

1. In the performance of this contract the contractor shall comply with all applicable Federal, State, and local laws governing safety, health, and sanitation (23 CFR Part 635). The contractor shall provide all safeguards, safety devices and protective equipment and take any other needed actions as it determines, or as the contracting officer may determine, to be reasonably necessary to protect the life and health of employees on the job and the safety of the public and to protect property in connection with the performance of the work covered by the contract. 23 CFR 635.108.

2. It is a condition of this contract, and shall be made a condition of each subcontract, which the contractor enters into pursuant to this contract, that the contractor and any subcontractor shall not permit any employee, in performance of the contract, to work in surroundings or under conditions which are unsanitary, hazardous or dangerous to his/her health or safety, as determined under construction safety and

health standards (29 CFR Part 1926) promulgated by the Secretary of Labor, in accordance with Section 107 of the Contract Work Hours and Safety Standards Act (40 U.S.C. 3704). 29 CFR 1926.10.

3. Pursuant to 29 CFR 1926.3, it is a condition of this contract that the Secretary of Labor or authorized representative thereof, shall have right of entry to any site of contract performance to inspect or investigate the matter of compliance with the construction safety and health standards and to carry out the duties of the Secretary under Section 107 of the Contract Work Hours and Safety Standards Act (40 U.S.C. 3704).

## **VIII. FALSE STATEMENTS CONCERNING HIGHWAY PROJECTS**

This provision is applicable to all Federal-aid construction contracts and to all related subcontracts.

In order to assure high quality and durable construction in conformity with approved plans and specifications and a high degree of reliability on statements and representations made by engineers, contractors, suppliers, and workers on Federal-aid highway projects, it is essential that all persons concerned with the project perform their functions as carefully, thoroughly, and honestly as possible. Willful falsification, distortion, or misrepresentation with respect to any facts related to the project is a violation of Federal law. To prevent any misunderstanding regarding the seriousness of these and similar acts, Form FHWA-1022 shall be posted on each Federal-aid highway project (23 CFR Part 635) in one or more places where it is readily available to all persons concerned with the project:

18 U.S.C. 1020 reads as follows:

"Whoever, being an officer, agent, or employee of the United States, or of any State or Territory, or whoever, whether a person, association, firm, or corporation, knowingly makes any false statement, false representation, or false report as to the character, quality, quantity, or cost of the material used or to be used, or the quantity or quality of the work performed or to be performed, or the cost thereof in connection with the submission of plans, maps, specifications, contracts, or costs of construction on any highway or related project submitted for approval to the Secretary of Transportation; or

Whoever knowingly makes any false statement, false representation, false report or false claim with respect to the character, quality, quantity, or cost of any work performed or to be performed, or materials furnished or to be furnished, in connection with the construction of any highway or related project approved by the Secretary of Transportation; or

Whoever knowingly makes any false statement or false representation as to material fact in any statement, certificate, or report submitted pursuant to provisions of the Federal-aid Roads Act approved July 11, 1916, (39 Stat. 355), as amended and supplemented;

Shall be fined under this title or imprisoned not more than 5 years or both."

## **IX. IMPLEMENTATION OF CLEAN AIR ACT AND FEDERAL WATER POLLUTION CONTROL ACT (42 U.S.C. 7606; 2 CFR 200.88; EO 11738)**

This provision is applicable to all Federal-aid construction contracts in excess of \$150,000 and to all related subcontracts. 48 CFR 2.101; 2 CFR 200.327.

By submission of this bid/proposal or the execution of this contract or subcontract, as appropriate, the bidder, proposer, Federal-aid construction contractor, subcontractor, supplier, or vendor agrees to comply with all applicable standards, orders or regulations issued pursuant to the Clean Air Act (42 U.S.C. 7401-7671q) and the Federal Water Pollution Control Act, as amended (33 U.S.C. 1251-1387). Violations must be reported to the Federal Highway Administration and the Regional Office of the Environmental Protection Agency. 2 CFR Part 200, Appendix II.

The contractor agrees to include or cause to be included the requirements of this Section in every subcontract, and further agrees to take such action as the contracting agency may direct as a means of enforcing such requirements. 2 CFR 200.327.

## **X. CERTIFICATION REGARDING DEBARMENT, SUSPENSION, INELIGIBILITY AND VOLUNTARY EXCLUSION**

This provision is applicable to all Federal-aid construction contracts, design-build contracts, subcontracts, lower-tier subcontracts, purchase orders, lease agreements, consultant contracts or any other covered transaction requiring FHWA approval or that is estimated to cost \$25,000 or more – as defined in 2 CFR Parts 180 and 1200. 2 CFR 180.220 and 1200.220.

### **1. Instructions for Certification – First Tier Participants:**

a. By signing and submitting this proposal, the prospective first tier participant is providing the certification set out below.

b. The inability of a person to provide the certification set out below will not necessarily result in denial of participation in this covered transaction. The prospective first tier participant shall submit an explanation of why it cannot provide the certification set out below. The certification or explanation will be considered in connection with the department or agency's determination whether to enter into this transaction. However, failure of the prospective first tier participant to furnish a certification or an explanation shall disqualify such a person from participation in this transaction. 2 CFR 180.320.

c. The certification in this clause is a material representation of fact upon which reliance was placed when the contracting agency determined to enter into this transaction. If it is later determined that the prospective participant knowingly rendered an erroneous certification, in addition to other remedies available to the Federal Government, the contracting agency may terminate this transaction for cause of default. 2 CFR 180.325.

d. The prospective first tier participant shall provide immediate written notice to the contracting agency to whom this proposal is submitted if any time the prospective first tier participant learns that its certification was erroneous when submitted or has become erroneous by reason of changed circumstances. 2 CFR 180.345 and 180.350.

e. The terms "covered transaction," "debarred," "suspended," "ineligible," "participant," "person," "principal," and "voluntarily excluded," as used in this clause, are defined in 2 CFR Parts 180, Subpart I, 180.900-180.1020, and 1200. "First Tier Covered Transactions" refers to any covered transaction between a recipient or subrecipient of Federal funds and a participant (such as the prime or general contract). "Lower Tier Covered Transactions" refers to any covered transaction under a First Tier Covered Transaction (such as subcontracts). "First Tier Participant" refers to the participant who has entered into a covered transaction with a recipient or subrecipient of Federal funds (such as the prime or general contractor). "Lower Tier Participant" refers any participant who has entered into a covered transaction with a First Tier Participant or other Lower Tier Participants (such as subcontractors and suppliers).

f. The prospective first tier participant agrees by submitting this proposal that, should the proposed covered transaction be entered into, it shall not knowingly enter into any lower tier covered transaction with a person who is debarred, suspended, declared ineligible, or voluntarily excluded from participation in this covered transaction, unless authorized by the department or agency entering into this transaction. 2 CFR 180.330.

g. The prospective first tier participant further agrees by submitting this proposal that it will include the clause titled "Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion-Lower Tier Covered Transactions," provided by the department or contracting agency, entering into this covered transaction, without modification, in all lower tier covered transactions and in all solicitations for lower tier covered transactions exceeding the \$25,000 threshold. 2 CFR 180.220 and 180.300.

h. A participant in a covered transaction may rely upon a certification of a prospective participant in a lower tier covered transaction that is not debarred, suspended, ineligible, or voluntarily excluded from the covered transaction, unless it knows that the certification is erroneous. 2 CFR 180.300; 180.320, and 180.325. A participant is responsible for ensuring that its principals are not suspended, debarred, or otherwise ineligible to participate in covered transactions. 2 CFR 180.335. To verify the eligibility of its principals, as well as the eligibility of any lower tier prospective participants, each participant may, but is not required to, check the System for Award Management website (<https://www.sam.gov/>). 2 CFR 180.300, 180.320, and 180.325.

i. Nothing contained in the foregoing shall be construed to require the establishment of a system of records in order to render in good faith the certification required by this clause. The knowledge and information of the prospective participant is not required to exceed that which is normally possessed by a prudent person in the ordinary course of business dealings.

j. Except for transactions authorized under paragraph (f) of these instructions, if a participant in a covered transaction knowingly enters into a lower tier covered transaction with a person who is suspended, debarred, ineligible, or voluntarily excluded from participation in this transaction, in addition to other remedies available to the Federal Government, the department or agency may terminate this transaction for cause or default. 2 CFR 180.325.

\* \* \* \* \*

## **2. Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion – First Tier Participants:**

a. The prospective first tier participant certifies to the best of its knowledge and belief, that it and its principals:

(1) Are not presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from participating in covered transactions by any Federal department or agency, 2 CFR 180.335;.

(2) Have not within a three-year period preceding this proposal been convicted of or had a civil judgment rendered against them for commission of fraud or a criminal offense in connection with obtaining, attempting to obtain, or performing a public (Federal, State, or local) transaction or contract under a public transaction; violation of Federal or State antitrust statutes or commission of embezzlement, theft, forgery, bribery, falsification or destruction of records, making false statements, or receiving stolen property, 2 CFR 180.800;

(3) Are not presently indicted for or otherwise criminally or civilly charged by a governmental entity (Federal, State or local) with commission of any of the offenses enumerated in paragraph (a)(2) of this certification, 2 CFR 180.700 and 180.800; and

(4) Have not within a three-year period preceding this application/proposal had one or more public transactions (Federal, State or local) terminated for cause or default. 2 CFR 180.335(d).

(5) Are not a corporation that has been convicted of a felony violation under any Federal law within the two-year period preceding this proposal (USDOT Order 4200.6 implementing appropriations act requirements); and

(6) Are not a corporation with any unpaid Federal tax liability that has been assessed, for which all judicial and administrative remedies have been exhausted, or have lapsed, and that is not being paid in a timely manner pursuant to an agreement with the authority responsible for collecting the tax liability (USDOT Order 4200.6 implementing appropriations act requirements).

b. Where the prospective participant is unable to certify to any of the statements in this certification, such prospective participant should attach an explanation to this proposal. 2 CFR 180.335 and 180.340.

\*\*\*\*\*

## **3. Instructions for Certification - Lower Tier Participants:**

(Applicable to all subcontracts, purchase orders, and other lower tier transactions requiring prior FHWA approval or estimated to cost \$25,000 or more - 2 CFR Parts 180 and 1200). 2 CFR 180.220 and 1200.220.

a. By signing and submitting this proposal, the prospective lower tier participant is providing the certification set out below.

b. The certification in this clause is a material representation of fact upon which reliance was placed when this transaction was entered into. If it is later determined that the prospective lower tier participant knowingly rendered an erroneous certification, in addition to other remedies available to the Federal Government, the department, or agency with which

this transaction originated may pursue available remedies, including suspension and/or debarment.

c. The prospective lower tier participant shall provide immediate written notice to the person to which this proposal is submitted if at any time the prospective lower tier participant learns that its certification was erroneous by reason of changed circumstances. 2 CFR 180.365.

d. The terms "covered transaction," "debarred," "suspended," "ineligible," "participant," "person," "principal," and "voluntarily excluded," as used in this clause, are defined in 2 CFR Parts 180, Subpart I, 180.900 – 180.1020, and 1200. You may contact the person to which this proposal is submitted for assistance in obtaining a copy of those regulations. "First Tier Covered Transactions" refers to any covered transaction between a recipient or subrecipient of Federal funds and a participant (such as the prime or general contractor). "Lower Tier Covered Transactions" refers to any covered transaction under a First Tier Covered Transaction (such as subcontracts). "First Tier Participant" refers to the participant who has entered into a covered transaction with a recipient or subrecipient of Federal funds (such as the prime or general contractor). "Lower Tier Participant" refers any participant who has entered into a covered transaction with a First Tier Participant or other Lower Tier Participants (such as subcontractors and suppliers).

e. The prospective lower tier participant agrees by submitting this proposal that, should the proposed covered transaction be entered into, it shall not knowingly enter into any lower tier covered transaction with a person who is debarred, suspended, declared ineligible, or voluntarily excluded from participation in this covered transaction, unless authorized by the department or agency with which this transaction originated. 2 CFR 1200.220 and 1200.332.

f. The prospective lower tier participant further agrees by submitting this proposal that it will include this clause titled "Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion-Lower Tier Covered Transaction," without modification, in all lower tier covered transactions and in all solicitations for lower tier covered transactions exceeding the \$25,000 threshold. 2 CFR 180.220 and 1200.220.

g. A participant in a covered transaction may rely upon a certification of a prospective participant in a lower tier covered transaction that is not debarred, suspended, ineligible, or voluntarily excluded from the covered transaction, unless it knows that the certification is erroneous. A participant is responsible for ensuring that its principals are not suspended, debarred, or otherwise ineligible to participate in covered transactions. To verify the eligibility of its principals, as well as the eligibility of any lower tier prospective participants, each participant may, but is not required to, check the System for Award Management website (<https://www.sam.gov/>), which is compiled by the General Services Administration. 2 CFR 180.300, 180.320, 180.330, and 180.335.

h. Nothing contained in the foregoing shall be construed to require establishment of a system of records in order to render in good faith the certification required by this clause. The knowledge and information of participant is not required to exceed that which is normally possessed by a prudent person in the ordinary course of business dealings.

i. Except for transactions authorized under paragraph e of these instructions, if a participant in a covered transaction knowingly enters into a lower tier covered transaction with a person who is suspended, debarred, ineligible, or voluntarily

excluded from participation in this transaction, in addition to other remedies available to the Federal Government, the department or agency with which this transaction originated may pursue available remedies, including suspension and/or debarment. 2 CFR 180.325.

\* \* \* \* \*

#### **4. Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion--Lower Tier Participants:**

a. The prospective lower tier participant certifies, by submission of this proposal, that neither it nor its principals:

(1) is presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from participating in covered transactions by any Federal department or agency, 2 CFR 180.355;

(2) is a corporation that has been convicted of a felony violation under any Federal law within the two-year period preceding this proposal (USDOT Order 4200.6 implementing appropriations act requirements); and

(3) is a corporation with any unpaid Federal tax liability that has been assessed, for which all judicial and administrative remedies have been exhausted, or have lapsed, and that is not being paid in a timely manner pursuant to an agreement with the authority responsible for collecting the tax liability. (USDOT Order 4200.6 implementing appropriations act requirements)

b. Where the prospective lower tier participant is unable to certify to any of the statements in this certification, such prospective participant should attach an explanation to this proposal.

\* \* \* \* \*

#### **XI. CERTIFICATION REGARDING USE OF CONTRACT FUNDS FOR LOBBYING**

This provision is applicable to all Federal-aid construction contracts and to all related subcontracts which exceed \$100,000. 49 CFR Part 20, App. A.

1. The prospective participant certifies, by signing and submitting this bid or proposal, to the best of his or her knowledge and belief, that:

a. No Federal appropriated funds have been paid or will be paid, by or on behalf of the undersigned, to any person for influencing or attempting to influence an officer or employee of any Federal agency, a Member of Congress, an officer or employee of Congress, or an employee of a Member of Congress in connection with the awarding of any Federal contract, the making of any Federal grant, the making of any Federal loan, the entering into of any cooperative agreement, and the extension, continuation, renewal, amendment, or modification of any Federal contract, grant, loan, or cooperative agreement.

b. If any funds other than Federal appropriated funds have been paid or will be paid to any person for influencing or attempting to influence an officer or employee of any Federal agency, a Member of Congress, an officer or employee of Congress, or an employee of a Member of Congress in connection with this Federal contract, grant, loan, or

cooperative agreement, the undersigned shall complete and submit Standard Form-LLL, "Disclosure Form to Report Lobbying," in accordance with its instructions.

2. This certification is a material representation of fact upon which reliance was placed when this transaction was made or entered into. Submission of this certification is a prerequisite for making or entering into this transaction imposed by 31 U.S.C. 1352. Any person who fails to file the required certification shall be subject to a civil penalty of not less than \$10,000 and not more than \$100,000 for each such failure.

3. The prospective participant also agrees by submitting its bid or proposal that the participant shall require that the language of this certification be included in all lower tier subcontracts, which exceed \$100,000 and that all such recipients shall certify and disclose accordingly.

#### **XII. USE OF UNITED STATES-FLAG VESSELS:**

This provision is applicable to all Federal-aid construction contracts, design-build contracts, subcontracts, lower-tier subcontracts, purchase orders, lease agreements, or any other covered transaction. 46 CFR Part 381.

This requirement applies to material or equipment that is acquired for a specific Federal-aid highway project. 46 CFR 381.7. It is not applicable to goods or materials that come into inventories independent of an FHWA funded-contract.

When oceanic shipments (or shipments across the Great Lakes) are necessary for materials or equipment acquired for a specific Federal-aid construction project, the bidder, proposer, contractor, subcontractor, or vendor agrees:

1. To utilize privately owned United States-flag commercial vessels to ship at least 50 percent of the gross tonnage (computed separately for dry bulk carriers, dry cargo liners, and tankers) involved, whenever shipping any equipment, material, or commodities pursuant to this contract, to the extent such vessels are available at fair and reasonable rates for United States-flag commercial vessels. 46 CFR 381.7.

2. To furnish within 20 days following the date of loading for shipments originating within the United States or within 30 working days following the date of loading for shipments originating outside the United States, a legible copy of a rated, 'on-board' commercial ocean bill-of-lading in English for each shipment of cargo described in paragraph (b)(1) of this section to both the Contracting Officer (through the prime contractor in the case of subcontractor bills-of-lading) and to the Office of Cargo and Commercial Sealift (MAR-620), Maritime Administration, Washington, DC 20590. (MARAD requires copies of the ocean carrier's (master) bills of lading, certified onboard, dated, with rates and charges. These bills of lading may contain business sensitive information and therefore may be submitted directly to MARAD by the Ocean Transportation Intermediary on behalf of the contractor). 46 CFR 381.7.

**ATTACHMENT A - EMPLOYMENT AND MATERIALS  
PREFERENCE FOR APPALACHIAN DEVELOPMENT  
HIGHWAY SYSTEM OR APPALACHIAN LOCAL ACCESS  
ROAD CONTRACTS (23 CFR 633, Subpart B, Appendix B)**

This provision is applicable to all Federal-aid projects funded under the Appalachian Regional Development Act of 1965.

1. During the performance of this contract, the contractor undertaking to do work which is, or reasonably may be, done as on-site work, shall give preference to qualified persons who regularly reside in the labor area as designated by the DOL wherein the contract work is situated, or the subregion, or the Appalachian counties of the State wherein the contract work is situated, except:

a. To the extent that qualified persons regularly residing in the area are not available.

b. For the reasonable needs of the contractor to employ supervisory or specially experienced personnel necessary to assure an efficient execution of the contract work.

c. For the obligation of the contractor to offer employment to present or former employees as the result of a lawful collective bargaining contract, provided that the number of nonresident persons employed under this subparagraph (1c) shall not exceed 20 percent of the total number of employees employed by the contractor on the contract work, except as provided in subparagraph (4) below.

2. The contractor shall place a job order with the State Employment Service indicating (a) the classifications of the laborers, mechanics and other employees required to perform the contract work, (b) the number of employees required in each classification, (c) the date on which the participant estimates such employees will be required, and (d) any other pertinent information required by the State Employment Service to complete the job order form. The job order may be placed with the State Employment Service in writing or by telephone. If during the course of the contract work, the information submitted by the contractor in the original job order is substantially modified, the participant shall promptly notify the State Employment Service.

3. The contractor shall give full consideration to all qualified job applicants referred to him by the State Employment Service. The contractor is not required to grant employment to any job applicants who, in his opinion, are not qualified to perform the classification of work required.

4. If, within one week following the placing of a job order by the contractor with the State Employment Service, the State Employment Service is unable to refer any qualified job applicants to the contractor, or less than the number requested, the State Employment Service will forward a certificate to the contractor indicating the unavailability of applicants. Such certificate shall be made a part of the contractor's permanent project records. Upon receipt of this certificate, the contractor may employ persons who do not normally reside in the labor area to fill positions covered by the certificate, notwithstanding the provisions of subparagraph (1c) above.

5. The provisions of 23 CFR 633.207(e) allow the contracting agency to provide a contractual preference for the use of mineral resource materials native to the Appalachian region.

6. The contractor shall include the provisions of Sections 1 through 4 of this Attachment A in every subcontract for work which is, or reasonably may be, done as on-site work.

## ARKANSAS DEPARTMENT OF TRANSPORTATION

## SUPPLEMENTAL SPECIFICATION

## EQUAL EMPLOYMENT OPPORTUNITY - NOTICE TO CONTRACTORS

Elsewhere in this contract are three Supplemental Specifications on Equal Employment Opportunity designated as PR-1273 Supplements. They are (1) Specific Equal Employment Opportunity Responsibilities (23 U.S.C. 140), (2) Equal Employment Opportunity - Goals and Timetables, and (3) Equal Employment Opportunity - Federal Standards. This notice is to clarify the responsibilities for review of compliance and enforcement for these separate supplemental specification requirements.

The first of the Supplemental Specifications cited above covers the requirements for the equal employment opportunity program under Title 23 for which the Arkansas Department of Transportation (ARDOT) is responsible. The ARDOT performs the necessary compliance review and enforcement of this Supplemental Specification which is applicable to all contractors holding Federal-aid highway contracts.

The latter two Supplemental Specifications are for the specific equal opportunity requirements for Executive Order 11246 which is the sole responsibility of the Office of Federal Contract Compliance Programs (OFCCP), Department of Labor. Review and enforcement under these Supplemental Specifications is performed by OFCCP.

OFCCP has, under Paragraph 8 of the EEO Federal Standards Supplemental Specification, recognized the Arkansas AGC Heavy Highway Affirmative Action Plan as meeting the provisions of that Supplemental Specification and Supplemental Specification (2) cited above. With this recognition, those contractors signatory to the AGC Plan have been waived from individual review by OFCCP. However, OFCCP retains the right to review any such contractors whenever circumstances warrant. Also, contractors non-signatory to the AGC Plan are subject to OFCCP review under EO 11246.

ARDOT and OFCCP have agreed to work towards eliminating duplicative reviews on individual contractors; however, each agency may make reviews at any time notwithstanding the cited agreement.

## ARKANSAS DEPARTMENT OF TRANSPORTATION

## SPECIAL PROVISION

SPECIFIC EQUAL EMPLOYMENT OPPORTUNITY RESPONSIBILITIES  
(23 U.S.C. 140)**1. General.**

a. Equal employment opportunity requirements not to discriminate and to take affirmative action to assure equal employment opportunity as required by Executive Order 11246 and Executive Order 11375 are set forth in Required Contract Provisions (Form FHWA-1273 and Supplements) and these Special Provisions which are imposed pursuant to Section 140 of Title 23, U.S.C., as established by Section 22 of the Federal-Aid Highway Act of 1968. The requirements set forth in these Special Provisions shall constitute the specific affirmative action requirements for project activities under this contract and supplement the equal employment opportunity requirements set forth in the Required Contract Provisions. The initial measure of the contractor's good faith efforts to comply with these Special Provisions shall be its efforts to meet the goals set forth in the "Notice of Requirement for Affirmative Action to Ensure Equal Employment Opportunity (Executive Order 11246)" for minority and female participation expressed in percentage terms for the contractor's work force in each trade on this project.

b. The contractor will work with the Department and the Federal Government in carrying out equal employment opportunity obligations and in their review of his/her activities under the contract.

c. The contractor and all his/her subcontractors holding subcontracts not including material suppliers, of \$10,000 or more, will comply with the following minimum specific requirement activities of equal employment opportunity: (The equal employment opportunity requirements of Executive Order 11246, as set forth in Volume 6, Chapter 4, Section 1, Subsection 1 of the Federal-Aid Highway Program Manual, are applicable to material suppliers as well as contractors and subcontractors.) The contractor will include these requirements in every subcontract of \$10,000 or more with such modification of language as is necessary to make them binding on the subcontractor.

**2. Equal Employment Opportunity Policy.**

The contractor will accept as his operating policy the following statement which is designed to further the provision of equal employment opportunity to all persons without regard to their race, color, religion, sex, age, disability, or national origin, and to promote the full realization of equal employment opportunity through a positive continuing program:

It is the policy of this Company to assure that applicants are employed, and that employees are treated during employment without regard to their race, color, religion, sex, age, disability, or national origin. Such action shall include: employment, upgrading, demotion, or transfer; recruitment or recruitment advertising; layoff or termination; rates of pay or other forms of compensation; and selection for training, including apprenticeship, preapprenticeship, and/or on-the-job training.

**3. Equal Employment Opportunity Officer.**

The contractor will designate and make known to the Department contracting officers an equal employment opportunity officer (hereinafter referred to as the EEO Officer) who will have the responsibility for and must be capable of effectively administering and promoting an active contractor program of equal employment opportunity and who must be assigned adequate authority and responsibility to do so.

**4. Dissemination of Policy.**

a. All members of the contractor's staff who are authorized to hire, supervise, promote, and discharge employees, or who recommend such action, or who are substantially involved in such action, will be made fully cognizant of, and will implement, the contractor's equal employment opportunity policy and contractual responsibilities to provide equal employment opportunity in each grade and classification of employment. To ensure that the above agreement will be met, the following actions will be taken as a minimum:

(1) Periodic meetings of supervisory and personnel office employees will be conducted before the start of work and then not less often than once every six months, at which time the contractor's equal employment opportunity policy and its implementation will be reviewed and explained. The meetings will be conducted by the EEO Officer or other knowledgeable company official.

(2) All new supervisory or personnel office employees will be given a thorough indoctrination by the EEO Officer or other knowledgeable company official covering all major aspects of the contractor's equal employment opportunity obligations within thirty days following their reporting for duty with the contractor.

(3) All personnel who are engaged in direct recruitment for the project will be instructed by the EEO Officer or appropriate company official in the contractor's procedures for locating and hiring minority and female employees.

b. In order to make the contractor's equal employment opportunity policy known to all employees, prospective employees and potential sources of employees, i.e., schools, employment agencies, labor unions (where appropriate), college placement officers, etc., the contractor will take the following actions:

(1) Notices and posters setting forth the contractor's equal employment opportunity policy will be placed in areas readily accessible to employees, applicants for employment, and potential employees.

(2) The contractor's equal employment opportunity policy and the procedures to implement such policy will be brought to the attention of employees by means of meetings, employee handbooks, or other appropriate means.

## **5. Recruitment.**

a. When advertising for employees, the contractor will include in all advertisements for employees the notation: "An Equal Opportunity Employer." All such advertisements will be published in newspapers or other publications having a large circulation among minority groups in the area from which the project work force would normally be derived.

b. The contractor will, unless precluded by a valid bargaining agreement, conduct systematic and direct recruitment through public and private employee referral sources likely to yield qualified minority and female applicants, including, but not limited to, State employment agencies, schools, colleges, and minority group organizations. To meet this requirement, the contractor will, through his EEO Officer, identify sources of potential minority and female employees, and establish with such identified sources procedures whereby minority and female applicants may be referred to the contractor for employment consideration.

In the event the contractor has a valid bargaining agreement providing for exclusive hiring hall referrals, he is expected to observe the provisions of that agreement to the extent that the system permits the contractor's compliance with equal employment opportunity contract provisions. (The U.S. Department of Labor has held that where implementation of such agreements has the effect of discriminating against minorities or women, or obligates the contractor to do the same, such implementation violates Executive Order 11246, as amended.)

c. The contractor will encourage his present employees to refer minority and female applicants for employment by posting appropriate notices or bulletins in areas accessible to all such employees. In addition, information and procedures with regard to referring minority and female applicants will be discussed with employees.

## **6. Personnel Actions.**

Wages, working conditions, and employee benefits shall be established and administered, and personnel actions of every type, including hiring, upgrading, promotion, transfer, demotion, layoff, and termination, shall be taken without regard to race, color, religion, sex, age, disability, or national origin. The following procedures shall be followed:

a. The contractor will conduct periodic inspections of project sites to insure that working conditions and employee facilities do not indicate discriminatory treatment of project site personnel.

b. The contractor will periodically evaluate the spread of wages paid within each classification to determine any evidence of discriminatory wage practices.

c. The contractor will periodically review selected personnel actions in depth to determine whether there is evidence of discrimination. Where evidence is found, the contractor will promptly take corrective action. If the review indicates that the discrimination may extend beyond the actions reviewed, such corrective action shall include all affected persons.

d. The contractor will promptly investigate all complaints of alleged discrimination made to the contractor in connection with his obligations under this contract, will attempt to resolve such complaints, and will take appropriate corrective action within a reasonable time. If the investigation indicates that the discrimination may affect persons other than the complainant, such corrective action shall include such other persons. Upon completion of each investigation, the contractor will inform every complainant of all of his avenues of appeal.

## **7. Training and Promotion.**

a. The contractor will assist in locating, qualifying, and increasing the skills of minority group and women employees and applicants for employment.

b. Consistent with the contractor's work force requirements and as permissible under Federal and State regulations, the contractor shall make full use of training programs, i.e., apprenticeship and on-the-job training programs for the geographical area of contract performance. Where feasible, 25 percent of apprentices or trainees in each occupation shall be in their first year of apprenticeship or training. In the event the Optional Training Special Provision is provided under this contract, this subparagraph will be superseded by that Special Provision.

c. The contractor will advise employees and applicants for employment of available training programs and entrance requirements for each.

d. The contractor will periodically review the training and promotion potential of minority group and women employees and will encourage eligible employees to apply for such training and promotion.

## **8. Unions.**

If the contractor relies in whole or in part upon unions as a source of employees, the contractor will use his/her best efforts to obtain the cooperation of such unions to increase opportunities for minority groups and women within the unions, and to effect referrals by such unions of minority and female employees. Actions by the contractor either directly or through a contractor's association acting as agent will include the procedures set forth below:

a. The contractor will use best efforts to develop, in cooperation with the unions, joint training programs aimed toward qualifying more minority group members and women for membership in the unions and increasing the skills of minority group employees and women so that they may qualify for higher paying employment.

b. The contractor will use best efforts to incorporate an equal employment opportunity clause into each union agreement to the end that such union will be contractually bound to refer applicants without regard to their race, color, religion, sex, age, disability, or national origin.

c. The contractor is to obtain information as to the referral practices and policies of the labor union, except that to the extent such information is within the exclusive possession of the labor union and such labor union refuses to furnish such information to the contractor, the contractor shall so certify to the State Highway Department and shall set forth what efforts have been made to obtain such information.

d. In the event the union is unable to provide the contractor with a reasonable flow of minority and women referrals within the time limit set forth in the collective bargaining agreement, the contractor will, through independent recruitment efforts, fill the employment vacancies without regard to race, color, religion, sex, age, disability, or national origin, making full efforts to obtain qualified and/or qualifiable minority group persons and women. (The U.S. Department of Labor has held that it shall be no excuse that the union with which the contractor has a collective bargaining agreement providing for exclusive referral failed to refer minority employees.) In the event the union referral practice prevents the contractor from meeting the obligations pursuant to Executive Order 11246, as amended, and these special provisions, such contractor shall immediately notify the Department.

## **9. Subcontracting.**

a. The contractor's attention is called to the Special Provision on Disadvantaged Business Enterprises in Federal-Aid Highway Construction.

b. The contractor will use his best efforts to ensure subcontractor compliance with their equal employment opportunity obligations.

## **10. Records and Reports.**

a. The contractor will keep such records as are necessary to determine compliance with the contractor's equal employment opportunity obligations. The records kept by the contractor will be designed to indicate:

(1) the number of minority and non-minority group members and women employed in each work classification on the project,

(2) the progress and efforts being made in cooperation with unions to increase employment opportunities for minorities and women (applicable only to contractors who rely in whole or in part on unions as a source of their work force),

(3) the progress and efforts being made in locating, hiring, training, qualifying, and upgrading minority and female employees, and

(4) the progress and efforts being made in securing the services of Disadvantaged Business Enterprises or subcontractors or subcontractors with meaningful minority and female representation among their employees.

b. All such records must be retained for a period of three years following completion of the contract work and shall be available at reasonable times and places for inspection by authorized representatives of the Department and the Federal Highway Administration.

c. The contractors will submit an annual report to the State Highway agency each July for the duration of the project, indicating the number of minority, women, and non-minority group employees currently engaged in each work classification required by the contract work. This information is to be reported on Form PR 1391.

## **11. Corrective Action Plans.**

The contractor understands that a designated representative of the Department will periodically review compliance by the contractor with all contractual provisions incorporated pursuant to Executive Order 11246, as amended, and Federal Highway Administration Equal Employment Opportunity Special Provisions implementing the Federal-Aid Highway Act of 1968, where applicable.

In the event that the designated representative of the Department finds that the contractor has failed to comply with any of the aforementioned contractual provisions, he will notify the contractor of this finding in writing. A declaration of default will result in the suspension of all future payments. No declaration of default will be made if the Department and the contractor formally agree to enter into a corrective action plan setting out the specified steps and timetables the contractor will be contractually obligated to perform in order to re-establish his compliance. This corrective action plan, in order to be accepted by the Department, shall include the following mandatory enforcement language:

"If, at any time in the future, the Office of Federal Contract Compliance Programs or the Federal Highway Administration or the Arkansas State Highway Commission or their successor(s) believe that (name of contractor) has violated any portion of this agreement, (name of contractor) shall be promptly notified of the fact in writing. This notification shall include a statement of the facts and circumstances relied upon in forming that belief. In addition, the notification shall provide (name of contractor) with 15 days to respond in writing to the notification except where the Office of Federal Contract Compliance Programs, the Federal Highway Administration or the Arkansas State Highway Commission alleges that such delay would result in irreparable injury. It is understood that enforcement proceedings for violation of this agreement may be initiated at any time after the 15-day period has elapsed (or sooner if irreparable injury is alleged) without issuance of a show cause notice."

"It is recognized that where the Office of Federal Contract Compliance Programs and/or the Federal Highway Administration and/or the Arkansas State Highway Commission believes that (name of contractor) has breached this agreement, evidence regarding the entire scope of (name of contractor) alleged noncompliance from which this agreement resulted, in addition to evidence regarding (name of contractor) alleged violation of this agreement, may be introduced at the enforcement proceeding."

"Violation of this agreement may subject (name of contractor) to sanctions pursuant to the Arkansas State Highway Commission contract administration procedures. It is further recognized that liability for violation of this agreement may also subject (name of contractor) to sanctions set forth in Section 209 of Executive Order 11246, as amended, and/or appropriate relief."

The contractor will submit quarterly reports to the Department as a result of any deficiencies cited during an equal employment opportunity compliance review. The reports will indicate the affirmative action steps taken to correct the deficiencies. Instructions for submission of the reports will be furnished by the Equal Employment Opportunity Section.

## ARKANSAS DEPARTMENT OF TRANSPORTATION

## SUPPLEMENTAL SPECIFICATION

## EQUAL EMPLOYMENT OPPORTUNITY - GOALS AND TIMETABLES

NOTICE OF REQUIREMENT FOR AFFIRMATIVE  
ACTION TO ENSURE EQUAL EMPLOYMENT  
OPPORTUNITY (EXECUTIVE ORDER 11246)

1. The Bidder's attention is called to the "Equal Opportunity Clause" and the "Standard Federal Equal Employment Specifications" set forth herein.

2. The goals and timetables for minority and female participation, expressed in percentage terms for the Contractor's aggregate workforce in each trade on all construction work in the covered area, are as follows:

MINORITIESCOUNTY

|              |       |              |       |
|--------------|-------|--------------|-------|
| Arkansas     | 16.4% | Lee          | 26.5% |
| Ashley       | 16.4% | Lincoln      | 16.4% |
| Baxter       | 3.3%  | Little River | 19.7% |
| Benton       | 3.3%  | Logan        | 6.6%  |
| Boone        | 3.3%  | Lonoke       | 16.4% |
| Bradley      | 16.4% | Madison      | 3.3%  |
| Calhoun      | 16.4% | Marion       | 3.3%  |
| Carroll      | 3.3%  | Miller       | 19.7% |
| Chicot       | 16.4% | Mississippi  | 26.5% |
| Clark        | 16.4% | Monroe       | 16.4% |
| Clay         | 26.5% | Montgomery   | 16.4% |
| Cleburne     | 16.4% | Nevada       | 20.2% |
| Cleveland    | 16.4% | Newton       | 3.3%  |
| Columbia     | 20.2% | Ouachita     | 16.4% |
| Conway       | 16.4% | Perry        | 16.4% |
| Craighead    | 26.5% | Phillips     | 26.5% |
| Crawford     | 5.6%  | Pike         | 20.2% |
| Crittenden   | 32.3% | Poinsett     | 26.5% |
| Cross        | 26.5% | Polk         | 6.6%  |
| Dallas       | 16.4% | Pope         | 16.4% |
| Desha        | 16.4% | Prairie      | 16.4% |
| Drew         | 16.4% | Pulaski      | 15.7% |
| Faulkner     | 16.4% | Randolph     | 26.5% |
| Franklin     | 6.6%  | Saline       | 15.7% |
| Fulton       | 16.4% | Scott        | 6.6%  |
| Garland      | 16.4% | Searcy       | 3.3%  |
| Grant        | 16.4% | Sebastian    | 5.6%  |
| Greene       | 26.5% | Sevier       | 20.2% |
| Hempstead    | 20.2% | Sharp        | 16.4% |
| Hot Spring   | 16.4% | Stone        | 16.4% |
| Howard       | 20.2% | St. Francis  | 26.5% |
| Independence | 16.4% | Union        | 16.4% |
| Izard        | 16.4% | Van Buren    | 16.4% |
| Jackson      | 16.4% | Washington   | 3.3%  |
| Jefferson    | 31.2% | White        | 16.4% |
| Johnson      | 16.4% | Woodruff     | 16.4% |
| Lafayette    | 20.2% | Yell         | 16.4% |
| Lawrence     | 26.5% |              |       |

FEMALES

Statewide - 6.9%

These goals are applicable to all the Contractor's construction work (whether or not it is Federal or federally assisted) performed in the covered area. If the Contractor performs construction work in a geographical area located outside of the covered area, it shall apply the goals established for such geographical area where the work is actually performed. With regard to this second area, the Contractor also is subject to the goals for both its federally involved and nonfederally involved construction.

The Contractor's compliance with the Executive Order and the regulations in 41 CFR Part 60-4 shall be based on its implementation of the Equal Opportunity Clause, specific affirmative action obligations required by the specifications set forth in 41 CFR 60-4.3(a), and its efforts to meet the goals. The hours of minority and female employment and training must be substantially uniform throughout the length of the contract, and in each trade, and the Contractor shall make a good faith effort to employ minorities and women evenly on each of its projects. The transfer of minority or female employees or trainees from Contractor to Contractor or from project to project for the sole purpose of meeting the Contractor's goals shall be a violation of the contract, the Executive Order and the regulations in 41 CFR Part 60-4. Compliance with the goals will be measured against the total work hours performed.

3. The Contractor shall provide written notification to the Director of the Office of Federal Contract Compliance Programs within 10 working days of award of any construction subcontract in excess of \$10,000 at any tier for construction work under the contract resulting from this solicitation. The notification shall list the name, address and telephone number of the subcontractor; employer identification number of the subcontractor; estimated dollar amount of the subcontract; estimated starting and completion dates of the subcontract; and the geographical area in which the subcontract is to be performed.

4. As used in this Notice, and in the contract resulting from this solicitation, the "covered area" is as described in the Proposal Form for this report.

## ARKANSAS DEPARTMENT OF TRANSPORTATION

## SUPPLEMENTAL SPECIFICATION

## EQUAL EMPLOYMENT OPPORTUNITY -FEDERAL STANDARDS

STANDARD FEDERAL EQUAL EMPLOYMENT OPPORTUNITY  
CONSTRUCTION CONTRACT SPECIFICATIONS  
(EXECUTIVE ORDER 11246)

## 1. As used in these specifications:

a. "Covered area" means the geographical area described in the solicitation from which this contract resulted;

b. "Director" means Director, Office of Federal Contract Compliance Programs, United States Department of Labor, or any person to whom the Director delegates authority;

c. "Employer identification number" means the Federal Social Security number used on the Employer's Quarterly Federal Tax Return, U.S. Treasury Department Form 941.

## d. "Minority" includes:

- i. Black (all persons having origins in any of the Black African racial groups not of Hispanic origin);
- ii. Hispanic (all persons of Mexican, Puerto Rican, Cuban, Central or South American or other Spanish Culture or origin, regardless of race);
- iii. Asian and Pacific Islander (all persons having origins in any of the original peoples of the Far East, Southeast Asia, the Indian Subcontinent, or the Pacific Islands); and
- iv. American Indian or Alaskan Native (all persons having origins in any of the original peoples of North American and maintaining identifiable tribal affiliations through membership and participation or community identification).

2. Whenever the Contractor, or any Subcontractor at any tier, subcontracts a portion of the work involving any construction trade, it shall physically include in each subcontract in excess of \$10,000 the provisions of these specifications and the Notice which contains the applicable goals for minority and female participation and which is set forth in the solicitations from which this contract resulted.

3. If the Contractor is participating (pursuant to 41 CFR 60-4.5) in a Hometown Plan approved by the U.S. Department of Labor in the covered area either individually or through an association, its affirmative action obligations on all work in the Plan area (including goals and timetables) shall be in accordance with that Plan for those trades which have unions participating in the Plan. Contractors must be able to demonstrate their participation in and compliance with the provisions of any such Hometown Plan. Each Contractor or Subcontractor participating in an approved

Plan is individually required to comply with its obligations under the EEO clause, and to make a good faith effort to achieve each goal under the Plan in each trade in which it has employees. The overall good faith performance by other Contractors or Subcontractors toward a goal in an approved Plan does not excuse any covered Contractor's or Subcontractor's failure to take good faith efforts to achieve the Plan goals and timetables.

4. The Contractor shall implement the specific affirmative action standards provided in paragraphs 7a through p of these specifications. The goals set forth in the solicitation from which this contract resulted are expressed as percentages of the total hours of employment and training of minority and female utilization the Contractor should reasonably be able to achieve in each construction trade in which it has employees in the covered area. Covered construction contractors performing construction work in geographical areas where they do not have a Federal or federally assisted construction contract shall apply the minority and female goals established for the geographical area where the work is being performed. Goals are published periodically in the Federal Register in notice form, and such notices may be obtained from any Office of Federal Contract Compliance Programs office or from Federal procurement contracting officers. The Contractor is expected to make substantially uniform progress in meeting its goals in each craft during the period specified.

5. Neither the provisions of any collective bargaining agreement, nor the failure by a union with whom the Contractor has a collective bargaining agreement, to refer either minorities or women shall excuse the Contractor's obligations under these specifications, Executive Order 11246, or the regulations promulgated pursuant thereto.

6. In order for the nonworking training hours of apprentices and trainees to be counted in meeting the goals, such apprentices and trainees must be employed by the Contractor during the training period, and the Contractor must have made a commitment to employ the apprentices and trainees at the completion of their training, subject to the availability of employment opportunities. Trainees must be trained pursuant to training programs approved by the U.S. Department of Labor.

7. The Contractor shall take specific affirmative actions to ensure equal employment opportunity. The evaluation of the Contractor's compliance with these specifications shall be based upon its effort to achieve maximum results from its actions. The

Contractor shall document these efforts fully, and shall implement affirmative action steps at least as extensive as the following:

a. Ensure and maintain a working environment free of harassment, intimidation, and coercion at all sites, and in all facilities at which the Contractor's employees are assigned to work. The Contractor, where possible, will assign two or more women to each construction project. The Contractor shall specifically ensure that all foremen, superintendents, and other on-site supervisory personnel are aware of and carry out the Contractor's obligation to maintain such a working environment, with specific attention to minority or female individuals working at such sites or in such facilities.

b. Establish and maintain a current list of minority and female recruitment sources, provide written notification to minority and female recruitment sources and to community organizations when the Contractor or its unions have employment opportunities available, and maintain a record of the organizations' responses.

c. Maintain a current file of the names, addresses and telephone numbers of each minority and female off-the-street applicant and minority or female referral from a union, a recruitment source or community organization and of what action was taken with respect to each such individual. If such individual was sent to the union hiring hall for referral and was not referred back to the Contractor by the union or, if referred, not employed by the Contractor, this shall be documented in the file with the reason therefor, along with whatever additional actions the Contractor may have taken.

d. Provide immediate written notification to the Director when the union or unions with which the Contractor has a collective bargaining agreement has not referred to the Contractor a minority person or woman sent by the Contractor, or when the Contractor has other information that the union referral process has impeded the Contractor's efforts to meet its obligations.

e. Develop on-the-job training opportunities and/or participate in training programs for the area which expressly include minorities and women, including upgrading programs and apprenticeship and trainee programs relevant to the Contractor's employment needs, especially those programs funded or approved by the Department of Labor. The Contractor shall provide notice of these programs to the sources compiled under 7b above.

f. Disseminate the Contractor's EEO policy by providing notice of the policy to unions and training programs and requesting their cooperation in assisting the Contractor in meeting its EEO obligations; by including it in any policy manual and collective bargaining agreement; by publicizing it in the company newspaper, annual report, etc.; by specific review of the policy with all management personnel and with all minority and female employees before the start of work and then not less often than once every six months; and by posting the company EEO policy on bulletin boards accessible to all employees at each location where construction work is performed.

g. Review the company's EEO policy and affirmative action obligations under these specifications with all employees having any responsibility for hiring, assignment, layoff, termination or other employment decisions including specific review of these items with on-site supervisory personnel such as Superintendents, General Foreman, etc., prior to the initiation of construction work at any job site and then not less often than once every six months. A written record shall be made and maintained identifying the time and place of these meetings, persons attending, subject matter discussed, and disposition of the subject matter.

h. Disseminate the Contractor's EEO policy externally by including it in any advertising in the news media, specifically including minority and female news media, and providing written notification to and discussing the Contractor's EEO policy with other Contractors and Subcontractors with whom the Contractor does or anticipates doing business.

i. Direct its recruitment efforts, both oral and written, to minority, female and community organizations, to schools with minority and female students and to minority and female recruitment and training organizations serving the Contractor's recruitment area and employment needs. Not later than one month prior to the date for the acceptance of applications for apprenticeship or other training by any recruitment source, the Contractor shall send written notification to organizations such as the above describing the openings, screening procedures, and test to be used in the selection process.

j. Encourage present minority and female employees to recruit other minority persons and women and, where reasonable, provide after school, summer and vacation employment to minority and female youth both on the site and in other areas of a Contractor's workforce.

k. Validate all tests and other selection requirements where there is an obligation to do so under 41 CFR Part 60-3.

l. Conduct, at least annually, an inventory and evaluation at least of all minority and female personnel for promotional opportunities and encourage these employees to seek or to prepare for, through appropriate training, etc., such opportunities.

m. Ensure that seniority practices, job classifications, work assignments and other personnel practices, do not have a discriminatory effect by continually monitoring all personnel and employment related activities to ensure that the EEO policy and the Contractor's obligations under these specifications are being carried out.

n. Ensure that all facilities and company activities are non-segregated except that separate or single-user toilet and necessary changing facilities shall be provided to assure privacy between sexes.

o. Document and maintain a record of all solicitations of offers for subcontractors for disadvantaged business

enterprise construction contractors and suppliers, including circulation of solicitations to minority and female contractor associations and other business associations.

p. Conduct a review, at least annually, of all supervisors' adherence to and performance under the Contractor's EEO policies and affirmative action obligations.

8. Contractors are encouraged to participate in voluntary associations which assist in fulfilling one or more of their affirmative action obligations (7a through p). The efforts of a contractor association, joint contractor-union, contractor-community, or other similar group of which the contractor is a member and participant, may be asserted as fulfilling any one or more of its obligations under 7a through p of these Specifications provided that the contractor actively participates in the group, makes every effort to assure that the group has a positive impact on the employment of minorities and women in the industry, ensures that the concrete benefits of the program are reflected in the Contractor's minority and female workforce participation, makes a good faith effort to meet its individual goals and timetables, and can provide access to documentation which demonstrates the effectiveness of actions taken on behalf of the Contractor. The obligation to comply, however, is the Contractor's and failure of such a group to fulfill an obligation shall not be a defense for the Contractor's non-compliance.

9. A single goal for minorities and a separate single goal for women have been established. The Contractor, however, is required to provide equal employment opportunity and to take affirmative action for all minority groups, both male and female, and all women, both minority and non-minority. Consequently, the Contractor may be in violation of the Executive Order if a particular group is employed in a substantially disparate manner (for example, even though the Contractor has achieved its goals for women generally, the Contractor may be in violation of the Executive Order if a specific minority group of women is underutilized).

10. The Contractor shall not use the goals and timetables or affirmative action standards to discriminate against any person because of race, color, religion, sex, national origin, age or disability.

11. The Contractor shall not enter into any Subcontract with any person or firm debarred from Government contracts pursuant to Executive Order 11246.

12. The Contractor shall carry out such sanctions and penalties for violation of these specifications and of the Equal Employment Opportunity Clause, including suspension, termination and cancellation of existing subcontracts as may be imposed or ordered pursuant to Executive Order 11246, as amended, and its implementing regulations, by the Office of Federal Contract Compliance Programs. Any Contractor who fails to carry out such sanctions and penalties shall be in violation of these specifications and Executive Order 11246, as amended.

13. The Contractor, in fulfilling its obligations under these specifications, shall implement specific affirmative action steps, at least as extensive as those standards prescribed in paragraph 7 of

these specifications, so as to achieve maximum results from its efforts to ensure equal employment opportunity. If the Contractor fails to comply with the requirements of the Executive Order, the implementing regulations, or these specifications, the Director shall proceed in accordance with 41CFR60-4.8.

14. The Contractor shall designate a responsible official to monitor all employment related activity to ensure that the company EEO policy is being carried out, to submit reports relating to the provisions hereof as may be required by the Government and to keep records. Records shall at least include for each employee the name, address, telephone numbers, construction trade, union affiliation if any, employee identification number when assigned, social security number, race, sex, status (e.g., mechanic, apprentice, trainee, helper, or laborer), dates of changes in status, hours worked per week in the indicated trade, rate of pay, and locations at which the work was performed. Records shall be maintained in an easily understandable and retrievable form; however, to the degree that existing records satisfy this requirement, contractors shall not be required to maintain separate records.

15. Nothing herein provided shall be construed as a limitation upon the application of other laws which establish different standards of compliance or upon the application of requirements for the hiring of local or other area residents (e.g., those under the Public Works Employment Act of 1977 and the Community Development Block Grant Program).

16. In addition to the reporting requirements set forth elsewhere in this contract, the contractor and the subcontractors holding subcontracts not including material suppliers, of \$10,000 or more, shall submit for every month of July during which work is performed employment data as contained under Form PR-1391 (Appendix C to 23 CFR, Part 230), and in accordance with the instructions included thereon.

7/26/96

Rev. 2/11/98

Rev. 2/20/03

Rev. 7/27/06

Rev. 10/24/06

Rev. 9/16/13

Rev. 8/22/17

Rev. 12/13/23

## FHWA-1273 SUPPLEMENTAL SPECIFICATION

### POSTERS AND NOTICES REQUIRED FOR FEDERAL-AID PROJECTS

| POSTER OR DOCUMENT REQUIRED                                                                      | REQUIRED BY                          | WHERE TO OBTAIN                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|--------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1. Equal Employment Opportunity – Know Your Rights                                               | U.S. Department of Labor<br>(OFCCP)  | ARDOT Resident Engineer                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| 2. Company EEO Policy<br>(prepared by the Contractor on the Company's letterhead)                | U. S. Department of Labor<br>(OFCCP) | Contractor to Prepare:<br><br>a. EEO policy statement.<br>b. Notice encouraging employees to refer minority and female applicants for employment.<br>c. Notice informing employees of an available training program and the entrance requirements.<br>d. Complaint procedures.<br>e. Notice identifying company EEO officer by name, including address and telephone number where EEO officer can be located.<br>f. Work environment statement.<br>g. Certification of nonsegregated facilities.<br>*h. Notice to unions disseminating EEO commitments and responsibilities and requesting their cooperation. |
| *Union Contractors Only                                                                          |                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| 3. Current Wage Rates (PR-1273 Supplement)<br>or SS Revisions of PR-1273 for Off-System Projects | U. S. Department of Labor            | Contained in contract. Extra copies may be obtained from Program Management - ARDOT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

7/26/96  
Rev. 2/11/98  
Rev. 2/20/03  
Rev. 7/27/06  
Rev. 10/24/06  
Rev. 9/16/13  
Rev. 8/22/17  
Rev. 12/13/23

**FHWA-1273 SUPPLEMENTAL SPECIFICATION**  
**POSTERS AND NOTICES REQUIRED FOR FEDERAL-AID PROJECTS**

| <b>POSTER OR DOCUMENT REQUIRED</b>                                                                               | <b>REQUIRED BY</b>                           | <b>WHERE TO OBTAIN</b>             |
|------------------------------------------------------------------------------------------------------------------|----------------------------------------------|------------------------------------|
| 4. "Employee Rights Under the Davis-Bacon Act"<br>(WH 1321)                                                      | U. S. Department of Labor                    | ARDOT Resident Engineer            |
| 5. "Employee Rights Under the Davis-Bacon Act"<br>(WH 1321 SPA)                                                  | U. S. Department of Labor                    | ARDOT Resident Engineer            |
| 6. Minimum Wage Rate (WH 1088)                                                                                   | U. S. Department of Labor                    | ARDOT Resident Engineer            |
| 7. "NOTICE" Federal Aid Projects<br>(PR-1022)                                                                    | U. S. Department of Transportation<br>(FHWA) | ARDOT Resident Engineer            |
| 8. Job Safety and Health Protection<br>OSHA 3165                                                                 | U. S. Department of Labor<br>(OSHA)          | ARDOT Resident Engineer            |
| 9. Job Safety and Health Protection<br>OSHA 3167 SPA                                                             | U. S. Department of Labor<br>(OSHA)          | ARDOT Resident Engineer            |
| 10. Emergency Phone Numbers of Doctors, Hospital and<br>Ambulance near Job Site for referring injured employees. | U. S. Department of Labor<br>(OSHA)          | ARDOT Resident Engineer            |
| 11. WCC Form AR-P<br>Workers Compensation Notice and Instructions to Employers<br>and Employees                  | State of Arkansas                            | Insurance Carrier                  |
| Self-Insurer                                                                                                     | State of Arkansas                            | Administrator - Self-Insured Group |

7/26/96  
Rev. 2/11/98  
Rev. 2/20/03  
Rev. 7/27/06  
Rev. 10/24/06  
Rev. 9/16/13  
Rev. 8/22/17  
Rev. 12/13/23

**FHWA-1273 SUPPLEMENTAL SPECIFICATION**  
**POSTERS AND NOTICES REQUIRED FOR FEDERAL-AID PROJECTS**

| <b>POSTER OR DOCUMENT REQUIRED</b>                                                                                                                                                                | <b>REQUIRED BY</b>                                       | <b>WHERE TO OBTAIN</b>  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------|-------------------------|
| 12. Log and Summary of Occupational Injuries and Illnesses (OSHA Form 300)<br>The Summary portion must be posted from February 1 to April 30, of the year following the year covered by the form. | U. S. Department of Labor<br>(OSHA)<br>Public Law 91-596 | ARDOT Resident Engineer |
| 13. Family and Medical Leave Act of 1993 (WH-1420)<br>Employers who employ 50 or more employees for at least 20 workweeks in the current or preceding calendar year.                              | U. S. Department of Labor                                | ARDOT Resident Engineer |
| 14. Employee Polygraph Protection Act (WH-1462)                                                                                                                                                   | U. S. Department of Labor                                | ARDOT Resident Engineer |
| 15. Your Rights Under USERRA (The Uniformed Services Employment and Reemployment Rights Act)                                                                                                      | U. S. Department of Labor                                | ARDOT Resident Engineer |
| 16. Arkansas Department of Labor Notice to Employer & Employee                                                                                                                                    | Arkansas Department of Labor                             | ARDOT Resident Engineer |
| 17. Pay Transparency Nondiscrimination Provision                                                                                                                                                  | U. S. Department of Labor<br>(OFCCP)                     | ARDOT Resident Engineer |

ARKANSAS DEPARTMENT OF TRANSPORTATION  
SUPPLEMENTAL SPECIFICATION  
WAGE RATE DETERMINATION

FHWA-1273 Supplemental  
Page 1 of 4

"General Decision Number: AR20260164 05/18/2026

State: Arkansas

Construction Types: Highway

Counties: Arkansas Counties of  
Garland

| Modification Number | Publication Date |
|---------------------|------------------|
| 0                   | 01/02/2026       |
| 1                   | 05/18/2026       |

SUAR2014-036 07/21/2014

|                                                                                   | Rates    | Fringes |
|-----------------------------------------------------------------------------------|----------|---------|
| TRUCK DRIVER: SEMI/TRAILER TRUCK.....                                             | \$ 12.50 | 0.00    |
| TRUCK DRIVER: WATER TRUCK.....                                                    | \$ 14.73 | 0.00    |
| TRUCK DRIVER: LOWBOY TRUCK.....                                                   | \$ 17.49 | 0.00    |
| TRUCK DRIVER: FLATBED TRUCK.....                                                  | \$ 21.03 | 0.00    |
| TRUCK DRIVER: DUMP TRUCK.....                                                     | \$ 14.87 | 0.00    |
| TRAFFIC CONTROL: LABORER-CONES/<br>BARRICADES/BARRELS - SETTER/MOVER/SWEEPER..... | \$ 11.60 | 0.00    |
| TRAFFIC CONTROL: FLAGGER.....                                                     | \$ 12.00 | 0.00    |
| OPERATOR: SCREED.....                                                             | \$ 15.01 | 0.00    |
| OPERATOR: SCRAPER.....                                                            | \$ 19.31 | 0.00    |
| OPERATOR: ROLLER.....                                                             | \$ 15.87 | 0.00    |
| OPERATOR: POST DRIVER (GUARDRAIL/FENCES).....                                     | \$ 16.97 | 0.00    |
| OPERATOR: PAVER (ASPHALT, AGGREGATE, AND<br>CONCRETE).....                        | \$ 21.04 | 0.00    |
| OPERATOR: OILER.....                                                              | \$ 18.46 | 0.00    |
| OPERATOR: MILLING MACHINE.....                                                    | \$ 17.52 | 0.00    |
| OPERATOR: MECHANIC.....                                                           | \$ 17.82 | 0.00    |
| OPERATOR: LOADER.....                                                             | \$ 17.05 | 0.00    |
| OPERATOR: HYDROSEEDER.....                                                        | \$ 10.79 | 0.00    |
| OPERATOR: GRADER/BLADE.....                                                       | \$ 19.86 | 0.00    |
| OPERATOR: DRILL.....                                                              | \$ 14.85 | 0.00    |
| OPERATOR: CRANE.....                                                              | \$ 21.13 | 0.00    |
| OPERATOR: BULLDOZER.....                                                          | \$ 16.10 | 0.00    |
| OPERATOR: BROOM/SWEEPER.....                                                      | \$ 12.00 | 0.00    |
| OPERATOR: BOBCAT/SKID STEER/SKID LOADER.....                                      | \$ 16.06 | 0.00    |
| OPERATOR: BACKHOE/EXCAVATOR/TRACKHOE.....                                         | \$ 16.57 | 0.00    |
| OPERATOR: ASPHALT SPREADER.....                                                   | \$ 15.80 | 0.00    |
| LABORER: PIPELAYER.....                                                           | \$ 14.33 | 0.00    |
| LABORER: MASON TENDER - CEMENT/CONCRETE.....                                      | \$ 15.23 | 0.00    |
| LABORER: COMMON OR GENERAL.....                                                   | \$ 11.45 | 0.00    |
| LABORER: ASPHALT, INCLUDES RAKER, SHOVELER,<br>SPREADER AND DISTRIBUTOR.....      | \$ 14.42 | 0.00    |
| IRONWORKER, STRUCTURAL.....                                                       | \$ 15.36 | 0.00    |
| IRONWORKER, REINFORCING.....                                                      | \$ 14.22 | 0.00    |
| HIGHWAY/PARKING LOT STRIPING: PAINTER.....                                        | \$ 21.75 | 0.00    |
| HIGHWAY/PARKING LOT STRIPING: OPERATOR (STRIPING<br>MACHINE).....                 | \$ 13.25 | 0.00    |

ARKANSAS DEPARTMENT OF TRANSPORTATION  
SUPPLEMENTAL SPECIFICATION  
WAGE RATE DETERMINATION

FHWA-1273 Supplemental  
Page 2 of 4

|                                                  |          |      |
|--------------------------------------------------|----------|------|
| ELECTRICIAN, INCLUDES TRAFFIC SIGNALIZATION..... | \$ 16.85 | 0.00 |
| CEMENT MASON/CONCRETE FINISHER.....              | \$ 17.44 | 0.00 |
| CARPENTER (FORM WORK ONLY).....                  | \$ 18.07 | 0.00 |

-----

-----  
WELDERS - Receive rate prescribed for craft performing  
operation to which welding is incidental.

=====

Note: Executive Order (EO) 13706, Establishing Paid Sick Leave for Federal Contractors applies to all contracts subject to the Davis-Bacon Act for which the contract is awarded (and any solicitation was issued) on or after January 1, 2017. If this contract is covered by the EO, the contractor must provide employees with 1 hour of paid sick leave for every 30 hours they work, up to 56 hours of paid sick leave each year. Employees must be permitted to use paid sick leave for their own illness, injury or other health-related needs, including preventive care; to assist a family member (or person who is like family to the employee) who is ill, injured, or has other health-related needs, including preventive care; or for reasons resulting from, or to assist a family member (or person who is like family to the employee) who is a victim of, domestic violence, sexual assault, or stalking. Additional information on contractor requirements and worker protections under the EO is available at <https://www.dol.gov/agencies/whd/government-contracts>.

Note: Executive Order 13658 generally applies to contracts subject to the Davis-Bacon Act that were awarded on or between January 1, 2015 and January 29, 2022, and that have not been renewed or extended on or after January 30, 2022. Executive Order 13658 does not apply to contracts subject only to the Davis-Bacon Related Acts regardless of when they were awarded. If a contract is subject to Executive Order 13658, the contractor must pay all covered workers at least \$13.65 per hour (or the applicable wage rate listed on this wage determination, if it is higher) for all hours spent performing on the contract from May 11, 2026, through December 31, 2026. The applicable Executive Order minimum wage rate will be adjusted annually. Additional information on contractor requirements and worker protections under Executive Order 13658 is available at [www.dol.gov/whd/govcontracts](http://www.dol.gov/whd/govcontracts).

Unlisted classifications needed for work not included within the scope of the classifications listed may be added after award only as provided in the labor standards contract clauses (29CFR 5.5 (a) (1) (iii)).

-----

The body of each wage determination lists the classifications and wage rates that have been found to be prevailing for the type(s) of construction and geographic area covered by the wage determination. The classifications are listed in alphabetical order under rate identifiers indicating whether the particular rate is a union rate (current union negotiated rate), a survey rate, a weighted union average rate, a state adopted rate, or a supplemental classification rate.

#### Union Rate Identifiers

A four-letter identifier beginning with characters other than **◆SU◆**, **◆UAVG◆**, **◆SA◆**, or **◆SC◆** denotes that a union rate was prevailing for that classification in the survey. Example: PLUM0198-005 07/01/2024. PLUM is an identifier of the union

whose collectively bargained rate prevailed in the survey for this classification, which in this example would be Plumbers. 0198 indicates the local union number or district council number where applicable, i.e., Plumbers Local 0198. The next number, 005 in the example, is an internal number used in processing the wage determination. The date, 07/01/2024 in the example, is the effective date of the most current negotiated rate.

Union prevailing wage rates are updated to reflect all changes over time that are reported to WHD in the rates in the collective bargaining agreement (CBA) governing the classification.

#### Union Average Rate Identifiers

The UAVG identifier indicates that no single rate prevailed for those classifications, but that 100% of the data reported for the classifications reflected union rates. EXAMPLE:

UAVG-OH-0010 01/01/2024. UAVG indicates that the rate is a weighted union average rate. OH indicates the State of Ohio. The next number, 0010 in the example, is an internal number used in producing the wage determination. The date, 01/01/2024 in the example, indicates the date the wage determination was updated to reflect the most current union average rate.

A UAVG rate will be updated once a year, usually in January, to reflect a weighted average of the current rates in the collective bargaining agreements on which the rate is based.

#### Survey Rate Identifiers

The ♦SU♦ identifier indicates that either a single non-union rate prevailed (as defined in 29 CFR 1.2) for this classification in the survey or that the rate was derived by computing a weighted average rate based on all the rates reported in the survey for that classification. As a weighted average rate includes all rates reported in the survey, it may include both union and non-union rates. Example: SUFL2022-007 6/27/2024. SU indicates the rate is a single non-union prevailing rate or a weighted average of survey data for that classification. FL indicates the State of Florida. 2022 is the year of the survey on which these classifications and rates are based. The next number, 007 in the example, is an internal number used in producing the wage determination. The date, 6/27/2024 in the example, indicates the survey completion date for the classifications and rates under that identifier.

♦SU♦ wage rates typically remain in effect until a new survey is conducted. However, the Wage and Hour Division (WHD) has the discretion to update such rates under 29 CFR 1.6(c)(1).

#### State Adopted Rate Identifiers

The ♦SA♦ identifier indicates that the classifications and prevailing wage rates set by a state (or local) government were adopted under 29 C.F.R 1.3(g)-(h). Example: SAME2023-007 01/03/2024. SA reflects that the rates are state adopted. ME refers to the State of Maine. 2023 is the year during which the state completed the survey on which the listed classifications and rates are based. The next number, 007 in the example, is an internal number used in producing the wage determination. The date, 01/03/2024 in the example, reflects the date on which

ARKANSAS DEPARTMENT OF TRANSPORTATION  
SUPPLEMENTAL SPECIFICATION  
WAGE RATE DETERMINATION

FHWA-1273 Supplemental  
Page 4 of 4

the classifications and rates under the **SA** identifier took effect under state law in the state from which the rates were adopted.

-----  
WAGE DETERMINATION APPEALS PROCESS

1) Has there been an initial decision in the matter? This can be:

- a) a survey underlying a wage determination
- b) an existing published wage determination
- c) an initial WHD letter setting forth a position on a wage determination matter
- d) an initial conformance (additional classification and rate) determination

On survey related matters, initial contact, including requests for summaries of surveys, should be directed to the WHD Branch of Wage Surveys. Requests can be submitted via email to [davisbaconinfo@dol.gov](mailto:davisbaconinfo@dol.gov) or by mail to:

Branch of Wage Surveys  
Wage and Hour Division  
U.S. Department of Labor  
200 Constitution Avenue, N.W.  
Washington, DC 20210

Regarding any other wage determination matter such as conformance decisions, requests for initial decisions should be directed to the WHD Branch of Construction Wage Determinations. Requests can be submitted via email to [BCWD-Office@dol.gov](mailto:BCWD-Office@dol.gov) or by mail to:

Branch of Construction Wage Determinations  
Wage and Hour Division  
U.S. Department of Labor  
200 Constitution Avenue, N.W.  
Washington, DC 20210

2) If an initial decision has been issued, then any interested party (those affected by the action) that disagrees with the decision can request review and reconsideration from the Wage and Hour Administrator (See 29 CFR Part 1.8 and 29 CFR Part 7). Requests for review and reconsideration can be submitted via email to [dba.reconsideration@dol.gov](mailto:dba.reconsideration@dol.gov) or by mail to:

Wage and Hour Administrator  
U.S. Department of Labor  
200 Constitution Avenue, N.W.  
Washington, DC 20210

The request should be accompanied by a full statement of the interested party's position and any information (wage payment data, project description, area practice material, etc.) that the requestor considers relevant to the issue.

3) If the decision of the Administrator is not favorable, an interested party may appeal directly to the Administrative Review Board (formerly the Wage Appeals Board). Write to:

Administrative Review Board  
U.S. Department of Labor  
200 Constitution Avenue, N.W.  
Washington, DC 20210.

=====  
END OF GENERAL DECISION"

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**CARGO PREFERENCE ACT REQUIREMENTS**

The requirements of the Cargo Preference Act (CPA) and implementing regulations (46 CFR 381.7(a)-(b)) are applicable to this contract. For additional information, see the FHWA's web page:

<https://www.fhwa.dot.gov/construction/cqit/cargo.cfm>

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**PROHIBITION OF CERTAIN TELECOMMUNICATIONS AND  
VIDEO SURVEILLANCE SERVICES OR EQUIPMENT**

In accordance with the requirements of 2 CFR 200.216, equipment utilized on this project for telecommunications and video surveillance services or equipment shall not be produced by:

- 1) Huawei Technologies Company or ZTE Corporation (or any subsidiary or affiliate of such entities).
- 2) Hytera Communications Corporation, Hangzhou Hikvision Digital Technology Company, or Dahua Technology Company (or any subsidiary or affiliate of such entities).

## ARKANSAS DEPARTMENT OF TRANSPORTATION

### SPECIAL PROVISION

JOB NO. A60063

### BUY AMERICA - CONSTRUCTION MATERIALS

**Description:** **Section 106, Control of Material**, of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The following is added as **Subsection 106.01(c) Construction Materials**

**Buy America – Construction Materials. (1) General.** The Bipartisan Infrastructure Law (BIL) was enacted on November 15, 2021 (BIL Build America, Buy America Act Publication L. No. 117-58). This provision expands the Buy America requirements beyond what was only required for steel and iron products. The steel and iron provisions have not changed with the new law. Buy America requirements are in effect only on Federal-Aid contracts and all construction materials shall be produced/manufactured in the United States. Items specifically excluded from this requirement are cement and cementitious materials; aggregates such as stone, sand, or gravel; aggregate binding agents or additives (including asphalt binders). All other materials permanently incorporated into the project will be subject to Buy America requirements.

**(2) Definitions.** A construction material includes an article, material, or supply that is or consists primarily of:

- non-ferrous metals;
- plastic and polymer-based products (including polyvinylchloride, composite building materials, and polymers used in fiber optic cable);
- glass (including optic glass);
- lumber; or
- drywall.

All construction materials shall be produced in the United States. This means all manufacturing processes to produce the construction materials shall occur in the United States. All manufacturing processes for construction materials shall mean the final manufacturing process and the immediately preceding manufacturing stage for the construction material.

All manufactured products permanently incorporated into the project must be manufactured in the United States or assembled from components that are mined, produced, or manufactured in the United States. The combined value of the domestic components of a manufactured product must be greater than 55 percent of the total cost of all components of the manufactured product.

**(3) Compliance.** All prospective bidders should obtain quotes from suppliers that can furnish the required domestic manufactured materials and the cost of such should be included in the contract unit prices bid for the various individual pay items. Waivers will only be considered when there is no domestic manufacturer of the specific item meeting the requirements in the appropriate section of the Standard Specifications. Questions relating to domestic product availability should be made pre-bid and responses, including possible waivers, will be posted on the Department's website.

The Contractor shall ensure that all manufacturing processes for each covered product comply with this Buy America Provision. Non-conforming products shall be replaced at no expense to the Department. It is the contractor's responsibility to assure all submittals required

## ARKANSAS DEPARTMENT OF TRANSPORTATION

### SPECIAL PROVISION

JOB NO. A60063

### BUY AMERICA - CONSTRUCTION MATERIALS

for Buy America are submitted to the Engineer prior to the products and or materials being incorporated into the project.

Buy America requirements do not apply to temporary elements not permanently incorporated into a project. This includes falsework, temporary sheet piling, detour bridges, temporary elements left in place at the contractor's convenience, unless the contract plans and specifications require steel or iron components or imply that the item be left in place, or items that are simply moved from one place to another within the same project. Buy America only applies to construction materials that are consumed in, incorporated into, or affixed to an infrastructure project. As such, it does not apply to tools, equipment, and supplies, such as temporary scaffolding, removed at or before completion of the project.

**(4) Certification.** The contractor shall provide a certification from the supplier for each construction material, stating that it meets the provisions of this specification or the Build America/Buy America act, prior to incorporating any construction material into the project. The supplier certifying may be the original manufacturer, fabricator, or vendor provided the supplier has sufficient control and knowledge of the manufacturing process to accept responsibility and certify full and complete conformance with the certification. In lieu of the manufacturer's certification, the Contractor or supplier may provide the Domestic Materials Self-Certification Form for the specific product from AASHTO's Product Evaluation & Audit Solution's datamine ([www.transportation.org/product-evaluation-and-audit-solutions](http://www.transportation.org/product-evaluation-and-audit-solutions))

**(5) Examples of Pay Items Affected.** The following are items from the Standard Specifications and common special provisions that must meet the requirements of this specification. This list is provided for bidders' information and is not to be considered as all-inclusive as other items covered by the standard specifications, supplemental specifications, and special provisions may also fall under these requirements:

| Non-Ferrous Metals                                                                                                                                   |                       |
|------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|
| Item                                                                                                                                                 | Specification Section |
| Aluminum Pipe Culverts                                                                                                                               | 606                   |
| Aluminum Chain Link Fence                                                                                                                            | 619                   |
| Aluminum Gates                                                                                                                                       | 619                   |
| Mailboxes                                                                                                                                            | 637                   |
| Electrical Conductors                                                                                                                                | 700, 708              |
| Controller Cabinet (cabinet assembly)                                                                                                                | 701, 702, 703         |
| Ground Rods                                                                                                                                          | 701, 712, 714, 715    |
| System Local Controller/Actuated Controller components (surge protector, conflict monitor, switches, flashers, relays, wiring harness, clocks, etc.) | 701. Job SP           |
| Pre-Timed Controller (cabinet and internal equipment)                                                                                                | 702                   |
| Flashing Beacon Controller (cabinet and all internal equipment)                                                                                      | 703                   |
| Loop Wiring                                                                                                                                          | 704                   |
| Vehicle Detectors (including all electrical components and mounting racks)                                                                           | 704                   |

## ARKANSAS DEPARTMENT OF TRANSPORTATION

### SPECIAL PROVISION

**JOB NO. A60063**

### BUY AMERICA - CONSTRUCTION MATERIALS

|                                                            |                            |
|------------------------------------------------------------|----------------------------|
| Feeder Wire                                                | 704                        |
| Preformed Detector Loops                                   | 704                        |
| Loop Wiring in Duct                                        | 705                        |
| Traffic Signal Heads (all types)                           | 706, Job SP                |
| Pedestrian Signal Heads                                    | 707                        |
| Traffic Signal Cable                                       | 708                        |
| Sign Supports - all types (including clips and fasteners)  | 724, 730                   |
| Sign Panels (including clips and fasteners)                | 723, 725, 726,<br>727, 728 |
| Video Detectors (detector, processor, and other equipment) | 733                        |
| Video Cable                                                | 733                        |
| Metal Bridge Railing                                       | 806                        |
| Bridge Name Plates                                         | 812                        |
| Accessible Pedestrian Signals (APS)                        | Job SP                     |
| Electrical Conductors for Luminaires                       | Job SP                     |
| Electrical Conductors-in-Conduit                           | Job SP                     |
| LED Roadway Illumination Poles                             | Job SP                     |
| Luminaires                                                 | Job SP                     |
| Pedestal Type Service Point Assembly                       | Job SP                     |
| Retroreflective Backplates                                 | Job SP                     |
| Wrong Way Detection System Controller Cabinet              | Job SP                     |
| Copper plumbing lines and fittings                         | Job SP                     |

| <b>Plastic/Polymer Based Products</b>                                                      |                              |
|--------------------------------------------------------------------------------------------|------------------------------|
| <b>Item</b>                                                                                | <b>Specification Section</b> |
| Joint Sealers (Types 3 and 4)                                                              | 501,503,<br>504,507,509      |
| Epoxy Coating for Dowel Bars and Reinforcing Steel                                         | 501, 502, 507,<br>804        |
| Epoxy Resin Anchoring Systems (Dowel Bars, Hand Rails, Metal Bridge Railing, Anchor Bolts) | 507, 633, 806,<br>807        |
| Polyethylene Pipe Culverts                                                                 | 606                          |
| PVC Pipe Culverts                                                                          | 606                          |
| RC Pipe Culvert Gaskets                                                                    | 606                          |
| Drop Inlet Steps                                                                           | 609, 610, 640                |
| ABS or Polyethylene Pipe for Underdrains                                                   | 611                          |
| PVC Pipe for Underdrain Laterals                                                           | 611                          |
| Filter Fabrics                                                                             | 611, 625, 629,<br>816        |
| Geotextile Fabrics                                                                         | 625                          |
| Tactile Panels for Wheelchair Ramps                                                        | 641, Job SP                  |

## ARKANSAS DEPARTMENT OF TRANSPORTATION

### SPECIAL PROVISION

**JOB NO. A60063**

### BUY AMERICA - CONSTRUCTION MATERIALS

|                                                                                                                                                      |             |
|------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| System Local Controller/Actuated Controller components (surge protector, conflict monitor, switches, flashers, relays, wiring harness, clocks, etc.) | 701, Job SP |
| Pre-Timed Controller (internal equipment)                                                                                                            | 702         |
| Flashing Beacon Controller (all internal equipment)                                                                                                  | 703         |
| Vehicle Detectors (all electrical components)                                                                                                        | 704         |
| Traffic Signal Heads (all types)                                                                                                                     | 706, Job SP |
| Pedestrian Signal Heads                                                                                                                              | 707         |
| Non-Metallic Conduit (PE & PVC)                                                                                                                      | 710         |
| Paint for Reflectorized Paint Pavement Markings                                                                                                      | 718         |
| Thermoplastic Pavement Markings (all)                                                                                                                | 719         |
| Permanent Pavement Marking Tape                                                                                                                      | 720         |
| Raised Pavement Markers (markers and epoxy adhesive)                                                                                                 | 721         |
| Sand Barrels/Lids for Impact Attenuation Barriers                                                                                                    | 731         |
| Video Detectors (detector, processor, and other equipment)                                                                                           | 733         |
| Paint Systems for Structural Steel                                                                                                                   | 807, 820    |
| Preformed Joint Seals                                                                                                                                | 809         |
| Silicone Joint Sealants                                                                                                                              | 809         |
| Accessible Pedestrian Signal (APS) components                                                                                                        | Job SP      |
| Cellular Modem                                                                                                                                       | Job SP      |
| Enhanced Thermoplastic Pavement Markings                                                                                                             | Job SP      |
| Ethernet Switch (all types)                                                                                                                          | Job SP      |
| Geogrids (all types)                                                                                                                                 | Job SP      |
| Hybrid Video/Radar Detection System components                                                                                                       | Job SP      |
| Latex Modifier in Latex Modified Concrete Overlays                                                                                                   | Job SP      |
| Lightweight Panels for Sound Reflecting Noise Barriers                                                                                               | Job SP      |
| Overhead Digital Message Sign Assembly                                                                                                               | Job SP      |
| Polymer Resin in Polymer Overlays                                                                                                                    | Job SP      |
| Polypropylene Pipe Culverts                                                                                                                          | Job SP      |
| PTZ Camera System                                                                                                                                    | Job SP      |
| Radar Detection System                                                                                                                               | Job SP      |
| Wrong Way Detection System FLIR Thermal Sensor                                                                                                       | Job SP      |
| Wrong Way Detection System Solar Panel                                                                                                               | Job SP      |
| PVC piping and fittings for building projects                                                                                                        | Job SP      |

| Glass                                                            |                       |
|------------------------------------------------------------------|-----------------------|
| Item                                                             | Specification Section |
| Glass Beads (drop on application)                                | 718, 719              |
| Fiber Optic Cable                                                | Job SP                |
| Solar Panels (Wrong Way Detection Systems and other ITS systems) | Job SP                |
| Windows in Building Construction                                 | Job SP                |

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**BUY AMERICA - CONSTRUCTION MATERIALS**

| <b>Lumber</b>                                                 |                              |
|---------------------------------------------------------------|------------------------------|
| <b>Item</b>                                                   | <b>Specification Section</b> |
| Wood Guard Rail Posts                                         | 617, 639                     |
| Wood Block Outs for Guardrail                                 | 617,639                      |
| Wood Posts for Guard Cable                                    | 618                          |
| Fence Posts and Braces (Type A, B, C and D)                   | 619                          |
| Mailbox Supports                                              | 637                          |
| Treated Wood Poles                                            | 716                          |
| Treated Lumber                                                | 817                          |
| Treated Bridge Timbers                                        | 817                          |
| Timber Piling                                                 | 818                          |
| Framing Lumber, Plywood, Trim Lumber in Building Construction | Job SP                       |

| <b>Drywall</b>                   |                              |
|----------------------------------|------------------------------|
| <b>Item</b>                      | <b>Specification Section</b> |
| Drywall in Building Construction | Job SP                       |

**ARKANSAS DEPARTMENT OF TRANSPORTATION****SPECIAL PROVISION****JOB NO. A60063****VENDOR REGISTRATION REQUIREMENT**

To ensure proper information is on file for all contractors on ARDOT construction projects, prime contractors and subcontractors shall submit vendor registration information using the ARDOT Vendor Registration Form.

The ARDOT Vendor Registration Form is a Microsoft Form developed to allow the Department to collect vendor information electronically and transmit that information into the Department's construction management system (CMS).

The form may be used both for initial registration and for submission of updated vendor information when changes are needed, such as updated contact information.

Contractors may complete the ARDOT Vendor Registration Form at any time to be included in the construction management system as a Vendor. The form allows contractors to indicate if they wish to be considered for Prequalification or for DBE Certification. The form will not complete the Prequalification or DBE Certification process but will instead initiate the process with the proper Divisions in ARDOT. All bidders must submit this form prior to bidding on any Proposal to ensure ARDOT data is correct and complete. Any contractors who will be added as Subcontractors on the Contract shall complete the ARDOT Vendor Registration Form prior to submitting the actual subcontract.

Vendors shall ensure that all information submitted through the ARDOT Vendor Registration Form is complete and accurate. The Department may require correction or resubmission of incomplete or inaccurate information before the registration is considered acceptable.

No direct payment will be made for furnishing and submitting vendor registration information. All costs associated with complying with this Special Provision shall be considered incidental to the contract.

The ARDOT Vendor Registration Form is available at the following link:

<https://forms.office.com/Pages/ResponsePage.aspx?id=k42YmO7x6EGK6v9zsAW4fbNdDoviCDRLsOknaQRB5A9UME5XOVc0T1pKMU84VFQwMUy5Nk5NQTY0MCQIQCN0PWcu>

**ARKANSAS DEPARTMENT OF TRANSPORTATION****SPECIAL PROVISION****JOB NO. A60063****DOCUMENTATION OF PAYMENTS MADE – PROMPT PAYMENT (SIGNET)**

In accordance with Section 108.01 of the Standard Specifications, the Contractor shall pay all subcontractors their respective subcontract amount within 10 calendar days after the Contractor receives payment from the Department. Payment is defined as issuing an Electronic Funds Transfer (EFT) or mailing a check to a subcontractor. The 10-day requirement is met on the date that payment is issued to the subcontractor.

First-tier subcontractors have the same obligation to any second-tier subcontractors. Subcontractors must pay their second-tier subcontractors within 10 days of receipt of payment from the Prime Contractor.

ARDOT monitors payments made by prime contractors to both DBE and non-DBE subcontractors to ensure compliance with prompt payment requirements. Prime contractors are required to report payments made to all subcontractors, and subcontractors must report payments made to any lower-tier subcontractors. Subcontractors are required to confirm receipt of payment.

The tracking of subcontractor prompt payment is conducted using the Signet™ application. Signet™ is a third-party service, supported by the software vendor, which is used by both Prime and Subcontractors. Signet™ is a reporting tool only and does not process financial transactions. ARDOT does not provide direct technical support for Signet™. Information about Signet™ may be found at <https://signet-help.zendesk.com> and by clicking the Signet™ tab.

Signet™ shall be required for use on this construction contract.

Upon completion of the first payment estimate on the contract Signet™ will automatically notify the Contractor via email prompting registration in Signet™ for that contract. The Prime Contractor will be required to pay a one-time, fixed fee of \$1,100 for this contract. Payment will be made to the Signet™ vendor. This will activate use of Signet™ for the Prime and all Subcontractors for the duration of that contract, regardless of contract value, number of subcontractors, contract duration, or number of payments reported. Subcontractors will not be charged any fee to register for contracts.

After each estimate, the Prime Contractor will report remitted payment to subcontractors in Signet™. This will trigger notification to each subcontractor via email requesting verification of the reported payment. The subcontractor will be given the opportunity to register with Signet™ at that time (for no cost).

The Prime or Subcontractor reporting payment must report the following information in Signet™:

- The name of the subcontractor or second-tier subcontractor receiving payment.
- The dollar amount of the payment made to the subcontractor or second-tier subcontractor.
- The date the payment was made to the subcontractor or second-tier subcontractor.
- Any retainage, which is only permitted if it was included in the individual subcontract when it was submitted to the Department for acknowledgement.
- The DBE Function performed for this payment (if the subcontractor/second-tier subcontractor is a DBE).
- Other information required by Signet™.

**ARKANSAS DEPARTMENT OF TRANSPORTATION****SPECIAL PROVISION****JOB NO. A60063****DOCUMENTATION OF PAYMENTS MADE – PROMPT PAYMENT (SIGNET)**

The contractor must report the return of retainage or other withholdings in separate, standalone payment entries (separate from routine, planned progress payment estimates).

In the event that no subcontract work is included in a payment estimate, such that no payment is due to any subcontractors, the Prime Contractor shall mark the payment complete within Signet™, and no other payments are required to be reported for that estimate.

Subcontractors must verify in the Signet™ application each payment reported by a payer within 10 days of the payment being reported by the payer. This verification includes whether the payment was received and, if so, whether it was as expected.

**Basis of Payment.** The cost of registration for the Signet™ application will be reimbursed by the Department using a line item in the contract. The reimbursement will be set to match the current cost of the registration fee for Signet™ and will not be bid by the contractor. All costs for usage, time, labor, or other costs for reporting payments to subcontractors through the Signet™ application will be considered incidental and no direct payment will be made for these.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SPECIAL PROVISION**  
**JOB NO. A60063**

**DOCUMENTATION OF PAYMENTS MADE TO  
DISADVANTAGED BUSINESS ENTERPRISES**

Although this contract does not have a Disadvantaged Business Enterprise (DBE) Goal, in accordance with Subsection 103.08(a) of the Standard Specifications all payments made to DBE Contractors, suppliers, manufacturers, and/or non-construction service firms must be reported by the Prime Contractor.

Documentation of payments made to DBEs will be as described in the “Documentation of Payments Made – Prompt Payment (Signet)” Special Provision.

## ARKANSAS DEPARTMENT OF TRANSPORTATION

### SPECIAL PROVISION

JOB NO. A60063

### BIDDING REQUIREMENTS AND CONDITIONS

**Section 102** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The fourth sentence of the second paragraph of **Subsection 102.01** is hereby deleted, and the following substituted therefore:

Prospective bidders may file a questionnaire at any time; however, prospective bidders will not be given authorization to submit a proposal unless a rating has been extended based on an acceptable questionnaire.

The following paragraph has been added to **Subsection 102.01**.

A contractor with common officers/owners/partners of any firm, partnerships, joint ventures, or corporations that is seeking prequalification, has been prequalified, or has entered into a previous or current contract with the Commission may have the prequalification denied, limited, or revoked for the reasons listed in Subsection 102.04(a)-(m).

The last paragraph of **Subsection 102.01** is hereby deleted.

The second sentence of **Subsection 102.02** is hereby deleted, and the following substituted therefore:

The Notice to Contractors will contain a description of the proposed work, and information regarding access to proposal documents, plans, specifications, and the amount and nature of the proposal guaranty.

**Subsection 102.03** is hereby deleted, renamed **Contents of Proposal Documents**, and the following substituted therefore:

The proposal documents will state the location and description of the contemplated construction and will show the estimate of the various quantities and kinds of work to be performed or materials to be furnished, and will have a schedule of items. The proposal documents will state the time in which the work must be completed, the amount of the proposal guaranty, and the date and time of the letting of work. The documents will also include any special provisions or requirements that vary from or are not contained in the standard specifications.

All forms included in the proposal documents are considered a part thereof. The plans, specifications, and other documents designated in the proposal documents will be considered a part of the proposal whether included or not.

## ARKANSAS DEPARTMENT OF TRANSPORTATION

### SPECIAL PROVISION

JOB NO. A60063

#### BIDDING REQUIREMENTS AND CONDITIONS

The first through fourth paragraphs of **Subsection 102.04** are hereby deleted, and the following substituted therefore:

To become an eligible bidder, prospective bidders must be registered to bid in Arkansas with Bid Express. Prospective bidders must also contact the Program Management Division at (501) 569-2261 during regular business hours between the date the project is advertised and 4:30 p.m. on the day prior to the scheduled bid opening to request to become eligible to bid specific projects. Only prequalified contractors or their authorized representative may request to become an eligible bidder.

If the prospective bidder's prequalification rating is not "unlimited", the bidder shall file a certification with the Department citing all contracts in force and the unfinished value of such work. A prospective bidder will not be allowed to submit a proposal until a certification for the current bidding period is on file and the amount of work the contractor may be allowed to undertake is determined. The contractor's prequalification rating, less the unfinished value of all contracts in force, will determine the amount of additional work that the contractor may be allowed to undertake. A contractor will not be allowed to submit a proposal on an individual project for which the estimated cost is more than the amount that the contractor may be allowed to undertake, but the contractor will be allowed to submit a proposal on more than one project, providing that the estimated cost of each project is not more than the amount that the contractor may be allowed to undertake. In the event a contractor submits a low bid on more than one project and the aggregate amount is greater than the amount the contractor may be allowed to undertake, the Commission will exercise its discretion in the award of a particular project or projects.

A charge will be assessed for authorization to submit a proposal, paper copies of the proposal documents, and plans issued. These services are provided during regular business hours until 4:30 p.m. on the day prior to the scheduled bid opening at the Arkansas Department of Transportation, 10324 Interstate 30, Little Rock, Arkansas 72209, (501) 569-2261. Payment shall be made at the time services are provided or upon receipt of statement therefore. No refund will be allowed for bids not submitted or for plans or proposal documents returned.

The second sentence of the first paragraph of **Subsection 102.06** is hereby deleted, and the following substituted therefore:

The bidder is expected to examine carefully the site of the proposed work, the proposal documents, plans, specifications, supplemental specifications, and special provisions before submitting a proposal.

## ARKANSAS DEPARTMENT OF TRANSPORTATION

### SPECIAL PROVISION

JOB NO. A60063

### BIDDING REQUIREMENTS AND CONDITIONS

The first paragraph of **Subsection 102.07** is hereby deleted, and the following substituted therefore:

The proposal shall only be submitted through the internet bidding service, Bid Express. The bidder shall specify a unit price in figures for each pay item for which a quantity is given. A unit price of "zero" (\$0.00) is a valid price and will be considered. A blank unit price is not considered valid. The unit bid price should not be carried beyond 1 cent (\$0.01). Any figures on the unit bid price beyond 1 cent will be dropped.

The second and third paragraphs of **Subsection 102.07** are hereby deleted.

The fifth paragraph of **Subsection 102.07** is hereby deleted, and the following substituted therefore:

The bidder's proposal must be submitted with a digital signature containing the name of the individual, one or more members of the partnership, one or more members or officers of each firm representing a joint venture, or one or more officers of a corporation, or by an agent of the Contractor legally qualified and acceptable to the Department.

The sixth paragraph of **Subsection 102.07** is hereby deleted, and the following substituted therefore:

If the proposal is submitted with a digital signature of any person who is not listed in the bidder's Prequalification Questionnaire (Questionnaire Form) as the individual, as a partner of a partnership, or as an officer of a corporation, authorization for such submittal should be on file with the Department prior to the download of bids. This authorization shall be made before the downloading of bids and be in the form of a Power of Attorney duly executed and signed by an official with power to constitute such authority.

The last sentence of the seventh paragraph of **Subsection 102.07** is hereby deleted, and the following substituted therefore:

Those items of Asphalt Binder that are subject to a minimum bid price will bear the note "(Minimum bid price is \$120.00 per ton)" within the Schedule of Items of the proposal documents.

The first sentence of the ninth paragraph of **Subsection 102.07** is hereby deleted, and the following substituted therefore:

The proposal documents for all federal aid projects will contain a bidders list.

The last sentence of the ninth paragraph of **Subsection 102.07** is hereby deleted, and the following substituted therefore:

The information provided will not be used for contract awarding purposes but must be provided before the Contractor will be given authorization to submit proposals for future lettings.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**BIDDING REQUIREMENTS AND CONDITIONS**

**Subsection 102.08 Irregular Proposals** is hereby deleted, and the following substituted therefore:

- (a) Proposals will be considered irregular and will be rejected for the following reasons:
  - (1) If the proposal does not contain a unit price for each pay item listed except in the case of authorized alternate pay items.
  - (2) If the proposal is not digitally signed by an authorized representative of the firm.
  - (3) If the proposal is not accompanied by the proper proposal guaranty.
  - (4) If a proposal is received from an individual, firm, partnership, or corporation with an interest, as principal, in another proposal for the same project.
  - (5) If the proposal is not accompanied by the Certification to Submit DBE Participation.
- (b) Proposals will be considered irregular and may be rejected for the following reasons:
  - (1) If the proposal is not accompanied by a bid schedule and bid schedule narrative as required in the proposal documents.
  - (2) Unbalanced proposals in which the prices for some items are out of proportion to the reasonable costs representative of those items.
  - (3) If there are irregularities of any kind that may tend to make the proposal incomplete, indefinite, or ambiguous as to its meaning.

The first sentence of **Subsection 102.09** is hereby deleted and the following substituted therefore:

No proposal will be considered by the Commission unless a guaranty in the form of a bank draft, certified check, or cashier's check drawn on a solvent bank or trust company, or a bidder's paper bond executed by an approved surety company has been received by the Program Management Division prior to the download of bids.

The following paragraph is hereby added after the first paragraph of **Subsection 102.09**:

Electronic bid bonds are allowed. The prospective bidder should verify their bid bond in their proposal prior to submission.

**Subsection 102.10** is hereby deleted and the following substituted therefore:

The proposal shall only be submitted through the internet bidding service, Bid Express.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**BIDDING REQUIREMENTS AND CONDITIONS**

**Subsection 102.11** is hereby deleted, and the following substituted therefore:

A bidder may withdraw or modify a proposal after it has been submitted to Bid Express, up to the time set for the deadline for proposals to be received. A proposal may also be withdrawn if the Commission fails to make an award within 40 calendar days after the date of downloading.

**Subsection 102.12** is hereby deleted, renamed **Downloading of Proposals**, and the following substituted therefore:

Proposals will be downloaded and then posted on the Department's website at the time and place indicated in the Notice to Contractors.

The last sentence of **Subsection 102.15** is hereby deleted, and the following substituted therefore:

In any case, the prospective bidders will be contacted prior to the download of bids.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**MANDATORY ELECTRONIC CONTRACT**

**Paper Contract Documents and Forms will not be accepted.**

The Department will only accept and execute an electronic contract for this project through Doc Express, a paperless contracting system. Prospective bidders will need to contact Doc Express to set up an account prior to the bid opening date. The toll-free phone number for Doc Express is 1-888-352-2439 and their website address is [www.docexpress.com](http://www.docexpress.com).

**Section 103** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows.

The first sentence of **Subsection 103.06(a)** is hereby deleted, and the following substituted therefore:

The Contract shall be electronically signed by the successful bidder and electronically submitted to the Program Management Division, Construction Contract Procurement Section, together with the required bonds and proof of liability insurance, within 10 business days after the notice of award has been issued.

**Subsection 103.08(d)(3)d.** is hereby deleted, and the following substituted therefore:

Documentation of the bidder's commitment to use a DBE subcontractor whose participation it submits to meet a contract goal; and

**Subsection 103.08(d)(3)e.** is hereby deleted, and the following substituted therefore:

Document confirmation from the DBE that it is participating in the contract as provided in the Contractor's commitment.

**Subsection 103.08(d)(5)** is hereby deleted, and the following substituted therefore:

The preceding information shall be submitted directly to the Arkansas Department of Transportation, Program Management Division, via Doc Express.

## **ARKANSAS DEPARTMENT OF TRANSPORTATION**

### **SPECIAL PROVISION**

**JOB NO. A60063**

### **MANDATORY ELECTRONIC DOCUMENT SUBMITTAL**

#### **Paper Document Submittals will not be accepted.**

The Department will only accept electronically-submitted documents for consideration on this project. All correspondence and submittals to the Department shall be submitted through Doc Express, a paperless contracting system. When signed originals are required, the original shall be the document uploaded to Doc Express and the signature shall be the electronic signature applied through Doc Express. The Contractor shall use the same organizational account for project documentation as used to fulfill the requirements of the Mandatory Electronic Contract Special Provision. The toll-free phone number for Doc Express is 1-888-352-2439 and their website address is [www.docexpress.com](http://www.docexpress.com).

Any reference in the Standard Specifications to document submittal in writing or by U.S. Mail, facsimile, or in person is hereby amended to require that such documents be submitted using Doc Express with the following exceptions:

- Material delivery tickets which are used for payment or for field verification shall be submitted on paper as required by the Standard Specifications for Highway Construction, Edition of 2014.
- Any document with specific submittal requirements in state and/or federal law or federal regulations that conflict with the requirements of this Special Provision shall be submitted in accordance with such state and/or federal law or federal regulations.

A user guide is available on the Department's web page to assist Contractors with the use of Doc Express. The "Contractor Guide to Using Doc Express" is available on the Department's web page at <https://ardot.gov/divisions/construction/doc-express/>.

The Contractor may provide access for subcontractors to view and submit items in Doc Express by following the instructions provided in the "Contractor Guide to Using Doc Express". Once an organizational account is activated and the Contractor provides access to the contract, a subcontractor may submit documents to the Contractor in Doc Express by uploading the electronic documents as directed in the User Guide. Any documents uploaded by the subcontractor must be then retrieved and published by the Contractor within Doc Express for further action by the Engineer. The Engineer will not review or take any actions on any documents submitted by the subcontractor until the document has been appropriately submitted by the Contractor.

Any submittals, documents, subcontracts, proposals, working drawings, or any other items submitted by the Contractor within Doc Express are not considered approved by the Engineer until written notification of the approval is published by the Engineer in the "CON-Correspondence-From Department to Contractor" drawer in Doc Express. Any action taken by the Contractor prior to this notification is taken at the Contractor's own risk.

The Department's System Administration team has no authority to take action on any documents submitted to the system. Access for this team is for management of the application only. Knowledge of any document submitted is not imputed to the Department by the knowledge of Systems Administration.

The requirements of this Special Provision shall supersede the requirements of all other Special Provisions unless such Special Provision includes a stated exception to this Special Provision.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**ASSESSMENT OF WORKING DAYS – MAINTENANCE OF TRAFFIC**

**DESCRIPTION:** To accommodate the off peak lane closure time limits shown in the contract “Maintenance of Traffic” Special Provision, the assessment of Calendar Days or Working Days will be based upon the same conditions as a normal Working Day.

For Calendar Day or Working Day projects, the Contractor shall be permitted to begin work on Sunday evening when the allowable lane closure period begins. Sunday evening shall be the allowable off peak lane closure time defined in the contract “Maintenance of Traffic” Special Provision but not prior to 6:00 p.m. On Working Day projects, time will not be assessed for Sunday. No other work will be allowed on Sunday unless an emergency is declared by the Department.

If the Contractor elects to work Friday and complete work on Saturday in accordance with the contract “Maintenance of Traffic” Special Provision, time will be assessed as appropriate for Saturday.

**ARKANSAS DEPARTMENT OF TRANSPORTATION****SPECIAL PROVISION****JOB NO. A60063****LIQUIDATED DAMAGES PROCEDURE FOR BID LETTINGS**

Department Standard Specification **Section 102.04 and Supplemental Specification 102-2** state that the Department reserves the right to refuse to issue, accept, or consider a proposal:

“If the prospective bidder is the Contractor on a current Contract with the Commission on which Liquidated Damages are being assessed, and there are no pending time extensions warranted to remove the project from Liquidated Damages.”

If the prospective bidder goes into liquidated damages on a current Contract with the Commission during the advertisement period for a letting, the Contractor will be notified seven business days prior to the letting that they will not be allowed to bid in the upcoming letting. This notification will be officially transmitted through Doc Express for the project in liquidated damages and via email.

Upon notification that they will not be allowed to bid in the upcoming letting, the Contractor will be provided an opportunity to request a reconsideration of this decision. This request must be transmitted in the form of a letter through Doc Express and via email to the Department for review within two (2) business days of receipt. The Department will review the reconsideration request and render a decision no later than the Friday prior to the letting.

Please note, a bid may be withdrawn at any time prior to the time specified for the bid letting. If a Contractor has been notified that they will not be allowed to bid, and they do not withdraw their bid, the bid will be considered invalid and rejected.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SPECIAL PROVISION**  
**JOB NO. A60063**  
**ELECTRONIC TICKETING SYSTEMS (E-TICKETING)**

Division 100 of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The following is added as **Subsection 109.01(m)**:

**(m) Electronic Ticketing System.** The Department has contracted with an Electronic Ticket Delivery System (E-Ticketing) application known as HaulHub for use by ARDOT personnel on projects. A Contractor/Supplier Portal is also available for use by the Contractor or Supplier, if desired. This portal is included at no cost to the Contractor or Supplier. HaulHub has provided a web page detailing how the software works and how to get started here: <https://www.haulhub.com/agency/arkansas>. Upon request of the Contractor, HaulHub may be used in lieu of paper tickets, subject to the requirements outlined herein. The Contractor must notify the Resident Engineer and email [sitemanager@ardot.gov](mailto:sitemanager@ardot.gov) to activate the E-Ticketing application.

The Contractor shall coordinate with HaulHub (and if applicable, the ACHM Supplier) to facilitate integration of HaulHub to the electronic ticket data. HaulHub can accommodate most configurations of systems, including API connections to data and direct database connections, among others. The connection with HaulHub will be a Read-Only connection, allowing the application to receive load information only. HaulHub can also work with other E-Ticketing vendors to share data, if that approach is needed/preferred.

The Contractor shall comply with all applicable laws and regulations pertaining to bills of lading and ensuring the trucks have proper documentation onboard during transport, but paper tickets will not typically be collected by Department personnel. At project locations where mobile devices cannot achieve consistent connectivity, alternative means of material ticket collection may be necessary at the discretion of the Engineer. Alternative methods may include software offline modes (handled by HaulHub) or hardcopy paper ticketing.

No additional compensation will be made for the use of HaulHub on this project. There should also be no direct cost to the Contractor or Supplier in most cases.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SPECIAL PROVISION**  
**JOB NO. A60063**  
**DESIGN AND QUALITY CONTROL OF ASPHALT MIXTURES**

**Division 400** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The eighth and tenth bullet within the first paragraph of **Subsection 404.01, Design of Asphalt Mixtures. (a) General** is hereby deleted and the following added:

- A one-gallon sample of performance grade asphalt binder to be used in all Section 405 Asphalt Concrete Hot Mix Base Course and Section 406 Asphalt Concrete Hot Mix Binder Course mix designs.
- Five blended aggregate samples for all Section 405 Asphalt Concrete Hot Mix Base Course and Section 406 Asphalt Concrete Hot Mix Binder Course mix designs.
- A two-gallon sample of performance grade asphalt binder to be used in all Section 407 Asphalt Concrete Hot Mix Surface Course mix designs.
- Ten blended aggregate samples for all Section 407 Asphalt Concrete Hot Mix Surface Course mix designs.

The last sentence of the last paragraph of **Subsection 404.01 Design of Asphalt Mixtures. (a) General** is hereby deleted and the following substituted therefor:

At least fifteen (15) business days shall be allowed for the review of the mix design.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**LONGITUDINAL JOINT DENSITIES FOR ACHM SURFACE COURSES**

**DIVISION 400, ASPHALT PAVEMENTS**, of the Standard Specifications, Edition of 2014, is hereby amended as follows:

The following is added after the first paragraph of **Subsection 407.04, Construction Requirements and Acceptance**:

A notched wedge joint is required along all unconfined longitudinal joints where paving lifts are 2 inches or greater in depth. Notched wedge joints shall have a slope no greater than 1:12 from the pavement mat and may only be used when the depth of the mat is greater than 1½ inches. The notched wedge is not required in areas of build up for slope adjustments. The adjacent lane may be milled to allow the placement of the notched wedge joint. Interstate projects that are mill and fill shall not mill the adjacent lane until the new asphalt has been placed. Joints shall not be placed in the wheel path. Notched wedge joints will not be required between the shoulder and travel lane.

For mill and fill locations that are not constructed using a notched wedge, a milled or cutback joint shall be formed using a milling machine or saw to create a vertical face in the first mat after it has been compacted. No more than 2" in width shall be cut or sawed into the new mat to create a clean joint free of loose aggregates or old asphalt. Tack shall cover the notched wedge and/or vertical face prior to placing the adjacent lane.

Joint densities shall be measured directly on, and centered over, the visible joint for cutback joints or centered over the wedge for joints constructed using a notched wedge paver attachment. The joint density core samples shall be 6" diameter and should be cut while the lane closure for the paving operation is still in place to provide proper traffic control for the coring operation. The core location may be cooled to permit coring. If the Contractor is unable to cut the cores while the lane closure is still in place, the coring operation must be performed using either a static or moving lane closure as detailed in the plans or MUTCD, and in accordance with any limitations contained in the Contract. The required joint density shall be 90% to 97% of the maximum theoretical density.

The third paragraph of **Subsection 410.07, Spreading and Finishing**, is hereby deleted and the following is substituted therefor:

The longitudinal joint in one layer shall offset that in the layer immediately below by approximately 6". When possible, the joint in the top layer shall be at the centerline of the pavement if the roadway comprises two lanes in width, or at lane lines if the roadway is more than two lanes in width. On roadways with a center turn lane, the Contractor may, at his option, elect to place a joint at the crown (i.e., middle of the center turn lane) of the roadway and eliminate the joints on the lane lines of that lane. The slight excess of asphalt at a longitudinal joint, generated by overlapping during placement of an adjacent mat to a previous mat, shall not be scattered across the mat.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**LONGITUDINAL JOINT DENSITIES FOR ACHM SURFACE COURSES**

The asphalt screed shall be operated in vibration mode while placing the mixture. Auger gates and tunnels should be extended to within 12 to 18 inches of the end gate to ensure material is not being pushed and segregated. An approved release agent may be applied to tow behind rollers used to compact notch wedge joints.

The second sentence of the fifth paragraph of **Subsection 410.07, Spreading and Finishing**, is hereby deleted and the following is substituted therefor:

The top layer of a notched wedge joint shall be placed within three days of constructing the notch.

The following is added after the last paragraph of **Subsection 410.08 Rolling and Density Requirements and Joints**:

When the material forming the two sides of a longitudinal joint comes from two different sublots, the theoretical maximum density used as a basis for density calculations shall be the average of the theoretical maximum density for the two sublots.

**Subsection 410.09 (a), General**, is expanded to include the following:

**(1) Joint Density.** The standard lot size for acceptance and adjustment in payment will be 40,000 linear feet, with each standard lot divided into four sublots of 10,000 linear feet each. These lengths will apply only to ACHM Final Surface Course areas in which both sides of the longitudinal joint have been formed, including the joints between the travel lanes and acceleration or deceleration lanes, but excluding the longitudinal joint between a shoulder and travel lane which will not be subject to this testing. Turn lanes are to be considered a travel lane for joint density requirements. Joint cores for ACHM Intermediate Surface Course areas will not be required.

Partial lots normally will be not less than 4,000 linear feet nor more than 44,000 linear feet.

The following is added after the last sentence of the second paragraph of **Subsection 410.09, Acceptance of the Pavement and Adjustments in Payment, (a) General**:

Field density tests on longitudinal joints shall be performed directly on the joint as soon as possible after placement of the hot lane. The core should be cut while the lane closure for the paving operation is still in place to provide proper traffic control for the coring operation. If the Contractor is unable to cut the cores while the lane closure is still in place, the coring operation must be performed using either a static or moving lane closure as detailed in the plans or MUTCD, and in accordance with any limitations contained in the Contract.

The first and second sentences of the third paragraph of **Subsection 410.09, Acceptance of the Pavement and Adjustments in Payment, (a) General** is hereby deleted and the following substituted therefor:

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SPECIAL PROVISION**  
**JOB NO. A60063**

**LONGITUDINAL JOINT DENSITIES FOR ACHM SURFACE COURSES**

The Contractor shall obtain, and test one sample taken at random from each subplot, including for longitudinal joint density testing. The Department will determine the location for each sample in the subplot by ARDOT Test Method 465.

**Subsection 410.09, (b) Acceptance of the Pavement** is hereby modified as follows:

The following is added as the second bullet following the first paragraph:

- The results of tests for the longitudinal joint density in Table 410-2

The following is added after the last paragraph of **Subsection 410.09(b)(1)**:

Acceptance for Longitudinal Joint Density as shown in Table 410-2 will be by lot. Acceptance of a standard longitudinal joint density lot will be based on the average of the five (5) tests performed on the lot. Acceptance of a partial lot will be based on the average of the actual number of tests made on that partial lot.

Incentives or disincentives will be added or deducted from the payment made for each acceptance lot for Longitudinal Joint Density according to Table 410-2. Lots or partial lots containing a lot or subplot test less than 90% or greater than 97% of the maximum theoretical density will not be eligible for incentive pay.

In addition to the disincentives provided within the table, any lot with density results which average below 88% shall be sealed at no cost to the Department. The entire length of the longitudinal joint within the lot shall be sealed with PG 64-22 asphalt cement. The asphalt cement sealant shall be heated and maintained between 265°F and 320°F. The sealant shall not be placed if the air temperature is below 40°F, unless otherwise permitted by the Engineer. The joint area of the pavement surface must be clean, dry, and free of any loose material and debris. Cleaning with a power broom may be required. Utilize a pressure applicator with a wand or nozzle capable of applying hot asphalt sealant in a straight and consistent width of 4 inches  $\pm$  1 inch and thickness of 1/16 inch  $\pm$  1/32 inch at specified temperature range and at a minimum rate of 0.013 gallons/linear foot. The center of the sealant band should be placed within 1 inch of the joint. Immediately level high spots with a squeegee or wand. Remove and dispose of excess sealant at no cost to the Department. Re-seal areas of the joint that are inconsistently or not completely covered. Any pavement markings marred by the sealing operation will be replaced at no additional cost to the Department.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SPECIAL PROVISION**  
**JOB NO. A60063**  
**LONGITUDINAL JOINT DENSITIES FOR ACHM SURFACE COURSES**

TABLE 410-2  
LONGITUDINAL JOINT DENSITY PAY TABLE

| % Gmm |      | \$/L.F./Lot |
|-------|------|-------------|
| Min.  | Max. |             |
| 98.0  | 100  | -0.70       |
| 97.0  | <98  | -0.42       |
| 96.0  | <97  | +1.00       |
| 95.0  | <96  | +1.00       |
| 94.0  | <95  | +0.98       |
| 93.0  | <94  | +0.77       |
| 92.0  | <93  | +0.42       |
| 91.0  | <92  | 0.00        |
| 90.0  | <91  | 0.00        |
| 89.0  | <90  | -0.42       |
| 88.0  | <89  | -0.77       |
| 87.0  | <88  | -0.98       |
|       | <87  | -1.00       |

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**SUBMISSION OF ASPHALT CONCRETE HOT MIX ACCEPTANCE TEST RESULTS**

**Division 106** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The following is hereby added to **Subsection 106.04, Acceptance of Materials**:

All ACHM Contractor Acceptance Tests shall be signed by the technician and submitted electronically through Doc Express in pdf format, and a signed paper copy be given to the ARDOT plant inspector after the completion of each subplot.

The ACHM Microsoft Excel Spreadsheet for Contractors/Suppliers is the required form for documentation and can be downloaded from the following website:

<https://ardot.gov/divisions/construction/construction-information/for-use-on-feb-2024-letting-and-later-achm-spreadsheet/>

To download this file, follow the instructions on the page linked above. Use of this file requires Microsoft Excel.

Any questions or issues arising from the use of this file should be referred to the Resident Engineer.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**PRICE ADJUSTMENT FOR ASPHALT BINDER**

A price adjustment clause is included in this Contract to provide additional compensation to the Contractor or a credit to the Department for fluctuations in asphalt binder prices. This price adjustment is dependent upon a change in the average price of asphalt binder which results in an increase or decrease in the price of products utilized on this project.

**Payment.** Payment will be made to the Contractor for monthly fluctuation in the price of asphalt binder used in performing the applicable items of Asphalt Concrete Hot Mix and Ultrathin Bonded Wearing Course work as listed in the table below when the asphalt binder price fluctuates from the base price defined below. Payment may be positive, negative, or nonexistent depending on the circumstances. Payments or deductions for the asphalt binder price adjustment will be included in the Contractors current estimates, and the payment or deduction authorized for each estimate will be based upon the quantities for applicable items of work.

The Asphalt Binder Price Adjustment will be a dollar amount paid as compensation to the Contractor, or as a credit to the Department as reflected on the Current (or Final) Estimate Summary Report as Payment Adjustments.

**Asphalt Binder Price Adjustment (ABPA).** The Asphalt Binder Price Adjustment (ABPA) for the current estimate will be computed according to the following formula:

$$ABPA = Q \times D \times (IQP / 100)$$

Where

- ABPA = Asphalt binder price adjustment, in dollars;
- Q = Quantities paid for the applicable items on the current estimate; tons of mix for ACHM items or square yards for Ultrathin Bonded Wearing Course
- D = Allowable price differential, in dollars;
- IQP = Item Quantity Percent, Quantity of Indexed Material per unit of the applicable item on the current estimate.

The above formula will be applied to each individual payment of the applicable item. When the Current (or Final) estimate is generated, the sum of these individual adjustments will be included as a Payment Adjustment.

| Applicable Items of Work                 |                      |                       |
|------------------------------------------|----------------------|-----------------------|
| ITEM OF WORK                             | SPECIFICATION NUMBER | ITEM QUANTITY PERCENT |
| Asphalt Binder in ACHM Base Course       | 405                  | 100                   |
| Asphalt Binder in ACHM Binder Course     | 406                  | 100                   |
| Asphalt Binder in ACHM Surface Course    | 407                  | 100                   |
| Ultrathin Bonded Wearing Course (Type B) | SP                   | 5.5                   |
| Ultrathin Bonded Wearing Course (Type C) | SP                   | 5.4                   |

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**PRICE ADJUSTMENT FOR ASPHALT BINDER**

The terms of this Special Provision will apply only to the items listed in this Special Provision table above. No other items on the contract will be subject to the terms of this Special Provision.

The allowable price differential, "D", for the current estimate will be computed according to the following formula, using the appropriate binder grades:

$$D = P - P(b)$$

P, the asphalt binder current price in dollars per ton, is the Monthly Asphalt Binder Price Index for the month in which the payment entry is entered.

P(b), the asphalt binder base price in dollars per ton, is the Monthly Asphalt Binder Price Index for the month in which the bids for the work were received.

**Asphalt Binder Index Determination.**

**PG64-22 Binders.** The Monthly Asphalt Binder Price Index for PG64-22 binders will be determined by calculating the average for performance-graded binder using the Selling Price of PG 64-22 paving grade. The monthly asphalt binder price will be an average of five asphalt binder prices. The prices will be furnished by the four largest asphalt binder suppliers in the State of Arkansas as determined by the previous calendar year. For an asphalt supplier to be included in the asphalt binder price index they must supply at least ten percent of the asphalt binder in Arkansas. The final component in the asphalt binder price index will be the Asphalt Weekly Monitor® furnished by Poten & Partners, Inc. The issue of the Asphalt Weekly Monitor® used will be for the last full week in the previous month received by the Department prior to the first day of the index month. The four largest suppliers included in the asphalt binder price index shall furnish the Department with their average price on the Thursday before the Friday of the last full week of the month. If any supplier fails to submit a price by this deadline, that supplier's price will not be included in the asphalt binder price index for that month.

**PG70-22 and PG76-22 Binders (including Asphalt Binder in Ultrathin Bonded Wearing Course).** The monthly Asphalt Binder Price Index for PG70-22 and PG76-22 binders (including asphalt binder in Ultrathin Bonded Wearing Course) will be determined by the same method above, except that the price from the Asphalt Weekly Monitor® will not be used in the calculation of the monthly average binder price. The monthly asphalt binder price for PG70-22 and PG76-22 binders will be calculated using the average of the prices supplied by the four largest binder suppliers in the State for those grades.

**Supplemental Items Subject to Adjustment.** Items included in the contract that are listed in the table above are subject to adjustment in accordance with this provision, regardless of any amount of overrun to the plan quantity. Any new items of work added to the Contract by supplemental agreement that are listed in the table above will be subject to the asphalt binder price adjustments in accordance with this provision. The base asphalt binder price, P(b), for any

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**PRICE ADJUSTMENT FOR ASPHALT BINDER**

newly added eligible items will be the same  $P(b)$  as the eligible items in the Contract, and the new unit price established by supplemental agreement will be determined accordingly.

**Viewing Asphalt Binder Price Index.** Historical asphalt binder price index values will be available in the "Asphalt Binder Index Report" document located on the ARDOT website at <https://ardot.gov/divisions/construction/construction-information/> under Asphalt Binder Information.

## ARKANSAS DEPARTMENT OF TRANSPORTATION

### SPECIAL PROVISION

JOB NO. A60063

#### PRICE ADJUSTMENT FOR FUEL

A price adjustment clause is included in this Contract to provide additional compensation to the Contractor or a credit to the Department for fluctuations in diesel fuel prices. This price adjustment is dependent upon a change in the average price of fuel which results in an increase or decrease in the price of products utilized on this project. For the purposes of this specification, it is assumed that all fuel used is diesel fuel and that the fuel use factors shown in the table below cover all fuel used in delivery to the plant, production, hauling to the job site, placement, and finishing of the items of work shown.

**Payment.** Payment will be made to the Contractor for monthly fluctuation in the price of diesel fuel used in performing the applicable items as listed in the table below when the diesel fuel price fluctuates from the base price defined below. Payments may be positive, negative, or nonexistent depending on the circumstances. Payments or deductions for the fuel price adjustment will be included in the Contractor's current estimates, and the payment or deduction authorized for each estimate will be based upon the quantities for applicable items of work. Subcontracts should include the payment or deduction of fuel price adjustments on pay items listed in the table below when those items are included in a subcontract.

The Fuel Price Adjustment will be a dollar amount paid as compensation to the Contractor, or as a credit to the Department as reflected on the Current (or Final) Estimate Summary Report as Payment Adjustments.

**Fuel Price Adjustment (FPA).** The Fuel Price Adjustment (FPA) for the current estimate will be computed according to the following formula:

$$FPA = Q \times F \times D$$

Where

- FPA = Fuel price adjustment, in dollars;
- Q = Quantities paid for the applicable items on the current estimate,
- F = The Fuel Use Factor for the applicable items of work subject to this price adjustment, as listed in the table below,
- D = Allowable price differential, in dollars.

The above formula will be applied to each individual payment of the applicable item. When the Current (or Final) estimate is generated, the sum of these individual adjustments will be included as a Payment Adjustment.

# **ARKANSAS DEPARTMENT OF TRANSPORTATION**

## **SPECIAL PROVISION**

**JOB NO. A60063**

## **PRICE ADJUSTMENT FOR FUEL**

| Fuel Use Factors                                                                                                                                                                                                                                  |                             |                          |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|--------------------------|
| Item of Work                                                                                                                                                                                                                                      | Specification Numbers       | Fuel Use Factor Per Unit |
| Earthwork:<br>(Unclassified Excavation, Compacted Embankment, Selected Material)                                                                                                                                                                  | 210,302                     | 0.34 gal./C.Y.           |
| Soil Stabilization                                                                                                                                                                                                                                | Special Provision           | 2.28 gal./ton            |
| Shaping:<br>(Shaping Roadway Section, Subgrade Preparation, Trenching and Shoulder Preparation, Scarifying and Recompacting Shoulders)                                                                                                            | 213,214,215,216             | 2.52 gal./Station        |
| Base Course and Stone:<br>(Stone Backfill, Aggregate Base Course, Soil Aggregate in Cement Treated Base Course, Aggregate in Cement Stabilized Crushed Stone Base Course, Mineral Aggregate in Asphalt Surface Treatment                          | 207,303,307,308,309,310,402 | 0.54 gal./ton            |
| ACHM Paving:<br>(ACHM Base Course, ACHM Binder Course, ACHM Surface Course, Open Graded Asphalt Base Course)                                                                                                                                      | 405,406,407,417             | 2.36 gal./ton            |
| Ultra-Thin Bonded Wearing Course (All Types)                                                                                                                                                                                                      | Special Provision           | 2.18 gal./ton            |
| Milling:<br>(Cold Milling Asphalt Pavement, Grinding Portland Cement Concrete Pavement)                                                                                                                                                           | 412, 510                    | 0.18 gal./S.Y.           |
| PCC Paving:<br>(Portland Cement Concrete Base, Open Graded Portland Cement Concrete Base, Portland Cement Concrete Pavement, High Early Strength Concrete Pavement, Continuously Reinforced Concrete Pavement, Portland Cement Concrete Driveway) | 309, 310,501,503,505        | 0.44 gal./S.Y.           |
| Structural Concrete<br>(Approach Slabs, Approach Gutters, Class B Concrete-Bridge, Class S Concrete-Bridge, Class S(AE) Concrete-Bridge, Seal Concrete-Bridge, Class A Concrete-Roadway, Class S Concrete-Roadway                                 | 504, 802                    | 1.75 gal./C.Y.           |
| Flatwork: (Concrete Ditch Paving, Concrete Islands, Concrete Walks, Wheelchair Ramps)                                                                                                                                                             | 605,632,633,641             | 0.30 gal./S.Y.           |

## ARKANSAS DEPARTMENT OF TRANSPORTATION

### SPECIAL PROVISION

JOB NO. A60063

### PRICE ADJUSTMENT FOR FUEL

When the units of measure in this contract for the items of work listed in the table do not correspond with the units shown in the table (i.e. Asphalt Concrete paid by the square yard, etc.), those items will not be subject to the terms of this special provision or any fuel price adjustment.

The allowable price differential, "D", for the current estimate will be computed according to the following formula:

$$D = P - P(b)$$

P, the current fuel price in dollars per gallon, is the Monthly Fuel Price Index for the month in which the payment entry is entered.

P(b), the fuel base price in dollars per gallon, is the Monthly Fuel Price Index for the month in which the bids for the work were received.

**Fuel Price Index Determination.** The Monthly Fuel Price Index will be determined by using the On-Highway retail price for No. 2 Diesel Fuel – ULS (Ultra Low Sulfur), as listed for the US Gulf Coast region on the U.S. Energy Information Administration's website. The value used will be that for either the closest Monday prior to the first calendar day of the index month or the first calendar day of the index month, if that is a Monday.

[https://www.eia.gov/opensdata/qb.php?sdid=PET.EMD\\_EPD2DXL0\\_PTE\\_R30\\_DPG.W](https://www.eia.gov/opensdata/qb.php?sdid=PET.EMD_EPD2DXL0_PTE_R30_DPG.W)

**Supplemental Items Subject to Adjustment.** Items included in the contract that are listed in the table above are subject to adjustment in accordance with this provision, regardless of any amount of overrun to the plan quantity. Any new items of work added to the Contract by supplemental agreement that are listed in the table above will be subject to the fuel price adjustments in accordance with this provision. The base fuel price, P(b), for any newly added eligible items will be the same P(b) as the eligible items in the Contract, and the new unit price established by supplemental agreement will be determined accordingly.

**Viewing Fuel Price Index.** Historical fuel price index values will be available in the "Asphalt Binder Index Report" document located on the ARDOT website under Fuel Price Information at <https://ardot.gov/divisions/construction/construction-information/>.

**Opt Out Option.** The Contractor, at its own discretion, can choose to opt out of the adjustments for fuel prices determined by this special provision. If the Contractor wishes to utilize this option, an authorized representative of the firm must sign the form on Page 4 of this special provision and submit it to the Department at [PMD@ardot.gov](mailto:PMD@ardot.gov) prior to the time and date of the bid letting for this project. This representative must currently be listed with the Department as an officer approved to sign contracts in the firm's name.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**PRICE ADJUSTMENT FOR FUEL**

**OPT OUT OF PRICE ADJUSTMENTS TO FUEL**

As an authorized representative of this company, I hereby choose the option to opt out of the price adjustments for fuel for all pay items allowable by this special provision for this contract. By signature of this form, my firm waives all payment adjustments for fuel indexing for the duration of this project and waives any subsequent appeals for additional compensation for fuel price fluctuations.

This action only applies to the construction contract for the job number listed in the header of this document.

Printed Name: \_\_\_\_\_ Title: \_\_\_\_\_

Signature: \_\_\_\_\_ Date: \_\_\_\_\_

Company Name: \_\_\_\_\_

**NOTE:** To opt out, this completed form must be submitted to the Department at [PMD@ardot.gov](mailto:PMD@ardot.gov) prior to the time and date of the bid letting for this project.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SPECIAL PROVISION**  
**JOB NO. A60063**  
**ASPHALT MIXTURES WITH PG 76-22 BINDER**

**Division 400** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The following is added after the last bullet following the first paragraph of **Subsection 404.01(b), Design Requirements**:

- A maximum of 15% Recycled Asphalt Pavement (RAP) material will be permitted in any mix using PG 76-22 asphalt binder provided that the design has a  $CT_{Index}$  (ASTM D8225) of  $\geq 75$ .
- RAP will not be allowed in Ultrathin Bonded Wearing Course.

The first sentence of the first paragraph of **Subsection 416.03, Materials and Composition**, is hereby deleted, and the following is substituted therefor:

If the Contractor elects to use RAP in the job mixture, the mixture may contain no more than 30% RAP for all binder grades except for PG 76-22 which can contain no more than 15%.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**WARM MIX ASPHALT**

**DESCRIPTION:** The Department will allow the use of Warm Mix Asphalt (WMA). All provisions for the production and placement of conventional HMA mixtures as stipulated in Section 410 Construction Requirements and Acceptance of Asphalt Concrete Plant Mix Courses of the Standard Specifications for Highway Construction, Edition 2014, are applicable except as noted below.

**Section 410 Construction Requirements and Acceptance of Asphalt Concrete Plant Mix Courses** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

**Section 410.03:** Replace the third sentence with "WMA production temperatures at the plant shall be according to the Contractor's approved mix design but may be adjusted based on recommendations of the WMA additive/process manufacturer."

Add the following paragraph: "Implementation of best management practices in the control of aggregate moisture content prior to introduction to the drying or mixing drum is highly recommended in order to achieve the maximum benefit of WMA technology."

**Section 410.07:** Replace the last sentence of the first paragraph with "Spreading and finishing temperatures shall be according to the Contractor's approved mix design, but in no case shall the WMA be placed at a temperature less than 220° F."

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**COLD MILLING - MILL & INLAY**

**Section 412** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The following is added following the last paragraph of **Subsection 412.03 Construction Requirements**:

Unless otherwise designated, the Contractor will receive up to 85% of the millings generated from this project, provided the Contractor utilizes an ACHM mix design which includes RAP on this project.

At least ten business days prior to beginning the cold milling operations, the Contractor shall submit a written request to retain a portion of the reclaimed pavement along with the proposed location of the stockpile”

Measurement of the millings will be by volume. The Engineer may designate a specific area of the roadway where the RAP material can be retained by the Contractor. Unless otherwise noted, this area shall be approximately 85% of the total plan quantity. The Engineer shall consider the designated location in relation to the Contractor’s stockpile location and shall make every effort to minimize haul distances. The Contractor may request consideration of specific locations to be retained; however, the final location will be determined by the Engineer. The quantities of millings may be increased or decreased appropriately as the result of a plan quantity that has been revised by an approved change order. Any pavement material removed as part of corrective work by the Contractor shall remain the property of the Contractor.

The contractor shall stockpile 15% of the millings generated on the project for the county in which the project is located or an adjoining county. The location(s) that will be stockpiled for the county will be designated on the plans or provided by the Engineer. The material designated for the county shall be transported and stockpiled at the location(s) shown in the plans.

The millings shall be stockpiled in a trapezoidal shape, or as directed by the Engineer. No direct payment will be made for loading, hauling, and stockpiling of the milled material. Full payment will be considered included in the unit price bid for Cold Milling Asphalt Pavement.

## **ARKANSAS DEPARTMENT OF TRANSPORTATION**

### **SPECIAL PROVISION**

**JOB NO. A60063**

### **MAINTENANCE OF TRAFFIC**

**Section 603 Maintenance of Traffic and Temporary Structures** of the Standard Specifications, Edition of 2014, is hereby expanded as follows:

The Contractor shall provide additional traffic control through the project as defined below, in order to provide a safe and convenient traffic flow at all times throughout the limits of each work zone and the approaches thereto.

The Contractor shall assume full responsibility for the safe and efficient movement of traffic through the construction area for the duration of the project. Prior approval by the Engineer shall be required for any alterations of traffic patterns shown on the plans.

All traffic control devices shall be in accordance with the details shown in the plans or on Standard Drawings TC-1, TC-1A, TC-2, TC-3, and TC-6. The Contractor will be responsible for furnishing, placing, maintaining, relocating, and subsequent removal of all traffic control devices within the limits of the project.

Except where shown on the plans, there shall be no two-way traffic operations permitted on the main lanes. Interchange ramps shall be kept operational at all times.

The Contractor shall notify the Engineer a minimum of 5 full business days prior to closing a lane. If the Contractor fails to give the proper notification, the lane closure will not be allowed until 5 full business days after the notification was given.

Only one (1) lane closure with a maximum work area of 2 miles will be provided for in the plans. The lane closure shall be installed such that it never exceeds the actual work area by more than  $\frac{1}{4}$  mile. The Contractor shall not close any portion of a lane unless active work will begin immediately. In addition, when gainful work is not being accomplished in an area where a lane has been previously closed, steps shall be taken to return traffic to normal conditions - that is, all lanes open to traffic in each direction within 2 hours after construction operations have ceased. All additional labor, materials, and incidentals needed to return the traffic to normal conditions shall be provided, maintained, removed, and replaced, if necessary, at no cost to the Department. Traffic shall not be permitted on any milled surface. The Contractor shall be responsible for maintaining positive drainage at all times.

**Failure to comply with this requirement will result in a lane use charge of \$10,000 per hour until work begins in the closed lane or the lane closure is removed. The lane use charge shall apply to all construction work and unexpected, but otherwise preventable (as determined by the Engineer), maintenance related lane closures within the prohibited times. This includes lane closures directed by the Engineer to address immediate maintenance needs resulting from a lack of proper preventative maintenance (as determined by the Engineer) within the allowable closure times. A lane closure will not be considered to be removed until all advance warning devices specific to the lane closure**

## **ARKANSAS DEPARTMENT OF TRANSPORTATION**

### **SPECIAL PROVISION**

#### **JOB NO. A60063**

#### **MAINTENANCE OF TRAFFIC**

**have been removed or revised. In assessing this lane use charge any portion of an hour will be counted as a full hour.**

The Contractor shall schedule his work so that no main lane closures exist and no work requiring main lane closures will be performed for the time period of the day before the Holiday through the day after the Holiday for the following Legal Holidays:

- New Year's Day
- Memorial Day
- Independence Day
- Labor Day
- Thanksgiving Day & the Following Day
- Christmas Eve & Christmas Day

If the Legal Holiday is immediately prior to a weekend or immediately following a weekend, the weekend will be considered a part of the Holiday.

**In addition, single lane closures of the Highway 7 main lanes will not be permitted during the following time periods:**

- Highway 7
  - Sunday through Saturday: 7:00 a.m. to 9:00 p.m.

**Failure to comply with this requirement will result in a lane use charge of \$10,000 per hour until work begins in the closed lane or the lane closure is removed. The lane use charge shall apply to all construction work and unexpected, but otherwise preventable (as determined by the Engineer), maintenance related lane closures within the prohibited times. This includes lane closures directed by the Engineer to address immediate maintenance needs resulting from a lack of proper preventative maintenance (as determined by the Engineer) within the allowable closure times. A lane closure will not be considered to be removed until all advance warning devices specific to the lane closure have been removed or revised. In assessing this lane use charge any portion of an hour will be counted as a full hour.**

The Contractor shall schedule and perform the work, including the placement and removal of traffic control devices, to ensure that all Highway 7 traffic lanes are open at all times, with the aforementioned exceptions.

Special events or occurrences could cause traffic to become congested. When this occurs, the Contractor shall immediately modify the work schedule, working methods, or procedures to lessen the impact of the work on traffic or as directed by the Engineer.

## **ARKANSAS DEPARTMENT OF TRANSPORTATION**

### **SPECIAL PROVISION**

**JOB NO. A60063**

### **MAINTENANCE OF TRAFFIC**

The Contractor will regulate the access of work vehicles and equipment to the work area while ensuring safety to the traveling public and minimum damage to highway facilities. Any damage to the highway facility or vegetation caused by the Contractor shall be repaired at no cost to the Department. Unless operating within the area closed to traffic, the Contractor's work vehicles shall travel in the direction of the normal traffic flow. Only those vehicles necessary for the work shall be allowed in the work zone. All other vehicles shall be parked at a safe location outside the work zone, as approved by the Engineer.

General equipment storage areas or operations centers will be allowed within the limits of the right of way only where permitted by the Engineer. At the end of the work day, equipment shall be either shielded from traffic by an approved positive barrier or placed so it is not within 30 feet of any lane carrying traffic.

The Contractor shall conduct his operations so that no equipment or personnel shall occupy any portion of the roadway that remains designated for the passage of traffic.

**BASIS OF PAYMENT:** There shall be no direct payment for fulfilling the requirements of the Special Provision, but compensation shall be considered included in the price bid for Maintenance of Traffic.

Traffic control devices, where shown on the plans for payment, will be paid for at the contract unit price for each item involved. All additional traffic control devices beyond the contract amount shall be provided, maintained, and replaced, if necessary, at no cost to the Department.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**ROADWAY CONSTRUCTION CONTROL – PAVEMENT PRESERVATION**

**Section 635 Roadway Construction Control** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby deleted and the following is substituted therefore:

**Section 635.01 Description.** This item shall consist of furnishing and maintaining all lines, grades, and measurements necessary for the proper execution of the work under the pavement preservation project Contract, all according to the plan, special provisions, and specifications.

**Section 635.02 Materials.** The Contractor shall furnish all stakes, surveying equipment, and other devices necessary for establishing, setting, checking, marking, and maintaining points, lines, grades, layout, and stationing of the work called for on the plans and in the specification.

**Section 635.03 Construction Requirements.**

**(a) Department Responsibilities.**

The Department will be responsible for taking all measurements to establish both current estimate and final estimate pay quantities. When making these measurements, the Engineer may use any points, stakes, lines, or elevations that have been set by the Contractor.

Any information provided by the Department shall be verified by the Contractor before use, and the Contractor shall accept full responsibility for any costs incurred as a result of the use of such information. Any checking performed by the Department will not relieve the Contractor of the responsibility for the final results.

**(b) Contractor Responsibilities.** Roadway Construction Control shall include the use by the Contractor of the plans to perform required construction surveying and layout as outlined below.

**(1) Projects without subgrade widening and/or profile grade line**

The Contractor shall mark the stationing by setting a stake at least every 200 feet along the roadway. These stakes shall be placed and maintained on the shoulder or slope so that they will not interfere with the construction operations, but will be usable for determining locations along the roadway. In urban areas where staking is not feasible, markings shall be clearly established and maintained so as to be easily identifiable, but not in a manner that is destructive to adjacent structures and/or monuments. The Begin Job Log Mile as identified in the plans, shall be established as station 100+00.

The Contractor shall establish and maintain centerline throughout the project. On projects without a profile grade line, the existing cross slopes are considered acceptable. The contractor shall be responsible for maintaining existing cross slopes unless otherwise shown on the plans.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**ROADWAY CONSTRUCTION CONTROL – PAVEMENT PRESERVATION**

**Projects with subgrade widening and/or profile grade line**

In addition to the requirements in 635.03(b)(1) above, the Contractor shall be responsible for the following.

The Contractor shall profile the existing pavement at the centerline, lane lines, and edges of pavement for the length of the widening section plus 500 feet on each end. This profile data shall be furnished to the Department for the Department's use in the establishment of the finished grade line. This finished grade line will be furnished to the Contractor for use in computing and setting all grades required to construct the finished roadway section.

The Contractor shall not be responsible for grades beyond the edge of shoulder or correcting preexisting cross and superelevation slopes unless otherwise shown on the plans.

The Contractor shall make all necessary calculations, marking, and staking, including, but not limited to, centerline, offset, stationing, slopes, pavement lines, lane lines, grade, guardrail, and any other points or lines deemed necessary for proper control of the work.

The Contractor shall be responsible for joining the work to contiguous roadways and/or bridges in an acceptable manner. This shall include making minor adjustments to the plan grade and/or typical section as necessary to construct a smooth transition to match the existing roadway.

The Contractor shall provide sufficient qualified personnel to complete the work accurately. The supervision of the Contractor's surveying and layout personnel shall be the responsibility of the Contractor, and any errors resulting from the operations of such personnel shall be adjusted or corrected by the Contractor at no cost to the Department.

The Contractor shall be responsible for the accuracy and uniformity of the construction stakes, lines, grades, and layouts. Any errors in the work constructed due to errors in the Contractor's Roadway Construction Control shall be adjusted or corrected by the Contractor at no cost to the Department.

The Contractor shall remove all stakes upon the Engineer's determination that the project is substantial complete.

**Section 635.04 Method of Measurement.** Roadway Construction Control will be measured as a complete unit.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**ROADWAY CONSTRUCTION CONTROL – PAVEMENT PRESERVATION**

**Section 635.05 Basis of Payment.** Work completed and accepted and measured as provided above will be paid for at the contract lump sum price bid for Roadway Construction Control, which price shall be full compensation for furnishing and maintaining all necessary lines, grades, and measurements; and for furnishing all engineering personnel, equipment, materials, tools, and incidentals necessary to complete the work.

No adjustments in the lump sum price bid will be made for Roadway Construction Control required due to normal increases or decreases in Contract quantities.

Payments for Roadway Construction Control will be made in proportion to the amount of work accomplished on the project. The amount may be adjusted by the Engineer for preliminary work as demonstrated by the Contractor.

No additional payment will be made for re-staking needed to maintain the control.

Payment will be made under:

**Pay Item**

Roadway Construction Control

**Pay Unit**

Lump Sum

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SPECIAL PROVISION**  
**JOB NO. A60063**  
**SURFACE-APPLIED DETECTABLE WARNING PANELS**

**DESCRIPTION:** This item shall consist of furnishing and installing surface-applied detectable warning panels, in accordance with these specifications and the Standard Drawings, in conformity with the color, of the dimensions shown on the plans, at the locations shown on the plans, or as directed by the Engineer. The panels shall be placed on existing concrete surfaces and the work shall comply with the appropriate manufacturer's installation instructions.

**MATERIALS:** Surface-applied panels used shall be from suppliers/manufacturers on the Department's Qualified Products List (QPL) for Cast-In-Place Tactile Panels or must have prior approval from the Engineer.

The color of the panels shall conform to Federal Color No. 33538 unless specified differently in the plans or with prior Engineer approval. The color of the panels shall be homogeneous throughout the product and be ultraviolet stabilized to minimize color fade.

The surface shall be non-slip and incorporate truncated domes made of the same material as the panel. Dimensions and spacing of the truncated domes shall be in accordance with Standard Drawings WR-1 or WR-2 and shall comply with applicable American with Disabilities Act Accessibility Guidelines (ADAAG) and American with Disabilities Act (ADA) regulations regarding detectable warning surfaces. The panels shall have beveled edges and serve as detectable warnings in accordance with ADA Standards for Accessible Design Title III Regulation 28 CFR Part 36 (2010) Section 705.

The tactile panels shall have a minimum nominal thickness of 0.18 inches, exclusive of the height of the truncated domes. The panels shall be supplied with a proper anchoring system and/or adhesive which shall be proven and accepted by the panel manufacturer.

**Construction Requirements:** Surface-Applied Detectable Warning Panels shall be installed utilizing adhesive and drilled anchors in accordance with the manufacturer's recommendations.

**Method of Measurement:** Surface-Applied Tactile Panels will be measured by the square foot.

**Basis of Payment:** Work completed and accepted and measured as provided above will be paid for at the contract unit price per square foot for Surface-Applied Detectable Warning Panels, which price shall be full compensation for furnishing all materials, cleaning and preparing the concrete surface, and for all labor, equipment, tools, and incidentals necessary to complete the work.

**Pay Item**

**Pay Unit**

Surface-Applied Detectable Warning Panels

Square Foot

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**LOOP WIRING REVISION 1.4**

1. **DESCRIPTION.** This item shall consist of furnishing and installing at locations shown on the plans or as directed, vehicle detector loop wiring as specified in accordance with these special provisions. This special provision supersedes the item for loop wiring as described in the Standard Specifications for Highway Construction, Edition of 2014. Some of the materials and items described below may not be utilized on a specific contract and are provided for information purposes only.
2. **MATERIALS.**
  - (a) **General.** The term "loop wiring" as used in these specifications shall refer to the sensing element consisting of single or multi conductor wire loop in the pavement, as well as the lead-in wire from the sensing element to the feeder wire. The wire shall be of the specified gauge stranded copper wire of the number conductors specified, and shall be insulated according to the requirements for the type specified as listed below.
  - (b) **Certification.** The Contractor shall submit to the Engineer for approval, two copies of the applicable manufacturer specifications containing design criteria for the components. This includes Loop Wire of the type required, backer rod and proposed material for sealing the loop. The Engineer will provide written notice of approval/disapproval of the design characteristics to notify the Contractor if the product(s) appears to be suitable for use on the contract. Approval is considered general agreement that the proposed product meets the specification, but in no way relieves the Contractor of the responsibility that the final installation meets the requirements of the contract.
  - (c) **Physical.** Approved materials for Loop Wire shall meet or exceed the minimum requirements of the "Class" specified as listed below:

**Class I (Standard Loop Wire)** - shall consist of 1c (single conductor) #14 gauge stranded copper wire and shall be insulated with RHH or RHW and be USE rated insulation not less than 0.045" (1.1 mm) thick. Products used for sealer shall be approved by the Engineer. Products include but are not limited to that listed on the Department's "Qualified Products List" (QPL) for loop wire sealer.

**Class III (High Pressure Rated, Filled, Single Conductor)** - shall be constructed of 1c (single conductor) with a minimum of #16 gauge stranded copper wire, inside a reinforced hose, double jacket or approved tubing. No wire splices shall be allowed within the pavement area. All connections shall be made in the box or enclosure for the feeder wire.
  - (d) **Approved Sealers.** Products proposed for sealing all classes of loop wire not included on the Department's QPL may be approved by the Engineer on a case-by-case basis for

## ARKANSAS DEPARTMENT OF TRANSPORTATION

### SPECIAL PROVISION

JOB NO. A60063

#### LOOP WIRING REVISION 1.4

test purposes. Previous approval on other state jobs does not insure that product will be allowed on the job covered by this special provision. Approval does not relieve the Contractor of the responsibility for meeting the requirements of the contract including warranty. The Contractor agrees that if the loop installation fails within the warranty period as a result of the product, Contractor will replace the loop utilizing an approved method at no cost to the Department. Failure includes, but is not limited to, deterioration of the roadway surface, failure of the sealer, floating out of the loop wire, or failure of the electrical test.

In cases where a product for loop sealing is recommended by the Department for test purposes, if failure occurs within the warranty period, Contractor agrees to replace the loop within the contract period at the established contract unit price for the item.

### 3. CONSTRUCTION REQUIREMENTS.

- (a) **General.** The vehicle detector loop wiring of the class specified shall be installed as shown on the plans or as directed by the Engineer.

**Class I** - shall be installed in a sawed slot approximately 1/4" to 3/8" (6 mm to 10 mm) wide, 2 1/2" (65 mm) minimum depth in asphalt or 2" (51 mm) in concrete, or 1 1/2" (40 mm) below the final pavement surface. Before sealing the slot, the wire shall be held down by backer rod wedges inserted into the slot at a maximum of 2' (0.6 m) intervals for cold pour sealer or with a continuous run of high temperature baker rod for hot-pour material.

**Class III** - detector loops shall be of the size and configuration as shown on the plans. Lead-in from the feeder wire to the loop shall be considered as two runs of Loop Wiring. Saw-cut slot shall be of sufficient width and to a depth such that the top of the loop is a minimum of 4" (100 mm) below the final surface for the entire length of the trench. The maximum width of any loop slot shall be 1 1/2" (38 mm). The minimum width shall be 1/8" (3 mm) total larger than the outer diameter of the loop wire. The corners of the trench should be drilled, cut at 45 degrees, or chiseled to remove sharp edges. The Engineer may approve other methods of cutting the slot for the loop.

- (b) **Overlaid Surface** - Where the road surface is to be overlaid, the loop wiring may be installed prior to the final surface. The Contractor shall seal the loop slot completely with a material and/or sealant recommended for placement under new asphalt. Where surface is not to be overlaid, an approved sealer shall be applied as needed to the minimum depth of 1/4" (6 mm) below the final surface. Where multiple backfill applications are required, the Contractor should allow a minimum of 14 days prior to each backfill.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**LOOP WIRING REVISION 1.4**

**(c) Connection to Feeder Wire** - of the loop wire shall be soldered and completely sealed in an approved manner against entry of moisture into the splice, jacket of the loop, and the feeder wire. No portion of the loop wire conductors shall be exposed. Approved methods include encapsulating the connections in waterproof dielectric grease inside a non-metallic shell.

**(d) Testing.** Loop wiring shall be tested by the Contractor utilizing an approved 500 Volt Meg Tester accurate to 0.1 M Ohm in the range of 1 M Ohm to 10 M Ohms and with continuity test accurate to 0.1 Ohm in the range of 1 to 10 Ohms.

- Meg-Test (500 Volt) - minimum resistance to ground 10.0 M Ohm

Note: Values greater than 1.0 M Ohm but less than 10 M Ohm are considered marginal and subject to further evaluation. Values less than 1.0 M Ohm are considered faulty and must be corrected by the Contractor, which includes re-sawing the loop if other methods do not prevail.

- Continuity – maximum loop resistance 3.0 Ohms (Typical)

Note: This value shall not exceed +/- 50% of the calculated value. If variation is outside this value, further testing shall be performed for inductance and quality of the loop.

**4. METHOD OF MEASUREMENT.** Loop Wiring of the class specified will be measured as described below:

**(a) Loop Wiring Class I** will be measured by the **linear foot of material in the saw-cut** which shall include twice the length of the lead-in from the loop to the connection with feeder wire or detector panel (where terminated in a controller cabinet). Payment for up to four feet of lead-in will be allowed in the pull box or cabinet.

**(b) Loop Wiring Class III** will be measured by the **linear foot of material in the saw-cut** which shall include twice the length of the lead-in from the loop to the connection with feeder wire or detector panel (where terminated in the controller cabinet). Payment for up to four feet of lead-in will be allowed in the pull box or cabinet.

**5. BASIS OF PAYMENT.** Work completed, accepted and measured as provided above will be paid for at the contract unit price bid for Loop Wire of the class and configuration specified, which price shall be full compensation for sawing and sealing; clearing the slot; removal of surplus material; and for all materials including loop wire, asphalt or sealer material, coupling and connectors; and for testing, labor, equipment, tools, and incidentals necessary to complete the work.

08-20-2009  
03-21-2013 Rev.  
01-05-2017 Rev.  
11-16-2017 Rev.  
12-06-2018 Rev.  
06-20-2019 Rev.

Page 4 of 4

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**LOOP WIRING REVISION 1.4**

Payment will be made under:

**Pay Item**

**Pay Unit**

Loop Wiring Class I  
Loop Wiring Class III (1c/16 A.W.G.)

Linear Foot  
Linear Foot

## ARKANSAS DEPARTMENT OF TRANSPORTATION

### SPECIAL PROVISION

JOB NO. A60063

### CONCRETE PULL BOX

**Section 711** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

**Subsection 711.02 Materials** is hereby deleted and the following substituted therefor:

The pull boxes shall be constructed with Portland Cement Concrete reinforced with welded wire or shall be polymer concrete reinforced with heavy weave fiberglass. No fiberglass shall be exposed. All exposed portions of the pull box shall be non-electrically conductive.

The minimum inside dimensions measured across the center of the box (horizontally) just below the lid support lip shall be as follows:

Concrete Pull Box – Type 1 and 1 HD:

8 3/4" (220 mm) wide x 14 1/4" (360 mm) long

Concrete Pull Box – Type 2 and 2 HD:

11" (280 mm) wide x 21" (530 mm) long

Concrete Pull Box – Type 3 and 3 HD:

15 1/4" (385 mm) wide x 28" (710 mm) long

The depth measured from the top of the lid shall be a minimum of 11½" (290 mm).

A non-metal electrically insulated cover shall be provided for each pull box. The covers shall have a skid resistant surface on top and a lifting eye.

The pull box and cover shall be constructed in such a manner that the assembly will support light vehicular traffic. The cover with pull box shall meet or exceed the following test loading:

| Type | Load   |      | Load Area          |                          |
|------|--------|------|--------------------|--------------------------|
|      | pounds | kg   | Sq. inch           | sq mm                    |
| 1    | 3800   | 1720 | 10 (3.16" x 3.16") | 6400 (80 mm square)      |
| 1 HD | 7500   | 3400 | 10                 | 6400                     |
| 2    | 3800   | 1720 | 20 (4" x 5")       | 13,000 (100 mm x 130 mm) |
| 2 HD | 7500   | 3400 | 20                 | 13,000                   |
| 3    | 3800   | 1720 | 20 (4" x 5")       | 13,000 (100 mm x 130 mm) |
| 3HD  | 7500   | 3400 | 20                 | 13,000                   |

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**CONCRETE PULL BOX**

Pull box with cover in place shall comply with the National Electric Code for exposed boxes rated at voltages up to 480 VAC.

All heavy-duty concrete pull boxes are to be installed as shown on the plans with an apron of concrete 12" (305 mm) wide and 6" (152 mm) in depth. The concrete shall comply with Section 802 for Class S Concrete. The Department will perform all acceptance sampling and testing at the frequencies shown for the Contractor acceptance testing in Subsection 802.06. Reinforcement consisting of 6" x 6" W1.4 x W1.4 (150 mm x 150 mm MW10 x MW10) welded wire fabric complying with the requirements of Subsection 804.02(b) is required to be placed in the concrete as shown in the plans.

**The pull box shall be permanently labeled with "ARDOT", "ELECTRIC" and "ALUMINUM", centered below, the manufacturer's name and model identifier.**

**Stainless steel vandal resistant Penta-head bolts shall be supplied for each pull box. Two Penta-head sockets shall be provided and turned over to Maintenance Authority.**

**Subsection 711.05 Basis of Payment** is hereby deleted and the following substituted therefor:

Work completed and accepted and measured as provided above will be paid for at the contract unit price bid each for Concrete Pull Box of the type specified, which price shall be full compensation for furnishing and installing the pull box; for excavation, backfill, compaction, removal of surplus materials, and replacement of the existing surface; for furnishing and placing the bedding material; for furnishing and placing welded wire fabric and concrete; and for all materials, labor, equipment, tools, and incidentals necessary to complete the work.

Payment will be made under:

| <b>Pay Item</b>             | <b>Pay Unit</b> |
|-----------------------------|-----------------|
| Concrete Pull Box (Type _ ) | Each            |

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SPECIAL PROVISION**  
**JOB A60063**  
**WATER POLLUTION CONTROL**

**Section 110** of the Standard Specifications for Highway Construction, Edition of 2014 is hereby amended as follows:

The following is added to **Section 110**:

Sedimentation, turbidity, water pollution, and other possible impacts shall be carefully controlled and minimized on this project. The project is located in the Kimzey Regional Water District surface water source protection area. Required actions of the Contractor shall include, but are not limited to, the following:

- **The Contractor shall have absorbents in forms such as booms, pillows, or rolls on the job site capable of absorbing up to 500 gallons of petroleum based liquids. The Contractor shall be prepared at any time to utilize these absorbents immediately as a defense response for hazardous waste spills such as emulsified asphalt products occurring as a result of this project. No work will be permitted to occur on the project unless one of the above referenced absorbents is physically on the project limits.**
- **Emulsified asphalt products shall not be placed when there is any likelihood of adverse weather.** Emulsified asphalt products shall be limited to 1,500 linear feet at any one time.
- No equipment with leaking fluids shall be allowed on the project.
- Storage areas for petroleum and/or chemical products cannot be placed within 500 feet of a stream crossing or as directed by the Engineer. No material shall be wasted or temporarily stockpiled in wetlands, flood plains, recharge areas, or where it can be eroded or washed into waters of the United States.

**METHOD OF MEASUREMENT AND BASIS OF PAYMENT:** The work involved in complying with the remainder of this Special Provision will not be measured or paid for separately, but will be considered included in the contract unit prices bid for other items of the contract.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SPECIAL PROVISION**

**JOB NO. A60063**

**PRIME CONTRACTOR PERFORMANCE EVALUATION**

All projects with a contract bid amount of \$10 million or greater will be evaluated in accordance with the Prime Contractor Performance Report Manual (PCPRM) adopted by the Department on September 30, 2025.

The manual can be found here:

<https://ardot.gov/wp-content/uploads/Prime-Contractor-Performance-Report-Manual-Final-09-30-2025.pdf>

The Engineer will evaluate the contractor using the metrics and at intervals identified in the PCPRM. The evaluation ratings will be used to provide constructive feedback and as a tool to identify areas for improvement. The contractor shall be given opportunity to review and comment on the evaluation as well as the opportunity to appeal the Engineer's rating.

No direct payment will be made for inclusion of the PCPRM in the contract.

**SPECIAL PROVISION****JOB NO. A60063****INSURANCE, CONSTRUCTION, AND FLAGGING REQUIREMENTS ON RAILROAD  
PROPERTY (G&W)****GENERAL:**

NOTE: Genesee & Wyoming Railroad Services, Inc. owns Arkansas Midland Railroad Company, Inc. (AKMD).

The requirements of this Special Provision are intended to apply to construction activities on Genesee & Wyoming Railroad's (AKMD) right-of-way in Garland County, Arkansas. These requirements are in addition to construction details shown on the Plans or called for elsewhere in the project documents.

- Hwy 7 (DOT# 437767Y), Hot Springs Subdivision, Railroad Mile Post 411.40.

**Railroad Right-of-Entry, Insurance and Flagging Requirements:**

This Special Provision applies to the construction activities on this project and supplements the Plans. Before beginning any work on the Railway's right-of-way, the Contractor must contact Mr. Greg Breaston, G&W's Public Projects Manager and Donna Killingsworth for a right-of-entry (ROE), digging, flagging and insurance requirements. The most current ROE information is also available on G&W's Real Estate website:

<https://www.gwrr.com/real-estate/accessing-property/>

|                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                       |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b><u>Greg Breaston</u></b><br>Manager, Public Projects<br>Genesee & Wyoming Railroad Services, Inc.<br>13901 Sutton Park Drive, Suite 270<br>Jacksonville, FL 32224<br>Cell: 904-719-4315<br><a href="mailto:greg.breaston@gwrr.com">greg.breaston@gwrr.com</a> | <b><u>Donna Killingsworth, MBA</u></b><br>Sr. Manager – Utilities<br>13901 Sutton Park Dr., S., Suite 270<br>Jacksonville, FL 32224<br><a href="mailto:donna.killingsworth@gwrr.com">donna.killingsworth@gwrr.com</a><br>904-900-6286 |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**RAIL TRAFFIC:**

As reported by FRA, current rail traffic is:

|                          |        |
|--------------------------|--------|
| Average Trains Per Day   | 2      |
| Average Train Speed      | 10 mph |
| Passenger Trains Per Day | 0      |

# Genesee & Wyoming Railroad Services, Inc.

**Real Estate Department, 13901 Sutton Park Dr., S, Suite 270, Jacksonville, FL 32224**

## Contractors Access/Occupancy on Railroad Property

☐ **Check box if Contractor unknown at this time** *(this form will need to be completed with contractor information and submitted prior to any work once bid process is complete)*

*Incomplete or Inaccurate Information will delay application request*

### Section 1 - Applicant Data

Complete Legal Name of  
Applicant to appear on License  
Agreement:

---

Applicant Mailing Address:

---



---

Applicant Overnight Address:

---



---

Type of Entity:

☐ Corporation    ☐ Partnership    ☐ Sole Proprietor    ☐ Individual  
☐ Municipality    ☐ Developer    ☐ Other

If other please explain:

State of Incorporation or  
Partnership:

---



---

### Contact during Application Process:

Name:

---

Contact

Email

Telephone

Address:

---

### Section 2 - Location Data

Railroad Name:

---

Estimated Start Date

---

Specify the amount of time access  
is required:

---

Reason for extension  
of time beyond 60  
days

---

Nearest City:

---

County:

---

State:

---

**REQUIRED: Latitude/Longitude  
(Convert to Decimal Format)  
(ex 12.3456789/-64.101112):**

---

**Address of  
proposed  
worksite:**

---



---

**Railroad**  
**Subdivision - if known** \_\_\_\_\_ **US DOT/AAR Crossing Number - if available** \_\_\_\_\_

### Section 3 - Existing Agreement Data

**Is there an Existing Agreement at this Location which will be affected by this Request?**

☐ Yes ☐ No If YES, List Agreement Number(s): \_\_\_\_\_

Will facility be exclusively used by Applicant? ☐ Yes ☐ No

If YES, List Name of Lessee: \_\_\_\_\_

**Describe the complete scope of work on or around Railroad property (REQUIRED):**

---



---



---



---

### Section 4 - Department of Transportation (D.O.T.)

Is this installation associated with a Department of Transportation project? ☐ Yes ☐ No

If Yes, complete the following:

D.O.T. Contract Number: \_\_\_\_\_ D.O.T. Project Number: \_\_\_\_\_ D.O.T. Project Name: \_\_\_\_\_

D.O.T. Contact Information: \_\_\_\_\_

Name: \_\_\_\_\_

Address: \_\_\_\_\_

City: \_\_\_\_\_ State: \_\_\_\_\_ Zip Code: \_\_\_\_\_

Phone Number \_\_\_\_\_ Email Address \_\_\_\_\_

### ***Some important items to note when completing the application:***

#### Checklist prior to submittal

- ☐ Latitude & longitudinal information converted to digital decimal format with an aerial map of location
- ☐ Payment for fees included - check payable to specific railroad
- ☐ If paying fees by credit card a completed signed credit card release is included - only Visa, MasterCard or Discover can be accepted - US Roads only
- ☐ Applications can be emailed with a copy of the check in order to start the approval process. Only the check for the doc prep fees needs to be mailed or overnighted when the complete application packet is emailed. Include a copy of the application to make sure the payment is matched to the correct project.
- ☐ **When returning the signed agreement and proof of insurance for final review and execution please allow 2-3 weeks prior to the start of work. Once all required fees are paid and documentation in place the agreement must go through an approval process before it can be finalized.**

## Section 5 - Insurance Requirements - US Roads

**Insurance Requirements prior to any construction project** - Both the Utility Owner and the Contractor completing installation are required to provide proof of current Commercial General Liability Insurance. Prior to construction the Contractor is required to provide current proof of Railroad Protective Liability Insurance.

**General Liability insurance** must meet the minimum requirements of \$2M per occurrence and \$6M aggregate per the terms of the written contract.

**Automobile Insurance** must meet the minimum requirements of \$1M bodily injury and property damage per occurrence.

The General Liability certificate is required to show proof of **CG2417 or its equivalent**. (*Contractual Liability Railroads*)

Evidence of **Workers Compensation** must be provided on certificate and meet the minimum requirements of \$1M. Certificate Holder naming (*specified Railroad*) **\*\*Specified Railroad names can be found at [www.gwrr.com](http://www.gwrr.com)\*\***

General Liability, Automobile Liability and Umbrella/Excess Liability provides additional insured status to the certificate holder and any other party(ies) specified in or required by written contract between the named insured and the certificate holder.

Where applicable and permitted by law, all policies include a blanket automatic waiver of subrogation endorsement that provides this feature in favor of the certificate holder and any other party(ies) specified in or required by written contract between the named insured and the certificate holder.

**Prior to Construction or any access within 50' of Railroad** a current **Certificate of Railroad Protective Liability insurance (RPL)** which shows the **specific Railroad** as named Insured. If the Contractor does not carry a policy of Railroad Protective Liability insurance, this coverage can be secured through the railroad. An application and current Fee structure for this coverage is available upon request.

**\*\*Insurance Requirements for potentially hazardous pipelines such as natural gas, oil, petroleum, etc. to be amended as shown below\*\***

**General Liability Insurance** which names the **specific Railroad** as additional insured and must meet the limits of **\$5M per occurrence and \$10M aggregate**. Such policy shall be endorsed to provide Waiver of Subrogation in favor of the certificate holder per written contract.

**Pollution Legal Liability Insurance** with minimum limits of **Five Million Dollars (\$5,000,000)** per occurrence naming the **certificate holder** as additional insured per written contract. Such policy shall be endorsed to provide Waiver of Subrogation in favor of the certificate holder per written contract.

## ***Section 6 - Insurance requirements - Canadian Roads***

**Insurance Requirements prior to any construction project** - Both the Utility Owner and the Contractor completing installation are required to provide proof of current Commercial General Liability Insurance.

**General Liability insurance** must meet the minimum requirements of \$2M per occurrence and \$2M aggregate per the terms of the written contract.

**Automobile Insurance** must meet the minimum requirements of \$1M bodily injury and property damage per occurrence.

Where applicable, the General Liability certificate is required to show proof of **CG2417 or its equivalent.** (Contractual Liability Railroads)

Evidence of **Workers Compensation** must be provided on certificate and meet the minimum requirements of \$1M. Certificate Holder naming (Specified Railroad) **\*\*Specified Railroad names can be found at [www.gwrr.com](http://www.gwrr.com)\*\***

General Liability, Automobile Liability and Umbrella/Excess Liability provides additional insured status to the certificate holder and any other party(ies) specified in or required by written contract between the named insured and the certificate holder.

Where applicable and permitted by law, all policies include a blanket automatic waiver of subrogation endorsement that provides this feature in favor of the certificate holder and any other party(ies) specified in or required by written contract between the named insured and the certificate holder.

### **IMPORTANT**

Prior to application submittal, Questions can be answered and additional contact information obtained by visiting the website at [www.gwrr.com](http://www.gwrr.com) - select the specific railroad and click on the link for Real Estate.

**Plans for proposed installations shall be submitted to and approved by the Railroad, on behalf of itself, its subsidiaries, and affiliates, and designated engineer before work can begin!** Applications submitted not meeting current specifications as outlined in the General Specifications for Sub-grade and Above grade Utility Crossings of Railway's Right-of-Way will be returned and may incur additional engineering review fees. For your convenience a copy of these specifications can be found on the website at [www.gwrr.com](http://www.gwrr.com).

Materials and installations are to be in strict accordance with specifications of National Electrical Safety Code, AREMA, current edition, and requirements of the Railroad.

Upon application approval, applicant agrees to reimburse Railroad for any cost incurred by Railroad incident to the installation, maintenance and/or supervision necessitated by the installation. Applicant further agrees to assume all liability for accidents or injuries that arise as a result of this installation.

**This section must be completed in full, signed and dated prior to submittal to the Real Estate Department for processing. Unsigned applications, incomplete or inaccurate Information will delay application request and may incur additional fees.**

|                    |                    |
|--------------------|--------------------|
| Date: _____        | Signature: _____   |
| Phone Number _____ | Printed Name _____ |
| Fax Number: _____  | Title: _____       |

**Please make check payable to the specific Railroad where proposed work is to occur**. A list of Genesee & Wyoming, Inc. subsidiary railroads can be found at: [www.gwrr.com](http://www.gwrr.com). W-9 information available upon request.

Mail the application for proposed project, along with the applicable non-refundable fee(s) in U.S. Funds (Canadian Applicants please pay all fee in Canadian Funds plus HST) to:

Genesee & Wyoming Railroad Services, Inc.

Attn: Real Estate Department

13901 Sutton Park Dr. S., Suite 270

Jacksonville, FL 32224

***In order for the application to be complete ALL required details pertinent to the proposed installation must be completed in full and submitted along with the following fees:***

|                          | # of Copies | Amount Due     | Description                                                                                                                                                                                                                                                                    |
|--------------------------|-------------|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input type="checkbox"/> | 1           | \$1,750        | Engineer review fee, plans/drawings, no larger than 11 x 17. Larger drawings may incur additional engineering fees.                                                                                                                                                            |
| <input type="checkbox"/> | 1           | \$1,750        | Completed Contractor's Access/Occupancy Application and Fee required with ALL application submittals. If the contractor is unknown at time of submittal just check the box under the heading on the form.                                                                      |
|                          |             | <hr/>          |                                                                                                                                                                                                                                                                                |
|                          |             | <b>\$3,500</b> | <b>Full amount due with submittal for new utility installations -</b><br><i>Unless prior arrangements are made, applications received without payment will not be processed until receipt of payment. This could extend the time frame for the processing of your request.</i> |

Standard Application processing takes approximately 6-8 weeks. **PLEASE READ IN FULL** - "Expedited processing" is available and will reduce the processing time to between 1-2 weeks at an additional cost of \$2,500. **PLEASE READ BEFORE SUBMITTING EXPEDITE FEE:** For **all expedited requests**, the application and plans submitted must meet engineering specifications and be approved in order for the applicable agreement(s) to be forwarded to the applicant for signature within 2 weeks **from receipt of all required information and full payment of required fees**. It is important to note that an incomplete application and plans submitted that do not meeting engineering specifications will cause a delay in the processing of expedited request and the two week guarantee no longer applies if revisions are required to be made by the applicant in order for them to meet engineering specs for engineering to approve the request.

The expedited processing of an application does not apply to the final review and execution phase of the agreement process. Once a signed agreement has been received and ALL required fees and insurance has been submitted the agreement(s) is(are) forwarded for final review by a VP of Real Estate, Legal and the signatory for the Railroad. This final review and execution process can take up to 2 weeks from receipt of **all required documentation and fees**. This part of the agreement process cannot be expedited.

At this time we are unable to expedite requests for the installation of new private grade crossings, industrial track agreements, and track leases. The process for these requests varies somewhat from the review and approval process for new utilities and takes a little longer to secure all required approvals.

**Entering or working on the railroad right of way or any other railroad property without the permission of the railroad is trespassing and illegal. Violators risk the possibility of serious, even fatal injury and will be prosecuted.**

**CONTRACTOR RIGHT OF ENTRY LICENSE AGREEMENT**

THIS AGREEMENT (the “Agreement”) is made as of \_\_\_\_\_, 20\_\_\_\_, (the “Effective Date”), by and between (“Railroad”) and (“Licensee”).

WITNESSETH:

WHEREAS, Licensee has submitted a written request or application to Railroad requesting permission to enter Railroad’s property at or near the location specified in Section 1 below for the limited purpose of performing certain work; and

WHEREAS, Railroad is willing to grant to Licensee the limited right and permission to enter upon such property for the limited purpose of performing such work in accordance with the terms provided herein.

NOW THEREFORE, in consideration of these promises, the Agreement herein, and other good and valuable consideration the receipt and sufficiency of which are hereby acknowledged, the parties agree as follows:

**Section 1. LOCATION/PAYMENT/WORK PRACTICES:**

1.1 Railroad hereby conveys to Licensee the limited right and permission to enter upon the Railroad’s property located at or near Milepost \_\_\_\_\_, Subdivision \_\_\_\_\_, Latitude: \_\_\_\_\_, Longitude: \_\_\_\_\_ located in \_\_\_\_\_, in the County of \_\_\_\_\_, State of \_\_\_\_\_ as reflected on the map attached hereto as Exhibit A and incorporated herein by reference (the “Property”) for the purpose of Licensee, through its employees, agents or contractors to (the “Work”); and

1.2 Upon payment of a fee referenced in Section 11 herein, Railroad hereby grants to Licensee, the right and permission to enter upon Railroad's Property for the purpose of performing the Work, subject to the terms, conditions and provisions set forth in this Agreement.

1.3 The Work shall be performed at the entire cost and expense of Licensee, in accordance with good and sound engineering practices, to the satisfaction of Railroad's Chief Engineer, or his duly authorized representative (the “Representative”), and in a manner to avoid accident, damage or harm to persons or property and delays to or interference with the operations of Railroad.

**Section 2. PRIOR NOTICE/FLAGGING/OTHER CONDITIONS.**

2.1 Licensee or Licensee’s contractor shall notify the Representative at least ten (10) business days before proceeding with any phase of the Work on the Property and shall abide by the instructions of the Representative concerning the safety of the Railroad. All persons entering the Property pursuant to the permission granted herein shall comply with and perform the Work in accordance with the following policies:

- a) Genesee & Wyoming Inc.’s Contractor Safety Rules, available at: <http://www.gwrr.com/wp-content/uploads/2021/05/GWI-Contractor-Safety-Rules.pdf>; and
- b) Genesee & Wyoming Inc.’s Code of Ethics and Conduct, available at: [http://gwrr.com/about\\_us/code-of-ethics](http://gwrr.com/about_us/code-of-ethics)

The following Personal Protective Equipment (“PPE”) must be worn at all times on the Property: Hard hats, safety footwear, certified eye protection with side shields and approved high-visibility work wear. Additional forms of PPE may be required under certain circumstances as specified in the aforesaid Contractor Safety Rules or as required by the Representative.

2.2 Railroad shall furnish such personnel, flagman or watchman which, in Railroad's sole discretion, may be necessary to protect the facilities and traffic of Railroad during the performance of the Work. If flagging or other special protective or safety measures are performed by Railroad, Railroad will invoice Licensee for such

expenses incurred by Railroad based on the current fee schedule annexed hereto as Exhibit D. Licensee shall pay such invoices within thirty (30) days of Licensee's receipt of billing. If Railroad performs any flagging, or other special protective or safety measures are performed by Railroad, Licensee agrees that Licensee is not relieved of any of its responsibilities or liabilities set forth in this Agreement. The Licensee or its contractor shall reimburse Railroad promptly for the actual cost of said services, including all applicable surcharges, upon receipt of bill or bills therefor.

2.3 Unless Prior arrangements have been made with the Chief Engineer or his representative, Licensee shall not place or operate equipment at a distance of less than fifty (50) feet from the center of track, nor perform any Work at a distance of less than fifty (50) feet from the center of Railroad's track. Further, no equipment shall be moved across the Railroad's track(s) except at an established public crossing, unless prior arrangements have been made with the Chief Engineer or his Representative. All reasonable precautions must be taken by Licensee to avoid interference with and/or damage to Railroad's facilities during the course of the Work.

2.4 Prior to entering upon the Property, Licensee agrees to comply with **RAILROAD'S ROADWAY WORKER PROTECTION TRAINING POLICY** as set forth in Exhibit B, attached hereto and incorporated herein by reference, if such training is applicable as determined in the sole discretion of Railroad.

2.5 The permission herein granted is subject to all existing leases, licenses and occupancies of the Property by third parties. Licensee acknowledges that, in executing this Agreement, Railroad acts on its own behalf only and has no authority to act, and does not claim to act, on behalf of any other entity or person with respect to any right any such other entity or person may have to object to this Agreement. Licensee shall secure the consent, and protect the facilities, of each such third-party occupier of the Property.

2.6 Licensee shall implement and enforce a safety program conforming to all applicable requirements of federal, state and local laws, rules and regulations.

### Section 3. LEGAL COMPLIANCE.

Licensee expressly agrees, at its own cost and expense, to comply and cause its agents, employees and contractor(s) to comply with all applicable ordinances, rules, regulations, requirements and laws of any governmental authority (state, federal or local) having jurisdiction over the Work or Licensee's activities, including the location, contact, excavation and protection regulations of the Occupational Safety and Health Act and state "One Call" - "Call Before You Dig" or similar requirements. Licensee shall indemnify, defend and save harmless Railroad, its parents, affiliates and subsidiaries, and the respective shareholders, directors, officers and employees of each (hereinafter collectively the "Railroad Indemnitees"), from and against, and shall pay, all expenses, damages, penalties, and claims, including without limitation reasonable counsel fees, that may arise from, or be imposed because of the failure of Licensee to comply with this Section.

### Section 4. LIABILITY/INDEMNITY.

4.1 Licensee hereby assumes risk of and agrees to indemnify, defend, protect and save the Railroad Indemnitees harmless from and against (a) injury to or death of any person or persons whomsoever, including but not limited to the agents, employees or contractor(s) of the parties hereto, and (b) the loss or damage to any property whatsoever, including property claims, demands, suits, judgments or expenses incurred in connection therewith, resulting from or arising out of the acts or omissions of Licensee, its agents, employees or contractor(s), or resulting from, arising out of, or occurring in connection with the entry or presence of Licensee, its agents, employees or contractor(s) on the Property, or resulting from, arising out of, or occurring in connection with the performance or execution of the Work performed under this Agreement or incidental thereto, regardless of any negligence on the part of Licensee or Railroad. THE INDEMNITY PROVIDED IN THIS SECTION 4 IS SPECIFICALLY MEANT TO INCLUDE INDEMNITY OF THE RAILROAD INDEMNITEES FOR THEIR OWN ORDINARY NEGLIGENCE, EVEN IF THE INJURY OR DAMAGE IS CAUSED ENTIRELY BY THE ORDINARY NEGLIGENCE OF THE RAILROAD INDEMNITEES AND THERE IS NO NEGLIGENCE ON

THE PART OF THE LICENSEE. LICENSEE'S INDEMNITY OBLIGATIONS IN THIS SECTION 4 SHALL NOT BE LIMITED IN ANY WAY BY ANY LIMITATION ON THE AMOUNT OR TYPE OF DAMAGES, COMPENSATION OR BENEFITS AVAILABLE UNDER WORKERS' OR WORKMEN'S COMPENSATION ACTS, DISABILITY ACTS OR EMPLOYEE BENEFITS ACTS.

4.2 IN NO EVENT UNDER THIS AGREEMENT WILL THE RAILROAD INDEMNITEES HAVE ANY LIABILITY FOR INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL OR CONSEQUENTIAL DAMAGES. ADDITIONALLY, THE TERM "RAILROAD INDEMNITEES" AS USED IN THIS SECTION 4 SHALL INCLUDE ANY OTHER RAILROAD COMPANY THAT MAY BE LAWFULLY OPERATING UPON AND OVER THE TRACKS OR THE TRACKS CROSSING OR ADJACENT TO THE TRACKS, AND THE OFFICERS, AGENTS, INVITEES AND EMPLOYEES THEREOF.

#### Section 5. INSURANCE.

Licensee agrees to comply with the **INSURANCE REQUIREMENTS FOR CONTRACTOR RIGHT-OF-ENTRY LICENSE AGREEMENTS** attached hereto as Exhibit C and incorporated herein by reference and shall provide the required Certificate of Insurance to Railroad with return of the signed duplicate original of this Agreement prior to the commencement of the Work.

#### Section 6. NOTIFICATION.

Licensee shall promptly notify the Chief Engineer of any loss, damage, injury or death arising out of or in connection with the Work.

#### Section 7. RESTORATION.

Upon completion of the Work or the termination or expiration of this Agreement, Contractor shall promptly remove from the Property all tools, equipment and materials placed thereon by Contractor. Contractor shall restore the Property to the same state and condition as when Contractor first entered thereon and shall leave the Property in a condition satisfactory to the Chief Engineer or the Representative.

#### Section 8. TERM/TERMINATION.

This Agreement and the permission conferred, and the license granted by it does not constitute a grant of permanent easement and shall terminate upon completion of the Work or at midnight 60 calendar days following the Effective Date, whichever occurs first, unless extended in writing by Railroad. Notwithstanding the foregoing, Railroad shall have the right to terminate this Agreement and the license granted hereunder immediately if Licensee defaults on any of the terms and/or conditions set forth herein.

#### Section 9. COMPLIANCE AND DOCUMENTATION.

Licensee agrees, and shall cause its agents, employees and contractor(s), to (a) understand and comply with the terms and conditions of this Agreement, (b) carry a copy of this Agreement at all times while on the Property, and (c) promptly present the copy of this Agreement to any employee of Railroad upon request.

#### Section 10. RAILROAD CONTACT INFORMATION.

The Railroad's Chief Engineer is:

,

The Railroad's Representative is:

Railroad **EMERGENCY** Phone Number:  
Reference Location: **Subdivision Milepost**

Section 11. FEE.

Upon execution of this Agreement, Licensee shall pay Railroad the sum of \$ toward the cost of preparing this Agreement and for the privileges granted to the Licensee.

Section 12. NON-WAIVER.

If either party fails to enforce its respective rights under this Agreement, or fails to insist upon the performance of the other party's obligations hereunder, such failure shall not be construed as a permanent waiver of any rights or obligations in this Agreement.

Section 13. APPLICABLE LAW.

This Agreement shall be governed by and construed under the laws of the State of , without regard to the choice of law provisions thereof.

Section 14. ASSIGNMENT.

Licensee shall not assign this Agreement without the prior written consent of Railroad, which consent may be granted or withheld at Railroad's sole discretion. This Agreement shall be binding upon the parties and their respective successors and permitted assigns.

Section 15. INTERPRETATION/SEVERABILITY.

To the maximum extent possible, each provision of this Agreement shall be interpreted in such manner as to be effective and valid under applicable law, but if any provision of this Agreement shall be prohibited by, or held to be invalid under, applicable law, such provision shall be ineffective solely to the extent of such prohibition or invalidity, and this shall not invalidate the remainder of such provision or any other provision of this Agreement.

Section 16. COUNTERPARTS.

This Agreement may be executed in multiple counterparts, each of which shall, for all purposes, be deemed an original but which together shall constitute one and the same instrument, and counterparts of this Agreement may also be exchanged electronically and any electronic facsimile of any party's signature shall be deemed to be an original signature for all purposes.

Section 17. HEADINGS.

The headings of the sections of this Agreement are inserted for convenience only and are not intended to govern, limit or aid in the construction of any term or provision of this Agreement.

Section 18. CONSTRUCTION OF TERMS.

The terms of this Agreement have been arrived at after mutual negotiation and, therefore, it is the intention of the Parties that its terms not be construed against any of the Parties by reason of the fact that it was prepared by one of the Parties.

Section 19. CONFIDENTIALITY.

The parties shall not disclose the terms of this Agreement to a third party (a) other than as required by law so long as such party required to disclose the terms of this Agreement under applicable law provides the other party with prior written notice of such requirement, or (b) as otherwise agreed in writing between the parties. Notwithstanding the foregoing, the parties may disclose the terms and conditions of the Agreement to (1) a parent, subsidiary or affiliated company; or (2) to their lawyers and consultants, including but not limited to its auditors, provided that all such parties agree to maintain the confidentiality of such information in accordance with the terms of this provision. If any party violates this paragraph, any adversely affected party may cancel this Agreement without penalty and exercise any available remedies under applicable law.

[Signature Page Follows]

IN WITNESS WHEREOF, the parties hereto have caused this Agreement to be executed as of the Effective Date.

RAILROAD:

LICENSEE:

By: \_\_\_\_\_

By: \_\_\_\_\_

Name:

Name:

Its:

Its:

Sample

EXHIBIT A

**DESCRIPTION OF PROPERTY**

Sample

EXHIBIT B**ROADWAY WORKER PROTECTION TRAINING POLICY**

A. In order to maintain the integrity and security of the Property and Railroad's operations, prior to each employee of Licensee and its contractor entering upon the Property (each a "Licensee Applicant"), Licensee shall cause its employees, and shall cause its contractor to require its employees, to successfully complete the Genesee & Wyoming Inc. Roadway Worker Training Program (the "Program") on an annual basis to be administered by Roadway Worker Training, Inc. (the "Program Administer"), at the sole cost and expense of the Licensee or contractor, as the case may be (the current cost of which is \$50.00 USD per Licensee Applicant). The Program shall be available via the internet and instructions to access the Program set forth in Paragraph K.

B. Upon completion of the Program, the Licensee Applicant shall be required to satisfactorily complete a test administered by the Program Administer. The Program Administer shall be responsible for scoring such test and verifying whether the Licensee Applicant satisfies the requirements of Railroad to perform work on the Property. Any Licensee Applicant who fails to achieve a satisfactory score or who refuses to complete such test shall not be permitted to enter the Property.

C. When a satisfactory score is achieved by the Licensee Applicant, the Program Administrator shall furnish a certificate (the "Certificate") to the business address of Licensee or its contractor, as the case may be, for distribution to the Licensee Applicant. Until receipt of the Certificate from the Program Administrator, the Licensee Applicant shall print a temporary certificate authorizing the Licensee Applicant's access to the Property.

D. For the avoidance of doubt, satisfactory completion of the Program as evidenced by receipt of a Certificate does not in itself grant permission to the Licensee Applicant to enter the Property, except as expressly permitted under and in strict compliance with the terms of the Agreement.

E. The Licensee Applicant shall be responsible for carrying the Certificate at all times when on the Property.

F. All communications regarding Licensee Applicants, the Program, or any other matters described in this Exhibit B should be addressed to:

Kyle Baker  
GWI Safety Department  
13901 Sutton Park Drive South, Suite 270  
Jacksonville, FL 32224  
kyle.baker@gwrr.com  
(904) 999-3356

G. Licensee and its contractor shall be responsible for managing and recovering Certificates from their employees who resign, retire or are terminated.

H. Notwithstanding the receipt of a Certificate by a Licensee Applicant, Railroad reserves the right to reject any Licensee Applicant from entering upon the Property in Railroad's sole discretion in accordance with:

- i) Genesee & Wyoming Inc. Code of Ethics and Conduct,
- ii) Genesee & Wyoming Inc. Contractor Safety Rules, or
- iii) upon failure to comply with the terms and conditions of the Agreement and all applicable laws.

I. To the extent that any portion of the requirements set forth in this Exhibit B violates any law, ordinance, statute or regulation that portion shall be ignored and the Licensee or contractor, as the case may be,

shall comply with all remaining portions of Railroad's Roadway Protection Training Policy, the Program or the related application process.

J. Licensee or its contractor, as the case may be, shall be primarily responsible for enforcement of the Program; *provided, however*, that both Railroad and the Federal Railroad Administration reserve the right to audit Licensee and its contractor, as the case may be, for compliance with the Program and Railroad's Roadway Protection Training Policy. Should a Licensee or its contractor, as applicable, be found out of compliance, any and all fines or penalties incurred by Railroad due to such non-compliance shall be the sole obligation of the Licensee.

K. To access the G&W Roadway Worker Protection Training for Railroad Contractors Course on the RWT On-Line please follow these instructions:

- Start at website  
<https://www.bistrainer.com/store/railpros-store/productdetails/genesee-and-wyoming-roadway-worker-protection-for-contractors-training>
- Click on the "On-Line Courses" button
- Select the G&W course by clicking on the course name
- On the right hand side of the page select "New User Registration"
- Fill out all of the fields on the registration page and submit
- You will receive a username and password via email
- After receiving the username and password go back to the On-Line Courses page and select the G&W course again
- Complete the registration process and training.

EXHIBIT C  
**INSURANCE REQUIREMENTS FOR RIGHT-OF-ENTRY LICENSE AGREEMENT**

(a) The Licensee shall, at its own cost and expense, prior to entry onto the Property or the commencement of any work pursuant to this Agreement, procure and thereafter maintain throughout the term of this Agreement the following types and minimum amounts of insurance:

(i) The Licensee shall maintain Public Liability or Commercial General Liability Insurance ("CGL"), including Contractual Liability Coverage and CG 24 17 "Contractual Liability – Railroads" endorsement, covering all liabilities assumed by the Licensee under this Agreement, without exception or restriction of any kind, with a combined single limit of not less than Two Million Dollars (\$2,000,000) for Bodily Injury and/or Property Damage Liability per occurrence, and an aggregate limit of not less than Six Million Dollars (\$6,000,000) per annual policy period. Such insurance policy shall be endorsed to provide a **Waiver of Subrogation in favor of the Railroad Indemnitees** and shall name the **Railroad Indemnitees as Additional Insureds**. An Umbrella or Excess policy may be utilized to satisfy the required limits of liability under this section but must "follow form" and afford no less coverage than the primary policy.

(ii) The Licensee shall maintain Commercial Automobile Insurance for all owned, non-owned and hired vehicles with a combined single limit of not less than One Million Dollars (\$1,000,000) for Bodily Injury and/or Property Damage Liability per occurrence. Such insurance policy shall be endorsed to provide a **Waiver of Subrogation in favor of the Railroad Indemnitees and shall name the Railroad Indemnitees as Additional Insureds**.

(iii) The Licensee shall maintain Statutory Workers' Compensation and Employers' Liability Insurance for its employees (if any) with minimum limits of not less than One Million Dollars (\$1,000,000) for Bodily Injury by Accident, Each Accident; One Million Dollars (\$1,000,000) for Bodily Injury by Disease, Policy Limit; One Million Dollars (\$1,000,000) for Bodily Injury by Disease, Each Employee. Such insurance policy shall be endorsed to provide a **Waiver of Subrogation in favor of the Railroad Indemnitees**.

(iv) **Prior to construction within 50' of the railroad tracks**, the Licensee shall purchase Railroad Protective Liability Insurance naming the Railroad Indemnitees as the named insured with limits of Two Million Dollars (\$2,000,000) each occurrence and Six Million Dollars (\$6,000,000) aggregate limit. The policy shall be issued on a standard ISO form CG 00 35 12 03 or, if available, obtain such coverage from the Railroad.

(b) The following general insurance requirements shall apply:

(i) The specified insurance policies must be affected under standard form policies underwritten by insurers licensed in the state where work is to be performed and carry a minimum Best's rating of "A-" and size "Class VII" or better. The Railroad reserves the right to reject as inadequate any insurance coverage provided by an insurer that is rated less than the ratings specified in this section.

(ii) All coverages shall be **primary and non-contributory to any insurance coverages maintained by the Railroad Indemnitees**.

(iii) All insurance policies shall be endorsed to provide the Railroad with thirty (30) days prior written notice of cancellation, non-renewal or material changes.

(iv) The Licensee shall provide the Railroad with certificates of insurance evidencing the insurance coverages, terms and conditions required prior to commencement of any activities on or about the Property. Said certificates should reference this Contractor Right of Entry License Agreement by agreement date and description

and shall be furnished to the Railroad at the following address, or to such other address as the Railroad may hereafter specify:

C/O Genesee & Wyoming Railroad Services, Inc.  
13901 Sutton Park Drive South, Suite 270  
Jacksonville, FL 32224

(v) If any policies providing the required coverages are written on a Claims-Made basis, the following shall apply:

- (1) The retroactive date shall be prior to the commencement of the work;
- (2) The Licensee shall maintain such policies on a continuous basis;
- (3) If there is a change in insurer or policies are canceled or not renewed, the Licensee shall purchase an extended reporting period of not less than three (3) years after the contract completion date; and
- (4) Licensee shall arrange for adequate time for reporting of any loss under this Agreement.

(c) The Railroad may require the Licensee to purchase additional insurance if the Railroad reasonably determines that the amount of insurance then being maintained by the Licensee is insufficient in light of all relevant factors. If the Licensee is required to purchase additional insurance, the Railroad will notify the Licensee. Failure of the Licensee to comply within thirty (30) days shall be considered a default subject to termination of the Agreement.

(d) Furnishing of insurance by the Licensee shall not limit the Licensee's liability under this Agreement but shall be additional security therefor.

(e) The above indicated insurance coverages shall be enforceable by any legitimate claimant after the termination or cancellation of this Agreement, or any amendment hereto, whether by expiration of time, by operation of law or otherwise, so long as the basis of the claim against the insurance company occurred during the period of time when the Agreement was in effect and the insurance was in force.

(f) Failure to provide the required insurance coverages or endorsements (including contractual liability endorsement) or adequate reporting time shall be at Licensee's sole risk.

(g) If contractors are utilized, the Licensee agrees to require all such contractors to comply with the insurance requirements of this Exhibit C.

EXHIBIT D

**INSERT APPLICABLE EXHIBIT D PER RAILROAD REGION**

Sample

## ATTACHMENT 1

### ROADWAY WORKER PROTECTION TRAINING POLICY

Railroad and Contractor have a mutual interest in providing a safe workplace for the employees of both parties and in maintaining the integrity and security of Railroad's facilities and property (the "Property"). To help ensure this goal, Railroad has instituted a training program for all employees of Contractor or its subcontractor(s) seeking admission to the Property (the "Program"). These employees must successfully complete the Program. Contractor shall cause its employees, and shall cause its subcontractor to require its employees, to successfully complete the Program on an annual basis, at their sole cost and expense, prior to their admission onto the Property. The Program will be available on-line and administered by a third party on behalf of GWI. The cost per employee certification attempt is \$80.00 USD, payable via credit or purchasing card.

To access the G&W Roadway Worker Protection Training for Railroad Contractors Course on the RWT On-Line Portal please follow these instructions:

- Start at website <https://railpros.com/training/>
- Click on the "Online Training" button
- Select the G&W course by clicking on the course name or simply add to cart
- If creating an account for multiple people, adjust the quantity purchased to match the tests needed
- Create an account as a new user or use previous login information
- A username will be assigned after an account is created
- Fill out all of the fields on the payment page and submit
- You will be asked if this is for you or someone else, if it is for your use select you. If it is for members of your team, enter the name and contact information of those that will be taking the test
- After receiving the username and password go back to the On-Line University page and select the G&W course again
- Complete the registration process and training

All employees of the Contractor or its subcontractor(s) will be required to submit a copy of their training certification to the railroad personnel managing the applicable project.

## ARKANSAS DEPARTMENT OF TRANSPORTATION

### SPECIAL PROVISION

### LIQUIDATED DAMAGES

As specified in the Contract, liquidated damages for this project will be as shown in the following table:

#### WORKING DAY PROJECTS

| ORIGINAL CONTRACT AMOUNT |                  |        |
|--------------------------|------------------|--------|
| FROM MORE THAN           | TO AND INCLUDING | RATE   |
| \$ 0                     | \$ 100,000       | \$ 140 |
| 100,000                  | 500,000          | 400    |
| 500,000                  | 1,000,000        | 660    |
| 1,000,000                | 2,000,000        | 800    |
| 2,000,000                | 5,000,000        | 1,380  |
| 5,000,000                | 10,000,000       | 1,800  |
| 10,000,000               | 15,000,000       | 2,620  |
| 15,000,000               | 20,000,000       | 2,720  |
| 20,000,000               | 30,000,000       | 2,940  |
| 30,000,000               | -----            | 3,500  |

#### FIXED DATE PROJECTS

| ORIGINAL CONTRACT AMOUNT |                  |       |
|--------------------------|------------------|-------|
| FROM MORE THAN           | TO AND INCLUDING | RATE  |
| \$ 0                     | \$ 100,000       | \$ 60 |
| 100,000                  | 500,000          | 80    |
| 500,000                  | 1,000,000        | 220   |
| 1,000,000                | 2,000,000        | 300   |
| 2,000,000                | 5,000,000        | 420   |
| 5,000,000                | 10,000,000       | 1,000 |
| 10,000,000               | 15,000,000       | 1,200 |
| 15,000,000               | 20,000,000       | 1,300 |
| 20,000,000               | 30,000,000       | 1,400 |
| 30,000,000               | -----            | 1,520 |

## ARKANSAS DEPARTMENT OF TRANSPORTATION

### SUPPLEMENTAL SPECIFICATION

#### CONTRACTOR'S LICENSE

**Section 102** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The third paragraph of **Subsection 102.01, Prequalification of Bidders**, is hereby deleted and the following substituted thereof:

The attention of prospective bidders is directed to Ark. Code Ann. §17-25-101 et seq., Act 150 of the 1965 Acts of Arkansas, being an "Act Regulating the Practice of Contracting in the State of Arkansas", and any subsequent amendments made thereto. When the work offered is financed in whole with State funds and is estimated to cost \$50,000 or more, the prospective bidder must show evidence of its license and evidence of registration or license of its subcontractors with the Contractors Licensing Board for the State of Arkansas before being furnished with a proposal form.

The third paragraph of **Subsection 108.01, Subletting of Contract**, is hereby deleted and the following substituted thereof:

It shall be the responsibility of the Contractor to determine that all parties performing work amounting to \$50,000 or more are currently licensed or registered by the Contractors Licensing Board for the State of Arkansas.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**DEPARTMENT NAME CHANGE**

All references to the Arkansas State Highway and Transportation Department contained within the Standard Specifications for Highway Construction (Edition of 2014), the Qualified Products List, the Manual of Field Sampling and Testing Procedures, plan sheets, Supplemental Specifications, and all Special Provisions contained in this proposal are hereby deleted and replaced with the title of Arkansas Department of Transportation.

All references to AHTD contained within the Standard Specifications for Highway Construction (Edition of 2014), the Qualified Products List, the Manual of Field Sampling and Testing Procedures, plan sheets, Supplemental Specifications, and all Special Provisions contained in this proposal are hereby deleted and replaced with the abbreviation ARDOT.

All references to the Arkansas State Highway Commission contained within the Standard Specifications for Highway Construction (Edition of 2014), the Qualified Products List, the Manual of Field Sampling and Testing Procedures, the Standard Drawings, plan sheets, Supplemental Specifications, and all Special Provisions contained in this proposal remain in effect.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**ISSUANCE OF PROPOSALS**

**Section 102** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

**Subsection 102.04(j)** is hereby deleted and the following is substituted therefore:

(j) If the prospective bidder is the Contractor on a current Contract with the Commission on which Liquidated Damages are being assessed, and there are no pending time extensions warranted to remove the project from Liquidated Damages.

**Subsection 102.04(k)** is hereby deleted and the following is substituted therefore:

(k) If the prospective bidder has a current Contract in default.

**Subsection 102.04(n)** is hereby added:

(n) If the prospective bidder has an individual, as an officer/owner/partner of any firm, partnerships or corporation, that has entered into a previous or current contract with the Commission that in the Department's sole discretion, is subject to any of the reasons listed in Subsection 102.04(a)-(m).

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**PREQUALIFICATION OF BIDDERS**

**Section 102** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The following paragraph has been added to **Subsection 102.01**:

A contractor with common officers/owners/partners of any firm, partnerships, joint ventures, or corporations that is seeking prequalification, has been prequalified, or has entered into a previous or current contract with the Commission may have the prequalification denied, limited, or revoked for the reasons listed in Subsection 102.04(a)-(m).

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SUPPLEMENTAL SPECIFICATION**

**CONTACT INFORMATION FOR MOTORIST DAMAGE CLAIMS**

**Section 103, AWARD AND EXECUTION OF CONTRACT**, of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The following is added as the fourth paragraph of **Subsection 103.05(b), Liability Insurance**:

Prior to beginning construction, the Contractor shall provide the Engineer with the name, phone number and e-mail address for the individual within their organization responsible for submission of claims for damages to motorists' vehicles inside the work zones. This information shall be updated annually or whenever this responsibility changes within the Contractor's organization. The information will be made available to the public on the Department's webpage.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**MAINTENANCE DURING CONSTRUCTION**

**Division 100** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

**Subsection 105.15** is hereby modified as follows:

The first paragraph of **Subsection 105.15** is hereby deleted and the following substituted therefor:

**105.15 Maintenance During Construction.** The Contractor shall maintain the work during construction and until the project is accepted. For contracts containing a Flexible Beginning of Work special provision, the responsibility for maintenance by the Contractor will begin at the earlier date of the following:

- when the Contractor begins work, or
- on the date of the beginning of time charges in accordance with the Work Order if the Contractor has not commenced work.

This maintenance shall constitute continuous and effective work prosecuted day by day, with adequate equipment and forces, to the end that the roadway or structures are kept in satisfactory condition at all times.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**RESTRAINING CONDITIONS**

**Section 107** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The following is hereby added after the first bullet of the first paragraph of **Subsection 107.10 Restraining Conditions (a), General**:

- Human remains, burials, and/or associated burial artifacts

The following is hereby added after the second paragraph of **Subsection 107.10 (b), Restraining Conditions Within the Right-of-Way**:

When restraining conditions under (1) and (2) below are encountered, the following provisions should be executed.

(1) If archeological sites and/or historically significant cultural resources are unexpectedly impacted or subsequently discovered during construction, the Contractor shall stop work with no ground-disturbing activities occurring within a two hundred (200)-foot radius of the location of the discovery. The Engineer shall be notified immediately, who will then notify the Environmental Division. A Department staff archeologist will inspect the discovery and determine if the established buffer radius is appropriate. The radius may be decreased or increased based on the nature of the discovery at the discretion of the archeologist. Work in the buffer radius shall not resume until the Environmental Division has provided written notification to the Engineer that construction activities can proceed.

(2) If human remains, burials, and/or associated burial artifacts are encountered during construction, the Contractor shall stop work with no ground-disturbing activities occurring within a two hundred (200)-foot radius of the location of the discovery and the location secured and protected by flagging or fencing. The human remains shall be covered with a canvas tarp and shall not be removed or collected. The Engineer shall be notified immediately, who then will notify the Environmental Division. A Department staff archeologist will inspect the remains and determine if the established buffer is appropriate. The radius may be decreased or increased based on the nature of the discovery at the discretion of the archeologist. The local law enforcement and Chief Medical Examiner will be notified by the Environmental Division. Work in the buffer radius shall not resume until the Environmental Division has provided written notification to the Engineer that construction activities can proceed.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**RESTRAINING CONDITIONS**

The following is hereby added after the third sentence of the first paragraph of **Subsection 107.10 (c), Restraining Conditions Outside the Right-of-Way, (2) Non-commercially Operated Site:**

The Contractor shall limit the amount of acres submitted for an off-site location to no more than 10 acres, except for commercial areas, previously approved locations, or where previous ground disturbance exists. If a Contractor requires more than 10 acres for a proposed off-site location, the Contractor may, at no cost to the Department, acquire approval for use of the site from the State Historic Preservation Officer and a qualified archeological consultant.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**WORK ALLOWED PRIOR TO ISSUANCE OF WORK ORDER**

**Section 108** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

**Subsection 108.02(b)(2)** is hereby deleted and the following is substituted therefore:

(2) The delivery to the Department for execution of the Contract and bonds properly executed on behalf of the Contractor and surety and the minimum 72 hours advance notice as required above shall constitute the Contractor's authority to begin the following items of work:

- Mobilization;
- Preparation of shop drawings and other required submissions;
- Ordering, fabrication, assembly, and/or stockpiling of materials;
- Driving Test Piling; and
- Contract surveying, when Roadway and/or Bridge Construction Control is included in the Contract.
- Erection of advance warning signs.
- Installation of netting on structures to prevent nesting of migratory birds in accordance with applicable Special Provisions (if included in the Contract).
- Set up, installation, and testing of Automated Work Zone Information Systems (if included in the Contract).
- Off-site area approval process per Section 107.10(c).

Such advance work shall be subject to the Contractor's assumption of the risk of cancellation of the award and the following:

- The Contractor shall, on commencing such operations, take all precautions required for public safety and shall observe all the provisions in the Contract;
- In the event of cancellation of the award, the Contractor shall at Contractor expense do such work as necessary to leave the site in a neat condition to the satisfaction of the Engineer;
- In the event of cancellation of the award, all work performed shall be deemed to be at the Contractor's expense; and
- All work done under this subsection in accordance with the Contract before its execution by the Commission will, when the Contract is executed, be considered authorized work and will be paid for as provided in the Contract.

Unless otherwise notified in writing, no time will be assessed for work performed prior to the effective date of a Work Order.

No payments will be made prior to the date established by the Engineer under Subsection 109.07, which date will be after the effective date of a Work Order.

The Contractor shall not be entitled to any additional compensation or an extension of time for any delay, hindrance, or interference caused by or attributable to commencement of work before the effective date of a Work Order.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SUPPLEMENTAL SPECIFICATION**

**WORK ORDER FOR FIXED COMPLETION DATE CONTRACTS**

**Section 108, Prosecution and Progress,** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

**Subsection 108.02(b)(4) a.** is hereby deleted, and the following is substituted therefor:

**a. Fixed Completion Date Contract.** Unless the Contractor is otherwise advised in writing, the Work Order for a fixed completion date contract shall become effective on the second business day following the execution of the Contract by the Department. (Example: If the contract is executed on Wednesday, March 1, the Work Order will be effective on Friday, March 3.) Should the effective date fall on Saturday, Sunday, legal holiday designated in Subsection 101.01(c), Monday following a holiday on Sunday, or Friday preceding a holiday on Saturday, the effective date shall still be on the second business day. The written Work Order from the Engineer will follow with the effective date being as specified.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SUPPLEMENTAL SPECIFICATION**

**QUALITY CONTROL AND ACCEPTANCE**

**Division 300** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The first sentence of the third paragraph **Subsection 306.03 Acceptance Testing** is hereby deleted and the following substituted therefor:

If the material being furnished is crushed stone the Department will furnish the PL, LL, and PI for the material, further tests for PL, LL, and PI are waived.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**TACK COATS**

**Division 400** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

**Section 401, Prime and Tack Coats and Emulsified Asphalt in Base Course**, is hereby modified as follows:

The first sentence of **Subsection 401.03(a)** is hereby deleted and the following substituted therefore:

The surface to be treated with prime or tack coat shall be cleaned of dust, dirt, and loose or foreign material by sweeping with mechanical brooms immediately preceding the application of the prime or tack coat.

Third sentence of **Subsection 401.03(c)** is hereby deleted and the following is substituted therefore:

No dilution beyond that which is part of the emulsification process is permitted. The tack coat shall not be diluted, cut, or otherwise thinned after receipt from the manufacturer's facility.

The fifth sentence of **Subsection 401.03(c)** is hereby deleted and the following substituted therefore:

The rate of application shall be from 0.03 gallon to 0.10 gallon per square yard (0.1 L/sq m to 0.5 L/sq m) of residual asphalt as designated by the Engineer.

**Section 410, Construction Requirements and Acceptance of Asphalt Concrete Plant Mix Courses**, is hereby modified as follows:

The sixth paragraph of **Subsection 410.05** is hereby deleted and the following substituted therefore:

For foreign material, or when the time lapse between courses is more than 8 hours, the earlier course shall be cleaned and given a tack coat before placing the succeeding course. When directed, the tack coat shall be applied and paid for under Section 401. If directed by the Engineer, a tack coat shall be used even though the elapsed time has been less than 8 hours.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**DESIGN AND QUALITY CONTROL OF ASPHALT MIXTURES**

**Division 400** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

**Section 404, QUALITY CONTROL OF ASPHALT MIXTURES**, is hereby modified as follows:

The fifth sentence of the second paragraph of **Subsection 404.01, Design of Asphalt Mixtures, (a) General**, is hereby deleted and the following substituted therefor:

A mix design that has not been produced on an ARDOT project in the last two years is inactive. The Contractor may submit a passing field verification test for the inactive asphalt mix design to the Materials Division to be reactivated. Asphalt mix designs with an expiration date may remain in production if they are not inactive.

The third through fifth paragraphs of **Subsection 404.04, Quality Control of Asphalt Mixtures**, are hereby deleted and the following substituted therefor:

The accepted mix design shall be field verified by the Contractor at the start of mix production or after an interruption of more than 120 calendar days. Production of Department approved mix designs for placement on non-ARDOT projects may be used for mix verification. The Contractor shall be allowed two attempts to verify the mix design if being placed on an ARDOT project and three attempts to verify the mix design if being placed on a non-ARDOT project. The Contractor shall notify the Engineer sufficiently in advance for Department personnel to witness all testing of this production and shall provide copies of all test results to the Department.

Verification will begin with testing the plant produced mix using the aggregate proportions and asphalt binder content shown on the accepted mix design. After the first attempt of verification of the initial design, the Contractor may elect to adjust aggregate proportions to vary the accepted mix design gradations and bring the mix properties near the center of the compliance limits. If the mix is in subplot rejection, all future attempts will only be allowed on non-ARDOT projects.

The mix will be verified if the test values for air voids, asphalt binder content, and VMA are within the compliance limits shown in Table 410-1, and when the accepted mix design has been produced within the gradation tolerances according to Subsection 404.04.

The Contractor may request a one-time field mix design be accepted by the Engineer of Materials. The Contractor will be notified in writing if the field mix design is accepted. A field mix design allows the Contractor to use the adjusted aggregate proportions for future verification of the mix design. Cold feed adjustments will be allowed to both the initial mix design and field mix design if they do not exceed more than 10% for any single cold feed or 20% overall from the initial mix design. No individual cold feed will be allowed to be eliminated by such changes. Gradation tolerances will be based off the initial job mix formula. All cold feed adjustments exceeding the limits outlined above will require a new mix design.

Once verified, the asphalt binder content shall be adjusted at the plant to obtain the optimum asphalt binder content shown on the mix design during production based on the lot average. At no time shall the asphalt binder content be adjusted in a manner to produce an asphalt binder content lower

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**DESIGN AND QUALITY CONTROL OF ASPHALT MIXTURES**

than the design value. Adjustments to the asphalt binder content are not allowed for control of any volumetric property. All changes to be made to the asphalt binder content must first be reported to the Engineer. If adjustments do not give the intended result, production shall be stopped, and the asphalt plant and equipment shall be recalibrated and adjusted so the asphalt binder content can be successfully obtained.

The test method ARDOT 461, (NOTE 3), and (NOTE 4) in the table of the tenth paragraph of **Subsection 404.04, Quality Control of Asphalt Mixtures**, are hereby deleted.

The thirteenth and fourteenth paragraphs of **Subsection 404.04, Quality Control of Asphalt Mixtures, NOTE 3 and NOTE 4** are hereby deleted.

The eighteenth paragraph of **Subsection 404.04, Quality Control of Asphalt Mixtures**, is hereby deleted.

The fourth and fifth sentences in the nineteenth paragraph of **Subsection 404.04, Quality Control of Asphalt Mixtures**, are hereby deleted and the following substituted therefor:

Individual aggregate cold feeds should be adjusted to bring the mix design properties near the center of compliance limits. If excessive changes are required, production will be suspended, and a new mix design shall be developed according to the applicable specifications. Excessive changes are cold feed adjustments that exceed more than 10% for any single cold feed change or 20% overall from the initial mix design. No individual cold feed will be allowed to be eliminated by such changes. All cold feed adjustments exceeding the limits outlined above will require a new mix design.

**Section 410, CONSTRUCTION REQUIREMENTS AND ACCEPTANCE OF ASPHALT CONCRETE PLANT MIX COURSES**, is hereby modified as follows:

The first through third sentences in the first paragraph of **Subsection 410.09(a), General**, are hereby deleted and the following is substituted therefor:

The accepted mix design shall be verified by the Contractor at the start of mix production for that design or after an interruption of more than 120 calendar days. A maximum of 200 tons (200 metric tons) of materials may be placed on the roadway during the verification process. If the mix produced does not verify the mix design, the material placed on the roadway shall be declared a partial lot. If all verification attempts have been exhausted, a new mix design shall be required.

**Section 411, ASPHALT CONCRETE COLD PLANT MIX**, is hereby modified as follows:

The third sentence of **Subsection 411.05 (b), Acceptance**, is hereby amended and the following is substituted therefor:

The accepted mix design shall be field verified by the Contractor at the start of mix production or after an interruption of more than 120 calendar days.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**PERCENT AIR VOIDS FOR ACHM MIX DESIGNS**

**Division 400** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The fourth sentence of the first paragraph of **Subsection 404.01(b), Design Requirements**, is hereby deleted and the following substituted therefor:

The optimum asphalt content is the asphalt binder content at 3.5% air voids for all asphalt mixtures.

The first bullet of the first paragraph of **Subsection 404.01(b), Design Requirements**, is hereby deleted and the following substituted therefor:

- All binder grades for all asphalt mixtures will be designed using 3.5% air voids.

The second paragraph of **Subsection 404.01(b), Design Requirements**, is hereby deleted and substituted therefor:

All Asphalt Base and Binder Courses will be designed at a Ndes of 75 gyrations. All Asphalt Surface Courses will be designed at a Ndes of 60 gyrations.

The second sentence of the second paragraph of **Subsection 404.04, Quality Control of Asphalt Mixtures**, is hereby deleted and the following substituted therefor:

Adjustments to the accepted mix design to conform to actual production values without redesign of the mixture shall be based on production of the mixture at a target value of 3.5% air voids in all asphalt mixture specimens and an asphalt binder content not less than that specified in the accepted mix design.

The table in the tenth paragraph of **Subsection 404.04, Quality Control of Asphalt Mixture**, is hereby amended by deleting the test method ARDOT 449/449A, AASHTO T 308, and Note 4 for asphalt binder content determination and substituting ARDOT TM 483, "Test Method for Determination of Binder Content and Development of Binder and Aggregate Correction Factors by Ignition Method."

The following is hereby added after the tenth paragraph of **Subsection 404.04, Quality Control of Asphalt Mixtures**:

**Ignition Ovens (Single, Multiple, and Replacement).** A single ignition oven shall be used for all ignition-oven determinations performed for Acceptance on a project unless otherwise approved in writing by the Engineer.

Ignition oven requirements apply only to mixtures for which asphalt binder content or gradation is determined using ignition methods for Acceptance.

A correction factor for determining asphalt binder content and gradation using the ignition oven shall be established in accordance with ARDOT TM 483. A separate correction factor shall be developed for each JMF and for each ignition oven used. The correction factor shall be reestablished at a minimum frequency of once every 12 months.

Documentation of the established correction factor shall be submitted to the Engineer prior to the start of production. The Engineer shall be given the opportunity to witness the correction factor determination process.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**PERCENT AIR VOIDS FOR ACHM MIX DESIGNS**

When the mass of a sample exceeds the capacity of the ignition oven or basket, the sample shall be reduced into multiple test portions using approved splitting procedures and tested in separate ignition-oven determinations using the same approved ignition oven. Asphalt binder content results shall be combined on a mass-weighted basis, and aggregate shall be recombined for gradation determinations.

**Use of More than One Ignition Oven (Prior Approval).** The use of more than one ignition oven may be approved in writing by the Engineer prior to the start of production for projects with high production rates, extended paving durations, or multiple simultaneous production operations. When more than one ignition oven is approved, the following shall apply:

1. Each ignition oven shall be identified and approved in writing by the Engineer prior to use.
2. A separate correction factor shall be established and documented for each approved ignition oven in accordance with ARDOT TM 483 prior to use for project testing.
3. Each approved ignition oven shall be assigned to a specific plant, production line, or testing stream and shall not be alternated based on test results.
4. Acceptance testing shall be performed using the assigned ignition oven for the applicable production stream.
5. Selection between approved ignition ovens based on test results shall not be permitted.
6. Changes to approved ignition oven assignments shall be made only with prior written approval from the Engineer.

**Replacement Ignition Oven During Production.** The use of a replacement ignition oven during production may be approved in writing by the Engineer only in the event of equipment failure or other unavoidable circumstances. When a replacement ignition oven is approved, the following shall apply:

1. Ignition-oven determinations intended for Acceptance shall be suspended until a correction factor is established for the replacement ignition oven.
2. A correction factor shall be established and documented for the replacement ignition oven in accordance with ARDOT TM 483 before results from the replacement ignition oven are used for Acceptance or for Department testing.
3. Once approved, the replacement ignition oven shall be used for the remainder of the project unless otherwise approved in writing by the Engineer.

**Bulk Specific Gravity.** When AASHTO T 166 is determined by the Department to be unsuitable, bulk specific gravity shall be determined using an automatic vacuum sealing system in accordance with AASHTO T 331. Use of AASHTO T 331 shall be permitted only when directed by the Department. Suitability shall be based on the ability to obtain reliable results in accordance with the applicable test method requirements. The vacuum sealing system shall be approved by the Engineer prior to use.

AASHTO T 275, Bulk Specific Gravity of Compacted Asphalt Mixtures Using Paraffin-Coated Specimens, shall not be permitted for use in mixture design or Acceptance testing.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**PERCENT AIR VOIDS FOR ACHM MIX DESIGNS**

The Contractor shall furnish the Department with access to a compliant vacuum sealing system for testing when bulk specific gravity is required to be determined in accordance with AASHTO T 331, when specified by the Department. This requirement may be satisfied through the Contractor's primary laboratory or by providing additional approved equipment as necessary to ensure that testing is performed in accordance with the specified method. The Department may also perform testing using Department-owned or independently furnished equipment.

Table 405-1 of **Subsection 405.03, Materials** is hereby deleted and the following substituted therefor:

**Table 405-1**  
**Design Requirements for Asphalt Concrete Hot/Warm Mix Base Course (1½")**

| Control Points                                      |                                                                                                                                                                                                                     |                        |                    |                |                      |                |                      |
|-----------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|--------------------|----------------|----------------------|----------------|----------------------|
| Sieve                                               | Percent Passing (%)                                                                                                                                                                                                 |                        |                    |                |                      |                |                      |
| 1½"                                                 | 100                                                                                                                                                                                                                 |                        |                    |                |                      |                |                      |
| 1"                                                  | 90 - 100                                                                                                                                                                                                            |                        |                    |                |                      |                |                      |
| ¾"                                                  | 90 max.                                                                                                                                                                                                             |                        |                    |                |                      |                |                      |
| No. 4                                               | -                                                                                                                                                                                                                   |                        |                    |                |                      |                |                      |
| No. 8                                               | 15 - 41                                                                                                                                                                                                             |                        |                    |                |                      |                |                      |
| No. 16                                              | -                                                                                                                                                                                                                   |                        |                    |                |                      |                |                      |
| No. 30                                              | -                                                                                                                                                                                                                   |                        |                    |                |                      |                |                      |
| No. 50                                              | -                                                                                                                                                                                                                   |                        |                    |                |                      |                |                      |
| No. 200                                             | 0 - 6                                                                                                                                                                                                               |                        |                    |                |                      |                |                      |
| Asphalt Binder Content                              | Design Value                                                                                                                                                                                                        |                        |                    |                |                      |                |                      |
| % Air Voids                                         | 3.5                                                                                                                                                                                                                 |                        |                    |                |                      |                |                      |
| % VMA                                               | 11.5 - 13.0                                                                                                                                                                                                         |                        |                    |                |                      |                |                      |
| Minimum Water Sensitivity Ratio                     | 80                                                                                                                                                                                                                  |                        |                    |                |                      |                |                      |
| % Anti-strip                                        | As Required                                                                                                                                                                                                         |                        |                    |                |                      |                |                      |
| Fines to Asphalt Ratio*                             | 0.6 - 1.4                                                                                                                                                                                                           |                        |                    |                |                      |                |                      |
| Wheel Tracking Test<br>(8000 cycles, 100 psi, 64°C) | <table> <tr> <th><u>Design PG Grade</u></th><th><u>Maximum Rut</u></th></tr> <tr> <td>64-22 or 67-22</td><td>0.315 in. (8.000 mm)</td></tr> <tr> <td>70-22 or 76-22</td><td>0.197 in. (5.000 mm)</td></tr> </table> | <u>Design PG Grade</u> | <u>Maximum Rut</u> | 64-22 or 67-22 | 0.315 in. (8.000 mm) | 70-22 or 76-22 | 0.197 in. (5.000 mm) |
| <u>Design PG Grade</u>                              | <u>Maximum Rut</u>                                                                                                                                                                                                  |                        |                    |                |                      |                |                      |
| 64-22 or 67-22                                      | 0.315 in. (8.000 mm)                                                                                                                                                                                                |                        |                    |                |                      |                |                      |
| 70-22 or 76-22                                      | 0.197 in. (5.000 mm)                                                                                                                                                                                                |                        |                    |                |                      |                |                      |

\*Fines to asphalt ratio shall be defined as the percent materials passing the No. 200 sieve (expressed as a percent of total aggregate weight) divided by the effective asphalt binder content.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**PERCENT AIR VOIDS FOR ACHM MIX DESIGNS**

Table 406-1 of **Subsection 406.04, Construction Requirements and Acceptance**, is hereby deleted and the following substituted therefor:

**Table 406-1**  
**Design Requirements for Asphalt Concrete Hot/Warm Mix Binder Course (1")**

| Control Points                  |                                           |
|---------------------------------|-------------------------------------------|
| Sieve                           | Percent Passing (%)                       |
| 1½"                             | 100                                       |
| 1"                              | 90 - 100                                  |
| ¾"                              | 90 max.                                   |
| No. 4                           | -                                         |
| No. 8                           | 19 - 45                                   |
| No. 16                          | -                                         |
| No. 30                          | -                                         |
| No. 50                          | -                                         |
| No. 200                         | 1 - 7                                     |
| Asphalt Binder Content          | Design Value                              |
| % Air Voids                     | 3.5                                       |
| % VMA                           | 12.5 - 14.0                               |
| Minimum Water Sensitivity Ratio | 80                                        |
| % Anti-strip                    | As Required                               |
| Fines to Asphalt Ratio*         | 0.6 - 1.4                                 |
| Wheel Tracking Test             | <u>Design PG Grade</u> <u>Maximum Rut</u> |
| (8000 cycles, 100 psi, 64°C)    | 64-22 or 67-22      0.315 in. (8.000 mm)  |
|                                 | 70-22 or 76-22      0.197 in. (5.000 mm)  |

\*Fines to asphalt ratio shall be defined as the percent materials passing the No. 200 sieve (expressed as a percent of total aggregate weight) divided by the effective asphalt binder content.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**PERCENT AIR VOIDS FOR ACHM MIX DESIGNS**

Table 407-1 and Table 407-2 of **Subsection 407.04, Construction Requirements and Acceptance**, are hereby deleted and the following substituted therefor:

**Table 407-1**  
**Design Requirements for Asphalt Concrete Hot/Warm Mix Surface Course (1/2")**

| Control Points                  |                        |
|---------------------------------|------------------------|
| Sieve                           | Percent Passing (%)    |
| 3/4"                            | 100                    |
| 1/2"                            | 90 - 100               |
| 3/8"                            | 90 max.                |
| No. 8                           | 28 - 58                |
| No. 16                          | -                      |
| No. 30                          | -                      |
| No. 50                          | -                      |
| No. 200                         | 3 - 7                  |
| Asphalt Binder Content          | Design Value           |
| % Air Voids                     | 3.5                    |
| % VMA                           | 14.5 - 16.0            |
| Minimum Water Sensitivity Ratio | 80.0                   |
| % Anti-strip                    | As Required            |
| Fines to Asphalt Ratio*         | 0.6 - 1.2              |
| Wheel Tracking Test             | <u>Design PG Grade</u> |
| (8000 cycles, 100 psi, 64°C)    | 64-22 or 67-22         |
|                                 | 70-22 or 76-22         |
|                                 | <u>Maximum Rut</u>     |
|                                 | 0.315 in. (8.000 mm)   |
|                                 | 0.197 in. (5.000 mm)   |

\*Fines to asphalt ratio shall be defined as the percent materials passing the No. 200 sieve (expressed as a percent of total aggregate weight) divided by the effective asphalt binder content.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**PERCENT AIR VOIDS FOR ACHM MIX DESIGNS**

**Table 407-2**

**Design Requirements for Asphalt Concrete Hot Mix Surface Course (3/8")**

| Control Points                  |                        |                      |
|---------------------------------|------------------------|----------------------|
| Sieve                           | Percent Passing (%)    |                      |
| 1/2"                            | 100                    |                      |
| 3/8"                            | 90 - 100               |                      |
| No. 4                           | 90 max.                |                      |
| No. 8                           | 32 - 67                |                      |
| No. 16                          | -                      |                      |
| No. 30                          | -                      |                      |
| No. 50                          | -                      |                      |
| No. 200                         | 3 - 7                  |                      |
| Asphalt Binder Content          | Design Value           |                      |
| % Air Voids                     | 3.5                    |                      |
| % VMA                           | 15.5 - 17.0            |                      |
| Minimum Water Sensitivity Ratio | 80.0                   |                      |
| % Anti-strip                    | As Required            |                      |
| Fines to Asphalt Ratio*         | 0.6 - 1.4              |                      |
| Wheel Tracking Test             | <u>Design PG Grade</u> | <u>Maximum Rut</u>   |
| (8000 cycles, 100 psi, 64°C)    | 64-22 or 67-22         | 0.315 in. (8.000 mm) |
|                                 | 70-22 or 76-22         | 0.197 in. (5.000 mm) |

\*Fines to asphalt ratio shall be defined as the percent materials passing the No. 200 sieve (expressed as a percent of total aggregate weight) divided by the effective asphalt binder content.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**PERCENT AIR VOIDS FOR ACHM MIX DESIGNS**

The Table 410-1 in **Subsection 410.09(b), Acceptance of the Pavement**, is hereby amended as follows:

**TABLE 410-1**  
**COMPLIANCE, PRICE REDUCTION AND REJECTION LIMITS FOR ASPHALT COURSES**

| Property                                                    | Compliance Limits          | Price Reduction Limits               | Lot Rejection Limits                 | Sublot Rejection Limits          |
|-------------------------------------------------------------|----------------------------|--------------------------------------|--------------------------------------|----------------------------------|
| Asphalt Binder Content                                      | ±0.3 from mix design value | more than ±0.3 from mix design value | more than ±0.6 from mix design value | ±0.8 from mix design value       |
| Air voids (AV)                                              | 2.5% to 4.5%               | 1.9% to 2.4%<br>4.6% to 5.0%         | 1.8% or less<br>5.1% or more         | 1.4% or less<br>5.6% or more     |
| Voids in Mineral Aggregate (VMA)*                           |                            |                                      |                                      |                                  |
| Asphalt Base Course (1½")                                   | 11.0% to 13.5%             | 10.5% to 10.9%<br>13.6% to 14.0%     | 10.4% or less<br>14.1% or more       | 9.9% or less<br>14.6% or more    |
| Asphalt Binder Course (1")                                  | 12.0% to 14.5%             | 11.5% to 11.9%<br>14.6% to 15.0%     | 11.4% to less<br>15.1 or more        | 10.9% or less<br>15.6% or more   |
| Asphalt Surface Course (1/2")                               | 14.0% to 16.5%             | 13.5% to 13.9%<br>16.6% to 17.0%     | 13.4% or less<br>17.1% or more       | 12.9% or less<br>17.6% or more   |
| Asphalt Surface Course (3/8")                               | 15.0% to 17.5%             | 14.5% to 14.9%<br>17.6% to 18.0%     | 14.4% or less<br>18.1% or more       | 13.9% or less<br>18.6% or more   |
| Density (% of theoretical)                                  | 92.0% to 97.0%             | 91.0% to 91.9%<br>97.1 to 98.0%      | 90.9% or less<br>98.1% or more       | 89.9% or less**<br>99.1% or more |
| Density (% of theoretical) where minimum specified is 90.0% | 90.0% to 97.0%             | 89.0% to 89.9%<br>97.1% to 98.0%     | 88.9% or less<br>98.1% or more       | 87.9% or less**<br>99.1% or more |

\*The values for VMA<sub>(actual)</sub> shall be determined by calculating the VMA<sub>(effective)</sub> and reducing it by the correction factor shown on the mix design.

\*\*Subject to further evaluation, see text.

## ARKANSAS DEPARTMENT OF TRANSPORTATION

### SUPPLEMENTAL SPECIFICATION

#### LIQUID ANTI-STRIP ADDITIVE

**Division 400** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

**Section 404, DESIGN AND QUALITY CONTROL OF ASPHALT MIXTURES**, is hereby modified as follows:

The following is added as the last bullet following the first paragraph of **Subsection 404.01(b), Design Requirements**:

- All ACHM mixes must contain a liquid, anti-strip additive.

**Section 409, MATERIALS AND EQUIPMENT FOR ASPHALT CONCRETE PLANT MIX COURSES**, is hereby modified as follows:

The second paragraph of **Subsection 409.02 Asphalt Binder** is hereby deleted and the following substituted therefor:

The asphalt binder for all Asphalt Concrete Hot Mixes shall contain a heat-stable, liquid anti-strip additive. The additive shall be furnished from the Qualified Products List. The additive shall not harm the completed bituminous concrete mixture and must be compatible with the aggregate and asphalt binder supplied for the project. The anti-strip additive shall be added either by an in-line blending process just before introduction of the asphalt binder to the mixer or by blending with the asphalt binder at the asphalt binder terminal. If blended at the terminal, the bill of lading accompanying the load being delivered to the hot mix asphalt plant shall include the anti-strip manufacturer's name, product name, and quantity of all anti-strip additive included in the load.

The liquid anti-strip additive shall be added at rates as indicated below:

- For ACHM mixes where the use of an anti-strip additive is required as determined by the laboratory analysis and mix design procedures, the anti-strip additive shall be added at the rate of 0.5% to 0.75% (0.05% to 0.10% for organosilane based materials) by weight of asphalt binder as determined by the laboratory analysis and laboratory mix design procedures.
- For all other mixes, the manufacturer's recommended dosage of the additive shall be used, but the rate of liquid anti-strip additive shall not be less than 0.25% (0.05% for organosilane based materials) by weight of the asphalt binder.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SUPPLEMENTAL SPECIFICATION**

**TRACKLESS TACK**

**Sections 401 and 403** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The following is hereby added after the second sentence of **Subsection 401.02 Materials:**

Trackless Tack meeting the requirements of this supplemental specification may be used as Tack Coat at no additional cost to the Department.

The following is hereby added after the fifth sentence of **Subsection 401.03(c), Application of Tack Coat:**

When Trackless Tack is used, the Contractor shall follow the manufacturer's recommendations for storage, application temperature, and application rate.

The following is hereby added as the second paragraph of **Subsection 401.06, Basis of Payment:**

If the Contractor elects to use Trackless Tack in lieu of Tack Coat, the application and payment for the material used will be measured and paid for at the contract unit price bid for Tack Coat per gallon (liter).

The following is hereby added after the second sentence of the first paragraph **Subsection 403.03, Asphalt Materials:**

The manufacturer shall submit certified test results for Trackless Tack to the Engineer.

# ARKANSAS DEPARTMENT OF TRANSPORTATION

## SUPPLEMENTAL SPECIFICATION

### TRACKLESS TACK

The following is hereby added as **Subsection 403.03 (g), Trackless Tack:**

Trackless tack shall be an anionic or cationic asphalt emulsion conforming to the requirements below:

|                                      | Test Method | Min  | Max |
|--------------------------------------|-------------|------|-----|
| Viscosity, Saybolt Furol at 25°C SFS | AASHTO T59  | 20   | 150 |
| Storage stability test, 24-h, %      | AASHTO T59  |      | 1   |
| Sieve test, %                        | AASHTO T59  |      | 0.3 |
| Residue by distillation, %           | AASHTO T59  | 50   |     |
| Tests on residue from distillation:  |             |      |     |
| Penetration, 25°C, 100 g, 5 s        | AASHTO T59  |      | 20  |
| *Solubility %                        | AASHTO T44  | 97.5 |     |
| *Ash Content                         | AASHTO T111 |      | 1   |
| Softening Point °C                   | AASHTO T53  | 65   |     |

\*Ash Content or Solubility may be used for testing purposes of the residue from distillation.

**ARKANSAS DEPARTMENT OF TRANSPORTATION****SUPPLEMENTAL SPECIFICATION****DESIGN OF ASPHALT MIXTURES**

**Section 400** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The following is added after the first sentence of paragraph 3 **Subsection 404.01 Design of Asphalt Mixtures. (b) Design Requirements:**

Any use of recycled engine oil bottoms (REOB) or other engine oil derivatives in the manufacture or modification of a binder are strictly prohibited. Ground Tire Rubber (GTR) may be added to asphalt binder with blending of GTR into asphalt occurring only at the asphalt terminal. GTR shall be Class 80-1 ground tire rubber as defined by ASTM D5603.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**ASPHALT LABORATORY FACILITY**

**Division 400** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

**Subsection 409.03(h), Plant Inspection**, is hereby deleted and the following substituted therefor:

**(h) Plant Inspection.** The Engineer shall have access to all parts of the plant.

The Contractor shall provide and maintain a laboratory facility for the exclusive use of the Engineer. This facility shall be located at the plant site. The dimensions and other requirements specified herein are minimums. The facility may be built by the Contractor for the specific purposes stated. Portable structures used as lab facilities must be anchored to the ground and have adequate reinforcement to the floor to provide stability for lab equipment. It is not intended, however, to preclude the use of commercially built trailers or prefabricated buildings that may deviate in minor dimension or detail from the requirements listed but may in some features exceed these requirements and in all major respects be entirely suitable for the purpose intended. The Contractor may furnish, in lieu of a separate building, a facility having sufficient space in a building, parts of which are used for other purposes, provided that the facility furnished meets all other requirements of this subsection; is physically separated from the remainder of the building; and has an outside entrance with unrestricted access allowed and reserved for the exclusive use of the Engineer. Adequate space shall be provided for parking of at least three Department vehicles in the vicinity of the facility. The Engineer will determine the suitability of any facility furnished.

General requirements for the laboratory facility are:

- Minimum working laboratory space of 380 square feet (35.3 sq m) for building widths between 8' to 12' (2.4 to 3.7 m) or 208 square feet (19.3 sq m) with a width of 12' (3.7 m) or greater.
- Minimum designated office space of 30 square feet (2.8 sq m) shall be included in addition to the laboratory square footage.
- A ceiling height of 8' (2.4 m) or greater.
- A desk or table approximately 24" x 36" (600 mm x 900 mm), with at least two drawers, each approximately 13" x 13" x 18" (330 mm x 330 mm x 450 mm) for storing records and at least three office style rolling chairs.
- At least one door with a substantial lock and all keys placed in the possession of the Engineer. The door must be a minimum of 36" (900 mm) wide. A second entry door at the end of trailers that are greater than 30' (9.1 m) in length will be required for safety reasons.
- Access to a well-maintained restroom, with a functioning sink, within reasonable proximity to the Department laboratory facility. Portable restrooms are not acceptable.
- Floored, weatherproof, and reasonably dustproof.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**ASPHALT LABORATORY FACILITY**

- Level and stable with substantial/durable structure capable of supporting required laboratory equipment. Movement in the lab shall not affect testing operations such as scale readings, etc.
- At least two glazed screened windows capable of being opened and locked only from the inside.
- Basic utility services shall be provided year-round as long as the plant is listed on the QPL. If utility services to the Department lab are voluntarily suspended at any time, the plant may be removed from the QPL.
- Equip the lab with heating and air conditioning units that maintain the ambient air temperature between 65 °F and 80 °F (18 °C and 27°C). The lab must be climate-controlled year-round.
- A work counter approximately 30" to 36" (760 to 900 mm) high with a minimum depth of 30" (760 mm). The countertop shall be metal capped with a rolled back edge of 2" (50 mm) if adjacent to the wall or other comparable durable surface. Total length of the work counter shall be approximately 35' (10.7 m) with a minimum of 12' (3.7 m) of counter length 36" (900 mm) deep.
- A minimum of 54" (1370 mm) width between parallel work counters.
- Adequate electric lights suitable for the purposes intended. At least one power outlet per every four feet of counter. At least two power outlets shall provide 220 VAC.
- An exhaust outlet with at least 3" (76 mm) inside diameter no farther than 8' (2.4 m) from the ignition oven shall be included near one of the 220 VAC outlets. Provide a surface for the ignition oven that is level, sturdy, and fireproof with at least 6" (152 mm) of clearance between the furnace and other vertical surfaces. The exhaust fumes exiting the furnace exhaust port may reach 270 °C (518 °F).
- An exhaust fan shall be installed over the equipment clean up area. The exhaust fan shall be equipped with a rheostat control and capable of exhausting in one minute a volume of air equal to the volume of the entire laboratory. The exhaust fan shall be maintained operational.
- A sink, approximately 24" (610 mm) square with a minimum depth of 9" (230 mm) with an outside drain.
- A clean water supply providing a minimum of 50 gallons (200 liters) storage capacity (or connected to a public or private water system), discharging through a faucet above the sink. A thermostat controlled hot water supply shall be provided to the laboratory sink.
- Adequate shelves and/or cabinets for storage of testing equipment that do not impede the operation of testing equipment.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**ASPHALT LABORATORY FACILITY**

- A storage area for storing nuclear equipment, complete with a substantial lock and all keys to this area placed in the possession of the Engineer.
- At least one Type ABC fire extinguisher (10-pound size minimum) with up-to-date inspection tag per 300 square feet of building.
- A local access touchtone telephone line (with access to toll free telephone numbers but otherwise blocked for outgoing long-distance calls), with a landline modular jack and touchtone telephone, shall be provided in the laboratory facility for use by Department personnel.
- Reliable Broadband Internet Service shall be provided.

The Broadband Internet Service shall be provided with an Internet Protocol (IP) address which is reachable on the global Internet (public) and which is permanently assigned (static). The Contractor is not required to provide this service if an IP address which is both static and public is not available.

If this service is not available at the beginning of a project but becomes available during the life of the project, the Contractor shall provide the service immediately from the date of availability.

The data transfer rate shall be 3 megabits per second (Mbps) download and 500 kilobits per second (kbps) upload, or higher, with latency not to exceed 150 milliseconds. If the Broadband Internet Service meets all of the requirements of this specification except for the data transfer rate and/or latency, then the best performing available connection shall be provided. The Broadband Internet Service shall be provided with equipment providing a minimum of one Ethernet port.

Prior to the selection of the Broadband Internet Service provider, the Contractor shall submit to the Resident Engineer, in writing, the proposed method for providing Broadband Internet Service. The Resident Engineer shall review this submittal and respond in writing regarding the acceptability of the proposed method.

Adequate maintenance of the laboratory facility shall be required for plant inclusion on the QPL and will be included as part of the annual ACHM plant inspection. Maintenance shall include, but is not limited to, HVAC and electrical systems, and plumbing. The Resident Engineer may determine a lab is in reasonable compliance with this specification if all required testing can be accomplished with reasonable ease by the Construction Materials Inspector.

The requirements of this Supplemental Specification shall be implemented to receive the next scheduled ACHM Plant Certification. If the requirements are not met and the Resident Engineer determines the laboratory is not within reasonable compliance an ACHM Plant Certification will not be provided until all requirements are fulfilled and/or the Resident Engineer is satisfied with the conditions of the facilities.

The field laboratory for asphalt mixing plants and the utility services provided will not be paid for directly but will be considered a part of the asphalt mixing plant.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SUPPLEMENTAL SPECIFICATION**

**CONSTRUCTION REQUIREMENTS AND ACCEPTANCE OF  
ASPHALT CONCRETE PLANT MIX COURSES**

**Section 410, Construction Requirements and Acceptance of Asphalt Concrete Plant Mix Courses**, of the Standard Specifications for Highway Construction, Edition of 2014, is hereby modified as follows:

**Subsection 410.10 Incentives** is hereby deleted.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SUPPLEMENTAL SPECIFICATION**

**DEVICES FOR MEASURING DENSITY FOR ROLLING PATTERNS**

**Section 410** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The fourth sentence of the first paragraph of **Subsection 410.08, Rolling and Density Requirements and Joints**, is hereby deleted and the following substituted therefor:

The Engineer will observe the Contractor's use of an electromagnetic surface contact device that meets ASTM D7113/D7113M or the use of a nuclear density gauge to verify that the maximum densities possible are obtained.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**EVALUATION OF ACHM SUBLOT REPLACEMENT MATERIAL**

**Section 410** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The following shall be added to the second to the last paragraph of **Subsection 410.09 (a)**  
**General:**

If the material used to replace unacceptable material is a different mix design from what was originally placed, the remaining material in the lot and the replacement material shall both be evaluated as separate partial lots.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**RECYCLED ASPHALT PAVEMENT**

**Division 400** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The fourth paragraph of **Subsection 416.03, Materials and Composition**, is hereby deleted and the following substituted therefor:

To ensure the “production” stockpile is distinguishable to anyone involved in the production of asphalt at the plant and no “unprocessed” materials are introduced into the process of ACHM mix manufacturing, the following shall be required for the use of Recycled Asphalt Pavement (RAP):

- RAP stockpiles should have only binder covered aggregates and therefore, there shall be no virgin aggregate or deleterious materials present in any RAP stockpile. Uncoated aggregate from asphalt plant produced material shall not be considered virgin aggregate as it applies to RAP. Plant startup and shut down materials will be considered binder covered and are allowed.
- Unprocessed RAP and processed RAP stockpiles shall be separated by distance and each stockpile signed accordingly.
- Only processed RAP shall be introduced into asphalt mixes. Processed is defined as efforts to create a uniform stockpile of material and may include, but is not limited to, crushing and/or fractionating. Use of the scalper screen on the plant does not define processed RAP.
- Processed RAP stockpiles shall be of adequate size for multiple operational days of asphalt mix production at the plant’s maximum production rate. Processed RAP must be stockpiled before use in plant production. Processed RAP may not be taken from underneath the crusher and placed directly into the cold feed bins. If the crusher is feeding the processed stockpile, the loader must load the cold feed bins from the opposite end of the processed stockpile.

Quality control testing for asphalt binder content and gradation of RAP shall be the contractor’s responsibility and conducted as follows:

- Tested as part of the field verification process. Field verification test results may be transferred from another ARDOT job given they are from the same mix design and were completed within 120 days of the current job’s field verification process.
- Minimum of one set of tests per job for jobs that contain at least 1,000 tons of ACHM.
- One set of tests for every 10,000 tons of ACHM produced.
- The first tests on the job must be performed within the first 3 days of production on the job.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**RECYCLED ASPHALT PAVEMENT**

The Contractor has the option of quality control testing while the processed stockpile is being built in lieu of testing during production. Quality control testing for asphalt binder content and gradation of RAP shall be the Contractor's responsibility and conducted as follows:

- Tested as part of the field verification process. Field verification test results may be transferred from another ARDOT job given they are from the same mix design and were completed within 120 days of the current job's field verification process.
- One set of tests for every 1,500 tons of RAP produced for each stockpile.
- The quantity of RAP being placed in the processed stockpile must be tracked.

The Contractor shall pick only one option of quality control method per processed RAP stockpile. The Engineer shall be given the opportunity to witness all testing. Test results shall be submitted to the Engineer by the next business day. The Contractor shall keep a logbook to track the consistency of the asphalt binder content and gradation.

If testing determines the properties of the RAP have deviated significantly from the mix design, as determined by the Engineer, changes to virgin binder content and/or aggregate proportions will be required before production of the ACHM continues. Once adjustments are made and the plant produced mix has the desired properties, the Contractor may request that a field mix design be accepted by the Engineer.

To create uniform, repeatable testing for RAP binder content, asphalt binder content of the RAP shall be determined using AASHTO T 308 with the specific requirements as follows:

- Sample shall be dried to a constant mass as per AASHTO T 329 using a drying temperature of  $230^{\circ}\text{F} \pm 9^{\circ}\text{F}$ .
- The ignition oven burn temperature used during the mix design process must be used for quality control. The burn temperature shall be reported on the mix design submittal.
- Asphalt Binder Content = % loss – Aggregate Correction Factor (ACF)
- An ACF for each processed RAP stockpile shall be submitted with the mix design if used. An ACF for the job mix formula shall be submitted on the mix design if used. If multiple ignition ovens are used, an ACF for each oven shall be submitted.
- Determination of the ACF may be based on regional historical data at the time of the change. This will ensure all parties involved are aware of the correction factor and therefore avoiding disagreements pertaining to manipulation/fluctuation in aggregate correction factors that could be used to adjust binder content data.

**ARKANSAS DEPARTMENT OF TRANSPORTATION****SUPPLEMENTAL SPECIFICATION****LANE CLOSURE NOTIFICATION**

**Division 600** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

**Section 603, Maintenance of Traffic and Temporary Structures**, is hereby modified as follows:

The first sentence of the third paragraph **Subsection 603.02 (d)** is hereby deleted and the following substituted therefor:

The Contractor shall provide the Engineer with a minimum of five full business days advance, written notification of any nonemergency lane closure or lane width restriction. The first full business day shall commence at midnight on the first business day following written notification to the Engineer. This advanced notification is required to allow adequate notice for the issuance of over width load permits by the Department.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**RETROREFLECTIVE SHEETING FOR**  
**TRAFFIC CONTROL DEVICES IN CONSTRUCTION ZONES**

**Section 604** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The following is inserted after the first paragraph of Subsection 604.02(b):

Retroreflective sheeting used on traffic drums shall meet the requirements of ASTM D4956 for Type III or IV with the additional requirements for Reboundable Sheeting. Retroreflective sheeting for delineators shall comply with section 728.

Retroreflective sheeting shall be applied to a properly treated substrate with mechanical equipment and in a manner specified by the sheeting manufacturer. Sign material (substrate) shall be of sufficient thickness and stability to maintain a substantial, effective sign for the duration of the project. One splice will be allowed in retroreflective sheeting on sign blanks. "Left", "Right", "Distances", and "Ahead" will be allowed on signs as inserts. All letters and numerals on inserts shall be of the same size and series as those on the sign face.

## ARKANSAS DEPARTMENT OF TRANSPORTATION

## SUPPLEMENTAL SPECIFICATION

## TRAFFIC CONTROL DEVICES IN CONSTRUCTION ZONES (MASH)

**Section 604** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The first paragraph of **Subsection 604.02 Materials (a) General** is hereby deleted and the following substituted therefor:

All work zone traffic control devices used on the project, including sign supports, barricades, traffic drums equipped with flashing lights, crash cushions, and impact attenuators, manufactured after December 31, 2019, shall comply with the requirements of the Manual for Assessing Safety Hardware (MASH). Such devices manufactured on or before December 31, 2019, and successfully tested to the requirements of National Cooperative Highway Research Program (NCHRP) Report 350 or the 2009 edition of MASH, may continue to be used throughout their normal service lives. The Contractor shall furnish a certification of such compliance from the manufacturer or supplier of all work zone traffic control devices prior to using the devices on the project. The certification shall state the device meets the requirements of MASH, or in the case that the device was manufactured on or before December 31, 2019, the certification shall state the device meets the requirements of NCHRP 350 or MASH. The certification shall include a copy of the Federal Highway Administration's (FHWA) approval letter with all attachments for each device. Devices shall be fabricated and installed in accordance with the plans and with the crash testing documentation provided in the FHWA approval letter which is available at:

[http://safety.fhwa.dot.gov/roadway\\_dept/policy\\_guide/road\\_hardware/](http://safety.fhwa.dot.gov/roadway_dept/policy_guide/road_hardware/).

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**CLASSIFICATION AND APPLICATION OF MARKINGS**

**Section 604** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The first paragraph of Subsection **604.03(f)(1)(c) Interim Pavement Markings** is hereby deleted and the following substituted therefor:

c. **Interim Pavement Markings.** Interim pavement markings are those that may be used for a short period of time until it is practical and possible to place either permanent or construction pavement markings. Interim pavement markings shall be replaced with permanent or construction markings or covered with a succeeding course of paving within seven (7) calendar days on high-volume roads or fourteen (14) calendar days on low-volume roads. Day 1 of the 7- or 14-day period is the first calendar day that it becomes practical and possible to place permanent or construction pavement markings. If interim markings are not covered or replaced with permanent or construction markings within the specified time period, no work on the project shall continue or commence until either permanent or construction pavement markings are in place. High-volume and low-volume roads will be designated on the plans.

The Subsection **604.03(f)(2)(a) Application of Markings, Final Surfaces**, is hereby deleted and the following substituted therefor:

a. **Final Surfaces.** Permanent or construction markings, as specified in the Contract, shall be in place on the final surface at the end of each day's operations on all lanes open to traffic. Unless otherwise specified, edge lines will not be required. The Contractor may, at Contractor option and expense, use interim pavement markings as follows:

*High volume roads.* On roadways designated on the plans as high volume, interim pavement markings may be used for not longer than 7 calendar days. All centerline and lane line permanent markings shall be placed within the 7-day period.

*Low volume roads.* On roadways designated on the plans as low volume, interim pavement markings may be used for not longer than 14 calendar days. All centerline and lane line permanent markings shall be placed within the 14-day period.

The Contractor shall carefully place all interim markings to avoid any overlapping by the permanent pavement markings. Interim pavement markings shall be removed from the final surface as soon as possible after the placement of permanent markings. Any voids caused by the removal of interim markings shall be repaired immediately at the Contractor's expense. For all markings that are to be removed, paint will not be allowed on the final surface unless otherwise authorized in writing by the Engineer.

On roadways open to traffic, if interim pavement markings are used, they shall be removed only after permanent pavement markings are in place.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**CONCRETE FOR STRUCTURES**

**Division 800** of the Standard Specifications for Highway Construction, Edition of 2014, is hereby amended as follows:

The first and second paragraph of **Subsection 802.02(a), Cement**, are hereby deleted and the following substituted therefor:

**(a) Cement.** Portland cement, blended cement, fly ash, and slag cement shall be from sources that are listed on the Department's Qualified Products List (QPL) in Division 500 and that have executed a certification agreement with the Department.

The first and second sentence of the third paragraph of **Subsection 802.02(a), Cement**, are hereby deleted and the following substituted therefor:

The total alkalis in the Portland or blended cement ( $\text{Na}_2\text{O} + 0.658 \text{ K}_2\text{O}$ ) shall not exceed 0.60%. The total alkalis in the cementitious material shall not exceed 5 lbs./cu yd (2.4 kg/cu m).

The sixth paragraph of **Subsection 802.02(b), Fine Aggregate**, is hereby deleted.

The sixth paragraph of **Subsection 802.02(c), Coarse Aggregate**, is hereby deleted.

**Subsection 802.02(e), Admixtures**, is hereby deleted and the following substituted therefor:

**(e) Admixtures.** Admixtures shall be from sources that are listed on the Department's QPL in Division 500. Admixtures will be reviewed and approved during the mix design submittal. Admixtures shall be compatible with each other, as advised by the manufacturer. The admixture dosage rate range as recommended by the manufacturer shall be used. Should the dosage rate for any admixture not yield desirable characteristics in the concrete, the dosage of admixture used shall be based on test results obtained by trial batches.

Admixtures shall be added to the mixing water by means of a mechanical dispenser that will accurately meter the additive throughout the mix water cycle. The dispenser shall be constructed and connected so that the amount of admixture entering the mixing water can be readily determined.

**Subsection 802.05(b), Mix Design by the Contractor**, is hereby deleted and the following substituted therefor:

**(b) Mix Design by the Contractor.** The proportions to be used in the mix for each class shall be determined by the Contractor using the absolute volume method. The Contractor may use the procedure provided in the ACI Standard 211.1 or Portland Cement Association "Design and Control of Concrete Mixtures", modified to comply with the minimum compressive strength and maximum water/cement ratio specified for the class of concrete. A minimum of 15 business days prior to the start of production of the concrete mixture, the Contractor shall submit test results and/or certifications for all materials and detailed mix design data to the Engineer of Materials for review and approval. The ARDOT Concrete Mix Design Submittal form is available for download on the Materials Division website and shall be used. The Department will assign a Mix Design ID, and it shall be included on the delivery ticket.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENTAL SPECIFICATION**  
**CONCRETE FOR STRUCTURES**

The Contractor will submit slump ranges during the mix design process. The Engineer of Materials will determine the allowable tolerances for slump during review of the mix design. The mixed concrete shall have a uniform consistency with a slump, as determined by AASHTO T 119, not exceeding the tolerances as listed on the mix design.

Acceptance of the mix design by the Engineer will be based on apparent conformity to the requirements shown in Table 802-1 and listed herein. If the mix design fails to produce acceptable results or if there is a change in the aggregates, fly ash, or cement being used, a new mix design will be required. It shall remain the Contractor's responsibility during production to produce concrete conforming to the mix design and the minimum acceptance criteria specified. When requested by the Engineer, the Contractor shall submit samples of all materials for verification testing. Production shall not begin until the mix design is accepted by the Engineer.

A mix design submitted for acceptance need not be prepared specifically for this project but may be a previously accepted design that uses the same materials and meets the same design criteria.

Mix designs accepted under this section will become the property of the Department and may be accepted for use on other projects, by other contractors, or by the Department.

In **Table 802-1**, Slump Range for all classes of concrete are hereby deleted.

The first paragraph of **Subsection 802.05(d), Fly Ash**, is hereby deleted and the following substituted therefor:

Fly ash may be used as a partial replacement for Portland or blended cement, not exceeding 25% by weight. Substitution shall be made at the rate of one pound (kilogram) of fly ash for each pound (kilogram) of cement replaced, in all classes of concrete except Class B. Substitution shall be made at the rate of one pound (kilogram) of fly ash for each pound (kilogram) of cement replaced. The water/cement ratio shall be calculated using the total weight of both cement and fly ash. Fly ash in Class B concrete shall meet the requirements specified in Subsection 802.05(c) and listed herein. Mixtures with fly ash shall meet the same requirements as mixtures without fly ash. Fly ash will not be allowed as a substitute in high early strength mixes. When fly ash is used, the total weight of both cement and fly ash will be used in design calculations.

ARKANSAS DEPARTMENT OF TRANSPORTATION  
CONSTRUCTION PLANS FOR STATE HIGHWAY

| DATE<br>REVISED | DATE<br>REVISED | FED. DIST. NO. | STATE | JOB NO. | SHEET<br>NO. | TOTAL<br>SHEETS |
|-----------------|-----------------|----------------|-------|---------|--------------|-----------------|
|                 |                 | 6              | ARK.  | A60063  | 1            | 16              |

# HWY. 7 IMPVTS. (HOT SPRINGS) (S)


GARLAND COUNTY

ROUTE 7 SECTION 9


## JOB A60063

FED. AID PROJ. STPSC-9210(62)

NOT TO SCALE



ARK. HWY. DIST. NO. 6



MID POINT OF PROJECT  
LATITUDE • N 34° 27' 42.18"  
LONGITUDE • W 93° 03' 42.08"

|              |    |         |               |    |             |
|--------------|----|---------|---------------|----|-------------|
| GROSS LENGTH | OF | PROJECT | 31025.28 FEET | OR | 5.876 MILES |
| NET          | "  | ROADWAY | 31025.28      | "  | 5.876       |
| NET          | "  | BRIDGES | 0.00          | "  | 0.000       |
| NET          | "  | PROJECT | 31025.28      | "  | 5.876       |

APPROVED



Lake, William H.  
Date: 2026.05.08  
10:43:31 -05'00'

DISTRICT ENGINEER

## INDEX OF SHEETS

| SHEET NO. | TITLE                                 |
|-----------|---------------------------------------|
| 1         | TITLE SHEET                           |
| 2         | INDEX OF SHEETS AND STANDARD DRAWINGS |
| 3         | GOVERNING SPECIFICATIONS              |
| 4         | GENERAL NOTES                         |
| 5 - 10    | TYPICAL SECTIONS OF IMPROVEMENT       |
| 11        | SPECIAL DETAILS                       |
| 12 - 15   | QUANTITIES                            |
| 16        | SUMMARY OF QUANTITIES AND REVISIONS   |

## ROADWAY STANDARD DRAWINGS

| DRWG.NO. | TITLE                                                          | DATE     |
|----------|----------------------------------------------------------------|----------|
| DR-3     | DETAILS OF DRIVEWAYS & STREET TURNOUTS (PAVEMENT PRESERVATION) | 04-13-23 |
| PM-1     | PAVEMENT MARKING DETAILS                                       | 04-09-26 |
| SD-4     | LOOP DETECTOR INSTALLATION                                     | 11-07-19 |
| TC-1     | STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION             | 08-14-25 |
| TC-1A    | STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION             | 04-09-26 |
| TC-2     | STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION             | 08-14-25 |
| TC-3     | STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION             | 08-14-25 |
| TC-6     | STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION             | 04-09-26 |
| WR-1     | WHEELCHAIR RAMPS NEW CONSTRUCTION AND ALTERATIONS              | 11-10-05 |
| WR-2     | WHEELCHAIR RAMPS ALTERATIONS ONLY                              | 10-09-03 |

## GOVERNING SPECIFICATIONS

ARKANSAS STATE HIGHWAY COMMISSION STANDARD SPECIFICATIONS FOR HIGHWAY  
CONSTRUCTION, EDITION OF 2014, AND THE FOLLOWING SPECIAL PROVISIONS  
AND SUPPLEMENTAL SPECIFICATIONS:




| NUMBER     | TITLE                                                                                  |
|------------|----------------------------------------------------------------------------------------|
| ERRATA     | ERRATA FOR THE BOOK OF STANDARD SPECIFICATIONS                                         |
| FHWA-1273  | REQUIRED CONTRACT PROVISIONS FEDERAL-AID CONSTRUCTION CONTRACTS                        |
| FHWA-1273  | SUPPLEMENT - EQUAL EMPLOYMENT OPPORTUNITY - NOTICE TO CONTRACTORS                      |
| FHWA-1273  | SUPPLEMENT - SPECIFIC EQUAL EMPLOYMENT OPPORTUNITY RESPONSIBILITIES (23 U.S.C. 140)    |
| FHWA-1273  | SUPPLEMENT - EQUAL EMPLOYMENT OPPORTUNITY - GOALS AND TIMETABLES                       |
| FHWA-1273  | SUPPLEMENT - EQUAL EMPLOYMENT OPPORTUNITY - FEDERAL STANDARDS                          |
| FHWA-1273  | SUPPLEMENT - POSTERS AND NOTICES REQUIRED FOR FEDERAL-AID PROJECTS                     |
| FHWA-1273  | SUPPLEMENT - WAGE RATE DETERMINATION                                                   |
| 100-3      | CONTRACTOR'S LICENSE                                                                   |
| 100-4      | DEPARTMENT NAME CHANGE                                                                 |
| 102-2      | ISSUANCE OF PROPOSALS                                                                  |
| 102-3      | PREQUALIFICATION OF BIDDERS                                                            |
| 103-2      | CONTACT INFORMATION FOR MOTORIST DAMAGE CLAIMS                                         |
| 105-4      | MAINTENANCE DURING CONSTRUCTION                                                        |
| 107-2      | RESTRAINING CONDITIONS                                                                 |
| 108-1      | LIQUIDATED DAMAGES                                                                     |
| 108-2      | WORK ALLOWED PRIOR TO ISSUANCE OF WORK ORDER                                           |
| 108-3      | WORK ORDER FOR FIXED COMPLETION DATE CONTRACTS                                         |
| 306-1      | QUALITY CONTROL AND ACCEPTANCE                                                         |
| 400-1      | TACK COATS                                                                             |
| 400-4      | DESIGN AND QUALITY CONTROL OF ASPHALT MIXTURES                                         |
| 400-5      | PERCENT AIR VOIDS FOR ACHM MIX DESIGNS                                                 |
| 400-6      | LIQUID ANTI-STRIP ADDITIVE                                                             |
| 400-7      | TRACKLESS TACK                                                                         |
| 404-3      | DESIGN OF ASPHALT MIXTURES                                                             |
| 409-2      | ASPHALT LABORATORY FACILITY                                                            |
| 410-1      | CONSTRUCTION REQUIREMENTS AND ACCEPTANCE OF ASPHALT CONCRETE PLANT MIX COURSES         |
| 410-2      | DEVICES FOR MEASURING DENSITY FOR ROLLING PATTERNS                                     |
| 410-4      | EVALUATION OF ACHM SUBLOT REPLACEMENT MATERIAL                                         |
| 416-1      | RECYCLED ASPHALT PAVEMENT                                                              |
| 603-1      | LANE CLOSURE NOTIFICATION                                                              |
| 604-1      | RETROREFLECTIVE SHEETING FOR TRAFFIC CONTROL DEVICES IN CONSTRUCTION ZONES             |
| 604-3      | TRAFFIC CONTROL DEVICES IN CONSTRUCTION ZONES (MASH)                                   |
| 604-4      | CLASSIFICATION AND APPLICATION OF MARKINGS                                             |
| 802-5      | CONCRETE FOR STRUCTURES                                                                |
| JOB A60063 | ASPHALT MIXTURES WITH PG 76-22 BINDER                                                  |
| JOB A60063 | ASSESSMENT OF WORKING DAYS - MAINTENANCE OF TRAFFIC                                    |
| JOB A60063 | BIDDING REQUIREMENTS AND CONDITIONS                                                    |
| JOB A60063 | BUY AMERICA - CONSTRUCTION MATERIALS                                                   |
| JOB A60063 | CARGO PREFERENCE ACT REQUIREMENTS                                                      |
| JOB A60063 | COLD MILLING - MILL & INLAY                                                            |
| JOB A60063 | CONCRETE PULL BOX                                                                      |
| JOB A60063 | DESIGN AND QUALITY CONTROL OF ASPHALT MIXTURES                                         |
| JOB A60063 | DOCUMENTATION OF PAYMENTS MADE - PROMPT PAYMENT (SIGNET)                               |
| JOB A60063 | DOCUMENTATION OF PAYMENTS MADE TO DISADVANTAGED BUSINESS ENTERPRISES                   |
| JOB A60063 | ELECTRONIC TICKETING SYSTEMS (E-TICKETING)                                             |
| JOB A60063 | INSURANCE, CONSTRUCTION, AND FLAGGING REQUIREMENTS ON RAILROAD PROPERTY (G&W)          |
| JOB A60063 | LIQUIDATED DAMAGES PROCEDURE FOR BID LETTINGS                                          |
| JOB A60063 | LONGITUDINAL JOINT DENSITIES FOR ACHM SURFACE COURSES                                  |
| JOB A60063 | LOOP WIRING REVISION 1.4                                                               |
| JOB A60063 | MAINTENANCE OF TRAFFIC                                                                 |
| JOB A60063 | MANDATORY ELECTRONIC CONTRACT                                                          |
| JOB A60063 | MANDATORY ELECTRONIC DOCUMENT SUBMITTAL                                                |
| JOB A60063 | PRICE ADJUSTMENT FOR ASPHALT BINDER                                                    |
| JOB A60063 | PRICE ADJUSTMENT FOR FUEL                                                              |
| JOB A60063 | PRIME CONTRACTOR PERFORMANCE EVALUATION                                                |
| JOB A60063 | PROHIBITION OF CERTAIN TELECOMMUNICATIONS AND VIDEO SURVEILLANCE SERVICES OR EQUIPMENT |
| JOB A60063 | ROADWAY CONSTRUCTION CONTROL - PAVEMENT PRESERVATION                                   |
| JOB A60063 | SUBMISSION OF ASPHALT CONCRETE HOT MIX ACCEPTANCE TEST RESULTS                         |
| JOB A60063 | SURFACE-APPLIED DETECTABLE WARNING PANELS                                              |
| JOB A60063 | VENDOR REGISTRATION REQUIREMENT                                                        |
| JOB A60063 | WARM MIX ASPHALT                                                                       |
| JOB A60063 | WATER POLLUTION CONTROL                                                                |


JOB NO. A60063

SHEET 3 OF 16  
GOVERNING SPECIFICATIONS


## GENERAL NOTES

1. THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING U. S. MAILBOXES WITHIN THE PROJECT LIMITS IN SUCH A MANNER THAT THE PUBLIC MAY RECEIVE CONTINUED MAIL SERVICE. PAYMENT WILL BE CONSIDERED INCLUDED IN THE PRICE BID FOR THE VARIOUS BID ITEMS.
2. ALL LAND MONUMENTS LOCATED WITHIN THE CONSTRUCTION AREA SHALL BE PROTECTED IN ACCORDANCE WITH SECTION 107.12 OF THE STANDARD SPECIFICATIONS.
3. THE CONTRACTOR SHALL PROVIDE 2-WAY RADIO COMMUNICATIONS FOR FLAG PERSONS.
4. THE CONTRACTOR SHALL FURNISH AND MAINTAIN STD. W8-1 "BUMP" SIGNS (30" X 30") WITH BLACK LEGEND ON ORANGE BACKGROUND AT ALL TRANSVERSE JOINTS EXPOSED TO TRAFFIC.
5. THE CONTRACTOR SHALL FURNISH AND MAINTAIN STD. W8-11 "UNEVEN LANES" SIGNS (48" X 48") WITH BLACK LEGEND ON ORANGE BACKGROUND AT ALL LONGITUDINAL JOINTS DURING MILLING AND PAVING OPERATIONS.
6. PRIOR TO OVERLAYING THE SHOULDERS AND DRIVING LANES, ALL UTILITY MANHOLES SHALL BE ADJUSTED TO MATCH THE FINAL SURFACE GRADE. THE ADJUSTMENT OF GRADE FOR UTILITY MANHOLES WILL NOT BE PAID DIRECTLY, BUT COMPENSATION SHALL BE CONSIDERED INCLUDED IN THE BID PRICES FOR THE CONTRACT'S PAY ITEMS.
7. UNLESS OTHERWISE NOTED, 85% OF MATERIAL GENERATED FROM COLD MILLING OPERATIONS SHALL BE RETAINED BY THE CONTRACTOR. THE CONTRACTOR SHALL STOCKPILE THE REMAINING 15% OF MATERIAL, FOR THE COUNTY, IN WHICH THE PROJECT IS LOCATED. NO DIRECT PAYMENT WILL BE MADE FOR LOADING, HAULING, AND STOCKPILING OF EXCESS MILLING MATERIAL; PAYMENT WILL BE CONSIDERED INCLUDED IN THE PRICE BID FOR COLD MILLING ASPHALT PAVEMENT. COLD MILLING SHALL BE STOCKPILED IN A TRAPEZOIDAL SHAPE, OR AS DIRECTED BY THE ENGINEER, WHICH CAN BE EASILY MEASURED.
8. TRAFFIC WILL BE PERMITTED TO TRAVEL ON MILLED SURFACES UP TO A MAXIMUM OF 48 HOURS. CONTRACTOR WILL BE RESPONSIBLE TO MAINTAIN POSITIVE DRAINAGE AT ALL TIMES.









5 LANE CURB & GUTTER INLAY  
LOG MILE 4.935 TO LOG MILE 5.090




5 LANE CURB & GUTTER W/ SHOULDER MILL & INLAY  
LOG MILE 5.090 TO LOG MILE 5.640




6 LANE CURB & GUTTER W/ SHOULDER MILL & INLAY  
LOG MILE 5.640 TO LOG MILE 5.928







### 5 LANE CURB & GUTTER INLAY



LOG MILE 7.013 TO LOG MILE 7.201  
LOG MILE 7.251 TO LOG MILE 7.435  
LOG MILE 7.675 TO LOG MILE 8.559  
LOG MILE 8.600 TO LOG MILE 8.968  
LOG MILE 9.970 TO LOG MILE 10.235








### 6 LANE CURB & GUTTER W/ SHOULDER MILL & INLAY

LOG MILE 7.201 TO LOG MILE 7.251







| LEGEND |                                                 |
|--------|-------------------------------------------------|
| •      | TRAIL VEHICLE                                   |
| ••     | SHADOW VEHICLE                                  |
| •••    | WORK VEHICLE                                    |
| ◻      | HEAVY WORK VEHICLE                              |
| ◻      | TRUCK MOUNTED ATTENUATOR (TMA)                  |
| ◁      | TRAFFIC FLOW                                    |
| ▶      | ADVANCE WARNING ARROW PANEL DISPLAY             |
| ◻      | RIGHT DIRECTIONAL                               |
| ◻      | LEFT DIRECTIONAL                                |
| ◻      | DOUBLE ARROW                                    |
| ◻      | CAUTION (ALTERNATING DIAMOND OR 4 CORNER FLASH) |

TYPICAL APPLICATION - MOBILE WORK ZONE

GENERAL NOTES:

1. TRAIL, SHADOW, AND LEAD VEHICLES SHALL BE EQUIPPED WITH ADVANCE WARNING ARROW PANELS AS ILLUSTRATED.
2. THE USE OF AMBER OR GREEN HIGH-INTENSITY ROTATING, FLASHING, OSCILLATING, OR STROBE LIGHTS ON ALL VEHICLES ARE REQUIRED. VEHICLE HAZARD WARNING SIGNALS SHALL NOT BE USED INSTEAD OF THE VEHICLE'S HIGH-INTENSITY ROTATING, FLASHING, OSCILLATING, OR STROBE LIGHTS.
3. THE USE OF TRUCK MOUNTED ATTENUATORS (TMA) ON THE SHADOW VEHICLE, ADVANCE WARNING AND TRAIL VEHICLE ARE REQUIRED.
4. EACH VEHICLE SHALL HAVE TWO-WAY RADIO COMMUNICATION CAPABILITY.
5. WHEN WORK CONVOYS MUST CHANGE LANES, THE TRAIL VEHICLE SHOULD CHANGE LANES FIRST TO SHADOW THE OTHER CONVOY VEHICLES. WHEN WORK CONVOY EXITS THE ROADWAY, THE TRAIL VEHICLE SHOULD EXIT LAST.
6. VEHICLE SPACING BETWEEN THE TRAIL VEHICLE AND THE SHADOW VEHICLE WILL VARY DEPENDING ON SIGHT DISTANCE RESTRICTIONS AND QUEUE LENGTHS. MOTORISTS APPROACHING THE CONVOY SHOULD BE ABLE TO SEE THE TRAIL VEHICLE IN TIME TO SLOW DOWN AND/OR CHANGE LANES AS THEY APPROACH THE TRAIL VEHICLE. VEHICLE SPACING BETWEEN THE WORK VEHICLE AND SHADOW VEHICLE AND VEHICLE SPACING BETWEEN THE WORK VEHICLE AND LEAD VEHICLE MAY VARY ACCORDING TO TERRAIN, WORK ACTIVITY AND OTHER FACTORS.
7. X VEHICLE CONVOY (WZ-2) OR WORK CONVOY (WZ-3) SIGNS SHALL BE USED ON TRAIL VEHICLES AND SHADOW VEHICLES AS SHOWN. AS AN OPTION 48" X 48" DIAMOND SHAPED WORK CONVOY (WZ-2A) OR X VEHICLE CONVOY (WZ-3A) SIGNS MAY BE USED WHERE ADEQUATE MOUNTING SPACE EXISTS. WHEN USED, THE X VEHICLE CONVOY SIGN SHALL HAVE THE NUMBER OF THE CONVOY VEHICLES DISPLAYED ON THE SIGN IN THE NUMBER DESIGNATION "X" LOCATION. THE X VEHICLE CONVOY SIGN SHALL NOT BE USED ON THE SHADOW VEHICLE.
8. FOR DIVIDED HIGHWAYS WITH TWO OR THREE LANES IN ONE DIRECTION, THE APPROPRIATE LEFT LANE CLOSED (WZ-W20-5L), RIGHT LANE CLOSED (WZ-W20-5R), OR CENTER LANE CLOSED (WZ-W20-5C) SIGN SHOULD BE USED ON THE ADVANCE WARNING VEHICLE. AS AN OPTION, A PORTABLE CHANGEABLE MESSAGE SIGN (PCMS) OR TRUCK MOUNTED CHANGEABLE MESSAGE SIGN (TMCMS) WITH A MINIMUM CHARACTER HEIGHT OF 12", AND DISPLAYING THE SAME LEGEND MAY BE SUBSTITUTED FOR THESE SIGNS. AN APPROPRIATE DIRECTIONAL ARROW DISPLAY, SIMULATING THE SIZE AND LEGIBILITY OF THE ADVANCE WARNING ARROW PANEL MAY BE USED IN THE SECOND PHASE OF THE PCMS/TMCMS MESSAGE. WHEN THIS IS DONE, THE ARROW BOARD WILL NOT BE REQUIRED ON THE ADVANCE WARNING VEHICLE.
9. A DOUBLE ARROW SHALL NOT BE DISPLAYED ON THE ADVANCE WARNING ARROW PANEL ON THE ADVANCE WARNING VEHICLE.
10. STANDARD DIAMOND SHAPE VERSIONS OF THE WZ SERIES SIGNS MAY BE USED AS AN OPTION IF THE RECTANGULAR SIGNS SHOWN ARE NOT AVAILABLE.
11. THE ADVANCE WARNING VEHICLE MAY STRADDLE THE EDGELINE WHEN SHOULDER WIDTH MAKES IT NECESSARY.
12. ON TWO-LANE TWO-WAY ROADWAYS, THE WORK AND PROTECTION VEHICLES SHOULD PULL OVER PERIODICALLY TO ALLOW MOTOR VEHICLE TRAFFIC TO PASS. A DO NOT PASS (R4-1) SIGN SHALL BE PLACED ON THE BACK OF THE REARMOST PROTECTION VEHICLE.
13. MOBILE WORK ZONE METHODS AS DEPICTED IN THIS STANDARD DRAWING SHALL BE UTILIZED ON ALL PROJECTS THAT INCLUDE INSTALLATION OR REMOVAL OF RAISED PAVEMENT MARKERS OR PAVEMENT MARKINGS UNLESS APPROVED BY THE ENGINEER ON PROJECTS LESS THAN 0.5 MILE IN LENGTH.
14. NO DIRECT PAYMENT WILL BE MADE FOR COMPLIANCE WITH THE METHODS DEPICTED IN THIS STANDARD DRAWING (WHICH INCLUDES ALL SIGNS, DEVICES, MATERIALS, LABOR, TOOLS, EQUIPMENT, AND INCIDENTALS NECESSARY TO COMPLY) BUT SHALL BE CONSIDERED SUBSIDIARY TO THE MAINTENANCE OF TRAFFIC PAY ITEM.

### CONSTRUCTION PAVEMENT MARKINGS AND PERMANENT PAVEMENT MARKINGS

| DESCRIPTION                                       | CONSTRUCTION<br>PAVEMENT<br>MARKINGS | RAISED PAVEMENT<br>MARKERS |           | THERMOPLASTIC PAVEMENT MARKING |        |       |       |                     |       |        |
|---------------------------------------------------|--------------------------------------|----------------------------|-----------|--------------------------------|--------|-------|-------|---------------------|-------|--------|
|                                                   |                                      | TYPE II                    | TYPE II   | 6"                             |        | 8"    | 24"   | RAILROAD<br>EMBLEMS | WORDS | ARROWS |
|                                                   |                                      | (WHITE/RED)                | (YEL/YEL) | WHITE                          | YELLOW | WHITE | WHITE |                     |       |        |
|                                                   | LIN. FT.                             | EACH                       | LIN. FT.  |                                |        |       |       |                     | EACH  | EACH   |
| CONSTRUCTION PAVEMENT MARKINGS                    | 106738                               |                            |           |                                |        |       |       |                     |       |        |
| RAISED PAVEMENT MARKERS TYPE II (WHITE/RED)       |                                      | 837                        |           |                                |        |       |       |                     |       |        |
| RAISED PAVEMENT MARKERS TYPE II (YEL/YEL)         |                                      |                            | 776       |                                |        |       |       |                     |       |        |
|                                                   |                                      |                            |           |                                |        |       |       |                     |       |        |
| THERMOPLASTIC PAVEMENT MARKING WHITE (6")         |                                      |                            |           | 38108                          |        |       |       |                     |       |        |
| THERMOPLASTIC PAVEMENT MARKING YELLOW (6")        |                                      |                            |           |                                | 68630  |       |       |                     |       |        |
| THERMOPLASTIC PAVEMENT MARKING WHITE (8")         |                                      |                            |           |                                |        | 1156  |       |                     |       |        |
| THERMOPLASTIC PAVEMENT MARKING WHITE (24")        |                                      |                            |           |                                |        |       | 4224  |                     |       |        |
| THERMOPLASTIC PAVEMENT MARKING (RAILROAD EMBLEMS) |                                      |                            |           |                                |        |       |       | 4                   |       |        |
| THERMOPLASTIC PAVEMENT MARKING (WORDS)            |                                      |                            |           |                                |        |       |       |                     | 42    |        |
| THERMOPLASTIC PAVEMENT MARKING (ARROWS)           |                                      |                            |           |                                |        |       |       |                     |       | 51     |
|                                                   |                                      |                            |           |                                |        |       |       |                     |       |        |
| TOTALS:                                           | 106738                               | 837                        | 776       | 38108                          | 68630  | 1156  | 4224  | 4                   | 42    | 51     |

NOTE: THIS IS A HIGH TRAFFIC VOLUME ROAD AS DEFINED IN SECTION 604.03, STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION.

NOTE: THE 6" YELLOW STRIPING QUANTITY HAS BEEN ESTIMATED BASED ON A DOUBLE YELLOW CENTERLINE STRIPE FOR THE ENTIRE PROJECT.

THE PROJECT MUST BE MARKED FOR PASSING/NO PASSING ZONES PRIOR TO THE PLACEMENT OF ANY FINAL STRIPING.

CONTACT THE MAINTENANCE DIVISION AFTER THE FINAL LIFT OF SURFACE COURSE HAS BEEN PLACED TO SCHEDULE THE ZONING OF THE PROJECT.

### ADVANCE WARNING SIGNS AND DEVICES

| SIGN<br>NUMBER | DESCRIPTION                                          | SIGN SIZE | TOTAL SIGNS REQUIRED |               |
|----------------|------------------------------------------------------|-----------|----------------------|---------------|
|                |                                                      |           | NO.                  | SQ. FT.       |
| R2-6aP         | FINES DOUBLE WHEN WORKERS ARE PRESENT                | 48"x36"   | 2                    | 24.0          |
| W20-1          | ROAD WORK 1500 FT.                                   | 48"x48"   | 2                    | 32.0          |
| W20-1          | ROAD WORK 1000 FT.                                   | 48"x48"   | 2                    | 32.0          |
| W20-1          | ROAD WORK 500 FT.                                    | 48"x48"   | 2                    | 32.0          |
| W20-1          | ROAD WORK AHEAD                                      | 48"x48"   | 59                   | 944.0         |
| G20-2          | END ROAD WORK                                        | 48"x24"   | 57                   | 456.0         |
| G20-1          | ROAD WORK NEXT xx MILES                              | 60"x24"   | 2                    | 20.0          |
| WZ-4           | STATE LAW NO HAND-HELD PHONE USE BY DRIVER WORK ZONE | 36"x54"   | 2                    | 27.0          |
|                |                                                      |           |                      |               |
|                |                                                      |           |                      |               |
| <b>TOTAL:</b>  |                                                      |           |                      | <b>1567.0</b> |

NOTE: THIS IS A HIGH TRAFFIC VOLUME ROAD AS DEFINED IN SECTION 604.03, STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION.

**BASE AND SURFACING**

| LOG MILE   | LOG MILE | LOCATION                                                                             | LENGTH  | TACK COAT |           |                   |          | ACHM SURFACE COURSE (1/2") |           |                 |          |
|------------|----------|--------------------------------------------------------------------------------------|---------|-----------|-----------|-------------------|----------|----------------------------|-----------|-----------------|----------|
|            |          |                                                                                      |         | AVG. WID. | SQ. YD.   | GALLONS / SQ. YD. | GALLON   | AVG. WID.                  | SQ. YD.   | POUND / SQ. YD. | PG 76-22 |
|            |          |                                                                                      | FEET    | FEET      |           |                   |          | FEET                       |           |                 | TON      |
| MAIN LANES |          |                                                                                      |         |           |           |                   |          |                            |           |                 |          |
| 4.369      | 4.780    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 2170.08 | 72.00     | 17360.64  | 0.17              | 2951.31  | 72.00                      | 17360.64  | 220.00          | 1909.67  |
| 4.780      | 4.905    | HWY. 7 SEC. 9 MILL AND INLAY                                                         | 660.00  | 70.00     | 5133.33   | 0.17              | 872.67   | 70.00                      | 5133.33   | 220.00          | 564.67   |
| 4.905      | 4.935    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 158.40  | 66.00     | 1161.60   | 0.17              | 197.47   | 66.00                      | 1161.60   | 220.00          | 127.78   |
| 4.935      | 5.090    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 818.40  | 56.00     | 5092.27   | 0.17              | 865.69   | 56.00                      | 5092.27   | 220.00          | 560.15   |
| 5.090      | 5.446    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 1879.68 | 74.00     | 15455.15  | 0.17              | 2627.38  | 74.00                      | 15455.15  | 220.00          | 1700.07  |
| 5.446      | 5.493    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (HIGDON FERRY INTERSECTION)           | 248.16  | 66.00     | 1819.84   | 0.17              | 309.37   | 66.00                      | 1819.84   | 220.00          | 200.18   |
| 5.493      | 5.640    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 776.16  | 68.00     | 5864.32   | 0.17              | 996.93   | 68.00                      | 5864.32   | 220.00          | 645.08   |
| 5.640      | 5.928    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 1520.64 | 74.00     | 12503.04  | 0.17              | 2125.52  | 74.00                      | 12503.04  | 220.00          | 1375.33  |
| 5.928      | 5.955    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (MALL ST. INTERSECTION)               | 142.56  | 80.00     | 1267.20   | 0.17              | 215.42   | 80.00                      | 1267.20   | 220.00          | 139.39   |
| 5.955      | 6.085    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 686.40  | 68.00     | 5186.13   | 0.17              | 881.64   | 68.00                      | 5186.13   | 220.00          | 570.47   |
| 6.085      | 6.106    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (TEMPERANCE HILL RD. INTERSECTION)    | 110.88  | 66.00     | 813.12    | 0.17              | 138.23   | 66.00                      | 813.12    | 220.00          | 89.44    |
| 6.106      | 6.437    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 1747.68 | 64.00     | 12427.95  | 0.17              | 2112.75  | 64.00                      | 12427.95  | 220.00          | 1367.07  |
| 6.437      | 6.524    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (LAKELAND DR./FILES RD. INTERSECTION) | 459.36  | 72.00     | 3674.88   | 0.17              | 624.73   | 72.00                      | 3674.88   | 220.00          | 404.24   |
| 6.524      | 6.730    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 1087.68 | 64.00     | 7734.61   | 0.17              | 1314.88  | 64.00                      | 7734.61   | 220.00          | 850.81   |
| 6.730      | 6.797    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (MEHTA CT./WALMART DR. INTERSECTION)  | 353.76  | 66.00     | 2594.24   | 0.17              | 441.02   | 66.00                      | 2594.24   | 220.00          | 285.37   |
| 6.797      | 6.842    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 237.60  | 60.00     | 1584.00   | 0.17              | 269.28   | 60.00                      | 1584.00   | 220.00          | 174.24   |
| 6.842      | 6.930    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 464.64  | 58.00     | 2994.35   | 0.17              | 509.04   | 58.00                      | 2994.35   | 220.00          | 329.38   |
| 6.930      | 6.982    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (BUENA VISTA RD. INTERSECTION)        | 274.56  | 72.00     | 2196.48   | 0.17              | 373.40   | 72.00                      | 2196.48   | 220.00          | 241.61   |
| 6.982      | 7.013    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 163.68  | 58.00     | 1054.83   | 0.17              | 179.32   | 58.00                      | 1054.83   | 220.00          | 116.03   |
| 7.013      | 7.201    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 992.64  | 50.00     | 5514.67   | 0.17              | 937.49   | 50.00                      | 5514.67   | 220.00          | 606.61   |
| 7.201      | 7.251    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (CORNERSTONE BLVD. INTERSECTION)      | 264.00  | 60.00     | 1760.00   | 0.17              | 299.20   | 60.00                      | 1760.00   | 220.00          | 193.60   |
| 7.251      | 7.435    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 971.52  | 50.00     | 5397.33   | 0.17              | 917.55   | 50.00                      | 5397.33   | 220.00          | 593.71   |
| 7.435      | 7.675    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (MLK BLVD. INTERCHANGE)               | 1267.20 | 66.00     | 9292.80   | 0.17              | 1579.78  | 66.00                      | 9292.80   | 220.00          | 1022.21  |
| 7.675      | 8.559    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 4667.52 | 50.00     | 25930.67  | 0.17              | 4408.21  | 50.00                      | 25930.67  | 220.00          | 2852.37  |
| 8.559      | 8.600    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (OAKLAWN RACING INTERSECTION)         | 216.48  | 52.00     | 1250.77   | 0.17              | 212.63   | 52.00                      | 1250.77   | 220.00          | 137.58   |
| 8.600      | 8.968    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 1943.04 | 50.00     | 10794.67  | 0.17              | 1835.09  | 50.00                      | 10794.67  | 220.00          | 1187.41  |
| 8.968      | 9.004    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 190.08  | 51.00     | 1077.12   | 0.17              | 183.11   | 51.00                      | 1077.12   | 220.00          | 118.48   |
| 9.004      | 9.262    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 1362.24 | 52.00     | 7870.72   | 0.17              | 1338.02  | 52.00                      | 7870.72   | 220.00          | 865.78   |
| 9.262      | 9.276    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (TRIVISTA ST. INTERSECTION)           | 73.92   | 51.00     | 418.88    | 0.17              | 71.21    | 51.00                      | 418.88    | 220.00          | 46.08    |
| 9.276      | 9.919    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 3395.04 | 52.00     | 19615.79  | 0.17              | 3334.68  | 52.00                      | 19615.79  | 220.00          | 2157.74  |
| 9.919      | 9.970    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 269.28  | 51.00     | 1525.92   | 0.17              | 259.41   | 51.00                      | 1525.92   | 220.00          | 167.85   |
| 9.970      | 10.235   | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 1399.20 | 50.00     | 7773.33   | 0.17              | 1321.47  | 50.00                      | 7773.33   | 220.00          | 855.07   |
| 10.235     | 10.245   | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (WEST GRAND AVE. INTERSECTION)        | 52.80   | 52.00     | 305.07    | 0.17              | 51.86    | 52.00                      | 305.07    | 220.00          | 33.56    |
| TOTALS:    |          |                                                                                      |         |           | 204445.72 |                   | 34755.76 |                            | 204445.72 |                 | 22489.03 |

**BASIS OF ESTIMATE:**

ACHM SURFACE COURSE (1/2").....94.3% MIN. AGGR.....5.7% ASPHALT BINDER

TACK COAT QUANTITIES WERE CALCULATED USING THE EMULSIFIED ASPHALT RATES. REFER TO SS-400-1 FOR THE RESIDUAL ASPHALT APPLICATION RATES.

# COLD MILLING ASPHALT PAVEMENT

| LOG MILE      | LOG MILE | LOCATION                                                                             | AVG. WIDTH | TOTAL LENGTH | COLD MILLING<br>ASPHALT PAVEMENT |
|---------------|----------|--------------------------------------------------------------------------------------|------------|--------------|----------------------------------|
|               |          |                                                                                      | FEET       | FEET         | SQ. YD.                          |
| 4.369         | 4.780    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 72.00      | 2170.08      | 17360.64                         |
| 4.780         | 4.905    | HWY. 7 SEC. 9 MILL AND INLAY                                                         | 70.00      | 660.00       | 5133.33                          |
| 4.905         | 4.935    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 66.00      | 158.40       | 1161.60                          |
| 4.935         | 5.090    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 56.00      | 818.40       | 5092.27                          |
| 5.090         | 5.446    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 74.00      | 1879.68      | 15455.15                         |
| 5.446         | 5.493    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (HIGDON FERRY INTERSECTION)           | 66.00      | 248.16       | 1819.84                          |
| 5.493         | 5.640    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 68.00      | 776.16       | 5864.32                          |
| 5.640         | 5.928    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 74.00      | 1520.64      | 12503.04                         |
| 5.928         | 5.955    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (MALL ST. INTERSECTION)               | 80.00      | 142.56       | 1267.20                          |
| 5.955         | 6.085    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 68.00      | 686.40       | 5186.13                          |
| 6.085         | 6.106    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (TEMPERANCE HILL RD. INTERSECTION)    | 66.00      | 110.88       | 813.12                           |
| 6.106         | 6.437    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 64.00      | 1747.68      | 12427.95                         |
| 6.437         | 6.524    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (LAKELAND DR./FILES RD. INTERSECTION) | 72.00      | 459.36       | 3674.88                          |
| 6.524         | 6.730    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 64.00      | 1087.68      | 7734.61                          |
| 6.730         | 6.797    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (MEHTA CT./WALMART DR. INTERSECTION)  | 66.00      | 353.76       | 2594.24                          |
| 6.797         | 6.842    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 60.00      | 237.60       | 1584.00                          |
| 6.842         | 6.930    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 58.00      | 464.64       | 2994.35                          |
| 6.930         | 6.982    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (BUENA VISTA RD. INTERSECTION)        | 72.00      | 274.56       | 2196.48                          |
| 6.982         | 7.013    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 58.00      | 163.68       | 1054.83                          |
| 7.013         | 7.201    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 50.00      | 992.64       | 5514.67                          |
| 7.201         | 7.251    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (CORNERSTONE BLVD. INTERSECTION)      | 60.00      | 264.00       | 1760.00                          |
| 7.251         | 7.435    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 50.00      | 971.52       | 5397.33                          |
| 7.435         | 7.675    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (MLK BLVD. INTERCHANGE)               | 66.00      | 1267.20      | 9292.80                          |
| 7.675         | 8.559    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 50.00      | 4667.52      | 25930.67                         |
| 8.559         | 8.600    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (OAKLAWN RACING INTERSECTION)         | 52.00      | 216.48       | 1250.77                          |
| 8.600         | 8.968    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 50.00      | 1943.04      | 10794.67                         |
| 8.968         | 9.004    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 51.00      | 190.08       | 1077.12                          |
| 9.004         | 9.262    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 52.00      | 1362.24      | 7870.72                          |
| 9.262         | 9.276    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (TRIVISTA ST. INTERSECTION)           | 51.00      | 73.92        | 418.88                           |
| 9.276         | 9.919    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 52.00      | 3395.04      | 19615.79                         |
| 9.919         | 9.970    | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 51.00      | 269.28       | 1525.92                          |
| 9.970         | 10.235   | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER)                                       | 50.00      | 1399.20      | 7773.33                          |
| 10.235        | 10.245   | HWY. 7 SEC. 9 MILL AND INLAY (CURB AND GUTTER) (WEST GRAND AVE. INTERSECTION)        | 52.00      | 52.80        | 305.07                           |
| <b>TOTAL:</b> |          |                                                                                      |            |              | <b>204445.72</b>                 |

NOTE: COORDINATE COLD MILLING STOCKPILE LOCATIONS WITH DISTRICT ENGINEER.  
 STOCKPILE LOCATIONS SHALL BE NO FARTHER THAN FIVE MILES FROM EACH SITE.  
 COLD MILLING DEPTH IS TYPICALLY 2". IN SPECIAL CIRCUMSTANCES ON THE PROJECT  
 THERE COULD BE LOCATIONS THAT NEED TO BE MILLED DEEPER TO INCREASE THE OPENINGS IN DROP INLETS.

## LOOP WIRING

| LOG MILE       | LOCATION                               | LOOP WIRING CLASS III<br>(1C/16 A.W.G.) |              | NON-METALLIC<br>2" CONDUIT | CONCRETE<br>PULL BOX<br>(TYPE 1 HD) |
|----------------|----------------------------------------|-----------------------------------------|--------------|----------------------------|-------------------------------------|
|                |                                        | FEEDER WIRE                             | LOOP WIRING  |                            |                                     |
|                |                                        | LIN. FT.                                | LIN.FT.      |                            |                                     |
| 6.093          | TEMPERANCE HILL RD. INTERSECTION       | 2180                                    | 5178         | 300                        | 4                                   |
| 6.779          | MEHTA CT./WALMART DR. INTERSECTION     | 2793                                    | 7201         | 310                        | 4                                   |
| 7.240          | CORNERSTONE BLVD. INTERSECTION         | 1804                                    | 3107         | 60                         | 1                                   |
| 8.456          | GOLF LINKS RD. INTERSECTION            | 1804                                    | 3107         | 415                        | 4                                   |
| 9.270          | TRIVISTA ST. INTERSECTION              | 2394                                    | 2799         | 120                        | 2                                   |
| 9.600          | GREENWOOD AVE./ALCORN ST. INTERSECTION | 3950                                    | 4029         | 265                        | 4                                   |
|                |                                        |                                         |              |                            |                                     |
|                |                                        |                                         |              |                            |                                     |
|                |                                        |                                         |              |                            |                                     |
|                |                                        |                                         |              |                            |                                     |
| <b>TOTALS:</b> |                                        | <b>14925</b>                            | <b>25421</b> | <b>1470</b>                | <b>19</b>                           |

QUANTITY ESTIMATED.

SEE SECTION 104.03 OF THE STD. SPECS.

TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER.

IF EXISTING PREFORMED LOOPS ARE DAMAGED DURING MILLING OPERATIONS AND/OR THEY ARE IN NEED OF REPLACEMENT, THEY ARE TO BE REPLACED AS DIRECTED BY THE ENGINEER.

DAMAGED LOOPS SHALL BE REPLACED PRIOR TO THE PLACEMENT OF THE FINAL ACHM SURFACE.

## ASPHALT CONCRETE PATCHING FOR MAINTENANCE OF TRAFFIC

| LOCATION                                                          | TON | TACK COAT |
|-------------------------------------------------------------------|-----|-----------|
|                                                                   |     | GALLON    |
| ENTIRE PROJECT - TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER | 147 | 294       |
|                                                                   |     |           |
| <b>TOTALS:</b>                                                    | 147 | 294       |

**BASIS OF ESTIMATE:**

|                                                           |              |
|-----------------------------------------------------------|--------------|
| ASPHALT CONCRETE PATCHING FOR MAINTENANCE OF TRAFFIC..... | 25 TON/MILE  |
| TACK COAT FOR MAINTENANCE OF TRAFFIC.....                 | 50 GAL./MILE |

## SURFACE-APPLIED DETECTABLE WARNING PANELS

| LOCATION                                                             | WARNING PANELS |               |
|----------------------------------------------------------------------|----------------|---------------|
|                                                                      | NO.            | SQ.FT.        |
| ENTIRE PROJECT - TO BE USED IF AND WHERE<br>DIRECTED BY THE ENGINEER | 265.0          | 2120.0        |
|                                                                      |                |               |
|                                                                      |                |               |
| <b>TOTALS:</b>                                                       | <b>265.0</b>   | <b>2120.0</b> |

NOTE: QUANTITY ESTIMATED.

SEE SECTION 104.03 OF THE STD. SPECS.


GROOVES IN SIDEWALK RAMPS SHALL BE FILLED WITH PANEL ADHESIVE TO ENSURE UNIFORM BONDING

### SUMMARY OF QUANTITIES


| ITEM NUMBER   | ITEM                                                    | QUANTITY | UNIT     |
|---------------|---------------------------------------------------------|----------|----------|
| SS & 401      | TACK COAT                                               | 35050    | GAL.     |
| SP, SS, & 407 | MINERAL AGGREGATE IN ACHM SURFACE COURSE (1/2")         | 21207    | TON      |
| SP, SS, & 407 | ASPHALT BINDER (PG 76-22) IN ACHM SURFACE COURSE (1/2") | 1282     | TON      |
| SP & 412      | COLD MILLING ASPHALT PAVEMENT                           | 204446   | SQ. YD.  |
| SP, SS, & 414 | ASPHALT CONCRETE PATCHING FOR MAINTENANCE OF TRAFFIC    | 147      | TON      |
| SP, SS, & 415 | ACHM PATCHING OF EXISTING ROADWAY                       | 500      | TON      |
| 601           | MOBILIZATION                                            | 1.00     | LUMP SUM |
| SP, SS, & 603 | MAINTENANCE OF TRAFFIC                                  | 1.00     | LUMP SUM |
| SS & 604      | SIGNS                                                   | 1567     | SQ. FT.  |
| 604           | CONSTRUCTION PAVEMENT MARKINGS                          | 106738   | LIN. FT. |
| SP & 635      | ROADWAY CONSTRUCTION CONTROL                            | 1.00     | LUMP SUM |
| SP            | SURFACE-APPLIED DETECTABLE WARNING PANELS               | 2120     | SQ. FT.  |
| SP            | LOOP WIRING CLASS III (1C/16 A.W.G.)                    | 25421    | LIN. FT. |
| 704           | FEEDER WIRE                                             | 14925    | LIN. FT. |
| 710           | NON-METALLIC CONDUIT (2")                               | 1470     | LIN. FT. |
| SP, SS, & 711 | CONCRETE PULL BOX (TYPE 1 HD)                           | 19       | EACH     |
| 719           | THERMOPLASTIC PAVEMENT MARKING WHITE (6")               | 38108    | LIN. FT. |
| 719           | THERMOPLASTIC PAVEMENT MARKING WHITE (8")               | 1156     | LIN. FT. |
| 719           | THERMOPLASTIC PAVEMENT MARKING WHITE (24")              | 4224     | LIN. FT. |
| 719           | THERMOPLASTIC PAVEMENT MARKING YELLOW (6")              | 68630    | LIN. FT. |
| 719           | THERMOPLASTIC PAVEMENT MARKING (WORDS)                  | 42       | EACH     |
| 719           | THERMOPLASTIC PAVEMENT MARKING (ARROWS)                 | 51       | EACH     |
| 719           | THERMOPLASTIC PAVEMENT MARKING (RAILROAD EMBLEMS)       | 4        | EACH     |
| 721           | RAISED PAVEMENT MARKERS (TYPE II)                       | 1613     | EACH     |
|               |                                                         |          |          |
|               |                                                         |          |          |

### REVISIONS


| DATE | REVISION | SHEET NUMBER |
|------|----------|--------------|
|      |          |              |
|      |          |              |
|      |          |              |
|      |          |              |
|      |          |              |
|      |          |              |
|      |          |              |
|      |          |              |
|      |          |              |
|      |          |              |
|      |          |              |
|      |          |              |
|      |          |              |
|      |          |              |



DETAIL FOR STATE HIGHWAY TURNOUTS  
(PAVEMENT PRESERVATION)



DETAIL FOR DRIVEWAY TURNOUTS  
(PAVEMENT PRESERVATION)




DETAIL FOR CITY STREET  
AND COUNTY ROAD TURNOUTS  
(PAVEMENT PRESERVATION)

NOTES:


1. TURNOUTS AND PRIVATE DRIVES SHALL BE MODIFIED WHERE NECESSARY TO MEET LOCAL CONDITIONS AS DIRECTED BY THE ENGINEER.
2. NORMAL ACHM SURFACE COURSE (1/2") (220 LBS PER SQ. YD.) SHALL BE USED ON DRIVEWAYS AND TURNOUTS UNLESS SHOWN OTHERWISE IN THE PLANS.
3. STATE HIGHWAY TURNOUTS SHALL BE PAVED TO THE BACK OF THE RADIUS.
4. CITY STREET AND COUNTY ROAD TURNOUTS SHALL BE PAVED TO THE RIGHT-OF-WAY LIMITS.

|          |                            |
|----------|----------------------------|
| 4-13-23  | REVISED PAVING AT TURNOUTS |
| 5-19-22  | ISSUED                     |
| DATE REV | DATE FILMED                |
|          | DESCRIPTION                |

ARKANSAS STATE HIGHWAY COMMISSION  
DETAILS OF DRIVEWAYS & STREET  
TURNOUTS (PAVEMENT PRESERVATION)  
STANDARD DRAWING DR-3




CONCRETE PAVEMENT




ASPHALT PAVEMENT


### BROKEN LINE STRIPING




SOLID LINE STRIPING ON CONCRETE PAVEMENT



SOLID LINE STRIPING ON ASPHALT PAVEMENT




ASPHALT PAVEMENT




CONCRETE PAVEMENT

### STRIPING AT ADJACENT NO PASSING LANES




YIELD LINE DETAIL



CROSSWALK AND STOP LINE DETAILS

- NOTES:
1. REFER TO THE STRIPING DETAILS FOR PAVEMENT MARKING LINE WIDTHS.
  2. THIS DRAWING SHALL BE USED IN CONJUNCTION WITH THE LATEST REVISED ADDITION OF THE "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES."
  3. RAISED PAVEMENT MARKERS SHALL BE PLACED ON AN 80 FEET SPACING UNLESS OTHERWISE SHOWN IN THE PLANS.

2" FOR ASPHALT OR CONCRETE PAVEMENT  
6" FOR BITUMINOUS SURFACE TREATMENT




PAVEMENT EDGE LINE MARKING

NOTE:  
THE RED LENS OF THE  
TYPE II R.P.M. SHALL  
FACE THE INCORRECT  
TRAFFIC MOVEMENT.

NOTE:  
DIMENSIONS SHOWN FOR RAISED PAVEMENT  
MARKERS ARE TYPICAL. THE CONTRACTOR  
MAY SUBSTITUTE SIMILAR MARKERS WITH  
THE APPROVAL OF THE ENGINEER. REQUESTING  
APPROVAL FOR SIMILAR MARKERS MAY BE  
MADE BY REFERRING TO THE ARDOT QUALIFIED  
PRODUCTS LIST.

TYPE II  
RED/CLEAR OR  
YELLOW/YELLOW

PRISMATIC REFLECTOR



DETAIL OF STANDARD  
RAISED PAVEMENT MARKERS

|                          |            |                         |
|--------------------------|------------|-------------------------|
| REV. NO.                 | 04-04-26   | NEW, PRESENTLY & STOP   |
|                          | 02-27-20   | LINE DETAILS            |
| REV. NO.                 | 06-01-17   | ADDED YIELD LINE DETAIL |
|                          | 05-12-16   | SPACING & NOTES         |
| REV. NO.                 | 04-12-13   | REVISED DETAIL OF       |
|                          | 04-12-13   | PAVEMENT MARKERS        |
| DATE                     | 04-09-2026 | DATE                    |
| REV.                     |            | REV.                    |
| DESCRIPTION              |            |                         |
| PAVEMENT MARKING DETAILS |            |                         |
| DATE EFFECTIVE           | 04-09-2026 | STANDARD DRAWING        |
|                          |            | PM-1                    |


# NOTES:

1. LOOPS WITH A PERIMETER GREATER THAN 40' SHALL HAVE TWO TURNS. LOOPS WITH A PERIMETER LESS THAN OR EQUAL TO 40' SHALL HAVE THREE TURNS, UNLESS OTHERWISE NOTED ON THE PLANS. QUADRUPOLE LOOPS SHALL BE TWO TURNS IN A (2-4-2 CONFIGURATION), UNLESS OTHERWISE NOTED ON THE PLANS.
2. LOOP AND FEEDER WIRE SHALL BE CONTINUOUS WITHOUT SPLICES EXCEPT AT THE LOOP/FEEDER WIRE SPlice AS SHOWN. SPLICES SHALL BE ROSIN SOLDERED AND WATERPROOFED WITH AN ACCEPTED SPlice KIT. A DRAIN WIRE SHALL BE GROUNDED IN THE CABINET AND INSULATED AT THE LOOP TO FEEDER WIRE SPlice.
3. THE LOOP TO FEEDER WIRE SPlice, THE FEEDER WIRE JACKET AND LOOP WIRE JACKET IN DUCT SHALL BE COMPLETELY SEALED AND WATERPROOFED.
4. THE CONTRACTOR MAY MAKE CONNECTIONS TO THE SIGNAL CABLE AND LOOP TO FEEDER WIRE CONNECTION AT THE TERMINAL STRIPS MOUNTED TO POLE INSIDE THE HAND HOLD COVER AS SHOWN IN DETAIL. HANDHOLE TERMINALS MUST BE EASILY ACCESSIBLE, BUT PROTECTED AGAINST ACCIDENTAL CONTACT. THE CONNECTION OF POWER CARRYING CIRCUITS MUST BE SEPARATED FROM LOOP OR LOGIC CIRCUITS. ALL CONNECTIONS TO TERMINAL STRIPS SHALL UTILIZE SPADE LUGS OR AS APPROVED BY THE ENGINEER.
5. EACH LOOP SHALL HAVE A SEPARATE "FEEDER WIRE" UNLESS OTHERWISE NOTED ON THE PLANS. ALL FEEDER WIRES SHALL BE LABELED AS TO LOOP NUMBER AS DESIGNATED ON THE PLANS.
6. ALL LOOP WIRE ENTERING CONCRETE PULL BOXES SHALL BE ENCLOSED IN CONDUIT. EACH LOOP WIRE SHALL ENTER CONCRETE PULL BOX OR POLE BASE THROUGH A SEPARATE PIECE OF ONE (1/25") INCH CONDUIT.
7. LOOP WIRE FROM LOOP TO CONDUIT IS NOT TWISTED. LOOP WIRE IN THE CONDUIT MUST BE TWISTED TWO TO FIVE TURNS PER FOOT.
8. "30-DAY PERFORMANCE TEST SHALL NOT COMMENCE UNTIL ALL LOOPS ARE TESTED BY THE CONTRACTOR, THEN APPROVED AND ACCEPTED BY THE ENGINEER, AND THE TESTING RECORDS HAVE BEEN SUBMITTED TO THE ENGINEER. THE WARRANTY PERIOD FOR LOOPS SHALL NOT COMMENCE UNTIL TESTED BY THE CONTRACTOR AND ACCEPTED BY THE ENGINEER. THE CONTRACTOR SHALL PERFORM TEST AND PROVIDE A RECORD TO THE ENGINEER AS LISTED IN THE LOOP DETECTOR TESTING PROCEDURE.
9. UNLESS OTHERWISE APPROVED BY THE ENGINEER, BACKER ROD SHALL BE INSTALLED IN SHORT SECTIONS SPACED NO MORE THAN 18" APART AND WEDGED INTO THE SLOT TO THE CABLE IN PLACE. CABLE SHALL BE TOTALLY ENCAPSULATED IN SEALER.
10. "HOT POUR" SEALER SHALL NOT ALLOW WITH 705-LOOP WIRING IN DUCT.
11. WHERE UNDERGROUND SPLICES OF SIGNAL CABLE ARE REQUIRED, CONNECTIONS SHALL BE SOLDERED AND COMPLETELY WATERPROOFED TO THE SATISFACTION OF THE ENGINEER. WATERPROOFING SHALL EXTEND A MINIMUM OF TWO (2") INCHES PAST THE SIGNAL CABLE JACKET AND SHALL COMPLETELY COVER ALL INDIVIDUAL CONDUCTORS OF THE SIGNAL CABLE. WATERPROOFING DOES NOT APPLY TO CONNECTIONS MADE IN POLE BASES.
12. THE CONTRACTOR SHALL CONNECT A SEPARATE NEUTRAL FOR EACH LOAD SWITCH REPRESENTED ON EACH SIGNAL POLE. ONLY ONE NEUTRAL IS REQUIRED FOR PEDESTRIAN SIGNALS. A SEPARATE 5C (TYPICAL) IS PROVIDED FOR PEDESTRIAN PUSH BUTTONS.
13. TRAFFIC CONTROLLER CABINET LAYOUT SHALL BE SUCH THAT IT IS NOT NECESSARY TO SHUT DOWN POWER TO REMOVE LOAD SWITCHES IN ORDER TO EASILY TEST OR MODIFY DETECTOR INPUTS TO THE CONTROLLER. THE CONTROLLER CABINET SHALL BE WIRED SUCH THAT THE POWER TO LOAD SWITCHES CANNOT BACKFEED TO THE LOAD SWITCH POWER BUSS DURING FLASH OPERATION.


## TYPICAL PROCEDURE FOR DETECTOR LOOP TESTING

1. DISCONNECT AND TEST CONTINUITY (< 10 OHMS) IF CONTINUITY IS BAD, GO TO TEST 3.
2. TEST INSULATION (@ 500 VOLT TEST > 10 MEG-OHM) IF TESTS 1 & 2 ARE GOOD, NO FURTHER TESTING IS NECESSARY. RECORDED RESULTS CONSIST OF TESTS 1 & 2 FROM CONTROL CABINET WITH FEEDER WIRE CONNECTED TO LOOP.
3. OPEN SPACE (DO NOT BREAK CONNECTION) REPEAT TEST 1 & 2 IF TEST 3 IS BAD, GO TO TEST 4.
4. BREAK SPlice, INSTALL JUMPER IN CABINET, REPEAT TESTS 1 & 2 SEPARATELY FOR FEEDER AND FOR LOOP.


FAILURES TYPICALLY RESULT FROM BROKEN WIRE IN PAVEMENT, FAULTY INSULATION OF LOOP OR FEEDER WIRE, OR POORLY INSULATED SPlice CONNECTION.



## TRENCHING DETAIL (FOR SAW CUT TRENCH IN ROADWAY)




NOTE: CONDUIT SHALL BE INSTALLED IN CURB AS SHOWN OR AS DIRECTED BY THE ENGINEER. THE END OF CONDUIT SHALL BE WATER-TIGHT.




ALTERNATE - WHEN INSTALLING PREFORMS ON SUBSTRATE, LEAD-INS MAY BE INSTALLED IN CONDUIT UNDERNEATH THE CURB AND GUTTER.

## LOOP DETECTOR INSTALLATION AND TESTING


### SERIES CONNECTED LOOPS




### HANDHOLE TERMINAL




### QUADRUPOLE LOOP



## TYPICAL INTERSECTION




## TRAFFIC SIGNAL PRE-EMPTION INTERFACE WIRING DIAGRAM



WHEN NECESSARY, USE A WOODEN STICK TO PUSH WIRE INTO SAWED SLOT.

## TYPICAL SECTIONS FOR PULSE AND PRESENCE LOOP DETECTORS






SPECIAL NOTE:  
IF FEEDER WIRE JACKET IS LEFT UNSEALED AND WATER IS ALLOWED TO ENTER JACKET, CONTRACTOR WILL BE REQUIRED TO REPLACE FEEDER WIRE AT NO COST TO DEPARTMENT.

|          |                                                      |        |                                   |
|----------|------------------------------------------------------|--------|-----------------------------------|
| 11-07-19 | REVISED NOTE 6 & TYPICAL FOR PRESENCE LOOP DETECTORS |        | ARKANSAS STATE HIGHWAY COMMISSION |
| 11-16-17 | REVISED NOTES                                        |        |                                   |
| 09-12-13 | ISSUED AS STANDARD DRAWING                           |        |                                   |
| 05-17-01 | REVISED                                              |        |                                   |
| 04-11-01 | REVISED                                              |        |                                   |
| 02-04-00 | REVISED PRE-EMPTION TEST SWITCH                      |        |                                   |
| 11-18-98 | REVISED NOTES                                        |        |                                   |
| 11-21-95 | ISSUED                                               |        |                                   |
| DATE     | REVISION                                             | FILMED |                                   |

## LOOP DETECTOR INSTALLATION

STANDARD DRAWING SD-4

|                                                                                                                                                                                    |                                                                                                                                                                                      |                                                                                                                                                                          |                                                                                                                                                                                              |                                                                                                                                                                           |                                                                                                                                                                                 |                                                                                                                                                                            |                                                                                                                                                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <div>RI-1</div> <div></div> <div>STANDARD 30"x30"<br/>EXPRESSWAY 36"x36"<br/>SPECIAL 48"x48"</div> | <div>RI-2</div> <div></div> <div>STD. 36"x36"x36"<br/>EXPWY. 48"x48"x48"<br/>FWY. 60"x60"x60"</div> | <div>R2-1</div> <div></div> <div>STD. 24"x30"<br/>EXPWY. 36"x48"<br/>FWY. 48"x60"</div> | <div>W3-5</div> <div></div> <div>STD. 36"x36"<br/>EXPWY. 48"x48"<br/>FWY. 48"x48"</div>                     | <div>W3-5a</div> <div></div> <div>STD. 36"x36"<br/>EXPWY. 48"x48"<br/>FWY. 48"x60"</div> | <div>R4-1</div> <div></div> <div>STD. 24"x30"<br/>EXPWY. 36"x48"<br/>FWY. 48"x60"</div>       | <div>R4-2</div> <div></div> <div>STD. 24"x30"<br/>EXPWY. 36"x48"<br/>FWY. 48"x60"</div> | <div>R2-6aP</div> <div></div> <div>48"x36"<br/><br/>* USE 6" C LETTERS<br/>** USE 4" D LETTERS</div> | <div>GENERAL NOTES:</div> <div><div>1. ALL TRAFFIC CONTROL DEVICES USED ON ROAD CONSTRUCTION SHALL CONFORM TO THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, LATEST EDITION, AND TO THE STANDARD HIGHWAY SIGNS, LATEST EDITION, OR AS APPROVED BY THE FEDERAL HIGHWAY ADMINISTRATION.</div><div>2. TRAFFIC CONTROL DEVICES SHALL BE SET UP JUST BEFORE THE START OF CONSTRUCTION OPERATIONS AND SHALL BE PROPERLY MAINTAINED DURING THE TIME SUCH CONDITIONS EXIST. THEY SHALL REMAIN IN PLACE ONLY AS LONG AS NEEDED AND REMOVED THEREAFTER.</div><div>3. EXISTING SIGNS AND CONSTRUCTION SIGNS SHALL BE KEPT IN PROPER POSITION, AND BE CLEAN AND LEGIBLE AT ALL TIMES. SIGNS THAT DO NOT APPLY TO EXISTING CONDITIONS SHALL BE REMOVED. SIGNS THAT ARE DAMAGED, DEFACED, OR THAT ACCUMULATE DIRT DURING CONSTRUCTION SHALL BE CLEANED, REPAIRED, OR REPLACED.</div><div>4. SIGNS ARE USUALLY MOUNTED ON A SINGLE POST, ALTHOUGH THOSE WIDER THAN 36" OR LARGER THAN 10 50 FT. SHALL BE MOUNTED ON TWO POSTS OR ABOVE A TYPE III BARRICADE.</div><div>5. SIGN POSTS DIRECT BURIED IN SOIL SHALL BE 2 LB. MINIMUM CHANNEL POST OR 4"x4" WOOD POSTS. CHANNEL POSTS SHALL BE PAINTED GREEN. WOOD POSTS SHALL BE PAINTED WHITE. ALL POSTS SHALL BE NEATLY CONSTRUCTED, AND SHALL BE REPLUMBED, CLEANED, OR REPAIRED AS NEEDED FOR THE DURATION OF THE JOB. THERE SHALL NOT BE MORE THAN 2 POSTS IN A 7' PATH FOR WOOD OR CHANNEL POSTS. ANY CHANNEL POST SPLICE SHALL BE IN ACCORDANCE WITH STANDARD DRAWING TC-3.</div><div>6. POST MOUNTED SIGNS IN RURAL AREAS SHALL BE CONSTRUCTED WITH THE NEAR EDGE OF THE SIGN FROM 6 TO 12 FEET FROM THE PAVEMENT EDGE. SIGNS IN URBAN AREAS AND BARRICADE MOUNTED SIGNS SHALL BE MOUNTED A MINIMUM OF 2 FEET FROM THE PAVEMENT EDGE.</div><div>7. ALL POST AND BARRICADE MOUNTED SIGNS MOUNTED IN URBAN AREAS SHALL BE MOUNTED A MINIMUM DISTANCE OF 7' FROM THE BOTTOM OF THE SIGN TO THE ROADWAY SURFACE. ALL POST AND BARRICADE MOUNTED SIGNS MOUNTED IN RURAL AREAS SHALL BE MOUNTED A MINIMUM DISTANCE OF 7' FROM THE BOTTOM OF THE SIGN TO THE ROADWAY SURFACE, EXCEPT A MINIMUM OF 6' SHALL BE USED WHEN MOUNTING AN ADVISORY SIGN BELOW A WARNING SIGN. TEMPORARY SIGNS MAY BE MOUNTED ON PORTABLE SUPPORTS FOR INTERMEDIATE TERM STATIONARY WORK CONDITIONS. THE SIGNS MINIMUM MOUNTING HEIGHT SHALL BE 5'. RETROREFLECTIVE DEVICES SHALL BE USED. TEMPORARY SIGNS MAY BE MOUNTED ON PORTABLE SUPPORTS FOR SHORT-TERM, SHORT DURATION, AND MOBILE CONDITIONS. THEY SHALL BE NO LESS THAN ONE (1) FOOT ABOVE THE TRAVELED WAY. LONG-TERM STATIONARY SIGNS SHALL BE DIRECT BURIED IN SOIL, UNLESS CONDITIONS NECESSITATE THE USE OF PORTABLE SIGNS, OR AS APPROVED BY THE ENGINEER. CONCRETE PADS, CONCRETE OR ROCK BALLAST, OR OTHER SOLID MATERIALS SHALL NOT BE UTILIZED WITH PORTABLE SIGN SUPPORTS.</div><div>8. FLAGGERS SHALL USE REFLECTORIZED STOP-SLOW PADDLES. FLAGS MAY BE USED ONLY FOR EMERGENCY SITUATIONS.</div><div>9. MOST OF THE SIGNS SHOWN ARE ORIENTED TO THE RIGHT. HOWEVER, THIS DOES NOT PRECLUDE THE USE OF MIRROR IMAGES OF THESE SIGNS WHERE THE REVERSE ORIENTATION MIGHT BETTER CONVEY TO MOTORISTS THE PROPER DIRECTION OF MOVEMENT.</div><div>10. R2-6aP PLAQUES SHALL BE MOUNTED BELOW AN APPLICABLE ADVANCE WARNING SIGN THAT IS LOCATED AT LEAST 1500' BUT NOT MORE THAN 1 MILE IN ADVANCE OF THE WORK ZONE. IF A SPEED LIMIT REDUCTION IS IN EFFECT, THE PLAQUE SHALL BE PLACED A MINIMUM OF 500' IN ADVANCE OF THE W3-5 'REDUCED SPEED AHEAD' SIGN. R2-5 SIGNS SHALL BE INSTALLED AT OR NEAR THE DOWNSTREAM END OF THE WORK ZONE. SEE STANDARD DRAWINGS TC-2, TC-3, AND TC-6 FOR TYPICAL PLACEMENT LOCATIONS.</div></div> <div>* NOTE: SUPPORTS FOR SIGNS, BARRICADES, AND VERTICAL PANELS THAT ARE DIFFERENT FROM THE REQUIREMENTS SHOWN IN NOTES 4 &amp; 5, BUT MEET THE REQUIREMENTS OF MANUAL FOR ASSESSING SAFETY HARDWARE (MASH), WILL BE ACCEPTED. COMPLIANCE WITH THE REQUIREMENTS OF MANUAL FOR ASSESSING SAFETY HARDWARE (MASH) IS REQUIRED FOR ALL PROJECTS.</div> |
| <div>R5-1</div> <div></div> <div>STD. 30"x30"<br/>EXPWY. 36"x36"<br/>SPECIAL 48"x48"</div>         | <div>R11-2</div> <div></div> <div>48"x30"</div>                                                     | <div>R11-3A</div> <div></div> <div>60"x30"</div>                                        | <div>R11-4</div> <div></div> <div>60"x30"</div>                                                             | <div>W21-5a</div> <div></div> <div>STD. 36"x36"<br/>FWY. 48"x48"</div>                   | <div>W1-1</div> <div></div> <div>STD. 36"x36"<br/>FWY. 48"x48"</div>                          | <div>W1-2</div> <div></div> <div>STD. 36"x36"<br/>FWY. 48"x48"</div>                    | <div>R2-11</div> <div></div> <div>36"x48"</div>                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <div>W1-3</div> <div></div> <div>STD. 48"x48"</div>                                               | <div>W1-4</div> <div></div> <div>STD. 48"x48"</div>                                                 | <div>W1-6</div> <div></div> <div>STD. 48"x24"<br/>SPECIAL 60"x30"</div>                 | <div>W1-8</div> <div></div> <div>STD. 18"x24"<br/>SPECIAL 24"x30"<br/>EXPWY. 30"x36"<br/>FWY. 36"x48"</div> | <div>W3-1</div> <div></div> <div>STD. 36"x36"<br/>SPECIAL 48"x48"</div>                  | <div>W3-2</div> <div></div> <div>STD. 36"x36"<br/>SPECIAL 48"x48"</div>                       | <div>W4-2</div> <div></div> <div>STD. 36"x36"<br/>FWY. 48"x48"</div>                    | <div>R56-1</div> <div></div> <div>STD. 18"x18"</div>                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <div>W5-1</div> <div></div> <div>STD. 36"x36"<br/>SPECIAL 48"x48"</div>                           | <div>W6-3</div> <div></div> <div>EXPWY. 36"x36"<br/>SPECIAL 48"x48"</div>                           | <div>W8-7</div> <div></div> <div>EXPWY. 36"x36"<br/>FWY. 48"x48"</div>                  | <div>W9-2</div> <div></div> <div>STD. 36"x36"<br/>FWY. 48"x48"</div>                                        | <div>W13-1</div> <div></div> <div>STD. 24"x24"</div>                                     | <div>W20-1</div> <div></div> <div>STD. 48"x48"</div>                                          | <div>W20-2</div> <div></div> <div>STD. 48"x48"</div>                                    | <div>W20-3</div> <div></div> <div>STD. 48"x48"</div>                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <div>W20-4</div> <div></div> <div>STD. 48"x48"</div>                                            | <div>W20-5</div> <div></div> <div>STD. 48"x48"</div>                                              | <div>W20-7a</div> <div></div> <div>STD. 36"x36"<br/>FWY. 48"x48"</div>                | <div>W21-2</div> <div></div> <div>STD. 30"x30"<br/>SPECIAL 36"x36"</div>                                  | <div>W21-5</div> <div></div> <div>STD. 30"x30"<br/>SPECIAL 36"x36"</div>               | <div>W24-1</div> <div></div> <div>STD. 36"x36"</div>                                        | <div>W1-4b</div> <div></div> <div>STD. 48"x48"</div>                                  |                                                                                                                                                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <div>W8-11</div> <div></div> <div>STD. 36"x36"<br/>FWY. 48"x48"</div>                           | <div>W8-9</div> <div></div> <div>STD. 36"x36"<br/>FWY. 48"x48"</div>                              | <div>G20-1</div> <div></div> <div>60"x24"</div>                                       | <div>G20-2</div> <div></div> <div>48"x24"</div>                                                           | <div>OM-3L OM-3R</div> <div></div> <div>12"x36"</div>                                  | <div>M4-9</div> <div></div> <div>STD. 30"x24"<br/>SPECIAL 48"x36"<br/>SPECIAL 60"x48"</div> | <div>M4-10</div> <div></div> <div>48"x18"</div>                                       |                                                                                                                                                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

08-14-2025  
REPLACES R55-1 WITH  
REVISED R55-1 &  
REVISED R55-2  
11-07-19  
REVISED FOR MSH  
& RELATED RSP-1  
04-13-17  
REVISED RSP-1  
11-19-16  
REVISED RSP-1  
09-02-15  
REVISED RSP-1  
12-15-11  
REVISED RSP-1

DESCRIPTION

DATE REV

DATE EFFECTIVE

08-14-2025




ARKANSAS STATE  
HIGHWAY COMMISSION

STANDARD TRAFFIC CONTROLS  
FOR HIGHWAY CONSTRUCTION


STANDARD DRAWING

TC-1


|                                                                                                                                   |  |  |  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|-----------------------------------------------------------------------------------------------------------------------------------|--|--|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>REPLACED RRS-1 WITH RRS-2, RRS-3, RRS-4, RRS-5, RRS-6, RRS-7, RRS-8, RRS-9, RRS-10, RRS-11 &amp; RRS-12. REVISED FOR MASH.</p> |  |  |  | <p>DELETED RSP-1 AND RSP-2. REVISED RSP-3, RSP-4, RSP-5, RSP-6, RSP-7, RSP-8, RSP-9, RSP-10, RSP-11, RSP-12, RSP-13, RSP-14, RSP-15, RSP-16, RSP-17, RSP-18, RSP-19, RSP-20, RSP-21, RSP-22, RSP-23, RSP-24, RSP-25, RSP-26, RSP-27, RSP-28, RSP-29, RSP-30, RSP-31, RSP-32, RSP-33, RSP-34, RSP-35, RSP-36, RSP-37, RSP-38, RSP-39, RSP-40, RSP-41, RSP-42, RSP-43, RSP-44, RSP-45, RSP-46, RSP-47, RSP-48, RSP-49, RSP-50, RSP-51, RSP-52, RSP-53, RSP-54, RSP-55, RSP-56, RSP-57, RSP-58, RSP-59, RSP-60, RSP-61, RSP-62, RSP-63, RSP-64, RSP-65, RSP-66, RSP-67, RSP-68, RSP-69, RSP-70, RSP-71, RSP-72, RSP-73, RSP-74, RSP-75, RSP-76, RSP-77, RSP-78, RSP-79, RSP-80, RSP-81, RSP-82, RSP-83, RSP-84, RSP-85, RSP-86, RSP-87, RSP-88, RSP-89, RSP-90, RSP-91, RSP-92, RSP-93, RSP-94, RSP-95, RSP-96, RSP-97, RSP-98, RSP-99, RSP-100, RSP-101, RSP-102, RSP-103, RSP-104, RSP-105, RSP-106, RSP-107, RSP-108, RSP-109, RSP-110, RSP-111, RSP-112, RSP-113, RSP-114, RSP-115, RSP-116, RSP-117, RSP-118, RSP-119, RSP-120, RSP-121, RSP-122, RSP-123, RSP-124, RSP-125, RSP-126, RSP-127, RSP-128, RSP-129, RSP-130, RSP-131, RSP-132, RSP-133, RSP-134, RSP-135, RSP-136, RSP-137, RSP-138, RSP-139, RSP-140, RSP-141, RSP-142, RSP-143, RSP-144, RSP-145, RSP-146, RSP-147, RSP-148, RSP-149, RSP-150, RSP-151, RSP-152, RSP-153, RSP-154, RSP-155, RSP-156, RSP-157, RSP-158, RSP-159, RSP-160, RSP-161, RSP-162, RSP-163, RSP-164, RSP-165, RSP-166, RSP-167, RSP-168, RSP-169, RSP-170, RSP-171, RSP-172, RSP-173, RSP-174, RSP-175, RSP-176, RSP-177, RSP-178, RSP-179, RSP-180, RSP-181, RSP-182, RSP-183, RSP-184, RSP-185, RSP-186, RSP-187, RSP-188, RSP-189, RSP-190, RSP-191, RSP-192, RSP-193, RSP-194, RSP-195, RSP-196, RSP-197, RSP-198, RSP-199, RSP-200, RSP-201, RSP-202, RSP-203, RSP-204, RSP-205, RSP-206, RSP-207, RSP-208, RSP-209, RSP-210, RSP-211, RSP-212, RSP-213, RSP-214, RSP-215, RSP-216, RSP-217, RSP-218, RSP-219, RSP-220, RSP-221, RSP-222, RSP-223, RSP-224, RSP-225, RSP-226, RSP-227, RSP-228, RSP-229, RSP-230, RSP-231, RSP-232, RSP-233, RSP-234, RSP-235, RSP-236, RSP-237, RSP-238, RSP-239, RSP-240, RSP-241, RSP-242, RSP-243, RSP-244, RSP-245, RSP-246, RSP-247, RSP-248, RSP-249, RSP-250, RSP-251, RSP-252, RSP-253, RSP-254, RSP-255, RSP-256, RSP-257, RSP-258, RSP-259, RSP-260, RSP-261, RSP-262, RSP-263, RSP-264, RSP-265, RSP-266, RSP-267, RSP-268, RSP-269, RSP-270, RSP-271, RSP-272, RSP-273, RSP-274, RSP-275, RSP-276, RSP-277, RSP-278, RSP-279, RSP-280, RSP-281, RSP-282, RSP-283, RSP-284, RSP-285, RSP-286, RSP-287, RSP-288, RSP-289, RSP-290, RSP-291, RSP-292, RSP-293, RSP-294, RSP-295, RSP-296, RSP-297, RSP-298, RSP-299, RSP-300, RSP-301, RSP-302, RSP-303, RSP-304, RSP-305, RSP-306, RSP-307, RSP-308, RSP-309, RSP-310, RSP-311, RSP-312, RSP-313, RSP-314, RSP-315, RSP-316, RSP-317, RSP-318, RSP-319, RSP-320, RSP-321, RSP-322, RSP-323, RSP-324, RSP-325, RSP-326, RSP-327, RSP-328, RSP-329, RSP-330, RSP-331, RSP-332, RSP-333, RSP-334, RSP-335, RSP-336, RSP-337, RSP-338, RSP-339, RSP-340, RSP-341, RSP-342, RSP-343, RSP-344, RSP-345, RSP-346, RSP-347, RSP-348, RSP-349, RSP-350, RSP-351, RSP-352, RSP-353, RSP-354, RSP-355, RSP-356, RSP-357, RSP-358, RSP-359, RSP-360, RSP-361, RSP-362, RSP-363, RSP-364, RSP-365, RSP-366, RSP-367, RSP-368, RSP-369, RSP-370, RSP-371, RSP-372, RSP-373, RSP-374, RSP-375, RSP-376, RSP-377, RSP-378, RSP-379, RSP-380, RSP-381, RSP-382, RSP-383, RSP-384, RSP-385, RSP-386, RSP-387, RSP-388, RSP-389, RSP-390, RSP-391, RSP-392, RSP-393, RSP-394, RSP-395, RSP-396, RSP-397, RSP-398, RSP-399, RSP-400, RSP-401, RSP-402, RSP-403, RSP-404, RSP-405, RSP-406, RSP-407, RSP-408, RSP-409, RSP-410, RSP-411, RSP-412, RSP-413, RSP-414, RSP-415, RSP-416, RSP-417, RSP-418, RSP-419, RSP-420, RSP-421, RSP-422, RSP-423, RSP-424, RSP-425, RSP-426, RSP-427, RSP-428, RSP-429, RSP-430, RSP-431, RSP-432, RSP-433, RSP-434, RSP-435, RSP-436, RSP-437, RSP-438, RSP-439, RSP-440, RSP-441, RSP-442, RSP-443, RSP-444, RSP-445, RSP-446, RSP-447, RSP-448, RSP-449, RSP-450, RSP-451, RSP-452, RSP-453, RSP-454, RSP-455, RSP-456, RSP-457, RSP-458, RSP-459, RSP-460, RSP-461, RSP-462, RSP-463, RSP-464, RSP-465, RSP-466, RSP-467, RSP-468, RSP-469, RSP-470, RSP-471, RSP-472, RSP-473, RSP-474, RSP-475, RSP-476, RSP-477, RSP-478, RSP-479, RSP-480, RSP-481, RSP-482, RSP-483, RSP-484, RSP-485, RSP-486, RSP-487, RSP-488, RSP-489, RSP-490, RSP-491, RSP-492, RSP-493, RSP-494, RSP-495, RSP-496, RSP-497, RSP-498, RSP-499, RSP-500, RSP-501, RSP-502, RSP-503, RSP-504, RSP-505, RSP-506, RSP-507, RSP-508, RSP-509, RSP-510, RSP-511, RSP-512, RSP-513, RSP-514, RSP-515, RSP-516, RSP-517, RSP-518, RSP-519, RSP-520, RSP-521, RSP-522, RSP-523, RSP-524, RSP-525, RSP-526, RSP-527, RSP-528, RSP-529, RSP-530, RSP-531, RSP-532, RSP-533, RSP-534, RSP-535, RSP-536, RSP-537, RSP-538, RSP-539, RSP-540, RSP-541, RSP-542, RSP-543, RSP-544, RSP-545, RSP-546, RSP-547, RSP-548, RSP-549, RSP-550, RSP-551, RSP-552, RSP-553, RSP-554, RSP-555, RSP-556, RSP-557, RSP-558, RSP-559, RSP-560, RSP-561, RSP-562, RSP-563, RSP-564, RSP-565, RSP-566, RSP-567, RSP-568, RSP-569, RSP-570, RSP-571, RSP-572, RSP-573, RSP-574, RSP-575, RSP-576, RSP-577, RSP-578, RSP-579, RSP-580, RSP-581, RSP-582, RSP-583, RSP-584, RSP-585, RSP-586, RSP-587, RSP-588, RSP-589, RSP-590, RSP-591, RSP-592, RSP-593, RSP-594, RSP-595, RSP-596, RSP-597, RSP-598, RSP-599, RSP-600, RSP-601, RSP-602, RSP-603, RSP-604, RSP-605, RSP-606, RSP-607, RSP-608, RSP-609, RSP-610, RSP-611, RSP-612, RSP-613, RSP-614, RSP-615, RSP-616, RSP-617, RSP-618, RSP-619, RSP-620, RSP-621, RSP-622, RSP-623, RSP-624, RSP-625, RSP-626, RSP-627, RSP-628, RSP-629, RSP-630, RSP-631, RSP-632, RSP-633, RSP-634, RSP-635, RSP-636, RSP-637, RSP-638, RSP-639, RSP-640, RSP-641, RSP-642, RSP-643, RSP-644, RSP-645, RSP-646, RSP-647, RSP-648, RSP-649, RSP-650, RSP-651, RSP-652, RSP-653, RSP-654, RSP-655, RSP-656, RSP-657, RSP-658, RSP-659, RSP-660, RSP-661, RSP-662, RSP-663, RSP-664, RSP-665, RSP-666, RSP-667, RSP-668, RSP-669, RSP-670, RSP-671, RSP-672, RSP-673, RSP-674, RSP-675, RSP-676, RSP-677, RSP-678, RSP-679, RSP-680, RSP-681, RSP-682, RSP-683, RSP-684, RSP-685, RSP-686, RSP-687, RSP-688, RSP-689, RSP-690, RSP-691, RSP-692, RSP-693, RSP-694, RSP-695, RSP-696, RSP-697, RSP-698, RSP-699, RSP-700, RSP-701, RSP-702, RSP-703, RSP-704, RSP-705, RSP-706, RSP-707, RSP-708, RSP-709, RSP-710, RSP-711, RSP-712, RSP-713, RSP-714, RSP-715, RSP-716, RSP-717, RSP-718, RSP-719, RSP-720, RSP-721, RSP-722, RSP-723, RSP-724, RSP-725, RSP-726, RSP-727, RSP-728, RSP-729, RSP-730, RSP-731, RSP-732, RSP-733, RSP-734, RSP-735, RSP-736, RSP-737, RSP-738, RSP-739, RSP-740, RSP-741, RSP-742, RSP-743, RSP-744, RSP-745, RSP-746, RSP-747, RSP-748, RSP-749, RSP-750, RSP-751, RSP-752, RSP-753, RSP-754, RSP-755, RSP-756, RSP-757, RSP-758, RSP-759, RSP-760, RSP-761, RSP-762, RSP-763, RSP-764, RSP-765, RSP-766, RSP-767, RSP-768, RSP-769, RSP-770, RSP-771, RSP-772, RSP-773, RSP-774, RSP-775, RSP-776, RSP-777, RSP-778, RSP-779, RSP-780, RSP-781, RSP-782, RSP-783, RSP-784, RSP-785, RSP-786, RSP-787, RSP-788, RSP-789, RSP-790, RSP-791, RSP-792, RSP-793, RSP-794, RSP-795, RSP-796, RSP-797, RSP-798, RSP-799, RSP-800, RSP-801, RSP-802, RSP-803, RSP-804, RSP-805, RSP-806, RSP-807, RSP-808, RSP-809, RSP-810, RSP-811, RSP-812, RSP-813, RSP-814, RSP-815, RSP-816, RSP-817, RSP-818, RSP-819, RSP-820, RSP-821, RSP-822, RSP-823, RSP-824, RSP-825, RSP-826, RSP-827, RSP-828, RSP-829, RSP-830, RSP-831, RSP-832, RSP-833, RSP-834, RSP-835, RSP-836, RSP-837, RSP-838, RSP-839, RSP-840, RSP-841, RSP-842, RSP-843, RSP-844, RSP-845, RSP-846, RSP-847, RSP-848, RSP-849, RSP-850, RSP-851, RSP-852, RSP-853, RSP-854, RSP-855, RSP-856, RSP-857, RSP-858, RSP-859, RSP-860, RSP-861, RSP-862, RSP-863, RSP-864, RSP-865, RSP-866, RSP-867, RSP-868, RSP-869, RSP-870, RSP-871, RSP-872, RSP-873, RSP-874, RSP-875, RSP-876, RSP-877, RSP-878, RSP-879, RSP-880, RSP-881, RSP-882, RSP-883, RSP-884, RSP-885, RSP-886, RSP-887, RSP-888, RSP-889, RSP-890, RSP-891, RSP-892, RSP-893, RSP-894, RSP-895, RSP-896, RSP-897, RSP-898, RSP-899, RSP-900, RSP-901, RSP-902, RSP-903, RSP-904, RSP-905, RSP-906, RSP-907, RSP-908, RSP-909, RSP-910, RSP-911, RSP-912, RSP-913, RSP-914, RSP-915, RSP-916, RSP-917, RSP-918, RSP-919, RSP-920, RSP-921, RSP-922, RSP-923, RSP-924, RSP-925, RSP-926, RSP-927, RSP-928, RSP-929, RSP-930, RSP-931, RSP-932, RSP-933, RSP-934, RSP-935, RSP-936, RSP-937, RSP-938, RSP-939, RSP-940, RSP-941, RSP-942, RSP-943, RSP-944, RSP-945, RSP-946, RSP-947, RSP-948, RSP-949, RSP-950, RSP-951, RSP-952, RSP-953, RSP-954, RSP-955, RSP-956, RSP-957, RSP-958, RSP-959, RSP-960, RSP-961, RSP-962, RSP-963, RSP-964, RSP-965, RSP-966, RSP-967, RSP-968, RSP-969, RSP-970, RSP-971, RSP-972, RSP-973, RSP-974, RSP-975, RSP-976, RSP-977, RSP-978, RSP-979, RSP-980, RSP-981, RSP-982, RSP-983, RSP-984, RSP-985, RSP-986, RSP-987, RSP-988, RSP-989, RSP-990, RSP-991, RSP-992, RSP-993, RSP-994, RSP-995, RSP-996, RSP-997, RSP-998, RSP-999, RSP-1000, RSP-1001, RSP-1002, RSP-1003, RSP-1004, RSP-1005, RSP-1006, RSP-1007, RSP-1008, RSP-1009, RSP-1010, RSP-1011, RSP-1012, RSP-1013, RSP-1014, RSP-1015, RSP-1016, RSP-1017, RSP-1018, RSP-1019, RSP-1020, RSP-1021, RSP-1022, RSP-1023, RSP-1024, RSP-1025, RSP-1026, RSP-1027, RSP-1028, RSP-1029, RSP-1030, RSP-1031, RSP-1032, RSP-1033, RSP-1034, RSP-1035, RSP-1036, RSP-1037, RSP-1038, RSP-1039, RSP-1040, RSP-1041, RSP-1042, RSP-1043, RSP-1044, RSP-1045, RSP-1046, RSP-1047, RSP-1048, RSP-1049, RSP-1050, RSP-1051, RSP-1052, RSP-1053, RSP-1054, RSP-1055, RSP-1056, RSP-1057, RSP-1058, RSP-1059, RSP-1060, RSP-1061, RSP-1062, RSP-1063, RSP-1064, RSP-1065, RSP-1066, RSP-1067, RSP-1068, RSP-1069, RSP-1070, RSP-1071, RSP-1072, RSP-1073, RSP-1074, RSP-1075, RSP-1076, RSP-1077, RSP-1078, RSP-1079, RSP-1080, RSP-1081, RSP-1082, RSP-1083, RSP-1084, RSP-1085, RSP-1086, RSP-1087, RSP-1088, RSP-1089, RSP-1090, RSP-1091, RSP-1092, RSP-1093, RSP-1094, RSP-1095, RSP-1096, RSP-1097, RSP-1098, RSP-1099, RSP-1100, RSP-1101, RSP-1102, RSP-1103, RSP-1104, RSP-1105, R</p> |
|-----------------------------------------------------------------------------------------------------------------------------------|--|--|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|




WZ-4 (INTERSTATE) SIGN




WZ-4 (NON-INTERSTATE) SIGN




WZ-2 SIGN



WZ-3 SIGN




WZ-W20-5L SIGN



WZ-W20-5R SIGN


NOTE: REFER TO STANDARD DRAWING TC-1 FOR GENERAL NOTES.



CONSTRUCTION PROJECT INFORMATION SIGN




WZ-1 (INTERSTATE) SIGN




WZ-W20-5C SIGN

MOBILE WORK ZONE SIGNS


| DATE                                               |                  | DESCRIPTION |
|----------------------------------------------------|------------------|-------------|
| 04-09-2026                                         | ISSUED           |             |
| 04-09-2026                                         | REV              |             |
| AR ARKANSAS STATE HIGHWAY COMMISSION               |                  |             |
| STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION |                  |             |
| DATE EFFECTIVE                                     | STANDARD DRAWING | TC-1A       |
| 04-09-2026                                         |                  |             |




(A) TYPICAL APPLICATION OF TRAFFIC CONTROL DEVICES ON A 2-LANE HIGHWAY WHERE THE ENTIRE ROADWAY IS CLOSED AND A BYPASS DETOUR IS PROVIDED.




(B) TYPICAL APPLICATION - 4-LANE DIVIDED ROADWAY WHERE ONE ROADWAY IS CLOSED.




(C) TYPICAL APPLICATION - 4-LANE UNDIVIDED ROADWAY WHERE HALF OF THE ROADWAY IS CLOSED.





(D) TYPICAL APPLICATION - ROADWAY CLOSED BEYOND DETOUR POINT.



(E) TYPICAL APPLICATION OF TRAFFIC CONTROL DEVICES ON 2-LANE HIGHWAY WHERE ONE LANE IS CLOSED AND FLAGGING IS PROVIDED.





- 000 ARROW PANEL (IF REQUIRED)
- CHANNELIZING DEVICE
- TRAFFIC DRUM

GENERAL NOTES:

- (C) TYPICAL APPLICATION - CONSTRUCTION OPERATIONS OF INTERMEDIATE TO LONG TERM DURATION ON A 4-LANE DIVIDED ROADWAY WHERE HALF OF THE ROADWAY IS CLOSED.

**CONES**

18" MIN.

**TYPE I BARRICADE**

8" TO 12" 45° 2' MIN. 3' MIN.

**TYPE II BARRICADE**

8" TO 12" 45° 2' MIN. 3' MIN.

**TYPE III BARRICADE**

8" TO 12" 45° 6' 6" 5' MIN. 4' MIN.

**PLASTIC DRUM**

18" MIN. 36" APPROX. 4" TO 8"

**TUBULAR MARKERS**

RETROREFLECTIVE BAND 2" TO 3" 36" MIN.

**VERTICAL PANEL VP-IR**

12" 24" MIN. 36" MIN. 4" 45° WHITE ORANGE

**VERTICAL PANEL PLACEMENT**

36" MIN. ROADWAY SURFACE DROP OFF > 3'


**NOTES:**

- WHEN CONES ARE USED ON FREEWAYS AND MULTI-LANE HIGHWAYS THEY SHALL BE 28" MIN. DURING HOURS OF DARKNESS, 28" CONES SHALL BE USED ON ALL ROADWAYS AND SHALL BE REFLECTORIZED IN ACCORDANCE WITH THE M.U.T.C.D.
- FOR ALL ROAD CLOSURES, THE TYPE III BARRICADES SHALL BE OF SUFFICIENT LENGTH TO EXTEND ACROSS ENTIRE ROADWAY.
- SPACING = 2X POSTED SPEED LIMIT OR AS NOTED ON PLAN

- WHEN CONES ARE USED ON FREEWAYS AND MULTI-LANE HIGHWAYS, THEY SHALL BE 28" MIN. DURING HOURS OF DARKNESS, 28" CONES SHALL BE USED ON ALL ROADWAYS, AND SHALL BE REFLECTORIZED IN ACCORDANCE WITH THE M.U.T.C.D.

NOTE:  
FOR ALL ROAD CLOSURES, THE TYPE III BARRICADES  
SHALL BE OF SUFFICIENT LENGTH TO EXTEND  
ACROSS ENTIRE ROADWAY.


A REVIEW BY THE ROADWAY DESIGN DIVISION OF THE HIGHWAY DEPARTMENT WILL BE REQUIRED PRIOR TO IMPLEMENTING A MULTIPLE LANE CLOSURE.




| INTERSTATE AND NON-INTERSTATE |        |                           |
|-------------------------------|--------|---------------------------|
| FORESLOPE                     | HEIGHT | TRAFFIC CONTROL           |
| 1:1                           | > 2 FT | PRECAST CONCRETE BARRIERS |
| 2:1                           | ≤ 5 FT | TRAFFIC DRUMS             |
| 2:1                           | > 5 FT | PRECAST CONCRETE BARRIERS |
| Flatter than 2:1              | N/A    | TRAFFIC DRUMS             |

GENERAL NOTES:

1. WHEN THE SHOULDER AREA IS USED AS PART OF THE TRAVELLED LANE AND THERE IS INSUFFICIENT WIDTH FOR TRAFFIC DRUMS ON THE REMAINING SHOULDER WIDTH, TRAFFIC PANELS SHALL BE USED.
2. WHEN THERE IS INSUFFICIENT WIDTH TO PLACE TRAFFIC DRUMS ON THE REMAINING SHOULDER WIDTH, A STABILIZED WEDGE SHALL BE USED.
3. PRECAST CONCRETE BARRIER WALLS SHALL BE USED IN LIEU OF A STABILIZED WEDGE, WB-17 SIGN, EDGE LINE STRIPPING, AND TRAFFIC DRUMS.
4. WHERE THERE ARE PRECAST CONCRETE BARRIER WALLS, THE WALL SHALL BE DIRECTED BY THE ENGINEER.
5. W21-S, W21-S6, AND/OR W21-S6 SIGNS SHALL BE USED WHERE THE ROADWAY IS UNOBSTRUCTED.
6. WHERE THERE ARE OBSTRUCTIONS, THE TIME LIMITATIONS MUST CONFORM TO SECTION 603 OF THE STANDARD SPECIFICATIONS FOR CONSTRUCTION.




NOTE:  
MATERIALS FOR THE STABILIZED WEDGE  
SHALL MEET THE REQUIREMENTS PROVIDED  
IN SECTION 603.02 OF THE STANDARD SPECIFICATIONS



NOTES:  
USE SPLICES ONLY WHEN NECESSARY  
FOR INSTALLATION. TYPICAL INSTALLATION  
SHOULD HAVE NO SPLICES (SEE STD. DRAW  
NO. SHS-2)

NORMAL INSTALLATIONS WILL REQUIRE 1/4" DIA. BOLTS TO MOUNT SIGNS TO POST AND 5/16" DIA. BOLTS TO ASSEMBLE THE VARIOUS POST SUPPORTS. EACH OF THESE BOLTS SHALL BE CARRIAGE BOLTS.


SIGN POSTS SHALL BE PAINTED GREEN;  
SIGNALS SHALL NOT BE PAINTED.



ARKANSAS STATE  
HIGHWAY COMMISSION

## STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION

|                                   |                                 |                                                                                                                               |                                                       |      |
|-----------------------------------|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------|------|
| 08-14-25 DODGED R2-63" AND R2-11" | REVISED TRAFFIC CONTROL NOTES.  | <br>ARKANSAS STATE<br>HIGHWAY COMMISSION | STANDARD TRAFFIC CONTROLS<br>FOR HIGHWAY CONSTRUCTION | TC-3 |
| 05-22-20                          | REVISED TRAFFIC CONTROL NOTES   |                                                                                                                               |                                                       |      |
| 08-12-21                          | REVISED TRAFFIC CONTROL NOTES   |                                                                                                                               |                                                       |      |
| 05-20-21                          | REVISED TRAFFIC CONTROL NOTES   |                                                                                                                               |                                                       |      |
| 02-27-20                          | REVISED TRAFFIC CONTROL DETAILS |                                                                                                                               |                                                       |      |
| DATE                              | REV                             | DESCRIPTION                                                                                                                   |                                                       |      |
| DATE EFFECTIVE                    |                                 |                                                                                                                               |                                                       |      |
| 08-14-2025                        |                                 | STANDARD DRAWING                                                                                                              |                                                       | TC-3 |



NOTE : W20-1(VARIOUS DISTANCE) ADVANCE SIGNS  
TO BE REPLACED AS NEEDED BY EQUIVALENT W20-5 SIGNS  
AS WORKING AREA SHIFTS.

(A) TYPICAL APPLICATION - ADVANCE WARNING SIGNS AT BEGINNING AND  
END OF JOB (FULLY CONTROLLED ACCESS FACILITIES) (ALL STAGES)

\*SEE GENERAL NOTE 2


\*SEE GENERAL NOTE 2

(B) TYPICAL APPLICATION - ADVANCE WARNING SIGNS AT BEGINNING AND  
END OF JOB (NON-FULLY CONTROLLED ACCESS FACILITIES) (ALL STAGES)





GENERAL NOTES:

1. FLAGS MAY BE MOUNTED TO SIGNS AT NIGHT AS NEEDED.
2. THE G20-SIGN SHOULD BE INSTALLED ON JOBS OF OVER TWO MILES IN LENGTH WHEN THE LANE CLOSURE IS NOT AT THE BEGINNING OF THE PROJECT, THE G20-SIGN SHALL BE ERCTED 125' IN ADVANCE OF THE JOB LIMIT, ADDITIONAL 200' CLOSURE (OR 1500 FT) SIGNS ARE NOT REQUIRED IN THIS CASE. THE CLOSURE SHALL BE BEGUN INSIDE THE 200' CLOSURE. THE DISTANCE DISPLAYED ON THE G20-SIGN SHALL BE STATED TO THE NEAREST WHOLE MILE.
3. PORTABLE CHANGEABLE MESSAGE SIGNS SHALL BE DELINEATED BY AFFIXING CONSPICUITY MATERIAL IN A CONTINUOUS LINE ON THE FACE OF THE TRAILER, WHEN PLACED ON OR ADJACENT TO THE SHOULDER OF THE ROAD BEHIND A PORTABLE MESSAGE SIGNS, EACH SHALL BE DELINEATED BY PLACING FIVE (5) TRAFFIC DRUMS EQUALLY SPACED ALONG THE TRAFFIC SIDE OF THE DEVICE. PAYMENT FOR TRAFFIC DRUMS SHALL BE CONSIDERED INCLUDED IN THE PRICE BID FOR PORTABLE CHANGEABLE MESSAGE SIGNS.
4. PORTABLE CHANGEABLE MESSAGE SIGNS SHALL MEET THE REQUIREMENTS OF THE MANUAL FOR ASSESSING SAFETY HARDWARE (MASH).

\*SEE GENERAL NOTE 2




|                |                                                 |                                                                                                                               |                                                       |  |
|----------------|-------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------|--|
| 04-09-26       | CORRECTED WZ-4 SIGN DIMENSIONS                  | <br>ARKANSAS STATE<br>HIGHWAY COMMISSION | STANDARD TRAFFIC CONTROLS<br>FOR HIGHWAY CONSTRUCTION |  |
| 01-22-26       | QUOTED WZ-4 AND REVISED QUOTED WZ-4 NOTE        |                                                                                                                               |                                                       |  |
| 01-22-26       | REPLACED "SPEED" WITH "REPLACED *SPEED" ON WZ-1 |                                                                                                                               |                                                       |  |
| 09-14-25       | ISSUED                                          |                                                                                                                               |                                                       |  |
| DATE REV       | DESCRIPTION                                     |                                                                                                                               |                                                       |  |
| DATE EFFECTIVE |                                                 |                                                                                                                               |                                                       |  |
| 04-09-2026     |                                                 | STANDARD DRAWING                                                                                                              | TC-6                                                  |  |





**TYPE 1 RAMP DIMENSIONS AND QUANTITIES**


| RADIUS<br>"F" | DISTANCE<br>"F" | DISTANCE<br>"F" | LENGTH<br>"F" | RAMP AREA<br>"F" |
|---------------|-----------------|-----------------|---------------|------------------|
| 15            | 11.67           | 18.82           | 32.18         | 26.21            |
| 20            | 11.52           | 22.28           | 35.46         | 30.07            |
| 25            | 11.43           | 26.68           | 38.77         | 33.80            |
| 30            | 11.37           | 30.26           | 40.93         | 36.90            |
| 35            | 11.32           | 33.51           | 43.11         | 39.77            |
| 40            | 11.30           | 36.45           | 45.26         | 42.45            |
| 45            | 11.27           | 39.16           | 47.34         | 44.97            |
| 50            | 11.26           | 41.69           | 49.36         | 47.35            |
| 55            | 11.24           | 44.07           | 51.31         | 49.63            |
| 60            | 11.22           | 46.33           | 53.21         | 51.80            |



NOTE:  
THE CROSS SLOPE OF THE RAMPS, LEVEL LANDINGS,  
AND SIDEWALKS SHALL NOT EXCEED 2% UNLESS  
REQUIRED TO MATCH STREET LONGITUDINAL GRADE.



**GENERAL NOTES FOR DETECTABLE WARNING DEVICES**  
THE DETECTABLE WARNING DEVICE SHALL BE LOCATED SO THAT THE NEAREST EDGE OF THE DEVICE IS 6 TO 8 INCHES FROM THE FACE OF THE CURB. TRUNCATED DOMES IN THE DETECTABLE WARNING SURFACE SHALL MEET THE REQUIREMENTS OF THE GEOMETRIC CONFIGURATION SHOWN. DOMES SHALL BE ALIGNED ON A SQUARE GRID IN THE PREDOMINANT DIRECTION OF TRAVEL TO PERMIT WHEELS TO ROLL BETWEEN DOMES. DETECTABLE WARNING DEVICE SHALL BE 24 INCHES IN THE DIRECTION OF TRAVEL AND EXTEND THE FULL WIDTH OF THE CURB RAMP OR FLUSH SURFACE. DETECTABLE WARNING DEVICE SHALL BE ON THE ADJUT QUALIFIED PRODUCTS LIST FOR CAST-IN-PLACE TACTILE PANELS (ADA DETECTABLE WARNING).



**DETECTABLE WARNING DEVICE DETAIL**

**GENERAL NOTES:**  
IN NEW CONSTRUCTION, UNLESS OTHERWISE INDICATED ON THE PLANS, WHEELCHAIR RAMPS ARE TO BE PROVIDED AT ALL CORNERS OF CURBED STREET INTERSECTIONS AND MID-BLOCK CROSSWALK LOCATIONS. IN ALTERATIONS WHEELCHAIR RAMPS ARE TO BE PROVIDED AT CURBED STREET INTERSECTIONS WITH PEDESTRIAN TRAFFIC AND MID-BLOCK CROSSWALK LOCATIONS. THE LENGTH OF THE RAMP SHALL BE SUCH THAT THE SLOPE DOES NOT EXCEED 121. THE SURFACE TEXTURE OF THE RAMP SHALL CONFORM TO A CLASS 6 FINISH ACCORDING TO SECTION 802.19. THE NORMAL GUTTER GRADE SHALL BE MAINTAINED THROUGH THE AREA OF THE RAMP. ALL PAVEMENT MARKINGS SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES PUBLISHED BY THE FEDERAL HIGHWAY ADMINISTRATION. THE MINIMUM THICKNESS OF THE RAMP, WALK, & LANDING SHALL BE 4". THE MINIMUM WIDTH OF THE RAMPS SHALL BE THE WALK WIDTH OR 36", WHICHEVER IS GREATER. RAMPS SHALL BE MODIFIED AS NECESSARY TO INSURE THAT THEY ARE PARALLEL TO A LINE DRAWN FROM THE CENTER OF ONE RAMP TO THE CENTER OF THE RAMP ON THE OPPOSITE SIDE OF THE INTERSECTION. THE DIMENSIONS AND QUANTITIES SHOWN ON THIS DRAWING ARE FOR A 90° INTERSECTION ONLY. DIMENSIONS AND QUANTITIES FOR SKEWED INTERSECTIONS WILL VARY, AND ARE TO BE DETERMINED BY THE ENGINEER.

**RAMP SELECTION CRITERIA**


|               | TYPE 1 CORNER LOCATIONS WITH THE WALK ADJACENT TO THE CURB (BOTH NEW CONSTRUCTION AND ALTERATIONS).                                                                                                                                                                                                                                                                       |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FIRST CHOICE  | TYPE 2 CORNER LOCATIONS WITH THE WALK OFFSET FROM THE CURB A DISTANCE INSUFFICIENT TO ALLOW THE REQUIRED RAMP SLOPE (BOTH NEW CONSTRUCTION AND ALTERATIONS).                                                                                                                                                                                                              |
|               | TYPE 3 CORNER LOCATIONS WITH THE WALK OFFSET FROM THE CURB A DISTANCE SUFFICIENT TO ALLOW THE REQUIRED RAMP SLOPE (BOTH NEW CONSTRUCTION AND ALTERATIONS).                                                                                                                                                                                                                |
|               | TYPE 4 TANGENT LOCATIONS (BOTH NEW CONSTRUCTION AND ALTERATIONS).                                                                                                                                                                                                                                                                                                         |
| SECOND CHOICE | TYPE 5 TANGENT LOCATIONS (ALTERATIONS ONLY).                                                                                                                                                                                                                                                                                                                              |
| THIRD CHOICE  | CORNER LOCATIONS (ALTERATIONS ONLY). THIS RAMP MAY BE USED ONLY IF THE TYPE 6 TYPE 5 RAMPS CANNOT BE PLACED AT THE ENDS OF THE RADIUS.                                                                                                                                                                                                                                    |
| FOURTH CHOICE | IF SITE CONSTRAINTS PREVENT THE CONSTRUCTION OF ANY OF THE TYPES LISTED, THEN AND ONLY THEN CAN THE 121 MAX. SLOPE ON THE RAMP BE EXCEEDED TO PROVIDE ACCESS TO THE STREET LEVEL (ALTERATIONS ONLY). THE SLOPE CAN BE STEEPER TO A 180 MAX. FOR A MAX. LENGTH OF 5' OR A B1 MAX. FOR A MAX. LENGTH OF 2'. SLOPES STEEPER THAN B1 ARE NOT ALLOWED UNDER ANY CIRCUMSTANCES. |

NOTE: IN ALTERATIONS, THE SELECTION OF THE TYPE OF WHEELCHAIR RAMP TO BE CONSTRUCTED SHALL BE BASED ON THE AMOUNT OF RIGHT-OF-WAY AVAILABLE, AND ON THE PRESENCE OF OTHER SITE CONSTRAINTS (UTILITIES, BUILDINGS, ETC.). THE TABLE ABOVE LISTS THE ORDER IN WHICH THE RAMPS ARE TO BE CONSIDERED. AN ALTERATION IS DEFINED AS A PROJECT THAT CHANGES OR AFFECTS THE USE OF A PEDESTRIAN PATHWAY (OVERLAYS, SIGNALIZATION PROJECTS, ETC.) BUT DOES NOT REQUIRE THE PURCHASE OF ADDITIONAL RIGHT-OF-WAY. ALL PROJECTS THAT REQUIRE THE PURCHASE OF ADDITIONAL RIGHT-OF-WAY WILL USUALLY BE CONSIDERED NEW CONSTRUCTION FOR THE PURPOSES OF THE CHART ABOVE.

| DATE    | REVISION                        | DATE FILED   |
|---------|---------------------------------|--------------|
| 6-10-05 | REVISED TO NEW SIDEWALK POLICY  |              |
| 6-10-05 | REVISED SIDEWALK POLICY         |              |
| 4-10-03 | REV. DETECTABLE WARNING DEVICES |              |
| 4-10-03 | ADD DETECTABLE WARNING DEVICES  |              |
| 3-10-00 | ADD SLOPE TRANS. & REV. SLOPES  |              |
| 6-8-98  | REVISED TEXTURE                 |              |
| 6-8-98  | REVISED NOTES                   |              |
| 7-02-98 | REDESIGNED & REISSUED           |              |
| 6-8-96  | CORRECTED DIMENSIONS            | 6-8-96       |
| 6-24-90 | FROM 100% MAX. SLOPES           | 5-24-90      |
| 7-15-88 | ADJUSTED MAX. SLOPE             | 6-22-7-15-88 |
| 7-14-88 | INCL. CONC. ISLAND PAY ITEM     |              |
| 6-02-76 | ISSUED-P&M                      | 299-7-26-76  |

**ARKANSAS STATE HIGHWAY COMMISSION**  
**WHEELCHAIR RAMPS**  
**NEW CONSTRUCTION**  
**AND ALTERATIONS**  
**STANDARD DRAWING WR-1**

GENERAL NOTES FOR DETECTABLE WARNING DEVICES  
 THE DETECTABLE WARNING DEVICE SHALL BE LOCATED SO THAT THE NEAREST EDGE OF THE DEVICE IS 6 TO 8 INCHES FROM THE FACE OF THE CURB. TRUNCATED DOMES IN THE DETECTABLE WARNING SURFACE SHALL MEET THE REQUIREMENTS OF THE GEOMETRIC CONFIGURATION SHOWN.  
 DOMES SHALL BE ALIGNED ON A SQUARE GRID IN THE PREDOMINANT DIRECTION OF TRAVEL TO PERMIT WHEELS TO ROLL BETWEEN DOMES.  
 DETECTABLE WARNING DEVICE SHALL BE 24 INCHES IN THE DIRECTION OF TRAVEL AND EXTEND THE FULL WIDTH OF THE CURB RAMP OR FLUSH SURFACE.  
 DETECTABLE WARNING DEVICE SHALL BE ON THE ARDOT QUALIFIED PRODUCTS LIST FOR CAST-IN-PLACE TACTILE PANELS (ADA DETECTABLE WARNING).



DETECTABLE WARNING DEVICE DETAIL

GENERAL NOTES:

IN ALTERATIONS WHEELCHAIR RAMPS ARE TO BE PROVIDED AT CURBED STREET INTERSECTIONS WITH PEDESTRIAN TRAFFIC AND MID-BLOCK CROSSWALK LOCATIONS.  
 THE LENGTH OF THE RAMP SHALL BE SUCH THAT THE SLOPE DOES NOT EXCEED 12:1. THE SURFACE TEXTURE OF THE RAMP SHALL CONFORM TO A CLASS 6 FINISH ACCORDING TO SECTION 802.19.  
 THE NORMAL CUTTER GRADE SHALL BE MAINTAINED THROUGH THE AREA OF THE RAMP.  
 ALL PAVEMENT MARKINGS SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES PUBLISHED BY THE FEDERAL HIGHWAY ADMINISTRATION.  
 THE MINIMUM THICKNESS OF THE RAMP, WALK, & LANDING SHALL BE 4".  
 THE MINIMUM WIDTH OF THE RAMPS SHALL BE THE EXISTING WALK WIDTH OR 36", WHICHEVER IS GREATER.  
 MINOR MODIFICATIONS OF THESE DETAILS, AS APPROVED BY THE ENGINEER, MAY BE MADE TO ADJUST TO LOCAL CONDITIONS.

RAMP SELECTION CRITERIA


|               |        |                                                                                                                                                                                                                                                                                                                                                                                 |
|---------------|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FIRST CHOICE  | TYPE 1 | CORNER LOCATIONS WITH THE WALK ADJACENT TO THE CURB (BOTH NEW CONSTRUCTION AND ALTERATIONS).                                                                                                                                                                                                                                                                                    |
|               | TYPE 2 | CORNER LOCATIONS WITH THE WALK OFFSET FROM THE CURB A DISTANCE INSUFFICIENT TO ALLOW THE REQUIRED RAMP SLOPE (BOTH NEW CONSTRUCTION AND ALTERATIONS).                                                                                                                                                                                                                           |
|               | TYPE 3 | CORNER LOCATIONS WITH THE WALK OFFSET FROM THE CURB A DISTANCE SUFFICIENT TO ALLOW THE REQUIRED RAMP SLOPE (BOTH NEW CONSTRUCTION AND ALTERATIONS).                                                                                                                                                                                                                             |
| SECOND CHOICE | TYPE 4 | TANGENT LOCATIONS (BOTH NEW CONSTRUCTION AND ALTERATIONS).                                                                                                                                                                                                                                                                                                                      |
|               | TYPE 5 | TANGENT LOCATIONS (ALTERATIONS ONLY).                                                                                                                                                                                                                                                                                                                                           |
| THIRD CHOICE  | TYPE 6 | CORNER LOCATIONS (ALTERATIONS ONLY). THIS RAMP MAY BE USED ONLY IF THE TYPE 5 RAMPS CANNOT BE PLACED AT THE ENDS OF THE RADIUS.                                                                                                                                                                                                                                                 |
| FOURTH CHOICE |        | IF SITE CONSTRAINTS PREVENT THE CONSTRUCTION OF ANY OF THE TYPES LISTED, THEN AND ONLY THEN CAN THE 12:1 MAX. SLOPE ON THE RAMP BE EXCEEDED TO PROVIDE ACCESS TO THE STREET LEVEL (ALTERATIONS ONLY). THE SLOPE CAN BE STEEPENED TO A 10:1 MAX. FOR A MAX. LENGTH OF 5' OR A 8:1 MAX. FOR A MAX. LENGTH OF 2'. SLOPES STEEPER THAN 8:1 ARE NOT ALLOWED UNDER ANY CIRCUMSTANCES. |

NOTE: IN ALTERATIONS, THE SELECTION OF THE TYPE OF WHEELCHAIR RAMP TO BE CONSTRUCTED SHALL BE BASED ON THE AMOUNT OF RIGHT-OF-WAY AVAILABLE, AND ON THE PRESENCE OF OTHER SITE CONSTRAINTS (UTILITIES, BUILDINGS, ETC.). THE TABLE ABOVE LISTS THE ORDER IN WHICH THE RAMPS ARE TO BE CONSIDERED.


AN ALTERATION IS DEFINED AS A PROJECT THAT CHANGES OR AFFECTS THE USE OF A PEDESTRIAN PATHWAY (OVERLAYS, SIGNALIZATION PROJECTS, ETC.) BUT DOES NOT REQUIRE THE PURCHASE OF ADDITIONAL RIGHT-OF-WAY. ALL PROJECTS THAT REQUIRE THE PURCHASE OF ADDITIONAL RIGHT-OF-WAY WILL USUALLY BE CONSIDERED NEW CONSTRUCTION FOR THE PURPOSES OF THE CHART ABOVE.

|                                   |                                          |            |
|-----------------------------------|------------------------------------------|------------|
| ARKANSAS STATE HIGHWAY COMMISSION |                                          |            |
| WHEELCHAIR RAMPS ALTERATIONS ONLY |                                          |            |
| STANDARD DRAWING WR-2             |                                          |            |
| 10-9-03                           | REVISED GENERAL NOTES & ADDED NOTE.      |            |
| 4-10-03                           | REVISED DETECTABLE WARNING DEVICE DETAIL |            |
| 8-22-02                           | ADDED DETECTABLE WARNING DEVICES DETAILS |            |
| 11-18-98                          | REV. FOURTH CHOICE NOTE                  |            |
| 8-12-98                           | REVISED TEXTURE                          |            |
| 7-02-98                           | ISSUED                                   |            |
| DATE                              | REVISION                                 | DATE FILED |

TYPE 5 RAMP



TYPE 6 RAMP




# **ARKANSAS STATE HIGHWAY COMMISSION**



## **STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION**

*EDITION OF 2014*



## ***PROPOSAL DOCUMENTS AND SCHEDULE OF ITEMS***

# ARKANSAS STATE HIGHWAY COMMISSION

## PROPOSAL DOCUMENTS

### PROPOSAL FOR CONSTRUCTING:

THE PURPOSE OF THIS PROJECT IS TO MILL AND OVERLAY APPROXIMATELY 5.876 MILES OF HIGHWAY 7 IN GARLAND COUNTY. THIS PROJECT CONSISTS OF ACHM SURFACE COURSE, COLD MILLING ASPHALT PAVEMENT, ACHM PATCHING OF EXISTING ROADWAY, MAINTENANCE OF TRAFFIC, LOOP WIRING, PAVEMENT MARKING, AND MISC. ITEMS.

State Highway 7, Section 9, in **GARLAND** County, Arkansas, in accordance with Standard Specifications for Highway Construction, Edition of 2014; the Supplemental Specifications and Special Provisions attached hereto; and the Construction Plans on file in the Office of the State Highway Commission, designated as

Job **A60063**                      **FEDERAL AID PROJECT STPSC-9210(62)**

Job Name: **HWY. 7 IMPVTS. (HOT SPRINGS) (S)**

said project being approximately **5.876 miles in length.**

Proposal received until 10:00 a.m. on June 24, 2026

### TO THE ARKANSAS STATE HIGHWAY COMMISSION:

Gentlemen: By submission of your bid, you agree to the following:

It is hereby certified that a careful examination has been made of the Plans, Specifications, Supplemental Specifications, Special Provisions, and Form of Contract and the site of the work throughout its whole extent. On the basis of the Plans, Specifications, Supplemental Specifications, Special Provisions, and Form of Contract, the bidder proposes to furnish all necessary machinery, equipment, tools, labor and other means of construction, and to furnish all materials as specified, in the manner and at the time prescribed, and to finish the entire project within the time hereinafter proposed. The bidder understands that the quantities of work mentioned herein are approximate only, and are subject to increase or decrease, and hereby proposes to perform all quantities of work, whether increased or decreased, in accordance with the provisions of the Specifications, and at the unit prices bid in the attached Schedule of Items.

Receipt is hereby specifically acknowledged, and complete examination expressly guaranteed of the following:

1. Standard Specifications for Highway Construction, Edition of 2014.
2. Supplemental Specifications.
3. Special Provisions.
4. Proposal Documents.
5. Schedule of Items .
6. Construction Plans.

The bidder further proposes to perform all Extra Work that may be required, on the basis provided in the Specifications, and to give such work personal attention, and to secure economical performance.

The bidder further proposes to execute the contract agreement, and to furnish satisfactory bonds within ten days after he has received notice that he has been awarded the contract. The bidder further agrees to begin work when ordered by the Engineer, or within ten days thereafter, and to complete the work **on or before November 25, 2026.**

## **PROPOSAL DOCUMENTS**

(Continued)

The bidder also proposes to furnish a surety Performance bond or bonds in a sum equal to the full amount of the contract and a surety Payment bond or bonds in a sum equal to 80% of the full amount of the contract. These bonds shall not only serve to guarantee the completion of the work and payment of all bills and claims by the bidder, but also to guarantee the excellence of both workmanship and material until the work is finally accepted and the provisions of the Plans, Specifications and Special Provisions fulfilled.

The bidder shall furnish a Proposal Guaranty in the form specified in Subsection 102.09 of the Specifications, in the amount of five percent (5%) of the total amount bid, which is submitted as a guarantee of the good faith of the proposal, and that the Bidder will enter into written contract, as provided, to do the work should the award be made to him; and it is hereby agreed that if, at any time other than as provided in Subsection 102.11 of the Standard Specifications, Withdrawal/Modification of Proposals, the bidder should withdraw his proposal, or should fail to execute the contract and furnish satisfactory bonds as herein provided, if his proposal is accepted, the Arkansas State Highway Commission, in either of such events, shall be entitled and is hereby given the right to retain the Proposal Guaranty, not as a penalty, but as liquidated damages, it being understood and agreed by the bidder that the amount of the Proposal Guaranty is a reasonable sum to be fixed as liquidated damages considering the damages the Arkansas State Highway Commission will sustain in the event of the bidder's withdrawal of his proposal, or failure to execute the contract and furnish satisfactory bonds if his proposal is accepted, and said amount is herein agreed upon and fixed as liquidated damages because of the difficulty of ascertaining the exact amount of damage that may be sustained by reason of the above set out circumstances.

Arkansas Department of Transportation  
Schedule of Items

State Job No.: A60063

Date Estimated: 4/24/2026

Job Name: HWY. 7 IMPVTS. (HOT SPRINGS) (S)

Date Revised:

Federal Aid Project: STPSC-9210(62)

| Line<br>Number              | Item Code and Description                                                                      | Estimated<br>Quantity | Unit Bid<br>Price | Price<br>Extension |
|-----------------------------|------------------------------------------------------------------------------------------------|-----------------------|-------------------|--------------------|
| Section 01 - PROPOSAL ITEMS |                                                                                                |                       |                   |                    |
| 0001                        | SS&401 - TACK COAT                                                                             | 35,050.000 GAL        |                   |                    |
| 0002                        | SPSS407 - MINERAL AGGREGATE IN ACHM<br>SURFACE COURSE (1/2")                                   | 21,207.000 TON        |                   |                    |
| 0003                        | SPSS407 - ASPHALT BINDER (PG 76-22) IN<br>ACHM SURFACE COURSE (1/2") (MINIMUM<br>BID \$120.00) | 1,282.000 TON         |                   |                    |
| 0004                        | SP&412 - COLD MILLING ASPHALT<br>PAVEMENT                                                      | 204,446.000 SQYD      |                   |                    |
| 0005                        | SPSS414 - ASPHALT CONCRETE PATCHING<br>FOR MAINTENANCE OF TRAFFIC                              | 147.000 TON           |                   |                    |
| 0006                        | SPSS415 - ACHM PATCHING OF EXISTING<br>ROADWAY                                                 | 500.000 TON           |                   |                    |
| 0007                        | SPSS603 - MAINTENANCE OF TRAFFIC                                                               | 1.000 L.S.            |                   |                    |
| 0008                        | SS&604 - SIGNS                                                                                 | 1,567.000 SQFT        |                   |                    |
| 0009                        | 604 - CONSTRUCTION PAVEMENT MARKINGS                                                           | 106,738.000 LF        |                   |                    |
| 0010                        | SP&635 - ROADWAY CONSTRUCTION<br>CONTROL                                                       | 1.000 L.S.            |                   |                    |
| 0011                        | SP - SURFACE-APPLIED DETECTABLE<br>WARNING PANELS                                              | 2,120.000 SQFT        |                   |                    |
| 0012                        | SP - LOOP WIRING CLASS III (1C/16 A.W.G.)                                                      | 25,421.000 LF         |                   |                    |
| 0013                        | 704 - FEEDER WIRE                                                                              | 14,925.000 LF         |                   |                    |
| 0014                        | 710 - NON-METALLIC CONDUIT (2")                                                                | 1,470.000 LF          |                   |                    |
| 0015                        | SPSS711 - CONCRETE PULL BOX (TYPE 1 HD)                                                        | 19.000 EACH           |                   |                    |
| 0016                        | 719 - THERMOPLASTIC PAVEMENT<br>MARKING WHITE (6")                                             | 38,108.000 LF         |                   |                    |
| 0017                        | 719 - THERMOPLASTIC PAVEMENT<br>MARKING WHITE (8")                                             | 1,156.000 LF          |                   |                    |
| 0018                        | 719 - THERMOPLASTIC PAVEMENT<br>MARKING WHITE (24")                                            | 4,224.000 LF          |                   |                    |
| 0019                        | 719 - THERMOPLASTIC PAVEMENT<br>MARKING YELLOW (6")                                            | 68,630.000 LF         |                   |                    |
| 0020                        | 719 - THERMOPLASTIC PAVEMENT<br>MARKING (WORDS)                                                | 42.000 EACH           |                   |                    |
| 0021                        | 719 - THERMOPLASTIC PAVEMENT<br>MARKING (ARROWS)                                               | 51.000 EACH           |                   |                    |
| 0022                        | 719 - THERMOPLASTIC PAVEMENT<br>MARKING (RAILROAD EMBLEMS)                                     | 4.000 EACH            |                   |                    |

Arkansas Department of Transportation  
Schedule of Items

State Job No.: A60063

Date Estimated: 4/24/2026

Job Name: HWY. 7 IMPVTS. (HOT SPRINGS) (S)

Date Revised:

Federal Aid Project: STPSC-9210(62)

| Line<br>Number    | Item Code and Description                                             | Estimated<br>Quantity | Unit Bid<br>Price | Price<br>Extension |
|-------------------|-----------------------------------------------------------------------|-----------------------|-------------------|--------------------|
| 0023              | 721 - RAISED PAVEMENT MARKERS (TYPE II)                               | 1,613.000 EACH        |                   |                    |
| Section 01 Total: |                                                                       |                       |                   |                    |
| Subtotal:         |                                                                       |                       |                   |                    |
| 0024              | 601 - MOBILIZATION (UNIT BID AMOUNT<br>MAY NOT EXCEED 5% OF SUBTOTAL) | 1.000 L.S.            |                   |                    |
| Bid Total:        |                                                                       |                       |                   |                    |

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENT TO PROPOSAL**  
**ANTI-COLLUSION AND DEBARMENT CERTIFICATION**

**FAILURE TO EXECUTE AND SUBMIT THIS CERTIFICATION SHALL RENDER THIS  
BID NONRESPONSIVE AND NOT ELIGIBLE FOR AWARD CONSIDERATION.**

As a condition precedent to the acceptance of the bidding document for this project, the bidder shall file this Affidavit executed by, or on behalf of the person, firm, association, or corporation submitting the bid. The original of this Affidavit shall be filed with the Arkansas Department of Transportation **at the time proposals are submitted.**

**A F F I D A V I T**

I hereby certify, under penalty of perjury under the laws of the United States and/or the State of Arkansas, that the bidder listed below has not, either directly or indirectly, entered into any agreement, participated in any collusion, or otherwise taken any action in restraint of free competitive bidding in connection with the submitted bid for this project, is not presently barred from bidding in any other jurisdiction as a result of any collusion or any other action in restraint of free competition, and that the foregoing is true and correct.

Further, that except as noted below, the bidder, or any person associated therewith in the capacity of owner, partner, director, officer, principal investigator, project director, manager, auditor, or any position involving the administration of Federal funds:

- a. is not currently under suspension, debarment, voluntary exclusion, or determination of ineligibility by any Federal, State, or Local agency;
- b. has not been suspended, debarred, voluntarily excluded or determined ineligible by any Federal, State, or Local agency within the past 3 years;
- c. does not have a proposed debarment pending; and
- d. has not been indicted, convicted, or had an adverse civil judgment rendered by a court of competent jurisdiction in any matter involving fraud or official misconduct within the past 3 years.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENT TO PROPOSAL**  
**ANTI-COLLUSION AND DEBARMENT CERTIFICATION**

**FAILURE TO EXECUTE AND SUBMIT THIS CERTIFICATION SHALL RENDER THIS  
BID NONRESPONSIVE AND NOT ELIGIBLE FOR AWARD CONSIDERATION.**

**EXCEPTIONS:**

| APPLIED TO | INITIATING AGENCY | DATES OF ACTION |
|------------|-------------------|-----------------|
| _____      | _____             | _____           |
| _____      | _____             | _____           |
| _____      | _____             | _____           |

Exceptions will not necessarily result in denial of award, but will be considered in determining bidder responsibility. Providing false information may result in criminal prosecution or administrative sanctions.

|                  |                           |
|------------------|---------------------------|
| Job No. _____    | _____                     |
|                  | (Name of Bidder)          |
| F.A.P. No. _____ | _____                     |
|                  | (Signature)               |
| _____            | _____                     |
| (Date Executed)  | (Title of Person Signing) |

The following Notary Public certification is **OPTIONAL** and may or may not be completed at the contractor's discretion.

State of \_\_\_\_\_)  
County of \_\_\_\_\_)ss.

\_\_\_\_\_, being duly sworn, deposes and says that he is

\_\_\_\_\_ of \_\_\_\_\_  
(Title) (Name of Bidder)

and that the above statements are true and correct.

Subscribed and Sworn to before me this \_\_\_\_\_ day of \_\_\_\_\_, 20\_\_\_\_.  
My commission expires: \_\_\_\_\_.

(NOTARY SEAL)

\_\_\_\_\_  
(Notary Public)



## SUPPLEMENT TO THE PROPOSAL CERTIFICATION FOR BOYCOTT AND ILLEGAL IMMIGRANT RESTRICTIONS

Pursuant to Arkansas law, a vendor must submit the below certifications prior to entering into a contract with a public entity for an amount as designated by the applicable laws.

- Israel Boycott Restriction:** For contracts valued at \$1,000 or greater.  
A public entity shall not enter into a contract with a company unless the contract includes a written certification that the person or company is not currently engaged in a boycott of Israel. If at any time after signing this certification the contractor decides to engage in a boycott of Israel, the contractor must notify the contracting public entity in writing. See Arkansas Code Annotated § 25-1-503.
- Illegal Immigrant Restriction:** For contracts exceeding \$25,000.  
No state agency may enter into or renew a public contract for services with a contractor who employs or contracts with an illegal immigrant. A contractor shall certify that it does not employ, or contract with, illegal immigrants. See Arkansas Code Annotated § 19-11-105.
- Energy, Fossil Fuel, Firearms, and Ammunition Industries Boycott Restriction:** For contracts valued at, or exceeding, \$75,000.  
A public entity shall not enter into a contract with a company unless the contract includes a written certification that the person or company is not currently engaged in, and agrees for the duration of the contract not to engage in, a boycott of an Energy, Fossil Fuel, Firearms, or Ammunition Industry. If a company does boycott any of these industries, see Arkansas Code Annotated § 25-1-1102.
- Scrutinized Company Restriction:** Required with bid or proposal submission.  
A state agency shall not contract with a Scrutinized Company or a company that employs a Scrutinized Company as a subcontractor. A Scrutinized Company is a company owned in whole or with a majority ownership by the government of the People's Republic of China. A state agency shall require a company that submits a bid or proposal for a contract to certify that it is not a Scrutinized Company and does not employ a Scrutinized Company as a subcontractor. See Arkansas Code Annotated § 25-1-1203.

The bidder hereby agrees and certifies that it does not, and shall not for the remaining aggregate term of the contract, participate in the activities checked below:

- ☐ Do not boycott Israel.
- ☐ Do not employ illegal immigrants.
- ☐ Do not boycott Energy, Fossil Fuel, Firearms, or Ammunition Industries.
- ☐ Do not employ a Scrutinized Company as a subcontractor.

|                |  |
|----------------|--|
| Job No.        |  |
| F.A.P. No.     |  |
| Name of Bidder |  |

\_\_\_\_\_  
Bidder Signature

\_\_\_\_\_  
Date

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENT TO PROPOSAL**  
**CERTIFICATION FOR FEDERAL-AID CONTRACTS**

The prospective contractor certifies, by signing and submitting this proposal, to the best of his or her knowledge and belief that:

1. No Federal appropriated funds have been paid or will be paid, by or on his or her behalf, to any person for influencing or attempting to influence an officer or employee of any Federal agency, a member of Congress, an officer or employee of Congress, or any employee of a member of Congress in connection with the awarding of any Federal contract, the making of any Federal grant, the making of any Federal loan, the entering into of any cooperative agreement, and the extension, continuation, renewal, amendment, or modification of any Federal contract, grant, loan, or cooperative agreement.
2. If any funds other than Federal appropriated funds have been paid or will be paid to any person for influencing or attempting to influence an officer or employee of any Federal agency, a member of Congress, an officer or employee of Congress, or an employee of a member of Congress in connection with this Federal-Aid contract, the prospective contractor shall complete and submit Standard Form-LLL, "Disclosure of Lobbying Activities", in accordance with its instructions. (Available from Arkansas Department of Transportation, Program Management Division.)

This Certification is a material representation of fact upon which reliance was placed when this transaction was made or entered into. This Certification is a prerequisite for making or entering into this transaction imposed by Section 1352, Title 31, U.S. Code.

During the period of performance of the contract, the contractor and all lower tier subcontractors must file a Form-LLL at the end of each calendar year quarter in which there occurs any event that requires disclosure or that materially affects the accuracy of the information contained in any previously filed disclosure form. Any person who fails to file the required Certification shall be subject to a civil penalty of not less than \$10,000 and not more than \$100,000 for each failure.

The prospective contractor also agrees by submitting his or her proposal that he or she shall require that the language of this Certification be included in all lower tier subcontracts which exceed \$100,000 and that all such subcontractors shall certify and disclose accordingly.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**  
**SUPPLEMENT TO PROPOSAL**  
**C E R T I F I C A T I O N**

**THIS CERTIFICATION SHALL BE COMPLETED BY THE BIDDER**  
**AS PART OF THIS PROPOSAL**

The bidder \_\_\_\_, proposed subcontractor \_\_\_\_, hereby certifies that he has \_\_\_\_, has not \_\_\_\_, participated in a previous contract or subcontract subject to the equal opportunity clause, as required by Executive Orders 10925, 11114, or 11246, and that he has \_\_\_\_, has not \_\_\_\_, filed with the Joint Reporting Committee, the Director of the Office of Federal Contract Compliance, a Federal Government contracting or administering agency, or the former President's Committee on Equal Employment Opportunity, all reports due under the applicable filing requirements.

(Currently, Standard Form 100 [EEO-1] is the only report required by the Executive Orders or their implementing regulations)

Job No. \_\_\_\_\_ (Company) \_\_\_\_\_

F.A.P. No. \_\_\_\_\_ By: \_\_\_\_\_

Date \_\_\_\_\_ (Title) \_\_\_\_\_

**NOTE:** The above certification is required by the Equal Employment Opportunity Regulations of the Secretary of Labor (41 CFR 60-1.7(b)(1)), and must be submitted by bidders and proposed subcontractors only in connection with contracts and subcontracts which are subject to the equal opportunity clause. Contracts and subcontracts which are exempt from the equal opportunity clause are set forth in 41 CFR 60-1.5. (Generally only contracts or subcontracts of \$10,000 or under are exempt.)

Proposed prime contractors and subcontractors who have participated in a previous contract or subcontract subject to the Executive Orders and have not filed the required reports should note that 41 CFR 60-1.7(b)(1) prevents the award of contracts and subcontracts unless such contractor submits a report covering the delinquent period or such other period specified by the Federal Highway Administration or by the Director, Office of Federal Contract Compliance, U.S. Department of Labor.

**ARKANSAS DEPARTMENT OF TRANSPORTATION**

**SUPPLEMENT TO PROPOSAL**

**USE OF FOREIGN MADE UNMANNED AIRCRAFT SYSTEMS**

In accordance with Office of Management and Budgets Memo M-26-02 and the American Security Drone Act, all contractors, subcontractors, or consultants utilizing a unmanned aircraft system (UAS) aircraft, flight controller, camera, or ground control station supplied by a manufacturer that is based in, or subject to the control of, a foreign adversary country, specifically the People's Republic of China, are directed to cease using the systems for activities associated with the contract pay items of Roadway Construction Control or Bridge Construction Control on federal aid projects.

Security risks have been found to exist on data collected by foreign manufactured drones and the federal government has issued restrictions on their use on federally funded projects. The use of foreign made drones may continue for applications not directly paid for by the Department, such as project update overflights, promotional or recruiting purposes, etc., but the Department strongly encourages that the overall use of foreign manufactured UAS be suspended in all contractor operations.

**USE OF FOREIGN MADE UNMANNED AIRCRAFT SYSTEMS**

As an authorized representative of this company, I hereby certify that any unmanned aircraft systems to be used or actually used on this federal aid project comply with the above referenced restrictions.

|            |       |           |
|------------|-------|-----------|
| Job No.    | _____ | _____     |
|            |       | (Company) |
| F.A.P. No. | _____ | By: _____ |
| Date       | _____ | _____     |
|            |       | (Title)   |

## ARKANSAS DEPARTMENT OF TRANSPORTATION

### BIDDERS LIST

JOB NUMBER A60063 LETTING DATE June 24, 2026  
 JOB NAME HWY. 7 IMPVTS. (HOT SPRINGS) (S)  
 CONTRACTOR \_\_\_\_\_

#### ➔ **ENTER THE WORK CODES TO BE PERFORMED BY THE PRIME CONTRACTOR**

The Department is required by 49 CFR 26.11, to create and maintain a master bidder's list of all firms attempting to participate on federally assisted projects. The Contractor shall provide the names and addresses of all subcontractors, truckers or material suppliers that bid or provided quotes on any item on the project, regardless of whether the quotes were used in preparing the proposal or not. Place an X in the box following the firm's name if DBE Contractor. Denote the firm's and annual gross receipts by checking the appropriate box. The general type of work to be performed should be indicated using the following codes; (01) removal and disposal items (including clearing and grubbing), (02) earthwork (including drainage items), (03) hauling, (04) paving (PCCP or ACHM), (05) miscellaneous concrete, (06) traffic control, (07) erosion control, (08) signals/electrical, (09) structures (includes steel suppliers), (10) material (aggregate) supplier (11) miscellaneous *items should be shown*. See <https://www.census.gov/naics/> for the NAICS codes to enter in the last column. Please contact the Department's Civil Rights Division at (501) 569-2297 with any questions.

| Firm Name<br>Address/Phone | DBE | Age of Firm                                                                                                                                                                                                  | Annual Gross Receipts                                                                                                                                                                                                               | Type of Work<br>(Enter Code) | NAICS code<br>(Enter Code) |
|----------------------------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|----------------------------|
|                            |     | <input type="checkbox"/> Less than 1 year<br><input type="checkbox"/> 1- 3 years<br><input type="checkbox"/> 4-7 years<br><input type="checkbox"/> 8-10 years<br><input type="checkbox"/> More than 10 years | <input type="checkbox"/> Less than \$1 million<br><input type="checkbox"/> \$1-3 million<br><input type="checkbox"/> \$3-6 million<br><input type="checkbox"/> \$6-10 million<br><input type="checkbox"/> Greater than \$10 million |                              |                            |
|                            |     | <input type="checkbox"/> Less than 1 year<br><input type="checkbox"/> 1- 3 years<br><input type="checkbox"/> 4-7 years<br><input type="checkbox"/> 8-10 years<br><input type="checkbox"/> More than 10 years | <input type="checkbox"/> Less than \$1 million<br><input type="checkbox"/> \$1-3 million<br><input type="checkbox"/> \$3-6 million<br><input type="checkbox"/> \$6-10 million<br><input type="checkbox"/> Greater than \$10 million |                              |                            |
|                            |     | <input type="checkbox"/> Less than 1 year<br><input type="checkbox"/> 1- 3 years<br><input type="checkbox"/> 4-7 years<br><input type="checkbox"/> 8-10 years<br><input type="checkbox"/> More than 10 years | <input type="checkbox"/> Less than \$1 million<br><input type="checkbox"/> \$1-3 million<br><input type="checkbox"/> \$3-6 million<br><input type="checkbox"/> \$6-10 million<br><input type="checkbox"/> Greater than \$10 million |                              |                            |
|                            |     | <input type="checkbox"/> Less than 1 year<br><input type="checkbox"/> 1- 3 years<br><input type="checkbox"/> 4-7 years<br><input type="checkbox"/> 8-10 years<br><input type="checkbox"/> More than 10 years | <input type="checkbox"/> Less than \$1 million<br><input type="checkbox"/> \$1-3 million<br><input type="checkbox"/> \$3-6 million<br><input type="checkbox"/> \$6-10 million<br><input type="checkbox"/> Greater than \$10 million |                              |                            |
|                            |     | <input type="checkbox"/> Less than 1 year<br><input type="checkbox"/> 1- 3 years<br><input type="checkbox"/> 4-7 years<br><input type="checkbox"/> 8-10 years<br><input type="checkbox"/> More than 10 years | <input type="checkbox"/> Less than \$1 million<br><input type="checkbox"/> \$1-3 million<br><input type="checkbox"/> \$3-6 million<br><input type="checkbox"/> \$6-10 million<br><input type="checkbox"/> Greater than \$10 million |                              |                            |